City of Agoura Hills

Agoura Business Center West and Agoura Business Center North Development Agreement

Final Initial Study and Mitigated Negative Declaration

rincon

Environmental

March 2012

Planners

Engineers

Scientists

Agoura Business Center West and Agoura Business Center North Development Agreement

Final Initial Study and Mitigated Negative Declaration

Prepared by:

City of Agoura Hills Planning and Community Development Department 30001 Ladyface Court Agoura Hills, CA 91301 Contact: Allison Cook, Principal Planner

Prepared with the assistance of:

Rincon Consultants, Inc.

180 N. Ashwood Avenue Ventura, California 93003

March 2012

This report is printed on 30% recycled paper with 10% post-consumer content.

TABLE OF CONTENTS

Introduction

Legal Authority and Findings	1
Impact Analysis and Significance Classification	
Use of Previous Environmental Documents in this Analysis	

Initial Study

List

Project Title	3
Lead Agency and Contact Person	3
Project Proponent	3
Project Site Characteristics	3
Description of the Project	6
Public Agencies Whose Approval May Be Required For Subsequent Actions.	10
Environmental Factors Affected	10
Determination	11
Evaluation of Environmental Impacts	
Aesthetics	12
Agriculture Resources	15
Air Quality	
Biological Resources	
Cultural Resources	22
Geology and Soils	24
Greenhouse Gas Emissions	27
Hazards and Hazardous Materials	31
Hydrology and Water Quality	
Land Use and Planning	
Mineral Resources	
Noise	
Population and Housing	41
Public Services	42
Recreation	43
Transportation/Traffic	44
Utilities and Service Systems	58
Mandatory Findings of Significance	59
References	61
of Tables	
Table 1 Agoura Business Center West/Agoura Business Center North App	oroved

Table 2	SCAQMD LSTs for Construction in SRA-6	18
Table 3	Maximum Daily Construction Emissions	19
Table 4	Combined Annual Emissions of Greenhouse Gases: Agoura Business	
	Center North Project	29
Table 5	Combined Annual Emissions of Greenhouse Gases: Agoura Business	
	Center West Project	30
Table 6	Typical Noise Levels at Construction Sites	40
Table 7	Existing Levels of Service	46
Table 8	Opening Year (2022) Agoura Business Center North Project Traffic	
	Contribution	48
Table 9	Cumulative Agoura Business Center North Project Traffic Contribution	50
Table 10	Opening Year (2022) Agoura Business Center West Project Traffic	
	Contribution	52
Table 11	Cumulative Agoura Business Center West Project Traffic Contribution	55

List of Figures

Figure 1	Regional Location	4
Figure 2	Project Location	5
0	Site Photographs	
0	Site Photographs	
1.800000		~

Appendices

Appendix A	Air Quality Modeling Results and Calculations
Appendix B	Greenhouse Gas Emissions Modeling Results and Calculations
Appendix C	Traffic Studies
Appendix D	Development Agreement
Appendix E	Response to Comments on the Draft MND
Appendix F	Mitigation Monitoring and Reporting Program

INTRODUCTION

This document is a Draft Initial Study and Mitigated Negative Declaration (IS-MND) that addresses the potential environmental effects resulting from a development agreement between the City and Agoura Business Center West, LLC/Agoura Business Center North, LLC. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, and would require Agoura Business Center West LLC/Agoura Business Center North LLC to construct additional roadway improvements along Canwood Street.

LEGAL AUTHORITY AND FINDINGS

This IS-MND has been prepared in accordance with the *California Environmental Quality Act* (*CEQA*) *Guidelines* and relevant provisions of CEQA of 1970, as amended.

Initial Study. Section 15063(c) of the *CEQA Guidelines* defines an Initial Study as the proper preliminary method of analyzing the potential environmental consequences of a project. The purposes of an Initial Study are:

- (1) To provide the Lead Agency with the necessary information to decide whether to prepare an Environmental Impact Report (EIR) or a Mitigated Negative Declaration;
- (2) To enable the Lead Agency to modify a project, mitigating adverse impacts, thus avoiding the need to prepare an EIR; and
- (3) To provide sufficient technical analysis of the environmental effects of a project to permit a judgment based on the record as a whole, that the environmental effects of a project have been adequately mitigated.

Negative Declaration or Mitigated Negative Declaration. Section 15070 of the *CEQA Guidelines* states that a public agency shall prepare a negative declaration or mitigated negative declaration for a project subject to CEQA when:

- (a) The initial study shows that there is no substantial evidence, in light of the whole record before the agency, that the project may have a significant effect on the environment; or
- (b) The Initial Study identifies potentially significant effects but:
 - 1. Revisions in the project plans or proposals made by, or agreed to by the applicant before a proposed mitigated negative declaration and initial study are released for public review would avoid the effects or mitigate the effects to a point where clearly no significant effects would occur; and
 - 2. There is no substantial evidence, in light of the whole record before the agency, that the project as revised may have a significant effect on the environment.

An IS-MND may be used to satisfy the requirements of CEQA when a proposed project would have no significant unmitigable effects on the environment. As discussed further in subsequent sections of this document, implementation of the proposed project would not result in any significant effects on the environment that cannot be reduced to below a level of significance with the mitigation measures included herein.

IMPACT ANALYSIS AND SIGNIFICANCE CLASSIFICATION

The following sections of this IS-MND provide discussions of the possible environmental effects of the proposed project for specific issue areas that have been identified on the CEQA Initial Study Checklist. For each issue area, potential effects are discussed and evaluated.

A "significant effect" is defined by Section 15382 of the CEQA Guidelines as "a substantial, or potentially substantial, adverse change in any of the physical conditions within the area affected by a project, including land, air, water, minerals, flora, fauna, ambient noise, and objects of historic or aesthetic significance." According to the *CEQA Guidelines*, "an economic or social change by itself shall not be considered a significant effect on the environment, but may be considered in determining whether the physical change is significant."

Following the evaluation of each environmental effect determined to be potentially significant is a discussion of mitigation measures and the residual effects or level of significance remaining after the implementation of the measures. In those cases where a mitigation measure for an impact could have a significant environmental impact in another issue area, this impact is discussed as a residual effect.

USE OF PREVIOUS ENVIRONMENTAL DOCUMENTS IN THIS ANALYSIS

The following environmental analyses and technical studies were used as a basis for this document. Each study is available upon request at the City of Agoura Hills Planning Department Front Counter.

- *City of Agoura Hills, General Plan 2035 EIR, February 2010.*
- City of Agoura Hills, Agoura Hills Business Park IS-MND, June 2008.
- City of Agoura Hills, Agoura Business Center West IS-MND, May 2009.

INITIAL STUDY

PROJECT TITLE

Agoura Business Center West and North Development Agreement

LEAD AGENCY AND CONTACT PERSON

City of Agoura Hills 30001 Ladyface Court Agoura Hills, CA 91301 *Contact:* Allison Cook, Principal Planner

PROJECT PROPONENT


William Poe Agoura Business Center North, LLC and Agoura Business Center West, LLC 5304 Derry Avenue, Suite A Agoura Hills, CA 91301

PROJECT SITE CHARACTERISTICS

Location: The project site is located at the northwest corner of the Derry Avenue and Canwood Street intersection in the City of Agoura Hills, Los Angeles County. The project site includes the Agoura Business Center West, LLC/Agoura Business Center North, LLC properties (28721 Canwood Street and 28631 Canwood Street, respectively), which were the subject of previously approved IS-MNDs for the Agoura Business Center West Project (SCH #2009031100) and the Agoura Hills Business Park Project (SCH #2008041078). The project site also includes the vacant property currently owned by the Agoura Hills Redevelopment Agency (28661 Canwood Street), located between the Agoura Business Center West LLC/Agoura Business Center North LLC properties. The project site measures approximately 16.5 acres. Figure 1 illustrates the location of the project site in its regional context and Figure 2 shows the location of the project site in the City of Agoura Hills.

Assessor Parcel Numbers: The Business Center West Project site is identified by Assessor's ID Numbers (APN) 2048-012-029 and 2048-012-031. The Business Park Project site is identified by APN 2048-012-033. The intervening vacant property owned by the Agoura Hills Redevelopment Agency is identified by APN 2048-012-901.


Existing General Plan Designation: The City of Agoura Hills General Plan land use designation for the southern portion of the Business Center West project site is Commercial Retail/ Service (CRS). The land use designation for the northern portion of the Business Center West project site, the Business Park project site, and the intervening vacant property owned by the Agoura Hills Redevelopment Agency is Business Park- Manufacturing (BP-M).



Regional Location



Imagery provided by National Geographic Society, ESRI and its licensors © 2012.



Project Location

Figure 2 *City of Agoura Hills*

Existing Zoning: The City of Agoura Hills zoning for the southern portion of the Business Center West project site is Commercial Retail/ Service (CRS). The zoning for the northern portion of the Business Center West project site, the Business Park project site, and the intervening vacant property owned by the Agoura Hills Redevelopment Agency is Business Park-Manufacturing (BP-M). The entire project site is additionally within the FC overlay zone.

Surrounding Land Uses: The project site is surrounded by commercial and light industrial development to the east and west, Canwood Street to the south, and multi-family residential development to the north. U.S. 101 is located south of Canwood Street. Commercial and industrial uses are located south of the project site, across Canwood Street, and east of the project site, across Derry Avenue. Photos of surrounding land uses can be seen on Figure 3.

DESCRIPTION OF THE PROJECT

The proposed project is a development agreement between the City and Agoura Business Center West LLC/Agoura Business Center North LLC (included in Appendix D). The Agoura Business Center North was formerly the Agoura Hills Business Park Project. The Agoura Business Center West Project and the Agoura Hills Business Park Project were the subject of previously approved IS-MNDs (SCH #2009031100 and SCH #2008041078, respectively). Both the "North" and "West" projects were granted CUPs (2008 and 2009, respectively), and both CUPs are set to expire in 2012. The buildout characteristics of the previously approved projects are shown in Table 1.

Agoura Business Center West			
One-story Retail Building	20,640 square feet (sf)		
Covered Walkway	1,956 sf		
Total Floor Area	20,640 sf		
Parking	89 spaces		
Project Site Area	2 acres		
Agoura Business Center North (formerly	v Agoura Hills Business Park)		
Building 1 (warehouse/office)	13,140 sf		
Building 2 (warehouse/office)	13,140 sf		
Building 3 (warehouse/office)	24,140 sf		
Building 4 (warehouse/office)	12,000 sf		
Building 5 (warehouse/office)	9,000 sf		
Building 6 (warehouse/office)	15,000 sf		
Building 7 (warehouse/office)	16,650 sf		
Total Floor Area	103,070 sf		
Parking	217 spaces		
Project Site Area	10 acres		

Table 1Agoura Business Center West/Agoura Business Center NorthApproved Project Components

Source:

Agoura Business Center West IS/MND, SCH #2009031100

Agoura Hills Business Park Project IS/MND, SCH #2008041078



Photo 1 - View from the southwestern corner of the project site, looking east on Canwood Street.



Photo 2 - View from the south side of Canwood Street across from the center parcel of the project site, looking north across Canwood Street onto the project site.

Project Site Photographs



Photo 3 - View from the center parcel of the project site, looking west across the project site along Canwood Street.



Photo 4 - View from the south side of Canwood Street across from the southeastern corner of the project site (at the intersection of Canwood Street and Derry Avenue), looking north across Canwood Street onto the project site.

Project Site Photographs

Both previously approved projects have already been granted the extensions allowed by the Municipal Code. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, and would require Agoura Business Center West LLC/Agoura Business Center North LLC to construct additional roadway improvements along Canwood Street. The 10-year extension would involve a "vested" right to develop the projects during that 10 year period with the assurance from the City that it will not change the development laws and policies applicable to the properties. The buildout characteristics of the two previously approved projects would remain unchanged. The new roadway improvements would occur on Canwood Street in front of the property currently owned by the Agoura Hills Redevelopment Agency (City RDA) (28661 Canwood Street), which is located between Agoura Business Center West parcel and the Agoura Business Center North parcel. Note that the street improvements and infrastructure in front of the Agoura Business Center North/West parcels were already incorporated into the original project descriptions for the projects, and analyzed as part of the previous entitlements.

The specified street and infrastructure improvements to occur in front of the City RDA parcel fronting Canwood Street would include:

- Installation of utilities (water, hydrant, gas, cable, telephone, storm drain);
- Installation of a curb, gutter, sidewalk on north side;
- Installation of a swale on south side;
- Installation of a street light, removal of an existing street light; and
- Street A.C. overlay and striping to include a third "storage lane" in the middle of the road for left turns but not a regular travel lane. In front of "West" parcel, this would involve additional paving to widen the roadway to accommodate the third lane. For the other parcels, there is sufficient room and only striping would be needed.

The specified street and infrastructure improvements along the portion of the City RDA parcel fronting Derry Avenue would include:

• Minor tie-ins, including utilities, sidewalk, curb, gutter on west side only (the east side already has these improvements).

These roadway improvements, involving minor changes to the 28661 Canwood Street property and the adjacent right-of-way, were not analyzed in the previously approved IS-MNDs for the Agoura Business Center West LLC/Agoura Business Center North LLC projects.

The development agreement also provides standard provisions relating to periodic review, cooperation between the parties, indemnification of the parties and diagrams and descriptions of the affected properties and the proposed improvements. The development agreement would incorporate by reference the City's approvals and conditions on the developers' properties.

PUBLIC AGENCIES WHOSE APPROVAL MAY BE REQUIRED FOR SUBSEQUENT ACTIONS (e.g. permits, financing approval, or participation agreement):

None other than the City of Agoura Hills (the development agreement would incorporate by reference the City's approvals and conditions on the developers' properties).

ENVIRONMENTAL FACTORS AFFECTED

The environmental factors checked below would be potentially affected by this project, involving at least one impact that could be lessened to a level of insignificance through incorporation of mitigation.

	Aesthetics	Agriculture Resources	Air Quality
	Biological Resources	Cultural Resources	Geology / Soils
	Greenhouse Gas Emissions	Hazards & Hazardous Materials	Hydrology / Water Quality
	Land Use / Planning	Mineral Resources	🗌 Noise
	Population / Housing	Public Services	Recreation
\boxtimes	Transportation/Traffic	Utilities / Service Systems	

DETERMINATION

On the basis of this initial evaluation:

- I find that the proposed project COULD NOT have a significant effect on the environment, and a NEGATIVE DECLARATION would be prepared.
- I find that although the proposed project could have a significant effect on the environment, there would not be a significant effect in this case because revisions in the project have been made by or agreed to by the applicant. A MITIGATED NEGATIVE DECLARATION would be prepared.
- I find that the proposed project MAY have a significant effect on the environment, and an ENVIRONMENTAL IMPACT REPORT is required.
- I find that the proposed project MAY have a "potentially significant impact" or "potentially significant unless mitigated" on the environment, but at least one effect 1) has been adequately analyzed in an earlier document pursuant to applicable legal standards, and 2) has been addressed by mitigation measures based on the earlier analysis as described on attached sheets. An ENVIRONMENTAL IMPACT REPORT is required, but it must analyze only the effects that remain to be addressed.
- I find that although the proposed project could have a significant effect on the environment, because all potentially significant effects (a) have been analyzed adequately in an earlier EIR pursuant to applicable standards, and (b) have been avoided or mitigated pursuant to that earlier EIR, including revisions or mitigation measures that are imposed upon the proposed project, nothing further is required.

Allison Čook, Principal Planner City of Agoura Hills

EVALUATION OF ENVIRONMENTAL IMPACTS

I. AESTHETICS – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Have a substantial adverse effect on a scenic vista?			\boxtimes	
b) Substantially damage scenic resources, including, but not limited to, trees, rock outcroppings, and historic buildings within a state scenic highway?			\boxtimes	
c) Substantially degrade the existing visual character or quality of the site and its surroundings?			\boxtimes	
d) Create a new source of substantial light or glare that would adversely affect day or nighttime views in the area?			\boxtimes	

a, c. The project site is surrounded by commercial and light industrial development to the east and west, Canwood Street to the south, and multi-family residential development to the north. U.S. 101 is located south of Canwood Street. Commercial and industrial uses are located south of the project site, across Canwood Street, and east of the project site, across Derry Avenue. Figure 2 shows the location of the project site within Agoura Hills. U.S. 101 runs parallel to Canwood Street to the south.

The majority of the project site is zoned Business Park-Manufacturing (BP-M), while a portion of the southern part of the project site is zoned Commercial Retail-Service (CRS). The entire project site is within the Freeway Corridor Overlay District (FC) (City of Agoura Hills Zoning Map, revised 2011). The purpose of the FC overlay district is to recognize the importance of land use, architectural design, and the appearance of development within the freeway corridor, which is a gateway into the City of Agoura Hills. The standards of the FC overlay district include requirements for naturalistic and native landscaping; use of compatible colors and materials to preserve and enhance scenic quality; and screening of unsightly uses with berms, decorative walls or landscaping. Moreover, development in this zone is required to be low intensity, compatible with a semi-rural character and have building facades that are articulated on all sides, and treated with natural materials and earth tones (City of Agoura Hills Municipal Code Section 9541.1).

The project site generally slopes upward from south to north. Vegetation within the site is sparse and is dominated by non-native, ruderal species (Refer to Figure 3). According to the City of Agoura Hills General Plan, Ladyface Mountain is a focal point of community pride and parallels the U.S. 101 corridor. The City of Agoura Hills General Plan identifies the following road segments as valuable scenic resources in the community that provide scenic views of the Santa Monica Mountains, including Ladyface Mountain:

- Reyes Adobe Road from Thousand Oaks Blvd. to Agoura Road
- Thousand Oaks Blvd. from westerly City limits to easterly City limits
- Agoura Road from westerly City limits to easterly City limits
- Kanan Road from Agoura Road south to the City limits

In addition, U.S. 101 is designated as eligible for State scenic highway designation.

The proposed development agreement would not affect scenic views from the aforementioned road segments. Buildings within the FC overlay district are required to comply with Municipal Code Section 965.8, which regulates the signage allowable on buildings.

Both of the previously approved developments on the project site were determined to result in less than significant impacts because they would be located among existing development, would be similar in size and scale to existing surrounding uses, and would utilize grading, and landscaping sensitive to the existing landscape within the area. The buildout characteristics of the two previously approved developments would remain unchanged under the proposed development agreement. Development of the previously approved Agoura Hills Business Park Project required Mitigation Measure AES-1, which required approval of a landscape plan prior to issuance of building permits (Agoura Hills Business Park IS-MND, June 2008). This mitigation measure would continue to apply under the proposed development agreement. The proposed development agreement would be consistent with the goals of the Agoura Hills General Plan and the City of Agoura Hills Municipal Code.

The specified street and infrastructure improvements would not obstruct vistas of ridgelines in the City, or views of Ladyface Mountain, or otherwise result in any additional impact to scenic vistas or the existing visual character of the site. Therefore, the proposed development agreement would not adversely affect a scenic vista or degrade the existing visual character or quality of the site and its surroundings.

Existing commercial and light industrial development located in the vicinity of the project site can be seen from U.S. 101. Ladyface Mountain is located south of Canwood Street and U.S. 101. The specified street and infrastructure improvements would not alter public viewsheds between Canwood Street and Ladyface Mountain, or the ridgelines along the southern edge of the City (on the south side of U.S. 101). Therefore, the proposed development agreement would not adversely affect scenic vistas from public viewpoints. Impacts would be **less than significant**.

b. The project site is visible from U.S. 101, albeit restricted by existing development along Canwood Street. While U.S. 101 is eligible for designation as a state scenic highway, it is not officially designated as such. There are no rock outcroppings, historic buildings, or other scenic resources on the project site.

As discussed in Section IV, *Biology*, there is minimal onsite native vegetation, and no specialstatus plant species in the project vicinity. The previously approved Agoura Hills Business Park Project was determined to require the removal of one oak tree protected under the City's Oak Tree Ordinance and the encroachment into the protected zone of one other protected oak tree. An Oak Tree Permit from the City Department of Planning and Community Development would still be required prior to the issuance of a grading permit for the approved development. In addition, development of the previously approved Agoura Hills Business Park Project prescribed Mitigation Measure AES-1, which required approval of a landscape plan prior to issuance of building permits (Agoura Hills Business Park IS-MND, June 2008). This mitigation measure would continue to apply under the proposed development agreement. The Agoura Business Center West Project was determined to result in less than significant impacts in this regard. Buildout characteristics of these two previously approved projects would remain unchanged. The specified street and infrastructure improvements would not result in significant impacts to trees, rock outcroppings, historic buildings or other scenic resources. Therefore, this impact would be **less than significant**.

d. The project site is currently vacant, with the exception of a surface parking lot in the eastern portion of the site. The lights and reflective surfaces of the automobiles in the parking lot are the only existing sources of light and glare on the project site. The light industrial and commercial developments located adjacent to the project site create light and glare in the vicinity of the project site.

Section 9305 of the Agoura Hills Municipal Code states that, "all lights and glare associated with operations of commercial buildings shall be shielded or directed so as to not illuminate adjacent businesses or cause glare to motorists."

The proposed development agreement would not involve the construction of new buildings or structures. Light and glare associated with the previously approved development on the project site would not be out of character with the existing surrounding land uses, which include primarily commercial and industrial uses. The closest residential neighborhoods lie approximately 700 feet northwest of the project site and approximately 900 feet east of the project site. The two previously approved projects incorporated design features to ensure that light cast by those projects would not adversely affect residents to the north or east of the project site. The buildout characteristics of these developments would remain unchanged under the proposed development agreement, and the development agreement would incorporate by reference the City's approvals and conditions on the developers' properties.

The specified street and infrastructure improvements, which include the replacement of an existing street light, would be the only new physical development that would result from the proposed development agreement. The proposed development agreement would not introduce new sources of light or glare on the project site. Therefore, impacts related to light and glare would be **less than significant**.

II. AGRICULTURE RESOURCES: In determining whether impacts to agricultural resources are significant environmental effects, lead agencies may refer to the California Agricultural Land Evaluation and Site Assessment Model (1997) prepared by the California Dept. of Conservation as an optional model to use in assessing impacts on agriculture and farmland. In determining whether impacts to forest resources, including timberland, are significant environmental effects, lead agencies may refer to information compiled by the California Department of Forestry and Fire Protection regarding the state's inventory of forest land, including th Forest and Range Assessment project; and forest carbor measurement methodology provided in Forest Protocols adopted by the California Air Resources Board. Would th project:

a) Convert Prime Farmland, Unique Farmland, or Farmland of Statewide Importance (Farmland), as shown on the maps prepared pursuant to the Farmland Mapping and Monitoring Program of the California Resources Agency, to non-agricultural use?

b) Conflict with existing zoning for agricultural use, or a Williamson Act contract?

c) Conflict with existing zoning for, or cause rezoning of, forest land (as defined in Public Resources Code section 12220(g)), timberland (as defined by Public Resources Code section 4526), or timberland zoned Timberland Production (as defined by Government Code section 51104(g))?

d) Result in the loss of forest land or conversion of forest land to non-forest use?

e) Involve other changes in the existing environment which, due to their location or nature, could result in conversion of Farmland, to non-agricultural use or conversion of forest land to non-forest use?

ie n ie	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
ו כ				
				\boxtimes
				\boxtimes
1				
				\boxtimes
				\boxtimes
				\boxtimes

a. The project site is previously disturbed, vacant land, and is not Prime Farmland, Unique Farmland, or Farmland of Statewide Importance as shown on the maps prepared by the Farmland Mapping and Monitoring Program (California Department of Conservation, 2008). The proposed development agreement does not involve development of new floor area. The only new physical development resulting from the proposed development agreement would be the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. **No impact** would occur.

b, c. The project site is currently zoned Business Park Manufacturing (BP-M) and Commercial Retail/ Service (CRS). The project site is additionally within the Freeway Corridor (FC) overlay zone. The City does not have agricultural zoning, timberland zoning, or Williamson Act contracts. Therefore, there would be no conflict with zoning for agricultural use or with a Williamson Act Contract. **No impact** would occur.

d. The project site is previously disturbed, vacant land and is not forested. **No impact** would occur.

e. The project site is previously disturbed, vacant land. The proposed development agreement, including the specified street and infrastructure improvements, would not result in the loss of farmland or forest land. Therefore, **no impact** would occur.

III. AIR QUALITY Where available, the significance criteria established by the applicable air quality management or air pollution control district may be relied upon to make the following determinations. Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Conflict with or obstruct implementation of the applicable air quality plan?			\boxtimes	
b) Violate any air quality standard or contribute substantially to an existing or projected air quality violation?			\boxtimes	
c) Result in a cumulatively considerable net increase of any criteria pollutant for which the project region is non- attainment under an applicable federal or state ambient air quality standard (including releasing emissions that exceed quantitative thresholds for ozone precursors)?			\boxtimes	
d) Expose sensitive receptors to substantial pollutant concentrations?			\boxtimes	
e) Create objectionable odors affecting a substantial number of people?				\boxtimes

a. The project site is located in the South Coast Air Basin, which is within the jurisdiction of the South Coast Air Quality Management District (SCAQMD). According to SCAQMD Guidelines, to be consistent with the Air Quality Management Plan (AQMP), a project must conform to the local General Plan and must not result in or contribute to an exceedance of the City's projected population growth forecast. The proposed development agreement involves a 10-year time extension for the entitlements for each of the two previously approved projects and would require the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement and development of the previously approved projects would not introduce new residential uses or directly generate an increase in population. Consequently, the project would not contribute to an exceedance of the City's projected population growth forecast. The proposed development agreement and development agreement and development of the previously approved projects would not introduce new residential uses or directly generate an increase in population. Consequently, the project would not contribute to an exceedance of the City's projected population growth forecast. The project's potential impact associated with air quality management plans would be **less than significant**.

b, c. The project site is located in the South Coast Air Basin, which is in nonattainment for the federal 8-hour ozone standard, the State 1-hour ozone standard, the federal 24-hour PM_{10} standard, and the State 24-hour and annual PM_{10} standards. The South Coast Air Basin is designated as attainment or unclassified for all other federal and state ambient air quality standards. Reactive organic gas (ROG), NO_X, and fine particulate matter (PM_{2.5} and PM₁₀) are the pollutants of primary concern for projects located in the SCAQMD.

Long-Term Operational Emissions

The proposed development agreement involves a 10-year time extension for the entitlements for each of the two previously approved projects and would require the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement would not result in any new pollution-generating uses on the project site. Similarly, the proposed development agreement and development of the previously approved projects would not introduce new traffic-generating uses that would result in air pollutant emissions from mobile sources. Therefore, the proposed development agreement's long-term impact to regional air quality would be **less than significant**.

Short-Term Construction Emissions.

Construction vehicles and equipment traveling along unpaved roads, grading, trenching, and stockpiled soils have the potential to generate fugitive dust (PM₁₀) through the exposure of soil to wind erosion and dust entrainment. In addition, exhaust emissions associated with heavy construction equipment would potentially degrade air quality. PM₁₀ and exhaust emissions associated with construction activities are considered to be temporary air quality impacts.

Temporary emissions from construction of the specified street and infrastructure improvements were estimated using the California Emissions Estimator Model (CalEEMod) (see Appendix A for air quality modeling assumptions and results). During project site preparation, the soils that underlie portions of the site could be turned over and pushed around, exposing the soil to wind erosion and dust entrainment by onsite operating equipment. The majority of emissions associated with construction activities on site come from off-road construction equipment, but some emissions are also associated with construction worker trips. Rule 403 of the SCAQMD Handbook requires implementation of measures to minimize emissions for all dust generating activity, regardless of whether it exceeds thresholds. The non-attainment status of the South Coast Air Basin for PM₁₀ dust emissions requires that Best Available Control Measures (BACMs) be used to minimize regional cumulative PM₁₀ impacts from all construction activities, even if any single project does not cause the thresholds to be exceeded. Additionally, the non-attainment basin status and the cumulative impact of all construction suggests that all reasonably available control measures for diesel exhaust shall be implemented even if individual thresholds are not exceeded.

SCAQMD has developed Localized Significance Thresholds (LSTs) in response to the Governing Board's Environmental Justice Enhancement Initiative (1-4). LSTs were devised in response to concern regarding exposure of individuals to criteria pollutants in local communities. LSTs represent the maximum emissions from a project that would not cause or contribute to an air quality exceedance of the most stringent applicable federal or state ambient air quality standard at the nearest sensitive receptor, taking into consideration ambient concentrations in each source receptor area (SRA), project size, distance to the sensitive receptor, etc. However, LSTs only apply to emissions within a fixed stationary location, including idling emissions during both project construction and operation. LSTs have been developed only for NO_X, CO, PM₁₀ and PM_{2.5}. LSTs are not applicable to mobile sources such as cars on a roadway (Final Localized Significance Threshold Methodology, SCAQMD, June 2003).

LSTs have been developed for emissions within areas up to 5 acres in size, with air pollutant modeling recommended for activity within larger areas. The SCAQMD provides a lookup table for sites that measure 1, 2 or 5 acres. The potential area of disturbance for the specified street and infrastructure improvements measures less than one acre and is located in Source Receptor Area 6 (SRA-6), which is designated by the SCAQMD as the West San Fernando Valley and includes the City of Agoura Hills. The LST construction emission thresholds shown in Table 2 are from the LST lookup tables for 1-acre project sites. The thresholds in Table 2 were determined based on the distance to nearby sensitive receptors.

Pollutant	Allowable emissions 82 feet from the 1- acre site boundary (Ibs/day)
Gradual conversion of NO _x to NO ₂	103
СО	426
PM ₁₀	4
PM _{2.5}	3

Table 2SCAQMD LSTs for Construction in SRA-6

Source: http://www.aqmd.gov/CEQA/handbook/LST/appC.pdf, accessed online February 2012.

As indicated in Table 3, emissions generated by the construction of the specified street and infrastructure improvements would be below SCAQMD regional thresholds and LSTs for this location. Nevertheless, Rule 403 of the SCAQMD Handbook requires implementation of measures to minimize emissions for all dust generating activity, regardless of whether it exceeds the thresholds. The non-attainment status of the South Coast Air Basin for PM₁₀ dust emissions requires that Best Available Control Measures (BACMs) such as adequate watering and the utilization of vegetative covering be implemented to minimize regional cumulative PM₁₀ impacts from all construction activities, even if any single project does not cause the thresholds to be exceeded. Additionally, the non-attainment basin status and the cumulative impact of all construction suggests that all reasonably available control measures for diesel exhaust shall be implemented even if individual thresholds are not exceeded. Implementation of SCAQMD rules would reduce construction impacts to air quality to a **less than significant** level.

d. Certain population groups are considered particularly sensitive to air pollution. Sensitive receptors include health care facilities, retirement homes, school and playground facilities, and residential areas. The closest sensitive receptors to the project site are residents located immediately north of the project site and one child care center approximately 275 feet to the west of the project site. The proposed development agreement involves a 10-year time extension for the entitlements for two previously approved development project, as well as the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement would not result in any new pollution-generating uses on the project site. As such, the proposed development agreement would not result in new development that would expose sensitive receptors to substantial pollutant concentrations and impacts would be **less than significant**.

Emission Source	ROG	NOx	со	PM 10	PM _{2.5}
Site Preparation (on-site)	1.7	12.6	8.7	1.3	0.8
Site Preparation (off-site)	>0.1	>0.1	0.4	0.1	>0.1
Grading (on-site)	2.0	13.9	9.5	1.8	1.5
Grading (off-site)	0.1	0.1	0.7	0.2	>0.1
Paving (on-site)	2.4	14.5	9.8	1.2	1.2
Paving (off-site)	0.1	0.1	1.3	0.3	>0.1
Maximum daily on-site emissions	2.4	14.5	9.8	1.8	1.5
Maximum daily total emissions	2.5	14.7	11.1	2.0	1.5
SCAQMD Thresholds (peak day)	75	100	550	150	55
Exceed SCAQMD Thresholds?	NO	NO	NO	NO	NO
Localized Significance Thresholds	n/a	103	426	4	3
Exceed Localized Significance Thresholds?	NO	NO	NO	NO	NO

Table 3Maximum Daily Construction Emissions1 (pounds per day)

¹Includes worker trips.

Source: California Emissions Estimator Model (CalEEMod) (See Appendix A for model assumptions and results)

e. The specified street and infrastructure improvements along Canwood Street are not anticipated to generate any objectionable odors. In addition, the proposed use of the site is not identified in "Land Uses Associated with Odor Complaints" of the 1993 SCAQMD's CEQA Air Quality Handbook. Therefore, it the proposed development agreement would not generate objectionable odors; there would be **no impact** associated with odors.

IV. BIOLOGICAL RESOURCES – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Have a substantial adverse effect, either directly or through habitat modifications, on any species identified as a candidate, sensitive, or special status species in local or regional plans, policies, or regulations, or by the California Department of Fish and Game or U.S. Fish and Wildlife Service?				
b) Have a substantial adverse effect on any riparian habitat or other sensitive natural community identified in local or regional plans, policies, regulations, or by the California Department of Fish and Game or U.S. Fish and Wildlife Service?				\boxtimes
c) Have a substantial adverse effect on federally protected wetlands as defined by Section 404 of the Clean Water Act (including, but not limited to, marsh, vernal pool, coastal, etc.) through direct removal, filling, hydrological interruption, or other means?				\boxtimes
d) Interfere substantially with the movement of any native resident or migratory fish or wildlife species or with established native resident or migratory wildlife corridors, or impede the use of native wildlife nursery sites?			\boxtimes	
e) Conflict with any local policies or ordinances protecting biological resources, such as a tree preservation policy or ordinance?				\boxtimes
f) Conflict with the provisions of an adopted Habitat Conservation Plan, Natural Community Conservation Plan, or other approved local, regional, or state habitat conservation plan?				\boxtimes

A Rincon Consultants biologist conducted a reconnaissance field survey of the previously approved Agoura Hills Business Center West project site on January 7, 2009 to document onsite biological resources. Michael Brandman Associates prepared a Biological Resources Assessment, dated November 14, 2006, for the previously approved Agoura Hills Business Park project.

The project site is surrounded by commercial and light industrial development to the east and west, Canwood Street to the south, and multi-family residential development to the north. U.S. 101 is located south of Canwood Street. Commercial and industrial uses are located south of the project site, across Canwood Street, and east of the project site, across Derry Avenue.

The project site consists of disturbed, rolling hills sloping from the north to the south. While vegetation within the site is sparse and dominated by non-native, ruderal species, there are 14 native valley oak trees clustered in the western parcel on the project site.

a. The project site provides suitable habitat for four sensitive wildlife species: coast horned lizard (*Phrynosoma coronatum blainvillei*), coastal western whiptail (*Aspidoscelis tigris stejnegeri*), golden eagle (*Aquila chryaetos*), and the burrowing owl (*Athene cunicularia*). These four species are classified by the California Department of Fish and Game as California Species of Concern;

however, none of these sensitive wildlife species are federally or state-listed as endangered or threatened. One of the four species, the burrowing owl (*Athene cunicularia*), is protected by the Migratory Birds Treaty Act (MBTA) and California Fish and Game Code (CFG). Given that the project site lacks the habitat typically associated with these species, the soils onsite have been disturbed, and the area surrounding the project site is developed, it is unlikely that these species would occur on the project site or in the nearby vicinity. The disturbed nature of the project site diminishes the possibility of special-status plant species on the site.

The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street. Development of the previously approved Agoura Hills Business Park Project and Agoura Business Center West Project required Mitigation Measure BIO-1, which required that removal or pruning of trees be conducted between September 15 and February 15, to avoid the accidental take of any migratory bird species or raptors (Agoura Hills Business Park IS-MND, June 2008; Agoura Business Center West IS-MND, May 2009). In addition, development of the previously approved Agoura Hills Business Park Project required Mitigation Measure BIO-2, which requires that a qualified biologist conduct surveys for burrowing owls in potential habitat areas 30 days prior to construction during both the wintering and nesting seasons (Agoura Hills Business Park IS-MND, June 2008). These measures would continue to apply to the previously approved projects under the new development agreement. Therefore, impacts related to nesting birds, candidate, sensitive or special status species would be **less than significant**.

b. The project site is not located within any designated critical habitat areas and no riparian habitat or other sensitive natural community is known to existing on the project site. Due to the disturbed nature of the project site and lack of sensitive habitat, **no impact** to any riparian habitat or other sensitive natural community is expected.

c. No jurisdictional wetlands are present onsite. As such, **no impact** to wetlands would occur.

d. The project site is located in an area characterized by multi-family residential and industrial development. Although the project site is not developed, the northern portion has been previously graded and is generally surrounded by development that limits wildlife use surrounding the site. The site is not located within a significant wildlife movement corridor (City of Agoura Hills, General Plan March 2010), and the project site does not provide any substantial or functional wildlife habitat for migrating wildlife. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. The specified street and infrastructure improvement of any native resident or migratory wildlife species or with established native resident or migratory wildlife species or with established native resident or migratory wildlife species to wildlife movement would be **less than significant**.

e. Oaks (*Quercus* spp.) within the City of Agoura Hills are protected by the City's Oak Tree Ordinance (City Council Resolution No. 374, City of Agoura Hills General Plan, March 2010). A permit is required to cut, move, or remove any oak tree larger than two inches in diameter, measured 3.5 feet above the tree's natural grade. In addition, a permit is required for encroachment within a qualified oak tree's protected zone, defined as no less than 15 feet from the trunk of an oak tree (City of Agoura Hills Municipal Code, Appendix A, Oak Tree Preservation). The previously approved Agoura Hills Business Park Project was determined to require the removal of one oak tree protected under the City's Oak Tree Ordinance and the encroachment into the protected zone of one other protected oak tree. Development of the previously approved Agoura Hills Business Park Project required Mitigation Measure BIO-3, which required that the project incorporate the recommendations of the City's Oak Tree Consultant, including planting of four replacement oak trees, fencing of oak trees to be preserved, notice to the City prior to approved work within the protected zone of any oak tree, and other restrictions on construction work within the protected zone of any oak tree (Agoura Hills Business Park IS-MND, June 2008). This mitigation measure would continue to apply under the proposed development agreement. In addition, an Oak Tree Permit from the City Department of Planning and Community Development would still be required prior to the issuance of a grading permit for the approved development. The proposed development agreement would not involve construction activities that would necessitate the removal of any existing oak trees, or encroach into the protected zone of any oak tree. No impact would occur.

f. The project site is located within an urban area that is not subject to an adopted Habitat Conservation Plan, Natural Conservation Community Plan, or other approved local, regional, or state habitat conservation plan (City of Agoura Hills General Plan, March 2010). **No impact** would occur.

V. CULTURAL RESOURCES – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Cause a substantial adverse change in the significance of a historical resource as defined in §15064.5?				\boxtimes
b) Cause a substantial adverse change in the significance of an archaeological resource pursuant to §15064.5?		\boxtimes		
c) Directly or indirectly destroy a unique paleontological resource or site or unique geologic feature?		\boxtimes		
d) Disturb any human remains, including those interred outside of formal cemeteries?		\boxtimes		

a. The project site is currently vacant and therefore lacking historical resources (Rincon Consultants, site visits, January 15, 2008 and January 19, 2008). **No impact** to historical resources would occur.

b-d. The project site is not known to contain any archaeological resources, paleontological resources or human remains (Agoura Hills Business Park IS-MND, June 2008; Agoura Business Center West IS-MND, May 2009). The proposed development agreement does not involve development of new floor area. The proposed development agreement would only result in new physical development related to the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. Although no archaeological resources,

paleontological resources or human remains are known to be present on the project site, site grading has the potential to disturb as yet undiscovered cultural resources. Development of the previously approved Agoura Hills Business Park Project and Agoura Business Center West Project required mitigation measures related to archaeological monitoring and notification of and evaluation by a qualified archaeologist. These measures would continue to apply to the previously approved development under the new development plan. Identical measures would be required for the specified street and infrastructure improvements; therefore, impacts would be **less than significant with mitigation incorporated**.

Mitigation Measures

Implementation of Mitigation Measures CR-1 and CR-2 would reduce impacts to unknown archaeological resources and human remains to a less than significant level.

CR-1 Monitoring. A qualified archaeologist shall monitor any grading, trenching, excavation, or other subsurface work that occurs in undisturbed soil. If artifacts are discovered, the developer shall notify the City of Agoura Hills' Environmental Analyst immediately, and construction activities shall cease until the archaeologist has documented and recovered the resources. Equipment stoppages prescribed by the archaeologist shall only involve those pieces of equipment that have actually encountered significant or potentially significant resources, and should not be construed to require stoppage of all equipment on the site unless the resources are thought by the archaeologist to be distributed throughout the entire site. The purpose of stopping the equipment is to protect cultural/scientific resources that would otherwise be impacted, and said equipment may undertake work in other areas of the site away from the discovered resources. If the find is determined by the archaeologist to be a unique archaeological resource, as defined by Section 2103.2 of the Public Resources Code, the site shall be treated in accordance with the provisions of Section 21083.2 of the Public Resources Code with mitigation as appropriate. If the find is determined not to be a unique archaeological resource, no further action is necessary and construction may continue.

In the event of discovery of human remains, work shall stop until the coroner has determined that no investigation of the cause of death is required; or, if descendants have made a recommendation of the property owner regarding proper disposal of the remains, or until descendants have failed to make a recommendation within 24 hours of notification. If no recommendation is received, remains shall be interred with appropriate dignity on the property in a location not subject to future development.

CR-2 Evaluation and Notification. Should archaeological resources be discovered and avoidance proves infeasible, the importance of the site

shall be evaluated by a qualified archaeologist. Preservation of sites in-place is the preferred manner of avoiding damage to historic and prehistoric archaeological resources.

	Potentially Significant	Less Than Significant With Mitigation	Less Than Significant	No
VI. GEOLOGY AND SOILS – Would the project:	Impact	Incorporated	Impact	Impact
 a) Expose people or structures to potential substantial adverse effects, including the risk of loss, injury, or death involving: 				
 i) Rupture of a known earthquake fault, as delineated on the most recent Alquist-Priolo Earthquake Fault Zoning Map issued by the State Geologist for the area or based on other substantial evidence of a known fault? Refer to 	_	_		
Division of Mines and Geology Special Publication 42.			\boxtimes	
ii) Strong seismic ground shaking?			\boxtimes	
iii) Seismic-related ground failure, including liquefaction?			\boxtimes	
iv) Landslides?			\boxtimes	
b) Result in substantial soil erosion or the loss of topsoil?			\boxtimes	
c) Be located on a geologic unit or soil that is unstable, or that would become unstable as a result of the project, and potentially result in on- or off-site landslide, lateral spreading, subsidence, liquefaction or collapse?			\boxtimes	
d) Be located on expansive soil, as defined in Table 18-1- B of the Uniform Building Code (1994), creating substantial risks to life or property?			\boxtimes	
e) Have soils incapable of adequately supporting the use of septic tanks or alternative waste water disposal systems where sewers are not available for the disposal of waste water?				\bowtie

The following analysis is based partially on Geotechnical Reports prepared for the previously approved Agoura Hills Business Park and Agoura Hills Business Center West Projects. The J. Byer Group prepared a Geologic Soils and Exploration report for the Agoura Hills Business Park Project in 1996, an updated report in 2004 and three addendums to the 2004 report. In addition to a rippability study being performed for the Agoura Hills Business Park project, Gorian and Associates prepared a Geotechnical Report for the Agoura Hills Business Center West Project in 2007. The findings of these reports have been incorporated by reference throughout this analysis.

a (i). There are no known active or potentially active faults within the immediate project area, as identified by the USGS mapping system (2008) or the State Geologist (Gorian & Associates, 2007; The J. Byer Group, 2004). The project site is situated in the seismically active Transverse Ranges Geomorphic province, and like any other area in the City, would experience ground

motion from earthquakes generated on regional faults, include the Malibu, San Fernando, Northridge, San Andreas, Newport-Inglewood and Malibu Coast Faults. The proposed development agreement would grant a 10-year time extension for the entitlements for the previously approved Agoura Hills Business Park and Agoura Hills Business Center West Projects, and would also include specified street and infrastructure improvements along Canwood Street. Buildings developed pursuant to the two previously approved projects would be required to be designed in accordance with City Building Code and California Building Code, and the buildout characteristics of these two previously approved projects would remain unchanged. The proposed development agreement does not involve the construction of any new structures. Therefore, impacts relating to rupture of a known fault would be **less than significant**.

a (ii, iii). Several active and/or potentially active faults in the surrounding region could produce ground shaking at the site. These faults include the Malibu Coast fault San Fernando, Northridge, San Andreas, Newport-Inglewood and Malibu Coast Faults. Each of these faults is located in close enough proximity to cause earth shaking in the case of high magnitude earthquakes (Gorian & Associates, 2007; The J. Byer Group, 2004). The City of Agoura Hills is on the Seismic Hazard Map for the Thousand Oaks Quadrangle, published by the California Department of Conservation in 2000 (City of Agoura Hills, February 2010). The map identifies an area within Agoura Hills that is subject to liquefaction in the eastern portion of the City, located immediately south of U.S. 101 and partially included in the Agoura Village Specific Plan area. This area of potential liquefaction is located approximately 0.20 miles south of the project site. Therefore, although it is possible that ground shaking may occur at the project site due to its proximity to active faults, secondary effects such as liquefaction are not expected to occur (J. Byer Group, 2004). Additionally, development of the previously approved Agoura Hills Business Center West Project required Mitigation Measure GEO-1, which required that the development incorporate design and construction recommendations of the City of Agoura (Agoura Business Center West IS-MND, May 2009). This mitigation measure would continue to apply under the proposed development agreement. Furthermore, the only new physical development related to the proposed development agreement would be the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. It does not involve the construction of new structures that would be impacted by ground shaking or liquefaction. In addition, the City of Agoura Hills is on the Seismic Hazard Map for the Thousand Oaks Quadrangle, published in November 2000. The map identifies an area within Agoura Hills that is subject to liquefaction in the eastern portion of the City, which does not include the project site (City of Agoura Hills, General Plan 2035 EIR, February 2010). Therefore, impacts associated with liquefaction and other seismic-related ground failure would be less than significant.

a (iv). The proposed development agreement is not located in an area delineated as a seismic landslide hazard zone by the California Department of Conservation Seismic Hazards Zone Map (1998) and the City of Agoura Hills General Plan (2010). According to the 2007 Gorian and Associates geotechnical report, no landslides present within the immediate area would affect the previously approved development. Therefore, impacts would be **less than significant**.

b. The proposed development agreement involves a 10-year extension for the entitlements for each of the two previously approved projects, as well as specified street and infrastructure

improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. Construction of the specified street improvements would increase the amount of impervious surface onsite over existing conditions. During construction of the specified infrastructure improvements, soil may erode due to wind entrainment and sediment may travel into storm drainage facilities. To reduce these impacts, standard dust control measures (AQMD Rule 403) and a Stormwater Pollution Prevention Plan would be required for project development (refer to Section II, *Air Quality*; and Section IX, *Hydrology and Water Quality*). These standard requirements and project components would serve to reduce the potential for soil loss on the project site, due to erosion, to a **less than significant** level.

c. According to the California Department of Conservation Seismic Hazards Zone Map (1998) and the City of Agoura Hills General Plan (2010), the potential for liquefaction to occur on the project site is low. As discussed above, potential landslides were not found in the vicinity of the project site. The previously approved Agoura Hills Business Center West Project required Mitigation Measure GEO-1, which required that the development incorporate design and construction recommendations of the City of Agoura (Agoura Business Center West IS-MND, May 2009). This mitigation measure would continue to apply under the proposed development agreement. Additionally, the only new physical development related to the proposed development of the City RDA parcel fronting Canwood Street. The proposed development agreement does not include the construction of any new buildings or structures. Therefore, conditions related to unstable soils, including lateral spreading, subsidence, and collapse, would be **less than significant**.

d. Development of the previously approved Agoura Hills Business Park Project and Agoura Business Center West Project required Measure GEO-1, which required that the Agoura Hills Business Park Project incorporate design and construction recommendations contained in the Geologic and Soils Engineering and Exploring Update and subsequent addendums for that project, conducted by the J. Byer Group (Agoura Hills Business Park IS-MND, June 2008), and Mitigation Measure GEO-1 which required that the Agoura Business Center West Project incorporate design and construction recommendations of the City of Agoura (Agoura Business Center West IS-MND, May 2009). These mitigation measures would continue to apply under the proposed development agreement. However, the buildout characteristics of these two previously approved projects would remain unchanged, and the only new physical development related to the proposed development agreement would be the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement does not include the construction of any new buildings or structures. Additionally, the proposed development agreement would incorporate by reference the City's approvals and conditions on the developers' properties. Therefore, potential impacts related to expansive soils would be less than significant.

e. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street. The proposed development agreement would not require the use of a septic system or an alternative wastewater disposal system. **No impact** would occur.

VII. GREENHOUSE GAS EMISSIONS – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Generate greenhouse gas emissions, either directly or indirectly, that may have a significant impact on the environment?			\boxtimes	
b) Conflict with an applicable plan, policy or regulation adopted for the purpose of reducing the emissions of greenhouse gases?				\boxtimes

Greenhouse gases (GHGs) are emitted by both natural processes and human activities. Of these gases, carbon dioxide (CO₂) and methane (CH₄) are emitted in the greatest quantities from human activities. Emissions of CO₂ are largely by-products of fossil fuel combustion, whereas CH₄ results from off-gassing associated with agricultural practices and landfills. Scientific modeling predicts that continued GHG emissions at or above current rates would induce more extreme climate changes during the4 21st century than were observed during the 20th century. Different types of GHGs have varying global warming potentials. The global warming potential of a GHG is the potential of a gas or aerosol to trap heat in the atmosphere over a specified timescale (generally, 100 years). Because GHGs absorb different amounts of heat, a common reference gas (CO₂) is used to relate the amount of heat absorbed to the amount of the gas emissions, referred to as "carbon dioxide equivalent" (CO₂E), and is the amount of a GHG emitted multiplied by its global warming potential.

According to the CalEPA's 2010 Climate Action Team Biennial Report, potential impacts of climate change in California may include loss in snow pack, sea level rise, more extreme heat days per year, more high ozone days, more large forest fires, and more drought years (CalEPA, April 2010). While these potential impacts identify the possible effects of climate change at a global and potentially statewide level, in general, scientific modeling tools are currently unable to precisely predict what impacts would occur locally.

Because the SCAQMD has not yet adopted GHG emissions thresholds that apply to land use projects where the SCAQMD is not the lead agency and no GHG emissions reduction plan or GHG emissions thresholds have been adopted in Agoura Hills, the proposed development agreement is evaluated based on the SCAQMD's recommended/ preferred option threshold for all land use types of 3,000 metric tons CO₂E per year (SCAQMD, "Proposed Tier 3 Quantitative Thresholds – Option 1", September 2010). It is important to note that the City has not recommended that threshold for any other purpose at this time, but that numeric threshold is recommended for this analysis.

a. The proposed development agreement involves a 10-year time extension for the entitlements for each of the two previously approved projects and would require the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement would not result in any new GHG-emitting uses on the project site. Similarly, the proposed development agreement would not introduce new traffic-generating uses that would result in GHG emissions from mobile sources. However, construction vehicles and equipment would emit GHGs during the construction phase.

Temporary GHG emissions from construction of the specified street and infrastructure improvements were estimated using the California Emissions Estimator Model (CalEEMod) (see Appendix A for construction modeling assumptions and results). Because climate change represents a long-term cumulative impact, emissions associated with construction activity (approximately 5.9 metric tons CO₂E) are generally amortized over a 30 year period (the anticipated life of the project) in order to more accurately compare them to the annual threshold. Therefore, the specified street and infrastructure improvements would result in approximately 0.2 metric tons CO₂E per year. Based on SCAQMD's recommended threshold of 3,000 metric tons CO₂E per year, the proposed development agreement would have a **less than significant** impact.

In addition to this analysis, because the previously approved IS-MNDs for the Agoura Business Center West and Agoura Hills Business Park Projects were approved prior to the passage of Senate Bill (SB) 97, which acknowledges that climate change requires analysis under CEQA, the potential GHG emissions of each of these two development projects are analyzed herein.

Agoura Business Center North Project

The Agoura Business Center North Project was formerly the Agoura Hills Business Park Project.

<u>Construction Emissions</u>. Based on the CalEEMod model results, construction activity for the Agoura Business Center North Project would result in an estimated 737 metric tons of CO₂E. Amortized over a 30-year period (the assumed life of the project), construction of the project would generate an estimated 25 metric tons of CO₂E per year.

<u>Energy Use</u>. Operation of the Agoura Business Center North Project would consume both electricity and natural gas. The generation of electricity through combustion of fossil fuels typically yields CO₂, and to a smaller extent, N₂O and CH₄. Electricity and natural gas consumption would generate approximately 524 metric tons of CO₂E per year.

<u>Solid Waste</u>. It is anticipated that the Agoura Business Center North Project would generate solid waste that would result in approximately 44 metric tons of CO_2E per year according to the CalEEMod output, which uses current waste disposal rates provided by CalRecycle.

<u>Water Use</u>. Based on the CalEEMod model estimate, water transportation to serve on site development would generate approximately 123 metric tons of CO_2E per year.

<u>Transportation</u>. Mobile source GHG emissions were estimated using total daily trips based on the Kunzman Associates traffic studies, which are based on the Institute of Transportation Engineers' *Trip Generation*, 8th Edition, 2008, and by the total vehicle miles traveled (VMT) estimated in CalEEMod. Based on the CalEEMod model estimate, mobile emissions resulting from on site development would generate an estimated 1,169 metric tons CO_2E per year.

<u>Combined Construction, Stationary and Mobile Source Emissions</u>. Table 4 combines the construction, operational (energy use, solid waste, and water use emissions), and mobile GHG

emissions associated with on site development for the Agoura Business Center North Project.

Agoura Dusiness Center North Project			
Emission Source	Annual Emissions (CO₂E)		
Construction	25 metric tons		
Operational Energy Solid Waste Water	524 metric tons 44 metric tons 123 metric tons		
Mobile	1,169 metric tons		
Total	1,885 metric tons		

Table 4
Combined Annual Emissions of Greenhouse Gases:
Agoura Business Center North Project

Sources: See Appendix B for calculations and for GHG emission factor assumptions.

The combined annual emissions would total 1,885 metric tons CO₂E per year. This emissions estimate indicates that the majority of the project's GHG emissions are associated with vehicular travel (62%). Based on SCAQMD's recommended threshold of 3,000 metric tons CO₂E per year, the Agoura Business Center North Project would have a **less than significant** impact.

Agoura Business Center West Project

<u>Construction Emissions</u>. Based on the CalEEMod model results, construction activity for the Agoura Business Center West Project would result in an estimated 337 metric tons of CO_2E . Amortized over a 30-year period (the assumed life of the project), construction of the project would generate an estimated 11 metric tons of CO_2E per year.

<u>Energy Use</u>. Operation of the Agoura Business Center West Project would consume both electricity and natural gas. The generation of electricity through combustion of fossil fuels typically yields CO₂, and to a smaller extent, N₂O and CH₄. Electricity and natural gas consumption would generate approximately 80 metric tons of CO₂E per year.

<u>Solid Waste</u>. It is anticipated that the Agoura Business Center West Project would generate solid waste that would result in approximately 10 metric tons of CO₂E per year according to the CalEEMod output, which uses current waste disposal rates provided by CalRecycle.

<u>Water Use</u>. Based on the CalEEMod model estimate, water transportation to serve on site development would generate approximately 10 metric tons of CO₂E per year.

<u>Transportation</u>. Mobile source GHG emissions were estimated using total daily trips

based on the Kunzman Associates traffic studies, which are based on the Institute of Transportation Engineers' *Trip Generation*, 8th Edition, 2008; San Diego Association of Governments, *Traffic Generators*, April 2002; and by the total vehicle miles traveled (VMT) estimated in CalEEMod. Based on the CalEEMod model estimate, mobile emissions resulting from on site development would generate an estimated 1,230 metric tons CO₂E per year.

<u>Combined Construction, Stationary and Mobile Source Emissions</u>. Table 5 combines the construction, operational (energy use, solid waste, and water use emissions), and mobile GHG emissions associated with on site development for the Agoura Business Center West Project.

Agoura Business Ochier West Project			
Emission Source	Annual Emissions (CO₂E)		
Construction	11 metric tons		
Operational Energy Solid Waste Water	80 metric tons 10 metric tons 10 metric tons		
Mobile	1,230 metric tons		
Total	1,341 metric tons		

Table 5Combined Annual Emissions of Greenhouse Gases:Agoura Business Center West Project

Sources: See Appendix B for calculations and for GHG emission factor assumptions.

The combined annual emissions would total 1,341 metric tons CO_2E per year. This emissions estimate indicates that the majority of the project's GHG emissions are associated with vehicular travel (92%). Based on SCAQMD's recommended threshold of 3,000 metric tons CO_2E per year, the Agoura Business Center West Project would have a **less than significant** impact.

b. Assembly Bill (AB) 32, signed in September 2006, requires the State's global warming emissions to be reduced to 1990 levels by 2020. After completing a comprehensive review and update process, the ARB-approved a 1990 statewide GHG level and 2020 limit of 427 MMT CO2E (ARB, October 2007).

Senate Bill (SB) 97, signed in August 2007, acknowledges that climate change requires analysis under CEQA. In March 2010, the California Resources Agency (Resources Agency) adopted amendments to the State CEQA Guidelines for the feasible mitigation of GHG emissions or the effects of GHG emissions. The adopted amendments give lead agencies the discretion to set quantitative or qualitative thresholds for the assessment and mitigation of GHG impacts.

Senate Bill (SB) 375, signed in August 2008, requires the inclusion of sustainable communities' strategies (SCS) in regional transportation plans (RTPs) for the purpose of reducing GHG

emissions. The bill requires the ARB to set regional targets for the purpose of reducing greenhouse gas emissions from passenger vehicles for 2020 and 2035.

None of these statewide regulations include requirements that apply to individual projects, such as the proposed development agreement, and no local or regional plans to reduce GHG emissions are currently in place. Therefore, the proposed development agreement would not conflict with any applicable plan, policy or regulation adopted for the purpose of reducing the emissions of greenhouse gases. **No impact** would occur.

VIII. HAZARDS AND HAZARDOUS MATERIALS – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Create a significant hazard to the public or the environment through the routine transport, use, or disposal of hazardous materials?				\boxtimes
b) Create a significant hazard to the public or the environment through reasonably foreseeable upset and accident conditions involving the release of hazardous materials into the environment?				\boxtimes
c) Emit hazardous emissions or handle hazardous or acutely hazardous materials, substances, or waste within one-quarter mile of an existing or proposed school?				\boxtimes
d) Be located on a site which is included on a list of hazardous materials sites compiled pursuant to Government Code Section 65962.5 and, as a result, would it create a significant hazard to the public or the environment?				\boxtimes
e) For a project located within an airport land use plan or, where such a plan has not been adopted, within two miles of a public airport or public use airport, would the project result in a safety hazard for people residing or working in the project area?				\boxtimes
f) For a project within the vicinity of a private airstrip, would the project result in a safety hazard for people residing or working in the project area?				\boxtimes
g) Impair implementation of or physically interfere with an adopted emergency response plan or emergency evacuation plan?				\boxtimes
h) Expose people or structures to a significant risk of loss, injury or death involving wildland fires, including where wildlands are adjacent to urbanized areas or where residences are intermixed with wildlands?			\boxtimes	

a) The proposed development agreement would grant a 10-year time extension for the entitlements for the previously approved Agoura Hills Business Park Project and Agoura Business Center West Project, including specified street and infrastructure improvements along

Canwood Street. The proposed development agreement would not involve the routine transport, use or disposal of hazardous substances. **No impacts** would occur.

b) There would be no hazardous materials, substances, or waste associated with the proposed development agreement. Therefore, the project would have **no impact** with release of hazardous materials into the environment.

c) The closest school is the Tutor Time Child Care/ Learning Center located on 5108 Clareton Dr., 0.3 miles away. As stated above, there would be no hazardous materials, substances, or waste associated with the proposed development agreement. No schools are located within ¹/₄ mile of the project site. Therefore, **no impact** would occur.

d) The project site does not appear on any hazardous material site list compiled pursuant to Government Code Section 65962.5 (Agoura Hills Business Park IS-MND, June 2008; Agoura Business Center West IS-MND, May 2009). The following databases were checked (January 23, 2012) for known hazardous materials contamination at the project site:

- Comprehensive Environmental Response, Compensation, and Liability Information System (CERCLIS) database;
- Geotracker search for leaking underground fuel tanks;
- Investigations- Cleanups (SLIC) and Landfill sites, Cortese list of Hazardous Waste and Substances Sites; and
- The Department of Toxic Substances Control's Site Mitigation and Brownfields Database.

The project site does not appear on any of the above lists; thus, **no impacts** would occur with respect to this issue.

e, f) There are no airports or airstrips located within the project vicinity. The project site is not within an area covered by an airport land use plan, nor is it located in the vicinity of a private air strip. **No impact** would occur.

g. Implementation of the proposed development agreement would not interfere with existing emergency evacuation plans, or emergency response plans in the area. The project would be required to comply with Fire Code and Los Angeles County Fire Department (LACFD) standards, including specific construction specifications, access design, location of fire hydrants, and other design requirements. **No impact** would occur.

h. The City of Agoura Hills is susceptible to both urban and wildland fire hazards (City of Agoura Hills General Plan, March 2010). The City of Agoura Hills Municipal Code classifies the City as a Very High Fire Hazard Severity Zone. The City of Agoura Hills Uniform Fire Code, found in Section 8200 of the City of Agoura Hills Municipal Code, includes modifications to the California Building Code that intend to prevent loss during a wildland fire, including design and instillation standards. The proposed development agreement does not involve the construction of any new structures. Impacts related to wildland fire would be **less than significant** with mandatory compliance with building standards and regulations.

Less Than

Significant Potentially With Less Than IX. HYDROLOGY AND WATER QUALITY - Would the Significant Mitigation Significant No project: Impact Incorporated Impact Impact a) Violate any water quality standards or waste discharge \boxtimes requirements? b) Substantially deplete groundwater supplies or interfere substantially with groundwater recharge such that there would be a net deficit in aquifer volume or a lowering of the local groundwater table level (e.g., the production rate of pre-existing nearby wells would drop to a level which would not support existing land uses or planned uses for \boxtimes which permits have been granted)? c) Substantially alter the existing drainage pattern of the site or area, including through the alteration of the course of a stream or river, in a manner which would result in \square substantial erosion or siltation on- or off-site? d) Substantially alter the existing drainage pattern of the site or area, including through the alteration of the course of a stream or river, or substantially increase the rate or amount of surface runoff in a manner which would result in \boxtimes flooding on- or off-site? e) Create or contribute runoff water which would exceed the capacity of existing or planned stormwater drainage systems or provide substantial additional sources of \boxtimes polluted runoff? f) Otherwise substantially degrade water quality? \mathbf{X} g) Place housing within a 100-year flood hazard area as mapped on a federal Flood Hazard Boundary or Flood Insurance Rate Map or other flood hazard delineation \square map? h) Place within a 100-year flood hazard area structures \square which would impede or redirect flood flows? i) Expose people or structures to a significant risk of loss, injury or death involving flooding, including flooding as a \square result of the failure of a levee or dam? \square j) Inundation by seiche, tsunami, or mudflow?

a, f. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. The project would only result in new physical development related to the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. Development of the previously approved Agoura Hills Business Park and Agoura Hills Business Center West Projects required preparation and implementation of a Storm Water Pollution Prevention Plan (SWPPP), a Standard Urban Storm Water Management

Plan (SUSMP), and a Wet Weather Erosion Control Plan (Agoura Hills Business Park IS-MND, June 2008; Agoura Business Center West IS-MND, May 2009). Preparation and implementation of the aforementioned plans would continue to apply to the previously approved developments under the new development agreement.

The specified street and infrastructure improvements are not anticipated to disturb large amounts of soil along the parcel frontage. However, if large amounts of bare soil were to be exposed during construction of the specified street and infrastructure improvements, or in the event of a storm, finely grained soils could be entrained, eroded from the site, and transported to drainages. The amount of material that could potentially erode from the site during temporary construction activities would be greater than under existing conditions due to the minor loss of vegetation and movement of soils. As a result, preparation and implementation of an SWPPP and a SUSMP would also be required for the specified street and infrastructure improvements.

Following construction, the middle of Canwood Street would be widened to accommodate a third "storage" lane along the frontage of the City RDA parcel and a bit further on the west, as well as the installation of a curb, gutter and sidewalk on the north side of Canwood Street and a swale on the south side of Canwood Street. The third lane would be used only as a left turn lane, not a regular travel lane. While most of the street improvements and infrastructure would occur in already paved areas, some new paved surfaces would replace existing vegetated, pervious ground cover immediately adjacent to the existing Canwood Street alignment, which can both absorb water and filter out pollutants. In contrast, paved surfaces accumulate pollutants such as deposite of oil, grease, and other vehicle fluids and hydrocarbons. Traces of heavy metals deposited on streets and parking areas from auto operation and/or fall out of airborne contaminants are common urban surface water pollutants. During storm events, these pollutants would be transported by runoff into storm drain systems and ultimately into the regional watershed. Although relatively minor, given the limited unpaved work area, the introduction of urban pollutants to runoff from the project area could adversely affect the water quality of runoff from the project site.

The project site is currently served by a system of pipes owned by the City and maintained by the Los Angeles County Flood Control Department. A 36-inch pipe is located on the southern portion of the site on Canwood Street and a 30-inch storm drain is located on Canwood Street. The 30-inch pipe was designed to handle all existing drainage that flows from Derry Avenue onto Canwood Street and that flows from the eastern portion of Canwood Street.

No stormwater detention would be required for the proposed development agreement under SUSMP County guidelines. However, Best Management Practices (BMP) treatment control measures would be implemented to ensure that the degradation of water quality due to runoff from the proposed development agreement would be a less than significant. Any potential concerns regarding water quality would be addressed through the use of BMP treatment control measures on and around the project site.

The project site is within the region covered by the Los Angeles County Municipal Storm Water NPDES Permit No. CAS004001 issued by the Los Angeles Regional Water Quality Control Board (LARWQCB). The purpose of this permit is to govern non-point discharges associated

with storm water drainage. Regulations under the federal Clean Water Act require compliance with the NPDES storm water permit for projects that would disturb greater than one acre during construction. Per State regulations, the applicant would be required to file a Notice of Intent with the LARWQCB and prepare a SWPPP. The SWPPP would list a series of measures, such as Best Management Practices (BMPs), to be utilized during construction to prevent storm water runoff pollution. Also as part of the SWPPP, the applicant would need to prepare a Wet Weather Erosion Control Plan to minimize erosion from the site and potential pollution of local waterways and ultimately the Pacific Ocean.

The SWPPP would be required by the City prior to issuance of a grading or building permit. Therefore, water quality impacts from runoff during temporary construction activities and long-term operational activities would be **less than significant** with implementation of the aforementioned county, state and federal requirements.

b. The proposed development agreement involves a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. The proposed development agreement would not result in a long-term increase in water use as compared to the previously approved projects. Therefore, the project would not substantially deplete ground water supplies. Project development would result in a minor increase in impermeable surface area on the project site immediately adjacent to the Canwood Street alignment, which may reduce groundwater recharge. However, given that the work area for the street and infrastructure improvements on unpaved surfaces is small, and that BMPs would be integrated, the project would not be expected to adversely affect groundwater in the vicinity of the project site and impacts would be **less than significant**.

c. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. The drainage pattern throughout the site would not be substantially modified by the proposed development agreement given the limited work area. Furthermore, the potential for adverse erosion and sedimentation effects would be reduced to a less than significant level with the preparation and implementation of a SWPPP and a SUSMP, as discussed above. Therefore, impacts would be **less than significant**.

d-e. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street. The specified street improvements would incrementally increase impervious surfaces, which would reduce, to a minor extent given the limited unpaved work area, the amount of water that percolates into the ground and increase the amount of water that is discharged to the storm drain system. However, the Los Angeles County Flood Control District (LACFCD) requires that no increase in peak flows in receiving waters should occur. Therefore, new development is required to meet or exceed pre-project conditions for storm water discharge, and the proposed development agreement would be required to retain any additional runoff onsite and discharge it to the storm drain system at

rates that do not exceed pre-project conditions. Due to the installation of an onsite swale, and other BMP treatment control measures, no storm water detention is required under SUSMP. Moreover, compliance with Flood Control District requirements would reduce impacts relating to the quantity of surface water runoff and storm drain capacity to a **less than significant** level.

g,h,i. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street. It does not involve the construction of any new housing or other buildings. Furthermore, the project site is outside the 100-year flood hazard zone (City of Agoura Hills General Plan, March 2010). Therefore, **no impact** with respect to flooding would occur.

j. Seiches are oscillations of the surface of an inland body of water that varies in period from a few minutes to several hours. Seismic excitations can induce such oscillations. Tsunamis are large sea waves produced by submarine earthquakes or volcanic eruptions. Since the site is not located close to an inland body of water and is at an elevation sufficiently above sea level to be outside the zone of a tsunami, the risk of these two hazards is not pertinent to the site. Therefore, **no impact** would occur.

X. LAND USE AND PLANNING – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Physically divide an established community?			\boxtimes	
b) Conflict with any applicable land use plan, policy, or regulation of an agency with jurisdiction over the project (including, but not limited to the general plan, specific plan, local coastal program, or zoning ordinance) adopted for				
the purpose of avoiding or mitigating an environmental effect?				\boxtimes
c) Conflict with any applicable habitat conservation plan or natural community conservation plan?				\boxtimes

a. The previously approved Agoura Business Center West and Agoura Hills Business Park Projects would provide infill development on a site surrounded by multi-family residential development to the north, commercial and light-industry to the west, commercial uses to the south across Canwood Street, and light industrial and commercial uses to the east across Derry Avenue. The project site is not currently utilized by nearby residents, pedestrians, or vehicles traveling through the area. The previously approved development would be similar to surrounding commercial and light-industrial uses on Canwood Street and would connect the commercial and light-industrial developments on Canwood Street east of the project site and the commercial and light-industrial developments on Canwood Street west of the project site. The proposed development plan would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. Therefore, the proposed development plan would not divide an established community and impacts would be **less than significant**.

b. The previously approved Agoura Business Center West Project involved:

- A zone change and associated General Plan amendment from Business Park-Manufacturing (BP-M)to Commercial Retail/ Service (CRS);
- A Conditional Use Permit in order to grade a slope greater than 10 percent and to move more than 50 cubic yards of earth;
- A Parcel Map adjustment to expand the project site parcel and to decrease the parcel to the north of the project site; and
- A variance for the proposed 17-foot high retaining wall.

Upon City approval of the zone change, General Plan Amendment, and Conditional Use Permit, the project was determined to be consistent with the City ordinances and impacts.

The previously approved Agoura Hills Business Park Project was determined to be consistent with the General Plan and zoning designations of Business Park Manufacturing (BP-M) and the Freeway Corridor overlay. In addition, the Agoura Hills Business Park Project was determined to require the removal of one oak tree protected under the City's Oak Tree Ordinance and the encroachment into the protected zone of one other protected oak tree. An Oak Tree Permit from the City Department of Planning and Community Development would still be required prior to the issuance of a grading permit for the approved development.

The proposed development agreement would incorporate by reference the City's approvals and conditions on the developers' properties. The specified street and infrastructure improvements are identified in the General Plan, would be within the Business Park-Manufacturing (BP-M) zone, and would not conflict with the BP-M zoning on the adjacent vacant property currently owned by the Agoura Hills Redevelopment Agency (28661 Canwood Street). **No impact** would occur with respect to the General Plan or zoning.

c. The project site is within an urban area and is not subject to an adopted habitat conservation plan (HCP), natural community conservation plan (NCCP), or any other approved local, regional, or state habitat conservation plans (City of Agoura Hills, General Plan 2035 EIR, February 2010). The closest protected community is the Las Virgenes vegetation community (Significant Ecological Area #6) located approximately ¼ mile south of the project site across U.S. 101. The wildlife corridor closest to the project site is approximately one mile southeast of the site on the southeastern boundary of the City. The project would not interfere with an adopted HCP or NCCP, any sensitive ecological area, or any wildlife corridor; therefore, **no impact** would occur.

XI. MINERAL RESOURCES Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Result in the loss of availability of a known mineral resource that would be of value to the region and the residents of the state?			\boxtimes	
b) Result in the loss of availability of a locally-important mineral resource recovery site delineated on a local general plan, specific plan or other land use plan?			\boxtimes	

a, b. According to the California Division of Mines and Geology (DMG), no significant mineral deposits are present within the City of Agoura Hills (City of Agoura Hills, General Plan March 2010). The majority of the City north of Agoura Road is classified as MRZ-1. This classification is used to delineate areas where adequate information is available to determine that no mineral deposits are present, and/or there is little likelihood for significant deposits to be present. The proposed development agreement would grant a 10-year time extension for the entitlements for two previously approved developments, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. The project site is located north of Agoura Road and is surrounded by development. Consequently, the conversion of the project site to mining is unlikely. Impacts would be **less than significant**.

XII. NOISE – Would the project result in:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Exposure of persons to or generation of noise levels in excess of standards established in the local general plan or noise ordinance, or applicable standards of other agencies?			\boxtimes	
b) Exposure of persons to or generation of excessive groundborne vibration or groundborne noise levels?			\boxtimes	
c) A substantial permanent increase in ambient noise levels in the project vicinity above levels existing without the project?			\boxtimes	
d) A substantial temporary or periodic increase in ambient noise levels in the project vicinity due to construction activities above levels existing without the project?			\boxtimes	
e) For a project located within an airport land use plan or, where such a plan has not been adopted, within two miles of a public airport or public use airport, would the project expose people residing or working in the project area to excessive noise levels?				\boxtimes
f) For a project within the vicinity of a private airstrip, would the project expose people residing or working in the project area to excessive noise levels?				\boxtimes

City of Agoura Hills

Noise level (or volume) is generally measured in decibels (dB) using the A-weighted sound pressure level (dBA). The A-weighting scale is an adjustment to the actual sound power levels to be consistent with that of human hearing response, which is most sensitive to frequencies around 4,000 Hertz (about the highest note on a piano) and less sensitive to low frequencies (below 100 Hertz). For the most sensitive uses, such as single family residential, 60 dBA Day-Night average level (Ldn) is the maximum normally acceptable exterior level. Ldn is the time average of all A-weighted levels for a 24-hour period, with a 10 dB upward adjustment added to those noise levels occurring between 10:00 p.m. and 7:00 a.m. to account for the general increased sensitivity of people to nighttime noise levels. The Community Noise Equivalent Level (CNEL) is similar to the Ldn except that it adds 5 additional dB to evening noise levels (7:00 p.m. to 10:00 p.m.). The City of Agoura Hills utilizes the CNEL for measuring noise levels.

a, c. The proposed development agreement involves a 10-year time extension for the entitlements for two previously approved development project, and would require the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement would not result in any new noise-generating uses on the project site or in the vicinity. Development of the Agoura Hills Business Park Project required Mitigation Measure N-1, which required noise reduction measures to reduce mechanical equipment noise (Agoura Hills Business Park IS-MND, June 2008). This mitigation measure would continue to apply under the proposed development agreement.

The previously approved Agoura Hills Business Park and Agoura Business Center West Projects were found to increase vehicle traffic on local roadways that would result in increased roadway noise affecting nearby sensitive land uses. However, roadway noise caused by projectgenerated vehicle traffic was found to be less than significant for both of the previously approved developments (Agoura Hills Business Park IS-MND, June 2008; Agoura Business Center West IS-MND, May 2009).

The proposed development agreement involves a 10-year time extension for the entitlements for each of the two previously approved projects and would also include the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement and development of the previously approved projects would not introduce new traffic-generating uses or otherwise generate an increase in roadway noise.

Therefore, the project would not expose sensitive land uses to noise exceeding the City's noise standards, or otherwise contribute to a long-term increase in noise in the project vicinity. Impacts would be **less than significant**.

b, d. The proposed development plan would grant a 10-year time extension for the entitlements for each of the two previously approved projects, and would not involve construction of additional new structures. Construction of the specified street and infrastructure improvements would generate a temporary increase in noise in the site vicinity. As shown in Table 6, maximum noise levels relating to construction range from 78-88 decibels (dB) at a distance of 50 feet (US EPA, 1971).

	Average Noise Level at 50 Feet				
Construction Phase	Minimum Required Equipment On-Site	All Pertinent Equipment On-Site			
Clearing	84 dBA	84 dBA			
Excavation	78 dBA	88 dBA			
Foundation/Conditioning	88 dBA	88 dBA			
Laying Subbase, Paving	78 dBA	79 dBA			
Finishing and Cleanup	84 dBA	84 dBA			

Table 6Typical Noise Levels at Construction Sites

Source: Bolt, Beranek and Newman, "Noise from Construction Equipment and Operations, Building Equipment, and Home Appliances," prepared for the U.S. Environmental Protection Agency, 1971.

Sensitive receptors are generally considered residential units, child care centers, libraries, hospitals, and nursing homes. The sensitive receptors closest to the project site are the multifamily residential development located approximately 900 feet north of the specified roadway improvements on Canwood Steet, and a childcare center located approximately 1,000 feet west of the specified roadway improvements on Canwood Steet. Construction noise generally attenuates by about 6 dBA per doubling of distance. Therefore, the maximum noise level during construction activities at the exterior of the residences 900 feet from the project site would measure approximately 63 dBA, and at the child care center would be 62 dBA. These noise levels are considered "normally compatible" with the given sensitive uses (Table N-1, General Plan, 2010). In addition, construction of the roadway improvements, as well as construction of the previously approved commercial development, would be required to comply with Article IV, Chapter 1, of the City's Municipal Code, which limits the use of construction equipment that generates noise in excess of 60 dBA to between the hours of 7:00 AM and 7:00 PM, Monday through Saturday. No construction activity is permitted between 7:00 PM and 7:00 AM that generates noise in excess of the 50 dBA nighttime standard, and no construction activity is permitted on Sundays or legal holidays.

The project site is not located in an area of excessive groundborne vibration and would not expose people to excessive levels of groundborne vibration. Given the nature of the specified street and infrastructure improvements, the proposed development agreement is not anticipated to result in groundborne vibration. Therefore, with mandatory compliance with the City's construction noise ordinance, impacts related to construction noise and vibration would be **less than significant**.

e, f. The project site is not located within the vicinity of an airport or private airstrip; and therefore, would not be affected by air traffic noise impacts. **No impact** would occur.

XIII. POPULATION AND HOUSING – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Induce substantial population growth in an area, either directly (for example, by proposing new homes and businesses) or indirectly (for example, through extension of roads or other infrastructure)?			\boxtimes	
b) Displace substantial numbers of existing housing, necessitating the construction of replacement housing elsewhere?				\boxtimes
c) Displace substantial numbers of people, necessitating the construction of replacement housing elsewhere?				\boxtimes

a. The proposed development agreement does not involve the construction of new buildings, including housing, and so would not induce population growth. Therefore, the proposed development agreement would not conflict with the Southern California Association of Governments (SCAG) projections, generate a significant demand for housing, or require the extension of infrastructure or roads. However, the proposed development agreement would result in new physical development related to the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The specified street and infrastructure improvements would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site and would not substantially induce population growth from the development agreement in the area. Therefore, impacts related to population growth would be **less than significant**.

b, c. The project site is primarily vacant, unused land. A parking lot serving a commercial/light industrial building is located on the eastern side of the project site. Therefore, implementation of the proposed development agreement would not displace people or housing. **No impact** would occur.

XIV. PUBLIC SERVICES	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Would the project result in substantial adverse physical impacts associated with the provision of new or physically altered governmental facilities, need for new or physically altered governmental facilities, the construction of which could cause significant environmental impacts, in order to maintain acceptable service ratios, response times or other performance objectives for any of the public services:				
i. Fire protection?				\boxtimes
ii. Police protection?				\boxtimes
iii. Schools?				\boxtimes
iv. Parks?				\boxtimes
v. Other public facilities?				\boxtimes

a (i). The City of Agoura Hills is served by the Los Angeles County Fire Department (LACFD). Fire Station #89, located at 29575 Canwood Street in Agoura Hills, approximately 1.5 miles west of the project site, serves the project site and surrounding areas. The previously approved Agoura Hills Business Park and Agoura Hills Business Center West Projects would be required to comply with the Fire Code and LACFD standards, including specific construction specifications, access design, location of fire hydrants, and other design requirements. The proposed development agreement would not require additional fire protection, as no new structures are proposed, and the project site is within a developed area currently served by the LACFD. The proposed development agreement would only result in new physical development related to the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street, which would not impact fire protection services. **No impacts** relating to fire services would occur.

a (ii). The City of Agoura Hills receives police protection from the Los Angeles County Sheriff's Department (LACSD). The previously approved projects are not expected to adversely affect police services as they would not result in an increase in population. The proposed development agreement is not anticipated to require additional police services, as no new structures are proposed, and the project site is within a developed area currently served by the LACSD. The proposed development agreement would only result in new physical development related to the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street, which would not impact police protection services. The proposed development agreement would have **no impact** with respect to police services.

a (iii). The previously approved projects would be required to pay state-mandated school impact fees. Pursuant to Section 65995 (3)(h) of the California Government Code (Senate Bill 50, chaptered August 27, 1998), the payment of statutory fees "...is deemed to be full and complete mitigation of the impacts of any legislative or adjudicative act, or both, involving, but not limited to, the planning, use, or development of real property, or any change in governmental

organization or reorganization." The proposed development agreement would incorporate by reference the City's approvals and conditions on the developers' properties. However, the proposed development agreement would not result in any new residences, or directly generate an increase in population. Therefore, no increase in students or impacts relating to school capacity would occur. Thus, **no impacts** would occur in this regard.

a (iv). The proposed development agreement involves a 10-year time extension for the entitlements for each of the two previously approved projects and would require the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement and development of the previously approved projects would not introduce new residential uses or directly generate an increase in population. Therefore, the proposed development agreement would not increase citywide demand for parks or result in a change to the City's parkland to population ratio. Consequently, there would be **no impact** to parks and other public services.

a (v). The proposed development agreement does not involve the construction of new residences; therefore, it would not directly increase the City's population. While the previously approved developments on the project site would generate some new jobs, they would not substantially increase the population of Agoura Hills. The previously approved projects may incrementally increase the demand for parks, recreational facilities and/or other public services. However, the proposed development agreement would not adversely affect existing parks, recreational facilities and/or other public services, nor would it create the need for new parks, recreational facilities or other public services. Therefore, **no impact** would occur.

XV. RECREATION	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Would the project increase the use of existing neighborhood and regional parks or other recreational facilities such that substantial physical deterioration of the facility would occur or be accelerated?				\boxtimes
b) Does the project include recreational facilities or require the construction or expansion of recreational facilities which might have an adverse physical effect on the environment?				\boxtimes

a-b. The previously approved Agoura Hills Business Park and Agoura Hills Business Center West Project's do not involve new residential development or development that would adversely affect existing park or recreational facilities. The proposed development agreement would not involve the construction of new residences. The project would only result in new physical development related to the specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement would not directly affect any existing park or recreational facility, nor would it substantially increase demand for parks or recreational facilities. Therefore, **no impacts** would occur.

XVI. TRANSPORTATION/TRAFFIC – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Conflict with an applicable plan, ordinance or policy establishing measures of effectiveness for the performance of the circulation system, taking into account all modes of transportation including mass transit and non- motorized travel and relevant components of the circulation system, including but not limited to intersections, streets, highways and freeways, pedestrian and bicycle paths, and mass transit?			\boxtimes	
b) Conflict with an applicable congestion management program, including, but not limited to level of service standards and travel demand measures, or other standard established by the county congestion management agency for designated roads or highways?				
c) Result in a change in air traffic patterns, including either an increase in traffic levels or a change in location that results in substantial safety risks?				\boxtimes
d) Substantially increase hazards due to a design feature (e.g., sharp curves or dangerous intersections) or incompatible uses (e.g., farm equipment)?			\boxtimes	
e) Result in inadequate emergency access?			\boxtimes	

a, b. The proposed development agreement involves a 10-year time extension for the entitlements for each of the two previously approved projects and would require the construction of specified street and infrastructure improvements in front of the City RDA parcel fronting Canwood Street. The proposed development agreement would not result in any new traffic-generating uses on the project site. However, construction vehicles and equipment may require temporary lane detours or closures. Due to the size of the project site and the temporary nature of the lane alterations, it would not be expected to result in a change in traffic that is substantial in relation to existing traffic patterns or capacity. Therefore, impacts related to project construction would be **less than significant**.

In addition, the potential traffic impacts of the Agoura Business Center West and Agoura Business Center North Projects are analyzed herein. The following analysis is partially based upon two traffic impact analyses performed by Kunzman Associates (February 2012), which analyzed the traffic impacts of the Agoura Business Center North and Agoura Business Center West Projects. The Los Angeles County Congestion Management Program (CMP) requires that traffic impact analyses must include all monitored intersections to which the project adds traffic above a certain minimum amount. In Los Angeles County, the monitored intersections are contained in Appendix A of the CMP. The traffic impact analyses were prepared in accordance with the County requirements except as noted. The traffic impact analyses not only examined the CMP system of roads and intersections, but also other roads and intersections. The complete traffic impact analysis reports are contained in Appendix C.

The project site is located at the northwest corner of the Derry Avenue and Canwood Street intersection in the City of Agoura Hills. The project site includes the Agoura Business Center

West, LLC/Agoura Business Center North, LLC properties (28721 Canwood Street and 28631 Canwood Street, respectively), as well as the vacant property currently owned by the Agoura Hills Redevelopment Agency (28661 Canwood Street), located between the Agoura Business Center West LLC/Agoura Business Center North LLC properties. Regional access to the site is provided by Highway 101. The nearest access to Highway 101 is via the on and off-ramps at Kanan Road, west of the project site.

The traffic studies examined fifteen intersections in the vicinity of the project site. The studied intersections are listed below and illustrated on Figure 1 of each of the two traffic studies. The traffic studies examined the following intersections in the vicinity of the project site:

- #1 Kanan Road and Thousand Oaks Boulevard
- *#2 Kanan Road and Canwood Street (East)*
- #3 Kanan Road and Canwood Street-U.S. 101 NB Ramps
- #4 Kanan Road and Roadside Drive-U.S. 101 SB Ramps
- #5 Kanan Road and Agoura Road
- #6 Canwood Street and Clareton Drive
- #7 Canwood Street and Agoura Business Center North Driveway
- #8 Canwood Street and Agoura Business Center West Driveway
- #9 Derry Avenue and Agoura Business Center West Driveway
- #10 Canwood Street and Derry Avenue
- #11 Canwood Street and Colodny Drive
- #12 Canwood Street/ Chesebro Road and Driver Avenue/Palo Comado Canyon Road
- #13 Palo Comado Canyon Road and U.S. 101 NB Ramps
- #14 Palo Comado Canyon Road and Chesebro Road
- #15 Dorothy Drive and U.S. 101 SB Ramps

The qualitative measure used to describe the condition of traffic flow is Level of Service (LOS). LOS ranges from A to F, where LOS A would be excellent conditions and LOS F would be overload conditions. The Intersection Capacity Utilization (ICU) method of intersection analysis was used to compare the volume of traffic with the capacity of the intersection on signalized intersections. On intersections that are not signalized, the Intersection Delay Method was used to compare the volume of traffic with the capacity of the intersection. The intersection volume-to-capacity (V/C) ratio allows for the calculation of the corresponding LOS for intersections in the vicinity of the project site. The LOS definitions can be found in the technical appendix of the traffic studies (Appendix C).

Table 7 summarizes the peak hour LOS at the twelve existing study intersections under existing conditions.

The data presented in Table 7 indicate that the study area intersections currently operate within acceptable Levels of Service during the peak hours for existing traffic conditions, except for the Kanan Road and Canwood Street-U.S. 101 NB Ramps intersection (#3) and the Palo Comado Canyon Road and U.S. 101 NB Ramps intersection (#13), which operate at unacceptable Levels of Service during the evening peak hour (see Table 7). The remainder of the study-area intersections operate at LOS C or better during the AM and PM peak hour periods.

Intersection	Peak Hour	Existing			
intersection	reak noui	Delay or V/C	LOS		
#1 Kanan Road and Thousand Oaks Boulevard	AM PM	0.725 0.732	СС		
#2 Kanan Road and Canwood Street (East)	AM	0.523	A		
	PM	0.706	C		
#3 Kanan Road and Canwood Street-U.S. 101	АМ	0.674	В		
NB Ramps	РМ	0.801	D		
#4 Kanan Road and Roadside Drive-U.S. 101 SB	AM	0.727	C		
Ramps	PM	0.786	C		
#5 Kanan Road and Agoura Road	AM	0.686	B		
	PM	0.640	B		
#6 Canwood Street and Clareton Drive	AM	13.4	B		
	PM	19.4	C		
#10 Canwood Street and Derry Avenue	AM	11.4	B		
	PM	12.1	B		
#11 Canwood Street and Colodny Drive	AM	11.2	B		
	PM	10.4	B		
#12 Canwood Street/ Chesebro Road and Driver	AM	10.7	B		
Avenue/Palo Comado Canyon Road	PM	15.7	C		
#13 Palo Comado Canyon Road and U.S. 101	АМ	17.6	C		
NB Ramps	РМ	99.9	F		
#14 Palo Comado Canyon Road and Chesebro	AM	10.8	B		
Road	PM	14.0	B		
#15 Dorothy Drive and U.S. 101 SB Ramps	AM	17.1	C		
	PM	16.0	C		

Table 7Existing Levels of Service

Bold text indicates an intersection that operates at an unacceptable Level of Service. Source: Kunzman Associates (2012). See Appendix A for complete traffic studies.

In the City of Agoura Hills, a proposed project is considered to result in a significant impact if, prior to mitigation, the proposed project:

i. Degrades operations at a signalized intersection as follows:

Intersection	Conditions with Project Traffic	Project-related Increase in V/C Ratio
LOS	V/C Ratio	
С	0.71 – 0.80	0.04 or more
D	0.81 – 0.90	0.02 or more
E or F	0.91 or more	0.01 or more

or

- ii. Degrades the Level of Service (LOS) at an unsignalized intersection to an unacceptable level of LOS D or worse; or
- iii. Increases delay at an unsignalized intersection operating at an unacceptable level by five or more seconds; or
- iv. Results in satisfying the most recent California Manual on Uniform Traffic Control Devices (CAMUTCD) peak hour volume warrant or other warrants for traffic signal installation at the intersection; or
- v. Increases the volume to capacity (v/c) ratio on a roadway segment operating at an unacceptable level (LOS D, E or F) by 0.05 or more.

Agoura Business Center North Project

<u>Trip Generation</u>. The Agoura Business Center North Project was formerly the Agoura Hills Business Park Project. Trip generation for the Agoura Business Center North Project was estimated using trip generation rates from the Institute of Transportation Engineers' *Trip Generation*, 8th Edition. The Agoura Business Center North Project is estimated to generate 718 daily vehicle trips, including 94 AM peak hour trips and 100 PM peak hour trips.

<u>Opening Year (2022) Traffic Conditions</u>. To account for area-wide growth on roadways, opening year (2022) traffic volumes have been calculated based on a 0.75% annual growth rate of existing traffic volumes over a 10-year period. The area-wide growth rate is based on SCAG and the City General Plan.

Table 8 depicts the opening year (2022) Agoura Business Center North Project traffic contribution at the study area intersections. Area-wide growth has been added to daily and peak hour traffic volumes on surrounding roadways, in addition to traffic generated by the Agoura Business Center North Project.

As shown in Table 8, the study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Opening Year (2022) with the Agoura Business Center North Project, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the evening peak hour:

- Kanan Road and Canwood Street-U.S. 101 NB Ramps (#3)
- Kanan Road and Roadside Drive-U.S. 101 SB Ramps (#4)
- *Canwood Street and Clareton Drive (Without Improvements) (#6)*
- Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements) (#13)

		Opening Year (2022)					
Intersection	Peak	Without F	Project	With Proj	ect	Increase	Ciamificant
Intersection	Hour	Delay or V/C	LOS	Delay or V/C	LOS	in V/C or Delay	Significant Impact?
#1 Kanan Road and Thousand Oaks Boulevard	AM PM	0.777 0.795	C C	0.781 0.796	C C	0.004 0.001	No No
#2 Kanan Road and Canwood Street (East)	AM PM	0.560 0.757	A C	0.562 0.776	A C	0.002 0.019	No No
#3 Kanan Road and Canwood Street-U.S. 101 NB Ramps	AM PM	0.721 0.859	С D	0.722 0.861	С D	0.001 0.002	No No ¹
#4 Kanan Road and Roadside Drive-U.S. 101 SB Ramps	AM PM	0.780 0.843	С D	0.781 0.844	С D	0.001 0.001	No No ¹
#5 Kanan Road and Agoura Road	AM PM	0.735 0.686	C B	0.736 0.689	C B	0.001 0.003	No No
#6 Canwood Street and Clareton Drive (Without Improvements)	AM PM	14.2 23.4	В С	15.1 28.7	С D	0.9 5.3	No Yes
#6 Canwood Street and Clareton Drive (With Improvements ²)	AM PM	0.309 0.581	A A	0.341 0.619	A B	0.032 0.038	No No
#7 Canwood Street and Agoura Business Center North Driveway	AM PM	N/A N/A	N/A N/A	10.4 11.7	B B	N/A N/A	N/A N/A
#10 Canwood Street and Derry Avenue	AM PM	11.7 12.7	B B	12.0 13.0	B B	0.3 0.3	No No
#11 Canwood Street and Colodny Drive	AM PM	11.5 10.6	B B	11.8 10.7	B B	0.3 0.1	No No
#12 Canwood Street/ Chesebro Road and Driver Avenue/Palo Comado Canyon Road	AM PM	11.2 18.5	B C	11.5 19.3	B C	0.3 0.8	No No
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements)	АМ РМ	20.9 262.7	C F	20.9 280.6	B F	0.0 17.9	No Yes
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps	AM PM	0.480 0.686	A B	0.494 0.704	A C	0.018 0.018	No No

Table 8Opening Year (2022) Agoura Business Center North
Project Traffic Contribution

			22)					
Intersection	Peak	Without Project		With Project		Increase	0	
	Hour	Delay or V/C	LOS	Delay or V/C	LOS	in V/C or Delay	Significant Impact?	
(With Improvements ³)								
#14 Palo Comado Canyon Road and Chesebro Road	AM PM	11.1 15.0	B C	11.1 15.1	B C	0.0 0.1	No No	
#15 Dorothy Drive and U.S. 101 SB Ramps	AM PM	20.7 18.9	C C	21.0 21.1	C C	0.3 2.2	No No	

Table 8Opening Year (2022) Agoura Business Center NorthProject Traffic Contribution

¹ This intersection would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above.

² Prior to construction, the project shall complete a focused traffic analysis to determine if a traffic signal is warranted (refer to Mitigation Measure TRA-1).

³ Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation.

Bold text indicates an intersection that operates at an unacceptable Level of Service.

Source: Kunzman Associates, 2012. See Appendix C for complete traffic study.

The intersections at Kanan Road and Canwood Street-U.S. 101 NB Ramps and Kanan Road and Roadside Drive-U.S. 101 SB Ramps would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above. A traffic signal is programmed for installation at the Palo Comado Canyon Road and U.S. 101 NB Ramps intersection, which would result in an acceptable Level of Service under "With Project" conditions. However, the Canwood Street and Clareton Drive intersection would result in an unacceptable Level of Service with the Agoura Business Center North Project, which would require mitigation; therefore, impacts would be **less than significant with mitigation incorporated**.

<u>Cumulative Traffic Conditions</u>. To account for area-wide growth on roadways, cumulative traffic forecasts were developed from existing traffic volumes plus 0.75% annual growth rate over a ten 10-year period, plus the approved and pending project tracking list. Table 6 in the Agoura Business Center North LLC Development Agreement Traffic Impact Analysis lists the proposed land uses for the other development. The area-wide growth rate has been obtained from SCAG and the City General Plan.

Table 9 depicts the cumulative Agoura Business Center North Project traffic contribution at the study area intersections. Area-wide growth and anticipated vehicle trips from the approved and pending project tracking list have been added to daily and peak hour traffic volumes on surrounding roadways, in addition to traffic generated by the Agoura Business Center North Project.

				Cum	ulative		
Intersection	Peak	Without F	Project	With Proj	ect	Increase	Oi ana ifi a ana t
	Hour	Delay or V/C	LOS	Delay or V/C	LOS	in V/C or Delay	Significant Impact?
#1 Kanan Road and Thousand Oaks Boulevard	AM PM	0.800 0.804	D D	0.805 0.806	D D	0.005 0.002	No ¹ No ¹
#2 Kanan Road and Canwood Street (East)	АМ РМ	0.575 0.797	A C	0.577 0.815	A D	0.002 0.018	No No ¹
#3 Kanan Road and Canwood Street-U.S. 101 NB Ramps	AM PM	0.758 0.906	С Е	0.760 0.908	C E	0.002 0.002	No No ¹
#4 Kanan Road and Roadside Drive-U.S. 101 SB Ramps	AM PM	0.785 0.871	С D	0.786 0.873	С D	0.001 0.002	No No ¹
#5 Kanan Road and Agoura Road	AM PM	0.744 0.754	C C	0.745 0.757	C C	0.001 0.003	No No
#6 Canwood Street and Clareton Drive (Without Improvements)	АМ РМ	14.6 27.0	B D	15.5 34.2	C D	0.9 7.2	No Yes
#6 Canwood Street and Clareton Drive (With Improvements ²)	AM PM	0.317 0.602	A B	0.349 0.640	A B	0.032 0.038	No No
#7 Canwood Street and Agoura Business Center North Driveway	AM PM	N/A N/A	N/A N/A	10.5 12.1	B B	N/A N/A	N/A N/A
#10 Canwood Street and Derry Avenue	AM PM	12.2 13.8	B B	12.5 14.2	B B	0.3 0.4	No No
#11 Canwood Street and Colodny Drive	AM PM	11.7 10.8	B B	10.9 11.9	B B	0.2 0.1	No No
#12 Canwood Street/ Chesebro Road and Driver Avenue/Palo Comado Canyon Road	AM PM	11.4 19.9	B C	11.7 20.5	B C	0.3 0.9	No No

 Table 9

 Cumulative Agoura Business Center North Project Traffic Contribution

		Cumulative									
Intersection	Peak	Without F	Project	With Proj	ect	Increase	Significant				
	Hour	Delay or V/C LOS		Delay or V/C LOS		in V/C or Delay	Impact?				
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements)	AM PM	26.1 361.9	D F	26.1 384.8	D F	0.0 22.9	No ¹ Yes				
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps (With Improvements ³)	AM PM	0.506 0.717	A C	0.508 0.735	A C	0.002 0.018	No No				
#14 Palo Comado Canyon Road and Chesebro Road	AM PM	11.5 18.3	B C	11.5 18.3	B C	0.0 0.0	No No				
#15 Dorothy Drive and U.S. 101 SB Ramps	АМ РМ	22.3 23.2	с с	22.6 26.5	С D	0.3 3.3	No No ¹				

 Table 9

 Cumulative Agoura Business Center North Project Traffic Contribution

¹ This intersection would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above.

² Prior to construction, the project shall complete a focused traffic analysis to determine if a traffic signal is warranted.

³ Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation. **Bold text** indicates an intersection that operates at an unacceptable Level of Service.

Source: Kunzman Associates, 2012. See Appendix C for complete traffic study.

As shown in Table 9, the study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Cumulative traffic conditions, with the Agoura Business Center North Project, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the peak hours:

- Kanan Road and Thousand Oaks Boulevard (#1)
- Kanan Road and Canwood Street (East) (#2)
- Kanan Road and Canwood Street-U.S. 101 NB Ramps (#3)
- Kanan Road and Roadside Drive-U.S. 101 SB Ramps (#4)
- *Canwood Street and Clareton Drive (Without Improvements)* (#6)
- Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements) (#13)
- Dorothy Drive and U.S. 101 SB Ramps (#15)

The intersections at Kanan Road and Thousand Oaks Boulevard, Kanan Road and Canwood Street, Kanan Road and Canwood Street-U.S. 101 NB Ramps, Kanan Road and Roadside Drive-U.S. 101 SB Ramps, and Dorothy Drive and U.S. 101 SB Ramps would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause

operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above. A traffic signal is programmed for installation at the Palo Comado Canyon Road and U.S. 101 NB Ramps intersection, which would result in an acceptable Level of Service under "With Project" conditions. However, the Canwood Street and Clareton Drive intersection would result in an unacceptable Level of Service with the Agoura Business Center North Project, which would require mitigation; therefore, impacts would be **less than significant with mitigation incorporated**.

Agoura Business Center West Project

<u>Trip Generation</u>. Trip generation for the Agoura Business Center West Project was estimated using trip generation rates from the Institute of Transportation Engineers' *Trip Generation*, 8th Edition, and San Diego Association of Governments, *Traffic Generators*, April 2002. The Agoura Business Center West Project is estimated to generate 916 daily vehicle trips, including 28 AM peak hour trips and 56 PM peak hour trips.

<u>Opening Year (2022) Traffic Conditions</u>. To account for area-wide growth on roadways, opening year (2022) traffic volumes have been calculated based on a 0.75% annual growth rate of existing traffic volumes over a 10-year period. The area-wide growth rate is based on SCAG and the City General Plan.

Table 10 depicts the opening year (2022) Agoura Business Center West Project traffic contribution at the study area intersections. Area-wide growth has been added to daily and peak hour traffic volumes on surrounding roadways, in addition to traffic generated by the Agoura Business Center West Project.

		Opening Year (2022)									
Intersection	Peak	Without F	Project	With Proj	ect	Increase	Significant				
	Hour	Delay or V/C	LOS	Delay or V/C	LOS	in V/C or Delay	Impact?				
#1 Kanan Road and Thousand Oaks Boulevard	AM PM	0.777 0.795	СС	0.779 0.796	C C	0.002 0.001	No No				
#2 Kanan Road and Canwood Street (East)	AM PM	0.560 0.757	A C	0.561 0.762	A C	0.001 0.005	No No				
#3 Kanan Road and Canwood Street-U.S. 101 NB Ramps	AM PM	0.721 0.859	С D	0.722 0.862	C D	0.001 0.003	No No ¹				
#4 Kanan Road and Roadside Drive-U.S. 101 SB Ramps	AM PM	0.780 0.843	С D	0.780 0.845	С D	0.000 0.002	No No ¹				

Table 10Opening Year (2022) Agoura Business Center WestProject Traffic Contribution

				Opening \	/ear (20	22)	
Intersection	Peak	Without F	Project	With Proj	ect	Increase	Significant
	Hour	Delay or V/C	LOS	Delay or V/C	LOS	in V/C or Delay	Significant Impact?
#5 Kanan Road and Agoura Road	AM PM	0.735 0.686	C B	0.736 0.688	C B	0.001 0.002	No No
#6 Canwood Street and Clareton Drive (Without Improvements)	АМ РМ	14.2 B 23.4 C		14.5 25.3	B D	0.3 1.9	No No ¹
#6 Canwood Street and Clareton Drive (With Improvements ²)	AM PM	0.309 0.581	A A	0.314 0.593	A A	0.005 0.012	No No
#8 Canwood Street and Agoura Business Center West Driveway	AM PM	N/A N/A	N/A N/A	9.1 10.0	A B	N/A N/A	N/A N/A
#9 Derry Avenue and Agoura Business Center West Driveway	AM PM	N/A N/A N/A N/A		8.9 10.1	A B	N/A N/A	N/A N/A
#10 Canwood Street and Derry Avenue	AM PM	11.7 12.7	B B	12.2 13.6	B B	0.5 0.9	No No
#11 Canwood Street and Colodny Drive	AM PM	11.5 10.6	B B	11.6 10.7	B B	0.1 0.1	No No
#12 Canwood Street/ Chesebro Road and Driver Avenue/Palo Comado Canyon Road	AM PM	11.2 18.5	B C	11.3 18.8	B C	0.1 0.3	No No
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements)	АМ РМ			C F	0.1 5.4	No Yes	
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps (With	AM PM	0.480 0.686	A B	0.488 0.698	A B	0.008 0.012	No No

Table 10Opening Year (2022) Agoura Business Center WestProject Traffic Contribution

Intersection		Opening Year (2022)									
	Peak	Without F	Project	With Proj	ect	Increase	Significant Impact?				
	Hour	Delay or V/C	LOS	Delay or V/C	LOS	in V/C or Delay					
Improvements ³)											
#14 Palo Comado Canyon Road and Chesebro Road	AM PM	11.1 15.0	B C	11.1 15.1	B C	0.0 0.1	No No				
#15 Dorothy Drive and U.S. 101 SB Ramps	AM PM	20.7 18.9	с с	21.0 19.6	C C	0.3 0.7	No No				

Table 10Opening Year (2022) Agoura Business Center WestProject Traffic Contribution

¹ This intersection would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above. ² Prior to construction, the project above above.

² Prior to construction, the project shall complete a focused traffic analysis to determine if a traffic signal is warranted (refer to Mitigation Measure TRA-1).
³ Based upon discussions with City of Accure Ullia staff, a traffic signal is the staff.

³ Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation. **Bold text** indicates an intersection that operates at an unacceptable Level of Service.

Source: Kunzman Associates, 2012. See Appendix C for complete traffic study.

As shown in Table 10, the study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Opening Year (2022) with the Agoura Business Center West Project, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the evening peak hour:

- Kanan Road and Canwood Street-U.S. 101 NB Ramps (#3)
- Kanan Road and Roadside Drive-U.S. 101 SB Ramps (#4)
- *Canwood Street and Clareton Drive (Without Improvements) (#6)*
- Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements) (#13)

The intersections at Kanan Road and Canwood Street-U.S. 101 NB Ramps and Kanan Road and Roadside Drive-U.S. 101 SB Ramps would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above. A traffic signal is programmed for installation at the Palo Comado Canyon Road and U.S. 101 NB Ramps intersection, which would result in an acceptable Level of Service under "With Project" conditions. However, the Canwood Street and Clareton Drive intersection would result in an unacceptable Level of Service with the Agoura Hills Business Center West Project, which would require mitigation; therefore, impacts would be **less than significant with mitigation incorporated**.

<u>Cumulative Traffic Conditions</u>. To account for area-wide growth on roadways, cumulative traffic forecasts were developed from existing traffic volumes plus 0.75% annual growth rate over a ten 10-year period, plus the approved and pending project tracking list. Table 6 in the Agoura Business Center West LLC Development Agreement Traffic Impact Analysis lists the proposed land uses for the other development. The area-wide growth rate has been obtained from SCAG and the City General Plan.

Table 11 depicts the cumulative Agoura Business Center West Project traffic contribution at the study area intersections. Area-wide growth and anticipated vehicle trips from the approved and pending project tracking list have been added to daily and peak hour traffic volumes on surrounding roadways, in addition to traffic generated by the Agoura Business Center West Project.

				Cumu	lative		
Intersection	Peak	Without F	Project	With Proj	ect	Increase	Significant
intersection	Hour	Delay or V/C	LOS	Delay or V/C	LOS	in V/C or Delay	Significant Impact?
#1 Kanan Road and Thousand Oaks Boulevard	AM PM	0.803 0.804	D D	0.805 0.806	D D	0.002 0.002	No No
#2 Kanan Road and Canwood Street (East)	АМ РМ	0.576 0.810	A D	0.577 0.815	A D	0.001 0.005	No No
#3 Kanan Road and Canwood Street-U.S. 101 NB Ramps	AM PM	0.759 0.905	С Е	0.760 0.908	C E	0.001 0.003	No No
#4 Kanan Road and Roadside Drive-U.S. 101 SB Ramps	AM PM	0.786 0.870	С D	0.786 0.873	С D	0.000 0.003	No No
#5 Kanan Road and Agoura Road	AM PM	0.744 0.756	C C	0.745 0.757	C C	0.001 0.001	No No
#6 Canwood Street and Clareton Drive (Without Improvements)	AM PM	15.1 30.4	С D	15.5 34.2	С D	0.4 3.8	No No
#6 Canwood Street and Clareton Drive (With Improvements ²)	AM PM	0.343 0.628	A B	0.349 0.640	A B	0.006 0.012	No No
#8 Canwood Street and Agoura Business Center West Driveway	AM PM	N/A N/A	N/A N/A			N/A N/A	N/A N/A
#9 Derry Avenue and Agoura Business Center West Driveway	AM PM	N/A N/A	N/A N/A			N/A N/A	N/A N/A
#10 Canwood Street and Derry Avenue	AM PM	12.0 13.2	B B	12.5 14.2	B B	0.5 1.0	No No
#11 Canwood Street	AM	11.9	В	10.9	В	0.0	No

Table 11Cumulative Agoura Business Center WestProject Traffic Contribution

				Cumu	lative			
Intersection	Peak	Without F	Project	With Proj	ect	Increase	Significant	
	Hour	Delay or V/C LOS		Delay or V/C	LOS	in V/C or Delay	Impact?	
and Colodny Drive	PM	10.8 B		11.9	В	0.1	No	
#12 Canwood Street/ Chesebro Road and Driver Avenue/Palo Comado Canyon Road	AM PM	11.6 20.1	B C	11.7 20.5	B C	0.1 0.4	No No	
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements)	AM PM	25.8 377.4	D F	26.1 384.8	D F	0.2 7.4	No Yes	
#13 Palo Comado Canyon Road and U.S. 101 NB Ramps (With Improvements ³)	AM PM	0.506 0.724	A C	0.508 0.735	A C	0.002 0.011	No No	
#14 Palo Comado Canyon Road and Chesebro Road	AM PM	11.5 18.2	B C	11.5 18.3	B C	0.0 0.1	No No	
#15 Dorothy Drive and U.S. 101 SB Ramps	АМ РМ	22.1 25.1	С D	22.6 26.5	С D	0.5 1.4	No No	

Table 11 Cumulative Agoura Business Center West Project Traffic Contribution

¹ This intersection would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above. ² Prior to construction, the project shall complete a focused traffic analysis to determine if a traffic signal is

² Prior to construction, the project shall complete a focused traffic analysis to determine if a traffic signal is warranted.

³ Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation. **Bold text** indicates an intersection that operates at an unacceptable Level of Service. Source: Kunzman Associates, 2012. See Appendix C for complete traffic study.

As shown in Table 11, the study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Cumulative traffic conditions, with the Agoura Business Center West Project, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the peak hours:

- Kanan Road and Thousand Oaks Boulevard (#1)
- Kanan Road and Canwood Street (East) (#2)
- Kanan Road and Canwood Street-U.S. 101 NB Ramps (#3)
- Kanan Road and Roadside Drive-U.S. 101 SB Ramps (#4)
- *Canwood Street and Clareton Drive (Without Improvements) (#6)*
- Palo Comado Canyon Road and U.S. 101 NB Ramps (Without Improvements) (#13)
- Dorothy Drive and U.S. 101 SB Ramps (#15)

The intersections at Kanan Road and Thousand Oaks Boulevard, Kanan Road and Canwood Street, Kanan Road and Canwood Street-U.S. 101 NB Ramps, Kanan Road and Roadside Drive-U.S. 101 SB Ramps, and Dorothy Drive and U.S. 101 SB Ramps would operate at an unacceptable Level of Service under "With Project" conditions, but the project would not cause operations to deteriorate such that the intersection would meet any of the City's criteria for a significant impact, described above. A traffic signal is programmed for installation at the Palo Comado Canyon Road and U.S. 101 NB Ramps intersection, which would result in an acceptable Level of Service under "With Project" conditions. However, the Canwood Street and Clareton Drive intersection would result in an unacceptable Level of Service with the Agoura Business Center West Project, which would require mitigation; therefore, impacts would be **less than significant with mitigation incorporated**.

c. Given the nature and scope of the proposed development agreement, and that there are no airports or airstrips in the project vicinity, the project would not change any air traffic patterns. **No impact** to air traffic would occur.

d, e. As discussed in the Agoura Business Center West and Agoura Hills Business Park Project IS-MNDs, the previously approved development projects on the site would be required to comply with Fire Code and LACFD standards including access design requirements. The proposed development agreement and specified street and infrastructure improvements are not expected to result in emergency access or hazardous internal design impacts, since they are improvements that would improve access along Canwood Street. Therefore, impacts would be **less than significant**.

Mitigation Measures

Implementation of Mitigation Measure TRA-1 would reduce impacts to traffic operations at the Canwood Street and Clareton Drive intersection to a less than significant level.

TRA-1 Focused Traffic Analysis and "Fair Share" Signalization Contribution. Prior to issuance of building permits, the applicant shall complete a focused traffic analysis to verify traffic conditions and the project's contribution to traffic at intersections in the project vicinity, and to determine if a traffic signal is warranted at the Canwood Street and Clareton Drive intersection. If a signal is required in order to maintain the City's Level of Service standards, the applicant shall contribute its "fair share" to the cost of a traffic signal at the intersection. The contribution shall be in proportion to the development's traffic increment at this location.

XVII. UTILITIES AND SERVICE SYSTEMS – Would the project:	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Exceed wastewater treatment requirements of the applicable Regional Water Quality Control Board?			\boxtimes	
b) Require or result in the construction of new water or wastewater treatment facilities or expansion of existing facilities, the construction of which could cause significant environmental effects?				
c) Require or result in the construction of new storm water drainage facilities or expansion of existing facilities, the construction of which could cause significant environmental effects?			\boxtimes	
d) Have sufficient water supplies available to serve the project from existing entitlements and resources, or are new or expanded entitlements needed?			\boxtimes	
e) Result in a determination by the wastewater treatment provider which serves or may serve the project that it has adequate capacity to serve the project's projected demand in addition to the provider's existing commitments?				
f) Be served by a landfill with sufficient permitted capacity to accommodate the project's solid waste disposal needs?				\boxtimes
g) Comply with federal, state, and local statutes and regulations related to solid waste?				\boxtimes

a,b,e. Wastewater generated in the Agoura Hills area is treated at the Tapia Water Reclamation Facility (TWRF), operated by Las Virgenes Municipal Water District (LVMWD). Development of the previously approved Agoura Hills Business Park and Agoura Hills Business Center West Projects would not exceed the wastewater treatment capacity of the TWRF. The proposed development plan would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial development agreement would not generate wastewater. Additionally, the proposed development agreement would provide utility connectivity for the City RDA parcel fronting Canwood Street. Therefore, impacts to wastewater treatment systems would be **less than significant**.

c. The proposed development agreement would grant a 10-year time extension for the entitlements for each of the two previously approved projects, including specified street and infrastructure improvements along Canwood Street, which would facilitate the connection between the commercial and light-industrial developments on Canwood Street to the east and west of the project site. Refer to Section IX, *Hydrology and Water Quality*, for further discussion of onsite runoff. The proposed development agreement would not generate storm water runoff and would provide storm water drainage connectivity for the City RDA parcel fronting

Canwood Street. Compliance with the requirements of the Los Angeles County Stormwater Ordinance (Chapter 12.80 of the County Municipal Code) would ensure that impacts would remain **less than significant**.

d. The Las Virgenes Municipal Water District (LVMWD) supplies potable water in the City of Agoura Hills. The LVMWD has no local sources of water and obtains all of its potable water supply from the Metropolitan Water District of Southern California (MWD), which in turn receives water from the State Water Project. Development of the previously approved projects would not exceed the water supply capacity of the LVMWD. The proposed development agreement would not result in any new structures, and would not increase water demand on the project site. Additionally, the proposed development agreement would provide water utility connectivity for the City RDA parcel fronting Canwood Street. Therefore, impacts related to water supply would be **less than significant**.

f, g. The Calabasas Sanitary Landfill, located adjacent to the Ventura Freeway on Lost Hills Road, would receive solid waste generated by the previously approved projects. Development of the previously approved projects would not exceed the solid waste capacity of the Calabasas Sanitary Landfill. The proposed development agreement would not result in any new wastegenerating uses. Therefore, **no impacts** would occur with respect to solid waste.

XVIII. MANDATORY FINDINGS OF SIGNIFICANCE	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
a) Does the project have the potential to degrade the quality of the environment, substantially reduce the habitat of a fish or wildlife species, cause a fish or wildlife population to drop below self-sustaining levels, threaten to eliminate a plant or animal community, reduce the number or restrict the range of a rare or endangered plant or animal or eliminate important examples of the major periods of California history or prehistory?		\boxtimes		
b) Does the project have impacts that are individually limited, but cumulatively considerable ("Cumulatively considerable" means that the incremental effects of a project are considerable when viewed in connection with the effects of past projects, the effects of other current projects, and the effects of probable future projects)?				
c) Does the project have environmental effects which will cause substantial adverse effects on human beings, either directly or indirectly?		\boxtimes		

a. As discussed in Section V, *Cultural Resources*, Mitigation Measures CR-1 and CR-2 would be required to reduce impacts to cultural resources to a less than significant level. With the implementation of the aforementioned mitigation measures, the proposed development agreement would not significantly degrade the quality of the environment, substantially reduce the habitat of a fish or wildlife species, cause a fish or wildlife population to drop below self-sustaining levels, threaten to eliminate a plant or animal community, reduce the number or restrict the range of a rare or endangered plant or animal or eliminate important examples of

the major periods of California history or prehistory. Therefore, impacts to biological resources and cultural resources would be **less than significant with mitigation incorporated**.

b. The proposed development agreement would not create any significant impacts that cannot be mitigated. The project's contribution to cumulative impacts would be **less than significant**.

c. Compliance with the City of Agoura Hills Municipal Code, compliance with State of California Regional Water Quality Control Board requirements, and compliance with all applicable state and federal regulations would reduce potential adverse effects to human beings to a less than significant level. As such, impacts to human beings would be **less than significant with mitigation incorporated**.

REFERENCES

- Agoura Hills, City of. City of Agoura Hills Municipal Code. Accessed January 20, 2012. Available online at: <u>http://ci.agoura-hills.ca.us/index.aspx?page=87</u>.
- Agoura Hills, City of. City of Agoura Hills General Plan. March 2010. Accessed January 20, 2012. Available online at: <u>http://ci.agoura-hills.ca.us/index.aspx?page=182</u>. Agoura Hills, City of. General Plan 2035 EIR. Volume I. February 2010.
- Agoura Hills, City of. City of Agoura Hills Zoning Map. Revised June 30, 2011.
- California Department of Conservation, Division of Land Resource Protection, Farmland Mapping and Monitoring Program, 2008.
- California Department of Conservation. Seismic Hazards Zone Map, Calabasas Quadrangle. February 1, 1998. Accessed January 24, 2012. Available online at: <u>http://gmw.consrv.ca.gov/shmp/download/pdf/ozn_calab.pdf</u>.
- California Department of Fish and Game (CDFG). 2008a. California Natural Diversity Database search of RareFind3. Updated January 3, 2012. The Resource Agency, State of California, Sacramento, California.
- California Environmental Protection Agency. *Climate Action Team Biennial Report*. Final Report. April 2010.
- California Native Plant Society (CNPS). 2001. Inventory of Rare and Endangered Plants of California. Sixth edition. (Special Publication No. 1.) September. Rare Plant Scientific Advisory Committee, David Tibor, Convening Editor, Sacramento, California.
- California, State of, Department of Toxic Substances Control. EnviroStor database. Accessed January 23, 2012. Available online at: <u>http://www.envirostor.dtsc.ca.gov/public/</u>.
- Geotracker. All Hazards Site Search. Accessed December 31, 2008. Available online at: <u>http://geotracker.waterboards.ca.gov/map/?CMD=runreport&myaddress=28661+canwood+st%2C+agoura+hills%2C+ca</u>.
- Gorian & Associates. Geotechnical Update and Evaluation of Revised Site Development, Agoura Business Center, 5301 Derry Avenue, Northwest Corner of Canwood Street and Derry Avenue, City of Agoura Hills, California. May 9, 2007.
- The J. Byer Group. Geologic and Soils Engineering Exploration Update, Proposed Commercial Development, Parcel Map 65503, 28000 Canwood Street, Agoura Hills, California. August 19, 2004.
- The J. Byer Group. Additional Comments, Proposed Commercial Development, Parcel Map 65503, 28000 Canwood Street, Agoura Hills, California. October 21, 2004.

- The J. Byer Group. *Rippability Study, Proposed Commercial Development, Parcel Map 65503, 28000 Canwood Street, Agoura Hills, California.* August 1, 2005.
- The J. Byer Group. Addendum Proposed Commercial Development, Parcel Map 65503, 28000 Canwood Street, Agoura Hills, California. March 1, 2007.
- The J. Byer Group. Addendum Proposed Commercial Development, Parcel Map 65503, 28000 Canwood Street, Agoura Hills, California. September 29, 2006.
- The J. Byer Group. Addendum Proposed Commercial Development, Parcel Map 65503, 28000 Canwood Street, Agoura Hills, California. July 12, 2006.
- Kunzman Associates. February 2012. Agoura Business Center North LCC Development Agreement Traffic Impact Analysis. February 2012.
- Kunzman Associates. February 2012. Agoura Business Center West LCC Development Agreement Traffic Impact Analysis. February 2012.
- Las Virgenes Municipal Water District. *Integrated Water System Master Plan Update* 2007. October 2007.
- Las Virgenes Municipal Water District. *Potable Water System Master Plan Update* 2007. October 2007.
- Michael Brandman Associates. *Biological Resources Assessment, Agoura Hills Business Park, Agoura Hills, Los Angeles County, California.* November 14, 2006.
- Rincon Consultants. Site visits on January 15, 2008; January 19, 2008, and January 31, 2012.
- United States, Environmental Protection Agency. Brownfields Database. Accessed January 23, 2012. Available online at: <u>http://www.epa.gov/enviro/html/bms/index2.html</u>.
- United States, Environmental Protection Agency. CERCLIS Superfund Site Search. Accessed January 23, 2012. Available online at: <u>http://cfpub.epa.gov/supercpad/cursites/srchsites.cfm</u>.
- United States, Environmental Protection Agency. *Noise from Construction Equipment and Operations, Building Equipment, and Home Appliances,* prepared by Bolt, Beranek, 1971.

United States Geologic Survey, 2008. Accessed online January 24, 2012.

Appendix A Air Quality Modeling Results and Calculations



CalEEMod Version: CalEEMod.2011.1.1

Date: 2/1/2012

Agoura Business Center West and North Development Agreement

Los Angeles-South Coast County, Summer

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric
Other Asphalt Surfaces	5	1000sqft

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Utility Company	Southern California Edison
Climate Zone	8	Precipitation Freq (Days)) 33		

1.3 User Entered Comments

Project Characteristics -

Land Use - Square footage of ground disturbance based on 250 feet of frontage of the Agoura Hills Redevelopment Agency owned parceland 20 foot width of disturbance from the existing roadway edge.

Construction Phase - Construction period based on default phase length, starting in 2013.

2.0 Emissions Summary

2.1 Overall Construction (Maximum Daily Emission)

Unmitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year	Year Ib/day							lb/day								
2013	2.50	14.64	11.16	0.02	0.91	1.21	1.95	0.42	1.21	1.47	0.00	1,639.79	0.00	0.22	0.00	1,644.44
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e		
Year	lb/day										lb/day							
2013	2.50	14.64	11.16	0.02	0.76	1.21	1.80	0.42	1.21	1.47	0.00	1,639.79	0.00	0.22	0.00	1,644.44		
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA		

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category	ry Ib/day										lb/day						
Area	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00	
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00	
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00	
Total	0.13	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00	0.00	0.00	

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category	ry Ib/day										lb/day						
Area	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00	
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00	
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00	
Total	0.13	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00	0.00	0.00	

3.0 Construction Detail

3.1 Mitigation Measures Construction

3.2 Site Preparation - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e		
Category	lb/day										lb/day							
Fugitive Dust					0.53	0.00	0.53	0.00	0.00	0.00						0.00		
Off-Road	1.72	12.58	8.68	0.01		0.81	0.81		0.81	0.81		1,402.64		0.15		1,405.88		
Total	1.72	12.58	8.68	0.01	0.53	0.81	1.34	0.00	0.81	0.81		1,402.64		0.15		1,405.88		

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Category	bry Ib/day										lb/day						
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00	
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00	
Worker	0.03	0.03	0.39	0.00	0.08	0.00	0.08	0.00	0.00	0.01		64.24		0.00		64.32	
Total	0.03	0.03	0.39	0.00	0.08	0.00	0.08	0.00	0.00	0.01		64.24		0.00		64.32	

3.2 Site Preparation - 2013

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Fugitive Dust					0.53	0.00	0.53	0.00	0.00	0.00						0.00
Off-Road	1.72	12.58	8.68	0.01		0.81	0.81		0.81	0.81	0.00	1,402.64		0.15		1,405.88
Total	1.72	12.58	8.68	0.01	0.53	0.81	1.34	0.00	0.81	0.81	0.00	1,402.64		0.15		1,405.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.03	0.03	0.39	0.00	0.00	0.00	0.01	0.00	0.00	0.01		64.24		0.00		64.32
Total	0.03	0.03	0.39	0.00	0.00	0.00	0.01	0.00	0.00	0.01		64.24		0.00		64.32

3.3 Grading - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Fugitive Dust					0.75	0.00	0.75	0.41	0.00	0.41						0.00
Off-Road	2.00	13.91	9.51	0.02		1.04	1.04		1.04	1.04		1,476.12		0.18		1,479.88
Total	2.00	13.91	9.51	0.02	0.75	1.04	1.79	0.41	1.04	1.45		1,476.12		0.18		1,479.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	day							lb/c	lay		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.07	0.07	0.78	0.00	0.15	0.01	0.16	0.01	0.01	0.01		128.48		0.01		128.65
Total	0.07	0.07	0.78	0.00	0.15	0.01	0.16	0.01	0.01	0.01		128.48		0.01		128.65

3.3 Grading - 2013

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Fugitive Dust					0.75	0.00	0.75	0.41	0.00	0.41						0.00
Off-Road	2.00	13.91	9.51	0.02		1.04	1.04		1.04	1.04	0.00	1,476.12		0.18		1,479.88
Total	2.00	13.91	9.51	0.02	0.75	1.04	1.79	0.41	1.04	1.45	0.00	1,476.12		0.18		1,479.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.07	0.07	0.78	0.00	0.01	0.01	0.01	0.01	0.01	0.01		128.48		0.01		128.65
Total	0.07	0.07	0.78	0.00	0.01	0.01	0.01	0.01	0.01	0.01		128.48		0.01		128.65

3.4 Paving - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Off-Road	2.32	14.52	9.76	0.02		1.20	1.20		1.20	1.20		1,408.52		0.21	1 1	1,412.88
Paving	0.06					0.00	0.00		0.00	0.00					• · ·	0.00
Total	2.38	14.52	9.76	0.02		1.20	1.20		1.20	1.20		1,408.52		0.21		1,412.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.12	0.12	1.40	0.00	0.28	0.01	0.29	0.01	0.01	0.02		231.27		0.01		231.56
Total	0.12	0.12	1.40	0.00	0.28	0.01	0.29	0.01	0.01	0.02		231.27		0.01		231.56

3.4 Paving - 2013

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Off-Road	2.32	14.52	9.76	0.02		1.20	1.20		1.20	1.20	0.00	1,408.52		0.21	1 1	1,412.88
Paving	0.06					0.00	0.00		0.00	0.00					• · ·	0.00
Total	2.38	14.52	9.76	0.02		1.20	1.20		1.20	1.20	0.00	1,408.52		0.21		1,412.88

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.12	0.12	1.40	0.00	0.01	0.01	0.02	0.01	0.01	0.02		231.27		0.01		231.56
Total	0.12	0.12	1.40	0.00	0.01	0.01	0.02	0.01	0.01	0.02		231.27		0.01		231.56

4.0 Mobile Detail

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Mitigated	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Unmitigated	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

4.2 Trip Summary Information

	Aver	rage Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Other Asphalt Surfaces	0.00	0.00	0.00		
Total	0.00	0.00	0.00		

4.3 Trip Type Information

		Miles			Trip %	
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW
Other Asphalt Surfaces	8.90	13.30	7.40	0.00	0.00	0.00

5.0 Energy Detail

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
NaturalGas Mitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
NaturalGas Unmitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

5.2 Energy by Land Use - NaturalGas

<u>Unmitigated</u>

	NaturalGas Use	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					lb/c	lay							lb/d	ay		
Other Asphalt Surfaces	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00

5.2 Energy by Land Use - NaturalGas

Mitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					lb/c	day							lb/d	ay		
Other Asphalt Surfaces	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00

6.0 Area Detail

6.1 Mitigation Measures Area

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	day							lb/c	day		
Mitigated	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Unmitigated	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00	• • • • • • • • •	0.00		0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

6.2 Area by SubCategory

<u>Unmitigated</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					lb/d	day							lb/c	lay		
Architectural Coating	0.03					0.00	0.00		0.00	0.00						0.00
Consumer Products	0.10					0.00	0.00		0.00	0.00						0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Total	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					lb/c	day							lb/c	lay		
Architectural Coating	0.03					0.00	0.00		0.00	0.00						0.00
Consumer Products	0.10					0.00	0.00		0.00	0.00						0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Total	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00

7.0 Water Detail

7.1 Mitigation Measures Water

8.0 Waste Detail

8.1 Mitigation Measures Waste

9.0 Vegetation

CalEEMod Version: CalEEMod.2011.1.1

Date: 2/1/2012

Agoura Business Center West and North Development Agreement Los Angeles-South Coast County, Winter

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric
Other Asphalt Surfaces	5	1000sqft

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Utility Company	Southern California Edison
Climate Zone	8	Precipitation Freq (Days)) 33		

1.3 User Entered Comments

Project Characteristics -

Land Use - Square footage of ground disturbance based on 250 feet of frontage of the Agoura Hills Redevelopment Agency owned parceland 20 foot width of disturbance from the existing roadway edge.

Construction Phase - Construction period based on default phase length, starting in 2013.

2.0 Emissions Summary

2.1 Overall Construction (Maximum Daily Emission)

Unmitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year		lb/day											lb/c	lay		
2013	2.51	14.66	11.09	0.02	0.91	1.21	1.95	0.42	1.21	1.47	0.00	1,622.77	0.00	0.22	0.00	1,627.41
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					lb/c	day				lb/c	lay					
2013	2.51	14.66	11.09	0.02	0.76	1.21	1.80	0.42	1.21	1.47	0.00	1,622.77	0.00	0.22	0.00	1,627.41
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay	_	
Area	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Total	0.13	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00	0.00	0.00

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Area	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Total	0.13	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00	0.00	0.00

3.0 Construction Detail

3.1 Mitigation Measures Construction

3.2 Site Preparation - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Fugitive Dust					0.53	0.00	0.53	0.00	0.00	0.00						0.00
Off-Road	1.72	12.58	8.68	0.01		0.81	0.81		0.81	0.81		1,402.64		0.15		1,405.88
Total	1.72	12.58	8.68	0.01	0.53	0.81	1.34	0.00	0.81	0.81		1,402.64		0.15		1,405.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.04	0.04	0.37	0.00	0.08	0.00	0.08	0.00	0.00	0.01		59.52		0.00		59.59
Total	0.04	0.04	0.37	0.00	0.08	0.00	0.08	0.00	0.00	0.01		59.52		0.00		59.59

3.2 Site Preparation - 2013

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Fugitive Dust					0.53	0.00	0.53	0.00	0.00	0.00						0.00
Off-Road	1.72	12.58	8.68	0.01		0.81	0.81		0.81	0.81	0.00	1,402.64		0.15		1,405.88
Total	1.72	12.58	8.68	0.01	0.53	0.81	1.34	0.00	0.81	0.81	0.00	1,402.64		0.15		1,405.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	lay							lb/c	lay		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.04	0.04	0.37	0.00	0.00	0.00	0.01	0.00	0.00	0.01		59.52		0.00		59.59
Total	0.04	0.04	0.37	0.00	0.00	0.00	0.01	0.00	0.00	0.01		59.52		0.00		59.59

3.3 Grading - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Fugitive Dust					0.75	0.00	0.75	0.41	0.00	0.41						0.00
Off-Road	2.00	13.91	9.51	0.02		1.04	1.04		1.04	1.04		1,476.12		0.18		1,479.88
Total	2.00	13.91	9.51	0.02	0.75	1.04	1.79	0.41	1.04	1.45		1,476.12		0.18		1,479.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.07	0.08	0.74	0.00	0.15	0.01	0.16	0.01	0.01	0.01		119.03		0.01		119.19
Total	0.07	0.08	0.74	0.00	0.15	0.01	0.16	0.01	0.01	0.01		119.03		0.01		119.19

3.3 Grading - 2013

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Fugitive Dust					0.75	0.00	0.75	0.41	0.00	0.41						0.00
Off-Road	2.00	13.91	9.51	0.02		1.04	1.04		1.04	1.04	0.00	1,476.12		0.18		1,479.88
Total	2.00	13.91	9.51	0.02	0.75	1.04	1.79	0.41	1.04	1.45	0.00	1,476.12		0.18		1,479.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	day							lb/c	lay		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.07	0.08	0.74	0.00	0.01	0.01	0.01	0.01	0.01	0.01		119.03		0.01		119.19
Total	0.07	0.08	0.74	0.00	0.01	0.01	0.01	0.01	0.01	0.01		119.03		0.01		119.19

3.4 Paving - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Off-Road	2.32	14.52	9.76	0.02		1.20	1.20		1.20	1.20		1,408.52		0.21	1 1	1,412.88
Paving	0.06					0.00	0.00		0.00	0.00					• · ·	0.00
Total	2.38	14.52	9.76	0.02		1.20	1.20		1.20	1.20		1,408.52		0.21		1,412.88

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	day		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.13	0.14	1.33	0.00	0.28	0.01	0.29	0.01	0.01	0.02		214.26		0.01		214.54
Total	0.13	0.14	1.33	0.00	0.28	0.01	0.29	0.01	0.01	0.02		214.26		0.01		214.54

3.4 Paving - 2013

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	day		
Off-Road	2.32	14.52	9.76	0.02		1.20	1.20		1.20	1.20	0.00	1,408.52		0.21	1 1	1,412.88
Paving	0.06					0.00	0.00		0.00	0.00					• · ·	0.00
Total	2.38	14.52	9.76	0.02		1.20	1.20		1.20	1.20	0.00	1,408.52		0.21		1,412.88

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/o	day							lb/c	lay		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Worker	0.13	0.14	1.33	0.00	0.01	0.01	0.02	0.01	0.01	0.02		214.26		0.01		214.54
Total	0.13	0.14	1.33	0.00	0.01	0.01	0.02	0.01	0.01	0.02		214.26		0.01		214.54

4.0 Mobile Detail

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
Mitigated	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Unmitigated	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00		0.00		0.00		0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

4.2 Trip Summary Information

	Aver	rage Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Other Asphalt Surfaces	0.00	0.00	0.00		
Total	0.00	0.00	0.00		

4.3 Trip Type Information

		Miles			Trip %	
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW
Other Asphalt Surfaces	8.90	13.30	7.40	0.00	0.00	0.00

5.0 Energy Detail

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/d	day							lb/c	lay		
NaturalGas Mitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
NaturalGas Unmitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

5.2 Energy by Land Use - NaturalGas

<u>Unmitigated</u>

	NaturalGas Use	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					lb/c	lay							lb/d	ay		
Other Asphalt Surfaces	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00

5.2 Energy by Land Use - NaturalGas

Mitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					lb/c	day							lb/d	ay		
Other Asphalt Surfaces	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00	0.00	0.00

6.0 Area Detail

6.1 Mitigation Measures Area

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					lb/c	day							lb/c	day		
Mitigated	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Unmitigated	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00	• • • • • • • • •	0.00		0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

6.2 Area by SubCategory

<u>Unmitigated</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					lb/d	day							lb/c	lay		
Architectural Coating	0.03					0.00	0.00		0.00	0.00						0.00
Consumer Products	0.10					0.00	0.00		0.00	0.00						0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Total	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					lb/c	day							lb/c	lay		
Architectural Coating	0.03					0.00	0.00		0.00	0.00						0.00
Consumer Products	0.10					0.00	0.00		0.00	0.00						0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00
Total	0.13	0.00	0.00	0.00		0.00	0.00		0.00	0.00		0.00		0.00		0.00

7.0 Water Detail

7.1 Mitigation Measures Water

8.0 Waste Detail

8.1 Mitigation Measures Waste

9.0 Vegetation

CalEEMod Version: CalEEMod.2011.1.1

Date: 2/1/2012

Agoura Business Center West and North Development Agreement

Los Angeles-South Coast County, Annual

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric
Other Asphalt Surfaces	5	1000sqft

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s)	2.2	Utility Company	Southern California Edison
Climate Zone	8	Precipitation Freq (Days)) 33		

1.3 User Entered Comments

Project Characteristics -

Land Use - Square footage of ground disturbance based on 250 feet of frontage of the Agoura Hills Redevelopment Agency owned parceland 20 foot width of disturbance from the existing roadway edge.

Construction Phase - Construction period based on default phase length, starting in 2013.

2.0 Emissions Summary

2.1 Overall Construction

Unmitigated Construction

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					ton	s/yr				MT	/yr					
2013	0.01	0.06	0.04	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	5.80	5.80	0.00	0.00	5.82
Total	0.01	0.06	0.04	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	5.80	5.80	0.00	0.00	5.82

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					ton	s/yr				MT	/yr					
2013	0.01	0.06	0.04	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	5.80	5.80	0.00	0.00	5.82
Total	0.01	0.06	0.04	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	5.80	5.80	0.00	0.00	5.82

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Area	0.02	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Waste						0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Water						0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

2.2 Overall Operational

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Area	0.02	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Mobile	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Waste						0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Water						0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

3.0 Construction Detail

3.1 Mitigation Measures Construction

3.2 Site Preparation - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.01	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.64	0.64	0.00	0.00	0.64
Total	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.64	0.64	0.00	0.00	0.64

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.03	0.00	0.00	0.03
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.03	0.00	0.00	0.03

3.2 Site Preparation - 2013

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.01	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.64	0.64	0.00	0.00	0.64
Total	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.64	0.64	0.00	0.00	0.64

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.03	0.00	0.00	0.03
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.03	0.03	0.00	0.00	0.03

3.3 Grading - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.01	0.01	0.00		0.00	0.00		0.00	0.00	0.00	1.34	1.34	0.00	0.00	1.34
Total	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.34	1.34	0.00	0.00	1.34

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.11	0.00	0.00	0.11
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.11	0.00	0.00	0.11

3.3 Grading - 2013

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.01	0.01	0.00		0.00	0.00		0.00	0.00	0.00	1.34	1.34	0.00	0.00	1.34
Total	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.34	1.34	0.00	0.00	1.34

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.11	0.00	0.00	0.11
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.11	0.00	0.00	0.11

3.4 Paving - 2013

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.01	0.04	0.02	0.00		0.00	0.00		0.00	0.00	0.00	3.19	3.19	0.00	0.00	3.20
Paving	0.00					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.01	0.04	0.02	0.00		0.00	0.00		0.00	0.00	0.00	3.19	3.19	0.00	0.00	3.20

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	0.50	0.00	0.00	0.50
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	0.50	0.00	0.00	0.50

3.4 Paving - 2013

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.01	0.04	0.02	0.00		0.00	0.00		0.00	0.00	0.00	3.19	3.19	0.00	0.00	3.20
Paving	0.00					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.01	0.04	0.02	0.00		0.00	0.00		0.00	0.00	0.00	3.19	3.19	0.00	0.00	3.20

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	7/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	0.50	0.00	0.00	0.50
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	0.50	0.00	0.00	0.50

4.0 Mobile Detail

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Unmitigated	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

4.2 Trip Summary Information

	Ave	rage Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Other Asphalt Surfaces	0.00	0.00	0.00		
Total	0.00	0.00	0.00		

4.3 Trip Type Information

		Miles			Trip %	
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW
Other Asphalt Surfaces	8.90	13.30	7.40	0.00	0.00	0.00

5.0 Energy Detail

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Electricity Mitigated						0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Electricity Unmitigated						0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
NaturalGas Mitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
NaturalGas Unmitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

5.2 Energy by Land Use - NaturalGas

<u>Unmitigated</u>

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					ton	s/yr							MT	/yr		
Other Asphalt Surfaces	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

5.2 Energy by Land Use - NaturalGas

Mitigated

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU		tons/yr										MT	/yr			
Other Asphalt Surfaces	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

5.3 Energy by Land Use - Electricity

<u>Unmitigated</u>

	Electricity Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	kWh		ton	s/yr			MT	/yr	
Other Asphalt Surfaces	0					0.00	0.00	0.00	0.00
Total						0.00	0.00	0.00	0.00

5.3 Energy by Land Use - Electricity

Mitigated

	Electricity Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	kWh		ton	s/yr			MT	/yr	
Other Asphalt Surfaces	0					0.00	0.00	0.00	0.00
Total						0.00	0.00	0.00	0.00

6.0 Area Detail

6.1 Mitigation Measures Area

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.02	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Unmitigated	0.02	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

6.2 Area by SubCategory

<u>Unmitigated</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	/yr		
Architectural Coating	0.01					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Consumer Products	0.02					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.03	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	/yr		
Architectural Coating	0.01					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Consumer Products	0.02					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.03	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

7.0 Water Detail

7.1 Mitigation Measures Water

	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Category		ton	s/yr			MT	/yr	
Mitigated					0.00	0.00	0.00	0.00
Unmitigated					0.00	0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA

7.2 Water by Land Use

<u>Unmitigated</u>

	Indoor/Outdoor Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		ton	s/yr			MT	/yr	
Other Asphalt Surfaces	0 / 0					0.00	0.00	0.00	0.00
Total						0.00	0.00	0.00	0.00

7.2 Water by Land Use

Mitigated

	Indoor/Outdoor Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		ton	s/yr			MT	/yr	
Other Asphalt Surfaces	0/0					0.00	0.00	0.00	0.00
Total						0.00	0.00	0.00	0.00

8.0 Waste Detail

8.1 Mitigation Measures Waste

Category/Year

	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
		ton	s/yr			MT	/yr	
Mitigated					0.00	0.00	0.00	0.00
Unmitigated					0.00	0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA

8.2 Waste by Land Use


<u>Unmitigated</u>

	Waste Disposed	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	tons		ton	s/yr			MT	/yr	
Other Asphalt Surfaces	0					0.00	0.00	0.00	0.00
Total						0.00	0.00	0.00	0.00

Mitigated

	Waste Disposed	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	tons		ton	s/yr			MT	/yr	
Other Asphalt Surfaces	0					0.00	0.00	0.00	0.00
Total						0.00	0.00	0.00	0.00

9.0 Vegetation





Agoura Hills Business Park Los Angeles-South Coast County, Annual

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric
General Office Building	103.07	1000sqft
Parking Lot	217	Space

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s) 2.2	Utility Company	Southern California Edison
Climate Zone	8	Precipitation Freq (Days) 33		

1.3 User Entered Comments

Project Characteristics -

Land Use -

Vehicle Trips - Trip rates derived from traffic study by Kunzman Associates, Inc.

2.0 Emissions Summary

2.1 Overall Construction

Unmitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					ton	s/yr							MT	/yr		
2011	0.98	6.59	4.69	0.01	0.21	0.41	0.63	0.05	0.41	0.46	0.00	701.66	701.66	0.08	0.00	703.31
2012	2.26	0.35	0.25	0.00	0.01	0.03	0.03	0.00	0.03	0.03	0.00	33.16	33.16	0.00	0.00	33.26
Total	3.24	6.94	4.94	0.01	0.22	0.44	0.66	0.05	0.44	0.49	0.00	734.82	734.82	0.08	0.00	736.57

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Year					ton	s/yr							MT	/yr		
2011	0.98	6.59	4.69	0.01	0.08	0.41	0.49	0.05	0.41	0.46	0.00	701.66	701.66	0.08	0.00	703.31
2012	2.26	0.35	0.25	0.00	0.00	0.03	0.03	0.00	0.03	0.03	0.00	33.16	33.16	0.00	0.00	33.26
Total	3.24	6.94	4.94	0.01	0.08	0.44	0.52	0.05	0.44	0.49	0.00	734.82	734.82	0.08	0.00	736.57

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Area	0.91	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Energy	0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	521.04	521.04	0.02	0.01	524.29
Mobile	0.80	2.03	8.09	0.01	1.24	0.09	1.33	0.05	0.09	0.14	0.00	1,167.84	1,167.84	0.06	0.00	1,169.05
Waste						0.00	0.00		0.00	0.00	19.46	0.00	19.46	1.15	0.00	43.61
Water						0.00	0.00		0.00	0.00	0.00	105.87	105.87	0.56	0.02	122.57
Total	1.72	2.08	8.13	0.01	1.24	0.09	1.33	0.05	0.09	0.14	19.46	1,794.75	1,814.21	1.79	0.03	1,859.52

2.2 Overall Operational

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Area	0.91	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Energy	0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	521.04	521.04	0.02	0.01	524.29
Mobile	0.80	2.03	8.09	0.01	1.24	0.09	1.33	0.05	0.09	0.14	0.00	1,167.84	1,167.84	0.06	0.00	1,169.05
Waste						0.00	0.00		0.00	0.00	19.46	0.00	19.46	1.15	0.00	43.61
Water						0.00	0.00		0.00	0.00	0.00	105.87	105.87	0.56	0.02	122.57
Total	1.72	2.08	8.13	0.01	1.24	0.09	1.33	0.05	0.09	0.14	19.46	1,794.75	1,814.21	1.79	0.03	1,859.52

3.0 Construction Detail

3.1 Mitigation Measures Construction

3.2 Demolition - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.10	0.80	0.46	0.00		0.04	0.04		0.04	0.04	0.00	68.12	68.12	0.01	0.00	68.29
Total	0.10	0.80	0.46	0.00		0.04	0.04		0.04	0.04	0.00	68.12	68.12	0.01	0.00	68.29

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.72	1.72	0.00	0.00	1.73
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.72	1.72	0.00	0.00	1.73

3.2 Demolition - 2011

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.10	0.80	0.46	0.00		0.04	0.04		0.04	0.04	0.00	68.12	68.12	0.01	0.00	68.29
Total	0.10	0.80	0.46	0.00		0.04	0.04		0.04	0.04	0.00	68.12	68.12	0.01	0.00	68.29

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.72	1.72	0.00	0.00	1.73
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.72	1.72	0.00	0.00	1.73

3.3 Site Preparation - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.05	0.00	0.05	0.02	0.00	0.02	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.03	0.22	0.13	0.00		0.01	0.01		0.01	0.01	0.00	18.13	18.13	0.00	0.00	18.18
Total	0.03	0.22	0.13	0.00	0.05	0.01	0.06	0.02	0.01	0.03	0.00	18.13	18.13	0.00	0.00	18.18

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.52	0.52	0.00	0.00	0.52
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.52	0.52	0.00	0.00	0.52

3.3 Site Preparation - 2011

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.05	0.00	0.05	0.02	0.00	0.02	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.03	0.22	0.13	0.00		0.01	0.01		0.01	0.01	0.00	18.13	18.13	0.00	0.00	18.18
Total	0.03	0.22	0.13	0.00	0.05	0.01	0.06	0.02	0.01	0.03	0.00	18.13	18.13	0.00	0.00	18.18

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.52	0.52	0.00	0.00	0.52
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.52	0.52	0.00	0.00	0.52

3.4 Grading - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.03	0.00	0.03	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.03	0.22	0.13	0.00		0.01	0.01		0.01	0.01	0.00	19.01	19.01	0.00	0.00	19.06
Total	0.03	0.22	0.13	0.00	0.03	0.01	0.04	0.01	0.01	0.02	0.00	19.01	19.01	0.00	0.00	19.06

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.69	0.69	0.00	0.00	0.69
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.69	0.69	0.00	0.00	0.69

3.4 Grading - 2011

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.03	0.00	0.03	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.03	0.22	0.13	0.00		0.01	0.01		0.01	0.01	0.00	19.01	19.01	0.00	0.00	19.06
Total	0.03	0.22	0.13	0.00	0.03	0.01	0.04	0.01	0.01	0.02	0.00	19.01	19.01	0.00	0.00	19.06

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.69	0.69	0.00	0.00	0.69
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.69	0.69	0.00	0.00	0.69

Unmitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.69	4.56	2.73	0.00		0.32	0.32		0.32	0.32	0.00	415.93	415.93	0.06	0.00	417.11
Total	0.69	4.56	2.73	0.00		0.32	0.32		0.32	0.32	0.00	415.93	415.93	0.06	0.00	417.11

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.07	0.71	0.52	0.00	0.03	0.03	0.06	0.00	0.03	0.03	0.00	87.54	87.54	0.00	0.00	87.61
Worker	0.06	0.07	0.70	0.00	0.11	0.00	0.11	0.00	0.00	0.01	0.00	90.00	90.00	0.01	0.00	90.13
Total	0.13	0.78	1.22	0.00	0.14	0.03	0.17	0.00	0.03	0.04	0.00	177.54	177.54	0.01	0.00	177.74

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.69	4.56	2.73	0.00		0.32	0.32		0.32	0.32	0.00	415.93	415.93	0.06	0.00	417.11
Total	0.69	4.56	2.73	0.00		0.32	0.32		0.32	0.32	0.00	415.93	415.93	0.06	0.00	417.11

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.07	0.71	0.52	0.00	0.00	0.03	0.03	0.00	0.03	0.03	0.00	87.54	87.54	0.00	0.00	87.61
Worker	0.06	0.07	0.70	0.00	0.00	0.00	0.01	0.00	0.00	0.01	0.00	90.00	90.00	0.01	0.00	90.13
Total	0.13	0.78	1.22	0.00	0.00	0.03	0.04	0.00	0.03	0.04	0.00	177.54	177.54	0.01	0.00	177.74

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr				MT	/yr					
Off-Road	0.01	0.06	0.04	0.00		0.00	0.00		0.00	0.00	0.00	5.50	5.50	0.00	0.00	5.51
Total	0.01	0.06	0.04	0.00		0.00	0.00		0.00	0.00	0.00	5.50	5.50	0.00	0.00	5.51

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.16	1.16	0.00	0.00	1.16
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.17	1.17	0.00	0.00	1.17
Total	0.00	0.01	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.33	2.33	0.00	0.00	2.33

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category		tons/yr											MT	/yr		
Off-Road	0.01	0.06	0.04	0.00		0.00	0.00		0.00	0.00	0.00	5.50	5.50	0.00	0.00	5.51
Total	0.01	0.06	0.04	0.00		0.00	0.00		0.00	0.00	0.00	5.50	5.50	0.00	0.00	5.51

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.16	1.16	0.00	0.00	1.16
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.17	1.17	0.00	0.00	1.17
Total	0.00	0.01	0.02	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.33	2.33	0.00	0.00	2.33

3.6 Paving - 2012

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.04	0.25	0.15	0.00		0.02	0.02		0.02	0.02	0.00	19.60	19.60	0.00	0.00	19.67
Paving	0.00					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.04	0.25	0.15	0.00		0.02	0.02		0.02	0.02	0.00	19.60	19.60	0.00	0.00	19.67

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.03	2.03	0.00	0.00	2.03
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.03	2.03	0.00	0.00	2.03

3.6 Paving - 2012

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.04	0.25	0.15	0.00		0.02	0.02		0.02	0.02	0.00	19.60	19.60	0.00	0.00	19.67
Paving	0.00					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.04	0.25	0.15	0.00		0.02	0.02		0.02	0.02	0.00	19.60	19.60	0.00	0.00	19.67

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.03	2.03	0.00	0.00	2.03
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.03	2.03	0.00	0.00	2.03

3.7 Architectural Coating - 2012

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	2.20					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.03	0.02	0.00		0.00	0.00		0.00	0.00	0.00	2.30	2.30	0.00	0.00	2.30
Total	2.20	0.03	0.02	0.00		0.00	0.00		0.00	0.00	0.00	2.30	2.30	0.00	0.00	2.30

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.42	1.42	0.00	0.00	1.42
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.42	1.42	0.00	0.00	1.42

3.7 Architectural Coating - 2012

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	2.20					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.03	0.02	0.00		0.00	0.00		0.00	0.00	0.00	2.30	2.30	0.00	0.00	2.30
Total	2.20	0.03	0.02	0.00		0.00	0.00		0.00	0.00	0.00	2.30	2.30	0.00	0.00	2.30

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.42	1.42	0.00	0.00	1.42
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.42	1.42	0.00	0.00	1.42

4.0 Mobile Detail

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.80	2.03	8.09	0.01	1.24	0.09	1.33	0.05	0.09	0.14	0.00	1,167.84	1,167.84	0.06	0.00	1,169.05
Unmitigated	0.80	2.03	8.09	0.01	1.24	0.09	1.33	0.05	0.09	0.14	0.00	1,167.84	1,167.84	0.06	0.00	1,169.05
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

4.2 Trip Summary Information

	Ave	rage Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Parking Lot	0.00	0.00	0.00		
General Office Building	718.40	718.40	718.40	2,294,196	2,294,196
Total	718.40	718.40	718.40	2,294,196	2,294,196

4.3 Trip Type Information

		Miles			Trip %	
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW
Parking Lot	8.90	13.30	7.40	0.00	0.00	0.00
General Office Building	8.90	13.30	7.40	33.00	48.00	19.00

5.0 Energy Detail

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Electricity Mitigated						0.00	0.00		0.00	0.00	0.00	468.29	468.29	0.02	0.01	471.22
Electricity Unmitigated						0.00	0.00		0.00	0.00	0.00	468.29	468.29	0.02	0.01	471.22
NaturalGas Mitigated	0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	52.75	52.75	0.00	0.00	53.07
NaturalGas Unmitigated	0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	52.75	52.75	0.00	0.00	53.07
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

5.2 Energy by Land Use - NaturalGas

<u>Unmitigated</u>

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					ton	s/yr							MT	/yr		
General Office Building	988441	0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	52.75	52.75	0.00	0.00	53.07
Parking Lot	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total		0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	52.75	52.75	0.00	0.00	53.07

Mitigated

	NaturalGas Use	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					ton	s/yr							MT	/yr		
General Office Building	988441	0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	52.75	52.75	0.00	0.00	53.07
Parking Lot	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total		0.01	0.05	0.04	0.00		0.00	0.00		0.00	0.00	0.00	52.75	52.75	0.00	0.00	53.07

5.3 Energy by Land Use - Electricity

<u>Unmitigated</u>

	Electricity Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	kWh		ton	s/yr			M	ſ/yr	
General Office Building	1.60995e+006					468.29	0.02	0.01	471.22
Parking Lot	0					0.00	0.00	0.00	0.00
Total						468.29	0.02	0.01	471.22

Mitigated

	Electricity Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	kWh		ton	s/yr			MT	/yr	
General Office Building	1.60995e+006					468.29	0.02	0.01	471.22
Parking Lot	0					0.00	0.00	0.00	0.00
Total						468.29	0.02	0.01	471.22

6.0 Area Detail

6.1 Mitigation Measures Area

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.91	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Unmitigated	0.91	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

6.2 Area by SubCategory

<u>Unmitigated</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	/yr		
Architectural Coating	0.22					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Consumer Products	0.69					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.91	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	/yr		
Architectural Coating	0.22					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Consumer Products	0.69					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.91	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

7.0 Water Detail

7.1 Mitigation Measures Water

	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Category		ton	s/yr			MT	/yr	
Mitigated					105.87	0.56	0.02	122.57
Unmitigated					105.87	0.56	0.02	122.57
Total	NA	NA	NA	NA	NA	NA	NA	NA

7.2 Water by Land Use

<u>Unmitigated</u>

	Indoor/Outdoor Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		ton	s/yr			MT	/yr	
General Office Building	18.319 / 11.2278					105.87	0.56	0.02	122.57
Parking Lot	0/0					0.00	0.00	0.00	0.00
Total						105.87	0.56	0.02	122.57

7.2 Water by Land Use

Mitigated

	Indoor/Outdoor Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	Mgal		ton	s/yr			MT	/yr	
General Office Building	18.319 / 11.2278					105.87	0.56	0.02	122.57
Parking Lot	0/0					0.00	0.00	0.00	0.00
Total						105.87	0.56	0.02	122.57

8.0 Waste Detail

8.1 Mitigation Measures Waste

Category/Year

	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e			
		ton	s/yr		MT/yr						
Mitigated					19.46	1.15	0.00	43.61			
Unmitigated					19.46	1.15	0.00	43.61			
Total	NA	NA	NA	NA	NA	NA	NA	NA			

Agoura Business Center West Los Angeles-South Coast County, Annual

1.0 Project Characteristics

1.1 Land Usage

Land Uses	Size	Metric				
Regional Shopping Center	20.64	1000sqft				
Parking Lot	89	Space				

1.2 Other Project Characteristics

Urbanization	Urban	Wind Speed (m/s) 2.	.2	Utility Company	Southern California Edison
Climate Zone	8	Precipitation Freq (Days) 33	3		

1.3 User Entered Comments

Project Characteristics -

Land Use -

Vehicle Trips - Trip rates derived from traffic study by Kunzman Associates, Inc.

2.0 Emissions Summary

2.1 Overall Construction

Unmitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e	
Year		tons/yr									MT/yr						
2011	1.31	3.48	2.44	0.00	0.06	0.24	0.30	0.01	0.24	0.25	0.00	335.40	335.40	0.05	0.00	336.53	
Total	1.31	3.48	2.44	0.00	0.06	0.24	0.30	0.01	0.24	0.25	0.00	335.40	335.40	0.05	0.00	336.53	

Mitigated Construction

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e		
Year		tons/yr									MT/yr							
2011	1.31	3.48	2.44	0.00	0.02	0.24	0.26	0.01	0.24	0.25	0.00	335.40	335.40	0.05	0.00	336.53		
Total	1.31	3.48	2.44	0.00	0.02	0.24	0.26	0.01	0.24	0.25	0.00	335.40	335.40	0.05	0.00	336.53		

2.2 Overall Operational

Unmitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category	ry tons/yr									MT/yr						
Area	0.27	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	79.10	79.10	0.00	0.00	79.60
Mobile	0.89	2.19	8.83	0.01	1.30	0.09	1.39	0.05	0.09	0.14	0.00	1,229.06	1,229.06	0.06	0.00	1,230.35
Waste						0.00	0.00		0.00	0.00	4.40	0.00	4.40	0.26	0.00	9.86
Water						0.00	0.00		0.00	0.00	0.00	8.84	8.84	0.05	0.00	10.23
Total	1.16	2.19	8.83	0.01	1.30	0.09	1.39	0.05	0.09	0.14	4.40	1,317.00	1,321.40	0.37	0.00	1,330.04

2.2 Overall Operational

Mitigated Operational

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Area	0.27	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Energy	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	79.10	79.10	0.00	0.00	79.60
Mobile	0.89	2.19	8.83	0.01	1.30	0.09	1.39	0.05	0.09	0.14	0.00	1,229.06	1,229.06	0.06	0.00	1,230.35
Waste						0.00	0.00		0.00	0.00	4.40	0.00	4.40	0.26	0.00	9.86
Water						0.00	0.00		0.00	0.00	0.00	8.84	8.84	0.05	0.00	10.23
Total	1.16	2.19	8.83	0.01	1.30	0.09	1.39	0.05	0.09	0.14	4.40	1,317.00	1,321.40	0.37	0.00	1,330.04

3.0 Construction Detail

3.1 Mitigation Measures Construction

3.2 Demolition - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr				MT	/yr					
Off-Road	0.06	0.43	0.26	0.00		0.03	0.03		0.03	0.03	0.00	35.79	35.79	0.00	0.00	35.89
Total	0.06	0.43	0.26	0.00		0.03	0.03		0.03	0.03	0.00	35.79	35.79	0.00	0.00	35.89

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							МТ	/yr	-	
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.49	1.49	0.00	0.00	1.50
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.49	1.49	0.00	0.00	1.50

3.2 Demolition - 2011

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr				MT	/yr					
Off-Road	0.06	0.43	0.26	0.00		0.03	0.03		0.03	0.03	0.00	35.79	35.79	0.00	0.00	35.89
Total	0.06	0.43	0.26	0.00		0.03	0.03		0.03	0.03	0.00	35.79	35.79	0.00	0.00	35.89

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.49	1.49	0.00	0.00	1.50
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.49	1.49	0.00	0.00	1.50

3.3 Site Preparation - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.04	0.02	0.00		0.00	0.00		0.00	0.00	0.00	2.95	2.95	0.00	0.00	2.96
Total	0.00	0.04	0.02	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	2.95	2.95	0.00	0.00	2.96

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.09	0.00	0.00	0.09
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.09	0.00	0.00	0.09

3.3 Site Preparation - 2011

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.04	0.02	0.00		0.00	0.00		0.00	0.00	0.00	2.95	2.95	0.00	0.00	2.96
Total	0.00	0.04	0.02	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	2.95	2.95	0.00	0.00	2.96

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.09	0.00	0.00	0.09
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.09	0.00	0.00	0.09

3.4 Grading - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.01	0.00	0.01	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.01	0.06	0.03	0.00		0.00	0.00		0.00	0.00	0.00	4.88	4.88	0.00	0.00	4.89
Total	0.01	0.06	0.03	0.00	0.01	0.00	0.01	0.01	0.00	0.01	0.00	4.88	4.88	0.00	0.00	4.89

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.18	0.18	0.00	0.00	0.18
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.18	0.18	0.00	0.00	0.18

3.4 Grading - 2011

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Fugitive Dust					0.01	0.00	0.01	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.01	0.06	0.03	0.00		0.00	0.00		0.00	0.00	0.00	4.88	4.88	0.00	0.00	4.89
Total	0.01	0.06	0.03	0.00	0.01	0.00	0.01	0.01	0.00	0.01	0.00	4.88	4.88	0.00	0.00	4.89

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.18	0.18	0.00	0.00	0.18
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.18	0.18	0.00	0.00	0.18

3.5 Building Construction - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr				MT	/yr					
Off-Road	0.54	2.63	1.71	0.00		0.19	0.19		0.19	0.19	0.00	232.32	232.32	0.04	0.00	233.23
Total	0.54	2.63	1.71	0.00		0.19	0.19		0.19	0.19	0.00	232.32	232.32	0.04	0.00	233.23

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.02	0.18	0.13	0.00	0.01	0.01	0.01	0.00	0.01	0.01	0.00	22.39	22.39	0.00	0.00	22.41
Worker	0.02	0.02	0.20	0.00	0.03	0.00	0.03	0.00	0.00	0.00	0.00	25.28	25.28	0.00	0.00	25.32
Total	0.04	0.20	0.33	0.00	0.04	0.01	0.04	0.00	0.01	0.01	0.00	47.67	47.67	0.00	0.00	47.73

3.5 Building Construction - 2011

Mitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr				MT	/yr					
Off-Road	0.54	2.63	1.71	0.00		0.19	0.19		0.19	0.19	0.00	232.32	232.32	0.04	0.00	233.23
Total	0.54	2.63	1.71	0.00		0.19	0.19		0.19	0.19	0.00	232.32	232.32	0.04	0.00	233.23

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.02	0.18	0.13	0.00	0.00	0.01	0.01	0.00	0.01	0.01	0.00	22.39	22.39	0.00	0.00	22.41
Worker	0.02	0.02	0.20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	25.28	25.28	0.00	0.00	25.32
Total	0.04	0.20	0.33	0.00	0.00	0.01	0.01	0.00	0.01	0.01	0.00	47.67	47.67	0.00	0.00	47.73

3.6 Paving - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.02	0.10	0.06	0.00		0.01	0.01		0.01	0.01	0.00	7.77	7.77	0.00	0.00	7.80
Paving	0.00					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.02	0.10	0.06	0.00		0.01	0.01		0.01	0.01	0.00	7.77	7.77	0.00	0.00	7.80

Unmitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.75	0.75	0.00	0.00	0.75
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.75	0.75	0.00	0.00	0.75

3.6 Paving - 2011

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Off-Road	0.02	0.10	0.06	0.00		0.01	0.01		0.01	0.01	0.00	7.77	7.77	0.00	0.00	7.80
Paving	0.00					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.02	0.10	0.06	0.00		0.01	0.01		0.01	0.01	0.00	7.77	7.77	0.00	0.00	7.80

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.75	0.75	0.00	0.00	0.75
Total	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.75	0.75	0.00	0.00	0.75

3.7 Architectural Coating - 2011

Unmitigated Construction On-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	0.65					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.02	0.01	0.00		0.00	0.00		0.00	0.00	0.00	1.28	1.28	0.00	0.00	1.28
Total	0.65	0.02	0.01	0.00		0.00	0.00		0.00	0.00	0.00	1.28	1.28	0.00	0.00	1.28

Unmitigated Construction Off-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.23	0.23	0.00	0.00	0.23
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.23	0.23	0.00	0.00	0.23

3.7 Architectural Coating - 2011

Mitigated Construction On-Site

	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Archit. Coating	0.65					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Off-Road	0.00	0.02	0.01	0.00		0.00	0.00		0.00	0.00	0.00	1.28	1.28	0.00	0.00	1.28
Total	0.65	0.02	0.01	0.00		0.00	0.00		0.00	0.00	0.00	1.28	1.28	0.00	0.00	1.28

Mitigated Construction Off-Site

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Hauling	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Vendor	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Worker	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.23	0.23	0.00	0.00	0.23
Total	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.23	0.23	0.00	0.00	0.23

4.0 Mobile Detail

4.1 Mitigation Measures Mobile

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.89	2.19	8.83	0.01	1.30	0.09	1.39	0.05	0.09	0.14	0.00	1,229.06	1,229.06	0.06	0.00	1,230.35
Unmitigated	0.89	2.19	8.83	0.01	1.30	0.09	1.39	0.05	0.09	0.14	0.00	1,229.06	1,229.06	0.06	0.00	1,230.35
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

4.2 Trip Summary Information

	Ave	rage Daily Trip Ra	ate	Unmitigated	Mitigated
Land Use	Weekday	Saturday	Sunday	Annual VMT	Annual VMT
Parking Lot	0.00	0.00	0.00		
Regional Shopping Center	916.00	916.00	916.00	2,401,755	2,401,755
Total	916.00	916.00	916.00	2,401,755	2,401,755

4.3 Trip Type Information

		Miles			Trip %	
Land Use	H-W or C-W	H-S or C-C	H-O or C-NW	H-W or C-W	H-S or C-C	H-O or C-NW
Parking Lot	8.90	13.30	7.40	0.00	0.00	0.00
Regional Shopping Center	8.90	13.30	7.40	16.30	64.70	19.00

5.0 Energy Detail

5.1 Mitigation Measures Energy

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Electricity Mitigated						0.00	0.00		0.00	0.00	0.00	76.85	76.85	0.00	0.00	77.33
Electricity Unmitigated						0.00	0.00		0.00	0.00	0.00	76.85	76.85	0.00	0.00	77.33
NaturalGas Mitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	2.26	2.26	0.00	0.00	2.27
NaturalGas Unmitigated	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	2.26	2.26	0.00	0.00	2.27
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

5.2 Energy by Land Use - NaturalGas

<u>Unmitigated</u>

	NaturalGas Use	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					ton	s/yr							MT	/yr		
Parking Lot	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Regional Shopping Center	42312	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	2.26	2.26	0.00	0.00	2.27
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	2.26	2.26	0.00	0.00	2.27

Mitigated

	NaturalGas Use	ROG	NOx	СО	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Land Use	kBTU					ton	s/yr							MT	/yr		
Parking Lot	0	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Regional Shopping Center	42312	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	2.26	2.26	0.00	0.00	2.27
Total		0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	2.26	2.26	0.00	0.00	2.27

5.3 Energy by Land Use - Electricity

<u>Unmitigated</u>

	Electricity Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	kWh		ton	s/yr			M	⊺/yr	
Parking Lot	0					0.00	0.00	0.00	0.00
Regional Shopping Center	264192					76.85	0.00	0.00	77.33
Total						76.85	0.00	0.00	77.33

Mitigated

	Electricity Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	kWh		ton	s/yr			M	/yr	
Parking Lot	0					0.00	0.00	0.00	0.00
Regional Shopping Center	264192					76.85	0.00	0.00	77.33
Total						76.85	0.00	0.00	77.33

6.0 Area Detail

6.1 Mitigation Measures Area

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
Category					ton	s/yr							MT	/yr		
Mitigated	0.27	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Unmitigated	0.27	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

6.2 Area by SubCategory

<u>Unmitigated</u>

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	/yr		
Architectural Coating	0.07					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Consumer Products	0.20					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.27	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

6.2 Area by SubCategory

Mitigated

	ROG	NOx	CO	SO2	Fugitive PM10	Exhaust PM10	PM10 Total	Fugitive PM2.5	Exhaust PM2.5	PM2.5 Total	Bio- CO2	NBio- CO2	Total CO2	CH4	N2O	CO2e
SubCategory					ton	s/yr							MT	/yr		
Architectural Coating	0.07					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Consumer Products	0.20					0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Landscaping	0.00	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Total	0.27	0.00	0.00	0.00		0.00	0.00		0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

7.0 Water Detail

7.1 Mitigation Measures Water

	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e	
Category		ton	s/yr		MT/yr				
Mitigated					8.84	0.05	0.00	10.23	
Unmitigated					8.84	0.05	0.00	10.23	
Total	NA	NA	NA	NA	NA	NA	NA	NA	

7.2 Water by Land Use

<u>Unmitigated</u>

	Indoor/Outdoor Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e	
Land Use	Mgal		tons/yr				MT/yr			
Parking Lot	0/0					0.00	0.00	0.00	0.00	
Regional Shopping Center	1.52886 / 0.937041					8.84	0.05	0.00	10.23	
Total						8.84	0.05	0.00	10.23	

7.2 Water by Land Use

Mitigated

	Indoor/Outdoor Use	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e	
Land Use	Mgal		tons/yr				MT/yr			
Parking Lot	0/0					0.00	0.00	0.00	0.00	
Regional Shopping Center	1.52886 / 0.937041					8.84	0.05	0.00	10.23	
Total						8.84	0.05	0.00	10.23	

8.0 Waste Detail

8.1 Mitigation Measures Waste

Category/Year

	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e	
		ton	s/yr		MT/yr				
Mitigated					4.40	0.26	0.00	9.86	
Unmitigated					4.40	0.26	0.00	9.86	
Total	NA	NA	NA	NA	NA	NA	NA	NA	

8.2 Waste by Land Use

<u>Unmitigated</u>

	Waste Disposed	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	tons		ton	s/yr		MT/yr			
Parking Lot	0					0.00	0.00	0.00	0.00
Regional Shopping Center	21.67					4.40	0.26	0.00	9.86
Total						4.40	0.26	0.00	9.86

Mitigated

	Waste Disposed	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e	
Land Use	tons		tons/yr				MT/yr			
Parking Lot	0					0.00	0.00	0.00	0.00	
Regional Shopping Center	21.67					4.40	0.26	0.00	9.86	
Total						4.40	0.26	0.00	9.86	

9.0 Vegetation

8.2 Waste by Land Use

<u>Unmitigated</u>

	Waste Disposed	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e
Land Use	tons		ton	s/yr		MT/yr			
General Office Building	95.86					19.46	1.15	0.00	43.61
Parking Lot	0					0.00	0.00	0.00	0.00
Total						19.46	1.15	0.00	43.61

Mitigated

	Waste Disposed	ROG	NOx	CO	SO2	Total CO2	CH4	N2O	CO2e	
Land Use	tons		tons/yr				MT/yr			
General Office Building	95.86					19.46	1.15	0.00	43.61	
Parking Lot	0					0.00	0.00	0.00	0.00	
Total						19.46	1.15	0.00	43.61	

9.0 Vegetation





AGOURA BUSINESS CENTER NORTH LLC DEVELOPMENT AGREEMENT TRAFFIC IMPACT ANALYSIS

February 7, 2012

Traffic Engineering | Transportation Planning | Parking | Noise/Vibration | Expert Witness Air Quality | Global Climate Change | Health Risk Assessment




Table of Contents

١.	Findi	ngs2
	А. В. С.	Existing Traffic Conditions
II.	Cong	estion Management Program Methodology6
	А. В. С.	County Congestion Management Program6 Prescribed Methodology for a Traffic Impact Analysis6 Mitigation Measures
III.	Proje	ect Description
	А. В.	Development Description
IV.	Exist	ing Traffic Conditions12
	A. B. C. D. E.	Surrounding Street System12Existing Travel Lanes and Intersection Controls13Existing Average Daily Traffic Volumes13Existing Levels of Service13Existing Traffic Signal Warrant Analysis14
v .	Proje	ect Traffic 20
	А. В. С.	Trip Generation20Trip Distribution20Trip Assignment20
VI.	Ореі	ning Year (2022) Traffic Conditions27
	А. В. С. D.	Method of Projection27Opening Year (2022) Average Daily Traffic Volumes27Opening Year (2022) Levels of Service27Significant Transportation Impact28
VII.	Cumu	alative Traffic Conditions
	В. С. D.	Method of Projection39Cumulative Average Daily Traffic Volumes39Cumulative Levels of Service39Significant Transportation Impact41
VIII.	Reco	mmendations
	А. В.	Site Access 56 Suggested Traffic Conditions 56 1. On- Site 56 2. Off-Site 56

APPENDICES

- Appendix A Glossary of Transportation Terms
- Appendix B Traffic Count Worksheets
- Appendix C Explanation and Calculation of Intersection Capacity Utilization/Delay
- Appendix D Canwood Street Improvement Plans

List of Tables

Table 1.	Existing Levels of Service	15
Table 2.	Project Traffic Generation	21
Table 3.	Opening Year (2022) Without Project Levels of Service	
Table 4.	Opening Year (2022) With "North" Project Levels of Service	
Table 5.	Opening Year (2022) Project Traffic Contribution	32
Table 6.	Other Development Traffic Generation	42
Table 7.	Cumulative Without Project Levels of Service	43
Table 8.	Cumulative With "North" Project Levels of Service	44
Table 9.	Cumulative Project Traffic Contribution	45

List of Figures

Figure 1.	Project Location Map	.10
Figure 2.	"North" Project Site Plan	.11
Figure 3.	Existing Through Travel Lanes and Intersection Controls	.16
Figure 4.	Existing Average Daily Traffic Volumes	.17
Figure 5.	Existing Morning Peak Hour Intersection Turning Movement Volumes	.18
Figure 6.	Existing Evening Peak Hour Intersection Turning Movement Volumes	.19
Figure 7.	"North" Project Outbound Traffic Distribution	
Figure 8.	"North" Project Inbound Traffic Distribution	.23
Figure 9.	"North" Project Average Daily Traffic Volumes	.24
Figure 10.	"North" Project Morning Peak Hour Intersection Turning Movement Volumes	.25
Figure 11.	"North" Project Evening Peak Hour Intersection Turning Movement Volumes	.26
Figure 12.	Opening Year (2022) Without Project Average Daily Traffic Volumes	.33
Figure 13.	Opening Year (2022) With "North" Project Average Daily Traffic Volumes	.34
Figure 14.	Opening Year (2022) Without Project Morning Peak Hour Intersection Turning	
	Movement Volumes	.35
Figure 15.	Opening Year (2022) Without Project Evening Peak Hour Intersection Turning	
	Movement Volumes	.36
Figure 16.	Opening Year (2022) With "North" Project Morning Peak Hour Intersection Turning	
	Movement Volumes	.37
Figure 17.	Opening Year (2022) With "North" Project Evening Peak Hour Intersection Turning	
	Movement Volumes	.38
-	Other Development Traffic Analysis Zone Map	
Figure 19.	Other Development Average Daily Traffic Volumes	.47
Figure 20.	Other Development Morning Peak Hour Intersection Turning Movement Volumes	.48
Figure 21.	Other Development Evening Peak Hour Intersection Turning Movement Volumes	.49
Figure 22.	Cumulative Without Project Average Daily Traffic Volumes	.50
Figure 23.	Cumulative With "North" Project Average Daily Traffic Volumes	.51
Figure 24.	Cumulative Without Project Morning Peak Hour Intersection Turning Movement	
	Volumes	.52
Figure 25.	Cumulative Without Project Evening Peak Hour Intersection Turning Movement	
	Volumes	
Figure 26.	Cumulative With "North" Project Morning Peak Hour Intersection Turning Movemen	t
	Volumes	.54
Figure 27.	Cumulative With "North" Project Evening Peak Hour Intersection Turning Movement	
	Volumes	.55
Figure 28.	Circulation Recommendations	.57

Agoura Business Center North LLC Development Agreement Traffic Impact Analysis

This report contains the traffic impact analysis for the development agreement between the City of Agoura Hills and Agoura Business Center North LLC. The Agoura Business Center West LLC center is owned by a separate corporate entity (but have the same representative). Agoura Business Center North (28721 Canwood Street) was formerly the Agoura Hills Business Park project. Both the "North" and "West" (28631 Canwood Street) projects were granted a CUP (2008 and 2009, respectively), which is set to expire in 2012 (after already being granted the extensions allowed by the Municipal Code). The purpose of the development agreement is to allow for a 10-year time extension for the entitlements, and for Agoura Business Center West LLC/Agoura Business Center North LLC to construct additional Canwood Street roadway improvements in front of their properties and just to the west of the "North" parcel, as well as the City's vacant property (28661 Canwood Street), which is in between the 2 properties, which were not analyzed in the prior MNDs for the 2 properties.

The Agoura Business Center North project consists of 103,070 square feet of light industrial¹.

The traffic report contains documentation of existing traffic conditions, traffic generated by the project, distribution of the project traffic to roads outside the project, an analysis of Opening Year (2022) traffic conditions without and with the project, and an analysis of Cumulative traffic conditions without and with the project.

Each of these topics is contained in a separate section of the report. The first section is "Findings", and subsequent sections expand upon the findings. In this way, information on any particular aspect of the study can be easily located by the reader. Although this is a technical report, every effort has been made to write the report clearly and concisely. To assist the reader with those terms unique to transportation engineering, a glossary of terms is provided within Appendix A.

¹ The Agoura Business Center North project description is based upon the <u>Agoura Hills Business Park Project Revised</u> <u>Traffic and Circulation Study</u> prepared by Associated Transportation Engineers (May 23, 2007).

This section summarizes the existing traffic conditions, project traffic impacts, and the proposed mitigation measures.

A. <u>Existing Traffic Conditions</u>

- 1. The project site is currently vacant and not generating significant traffic.
- 2. The study area includes the following intersections:

Kanan Road (NS) at: Thousand Oaks Boulevard (EW) - #1 Canwood Street (EW) - #2 SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4 Agoura Road (EW) - #5

Clareton Drive (NS) at: Canwood Street (EW) - #6

Agoura Business Center North Driveway (NS) at: Canwood Street (EW) - #7

Derry Avenue (NS) at: Canwood Street (EW) - #10

Colodny Drive (NS) at: Canwood Street (EW) - #11

Chesebro Road/Canwood Street (NS) at: Driver Avenue/Palo Comado Canyon Road (EW) - #12

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13 Chesebro Road (EW) - #14

SR-101 Freeway SB Ramps (NS) at: Dorothy Drive (EW) - #15

3. The study area intersections currently operate within acceptable Levels of Service during the peak hours for <u>existing</u> traffic conditions, except for the following study area intersections that operate at unacceptable Levels of Service during the evening peak hour (see Table 1):

Kanan Road (NS) at: SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

4. Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation at the following study area intersection:

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

B. <u>Traffic Impacts</u>

- 1. The Agoura Business Center North project consists of 103,070 square feet of light industrial. The project site will have access to Canwood Street.
- 2. The Agoura Business Center North project is projected to generate approximately 718 daily vehicle trips, 94 of which will occur during the morning peak hour and 100 of which will occur during the evening peak hour.
- 3. The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for <u>Opening Year (2022) Without Project</u> traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the evening peak hour (see Table 3):

Kanan Road (NS) at: SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

4. The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for <u>Opening Year (2022) With "North" Project</u> traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the evening peak hour (see Table 4):

Kanan Road (NS) at: SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4

Clareton Drive (NS) at: Canwood Street (EW) - #6

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

5. The project traffic does <u>not</u> significantly impact the study area intersections for <u>Opening Year (2022)</u> traffic conditions, with traffic signal improvements (see Table 5).

6. The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for <u>Cumulative Without Project</u> traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the peak hours (see Table 7):

Kanan Road (NS) at: Thousand Oaks Boulevard (EW) - #1 SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4

Clareton Drive (NS) at: Canwood Street (EW) - #6

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

7. The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for <u>Cumulative With "North" Project</u> traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the peak hours (see Table 8):

> Kanan Road (NS) at: Thousand Oaks Boulevard (EW) - #1 Canwood Street (EW) - #2 SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4

Clareton Drive (NS) at: Canwood Street (EW) - #6

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

SR-101 Freeway SB Ramps (NS) at: Dorothy Drive (EW) - #15

8. The project traffic does <u>not</u> significantly impact the study area intersections for <u>Cumulative</u> traffic conditions, with traffic signal improvements (see Table 9).

C. <u>Recommendations</u>

The following measures are recommended traffic conditions for the project:

- 1. Site-specific circulation and access recommendations are depicted on Figure 28.
- 2. The Agoura Business Center West LLC/Agoura Business Center North LLC shall construct additional Canwood Street roadway improvements in front of their

properties and just to the west of the "North" parcel, as well as the City's vacant property (28661 Canwood Street), which is in between the two properties (see Appendix D).

- 3. Sufficient on-site parking shall be provided to meet City of Agoura Hills parking code requirements.
- 4. Sight distance at the project access should be reviewed with respect to California Department of Transportation/City of Agoura Hills standards in conjunction with the preparation of final grading, landscaping, and street improvement plans.
- 5. On-site traffic signing and striping should be implemented in conjunction with detailed construction plans for the project.
- 6. As is the case for any roadway design, the City of Agoura Hills should periodically review traffic operations in the vicinity of the project once the project is constructed to assure that the traffic operations are satisfactory.

This section discusses the County Congestion Management Program. The purpose, prescribed methodology, and definition of a significant traffic impact are discussed.

A. <u>County Congestion Management Program</u>

The Congestion Management Program is a result of Proposition 111 which was a statewide initiative approved by the voters in June 1990. The proposition allowed for a nine cent per gallon state gasoline tax increase over a five-year period.

Proposition 111 explicitly stated that the new gas tax revenues were to be used to fix existing traffic problems and was not to be used to promote future development. For a city to get its share of the Proposition 111 gas tax, it has to follow certain procedures specified by the State Legislature. The legislation requires that a Traffic Impact Analysis be prepared for new development. The traffic impact analysis is prepared to monitor and fix traffic problems caused by new development.

The Legislature requires that adjacent jurisdictions use a standard methodology for conducting a traffic impact analysis. To assure that adjacent jurisdictions use a standard methodology in preparing traffic impact analyses, one common procedure is that all cities within a county, and the county agency itself, adopt and use one standard methodology for conducting traffic impact analyses.

Although each county has developed standards for preparing traffic impact analyses, traffic impact analysis requirements do vary in detail from one county to another, but not in overall intent or concept. The general approach selected by each county for conducting traffic impact analyses has common elements.

The general approach for conducting a traffic impact analysis is that existing weekday peak hour traffic is counted and the percent of roadway capacity currently used is determined. Then growth in traffic is accounted for and added to existing traffic and the percent of roadway capacity used is again determined. Then the project traffic is added and the percent of roadway capacity used is again determined. If the new project adds traffic to an overcrowded facility, then the new project has to mitigate the traffic impact so that the facility operates at a level that is no worse than before the project traffic was added.

If the project size is below a certain minimum threshold level, then a project does not have to have a traffic impact analysis prepared, once it is shown or agreed that the project is below the minimum threshold. If a project is bigger than the minimum threshold size, then a traffic impact analysis is required.

B. <u>Prescribed Methodology for a Traffic Impact Analysis</u>

The traffic impact analysis must include all monitored intersections to which the project adds traffic above a certain minimum amount. In Los Angeles County, the monitored

intersections are contained in Appendix A of the <u>Congestion Management Program for the</u> <u>County of Los Angeles</u>.

The City of Agoura Hills maintains a LOS C standard on most roadways within the City. A reduced LOS standard of D, E, or F is considered acceptable on the following roadways in the study area:

- Kanan Road, due to heavy existing and projected existing and projected volumes and desire to maintain the existing 4-lane cross-section with sidewalks, bicycle lanes, and landscaped median islands.
- Dorothy Drive between Lewis Road and US-101 ramps, due to the projected volumes and direct access to/from the southbound US-101 ramps.
- Canwood Street east of Kanan Road, due to the heavy projected volumes under future conditions with development under the General Plan. Further widening beyond the propOsed General Plan improvement (three-lane cross section with a continuous left-turn lane), is not feasible within the available right-of-way.

If a project adds more traffic than the minimum threshold amount to an intersection, then that intersection has to be analyzed for deficiencies.

If the intersection has to be analyzed for deficiencies, then mitigation is required if the existing traffic plus anticipated traffic growth plus project traffic does cause the Intersection Capacity Utilization/Delay to go above a certain point.

In the City of Agoura Hills, a proposed project is considered to result in a significant impact if, prior to mitigation, the proposed project:

	Study Intersections										
Pr	e-Project	Increase in V/C									
LOS	V/C	Increase in V/C									
С	0.71 – 0.80	0.04 or more									
D	0.81 - 0.90	0.02 or more									
E/F	0.91 or more	0.01 or more									

i. Degrades operations at a signalized intersection as follows:

or

- ii. Degrades the Level of Service (LOS) at an unsignalized intersection to an unacceptable level of LOS D or worse; or
- iii. Increases delay at an unsignalized intersection operating at an unacceptable level by five or more seconds; or
- Results in satisfying the most recent <u>California Manual on Uniform Traffic Control</u> <u>Devices (CAMUTCD)</u> peak hour volume warrant or other warrants for traffic signal installation at the intersection; or
- v. Increases the volume to capacity (v/c) ratio on a roadway segment operating at an unacceptable level (LOS D, E or F) by 0.05 or more.

In the City of Agoura Hills, the signalized intersection analysis technique used to calculate Intersection Capacity Utilization is as follows. Lane capacity is 1,600 vehicles per lane per hour for all through and turn lanes and 2,880 total for dual turn lanes. A total yellow clearance time of 0.05 is added.

The technique used to assess the operation of a signalized intersection is known as Intersection Capacity Utilization, as described in Appendix C. To calculate an Intersection Capacity Utilization value, the volume of traffic using the intersection is compared with the capacity of the intersection. The Intersection Capacity Utilization represents that portion of the hour required to provide sufficient capacity to accommodate all intersection traffic if all approaches operate at capacity.

The technique used to assess the capacity needs of an unsignalized intersection is known as the Intersection Delay Method (see Appendix C). To calculate delay, the volume of traffic using the intersection is compared with the capacity of the intersection.

Project traffic is generated using rates and procedures contained in the Institute of Transportation Engineers, <u>Trip Generation</u>, 8th Edition, 2008. The project traffic distribution is provided by the reviewing agency or is agreed to in advance of the traffic impact analysis being prepared. The traffic impact analysis has to be prepared by a licensed Traffic Engineer.

This traffic analysis has been prepared in accordance with the traffic impact analysis requirements except as noted. The traffic impact analysis not only examined the Congestion Management Program system of roads and intersections, but also other roads and intersections.

The project-generated traffic was added to intersections, and a full intersection analysis was conducted, even when the project added traffic failed to meet the minimum thresholds that require an intersection analysis.

C. <u>Mitigation Measures</u>

If a project is large enough to require that a traffic impact analysis be prepared, and if the project adds traffic to an intersection above a minimum threshold, and if the intersection is operating at above an acceptable level of operation, then the project must mitigate its traffic impact.

Traffic mitigation can be in many forms including adding lanes. Lanes can sometimes be obtained through restriping or elimination of parking, and sometimes require spot roadway widening.

III. Project Description


This section discusses each of the project's location and proposed development. Figure 1 shows the project location map. Figure 2 illustrates the site plan.


A. <u>Development Description</u>

This report contains the traffic impact analysis for the development agreement between the City of Agoura Hills and Agoura Business Center North LLC. The Agoura Business Center West LLC center is owned by a separate corporate entity (but have the same representative). Agoura Business Center North (28721 Canwood Street) was formerly the Agoura Hills Business Park project. Both the "North" and "West" (28631 Canwood Street) projects were granted a CUP (2008 and 2009, respectively), which is set to expire in 2012 (after already being granted the extensions allowed by the Municipal Code). The purpose of the development agreement is to allow for a 10-year time extension for the entitlements, and for Agoura Business Center West LLC/Agoura Business Center North LLC to construct additional Canwood Street roadway improvements in front of their properties and just to the west of the "North" parcel, as well as the City's vacant property (28661 Canwood Street), which is in between the 2 properties, which were not analyzed in the prior MNDs for the 2 properties.

B. <u>Proposed Development</u>

The Agoura Business Center North project consists of 103,070 square feet of light industrial. The project site will have access to Canwood Street.





The traffic conditions as they exist today are discussed below and illustrated on Figures 3 to 6.

A. <u>Surrounding Street System</u>

Study area roadways that will be utilized by the development include Thousand Oaks Boulevard, Driver Avenue, Canwood Street, Roadside Drive, Agoura Road, Kanan Road, Clareton Drive, Derry Avenue, Colodny Drive, Chesebro Road, and Palo Comado Canyon Road.

<u>Thousand Oaks Boulevard</u>: This east-west roadway currently is four lanes divided in the study area. It is classified as an Arterial on the City of Agoura Hills General Plan Circulation Element. Thousand Oaks Boulevard currently carries approximately 11,800 to 14,500 vehicles per day in the study area.

<u>Driver Avenue</u>: This east-west roadway currently is two lanes undivided in the study area. It is classified as a Collector on the City of Agoura Hills General Plan Circulation Element. Driver Avenue currently carries approximately 6,700 vehicles per day in the study area.

<u>Canwood Street:</u> This east-west roadway currently is two lanes undivided to three lanes divided in the study area. It is classified as an Arterial on the City of Agoura Hills General Plan Circulation Element. Canwood Street currently carries approximately 4,700 to 9,000 vehicles per day in the study area.

<u>Roadside Drive</u>: This east-west roadway currently is two lanes undivided in the study area. It is not classified on the City of Agoura Hills General Plan Circulation Element. Roadside Drive currently carries approximately 6,500 vehicles per day in the study area.

<u>Agoura Road:</u> This east-west roadway currently is two lanes undivided in the study area. It is classified as an Arterial on the City of Agoura Hills General Plan Circulation Element. Agoura Road currently carries approximately 6,800 to 7,900 vehicles per day in the study area.

<u>Kanan Road</u>: This north-south roadway currently is four lanes divided to five lanes divided in the study area. It is classified as an Arterial on the City of Agoura Hills General Plan Circulation Element. Kanan Road currently carries approximately 14,400 to 38,600 vehicles per day in the study area.

<u>Clareton Drive</u>: This north-south roadway currently is two lanes undivided in the study area. It is not classified on the City of Agoura Hills General Plan Circulation Element. Clareton Drive currently carries approximately 6,300 vehicles per day in the study area.

<u>Derry Avenue</u>: This north-south roadway currently is two lanes undivided in the study area. It is not classified on the City of Agoura Hills General Plan Circulation Element. Derry Avenue currently carries approximately 4,600 vehicles per day in the study area. <u>Colodny Drive</u>: This north-south roadway currently is two lanes undivided in the study area. It is not classified on the City of Agoura Hills General Plan Circulation Element. Colodny Drive currently carries approximately 1,000 vehicles per day in the study area.

<u>Chesebro Road:</u> This north-south roadway currently is two lanes undivided in the study area. It is classified as an Arterial on the City of Agoura Hills General Plan Circulation Element. Chesebro Road currently carries approximately 1,200 to 7,000 vehicles per day in the study area.

<u>Palo Comado Canyon Road:</u> This north-south roadway currently is two lanes undivided in the study area. It is classified as an Arterial on the City of Agoura Hills General Plan Circulation Element. Palo Comado Canyon Road currently carries approximately 11,300 to 12,300 vehicles per day in the study area.

B. <u>Existing Travel Lanes and Intersection Controls</u>

Figure 3 identifies the existing roadway conditions for study area roadways. The number of through lanes for existing roadways and the existing intersection controls are identified.

C. Existing Average Daily Traffic Volumes

Figure 4 depicts the existing average daily traffic volumes. The existing average daily traffic volumes have been obtained from the <u>2011 Traffic Volumes on California State Highways</u> by the California Department of Transportation and factored¹ to Year 2012 from Year 2007 peak hour counts using the following formula for each intersection leg:

PM Peak Hour (Approach Volume + Exit Volume) x 10 = Leg Volume.

D. Existing Levels of Service

The technique used to assess the operation of a signalized intersection is known as Intersection Capacity Utilization, as described in Appendix C. To calculate an Intersection Capacity Utilization value, the volume of traffic using the intersection is compared with the capacity of the intersection. The Intersection Capacity Utilization represents that portion of the hour required to provide sufficient capacity to accommodate all intersection traffic if all approaches operate at capacity.

The technique used to assess the capacity needs of an unsignalized intersection is known as the Intersection Delay Method (see Appendix C). To calculate delay, the volume of traffic using the intersection is compared with the capacity of the intersection.

The Intersection Capacity Utilization/Delay for the existing traffic conditions have been calculated and are shown in Table 1. Existing Intersection Capacity Utilization/Delay are based upon manual morning and evening peak hour intersection turning movement counts

¹ To account for areawide growth on roadways, existing traffic volumes have been calculated based on a 0.75 percent annual growth rate. The areawide growth rate has been obtained from previous traffic studies conducted in the City of Agoura Hills.

factored¹ to Year 2012 from Year 2007 peak hour counts (see Figures 5 and 6). Traffic count worksheets are provided in Appendix B.

There are two peak hours in a weekday. The morning peak hour is between 7:00 AM and 9:00 AM, and the evening peak hour is between 4:00 PM and 6:00 PM. The actual peak hour within the two-hour interval is the four consecutive 15-minute periods with the highest total volume when all movements are added together. Thus, the evening peak hour at one intersection may be 4:45 PM to 5:45 PM if those four consecutive 15-minute periods have the highest combined volume.

The study area intersections currently operate within acceptable Levels of Service during the peak hours for existing traffic conditions, except for the following study area intersections that operate at unacceptable Levels of Service during the evening peak hour (see Table 1).

Kanan Road (NS) at: SR-101 Freeway NB Ramps/Canwood Street (EW) - #3

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

Existing Intersection Capacity Utilization/Delay worksheets are provided in Appendix C.

E. Existing Traffic Signal Warrant Analysis

Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation at the following study area intersection:

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

¹ To account for areawide growth on roadways, existing traffic volumes have been calculated based on a 0.75 percent annual growth rate. The areawide growth rate has been obtained from previous traffic studies conducted in the City of Agoura Hills.

Existing Levels of Service

			Intersection Approach Lanes ¹								Peak Hour				
	Traffic	Northbound		Southbound			Eastbound			We	estbou	und	V/C or	Delay ²	
Intersection	Control ³	L	Т	R	L	Т	R	L	Т	R	L	Т	R	Morning	Evening
Kanan Road (NS) at:															
Thousand Oaks Boulevard (EW) - #1	TS	1	2	d	1	2	d	2	2	d	1	2	d	0.725-C	0.732-C
Canwood Street (EW) - #2	TS	0	2	1	2	3	0	0	0	0	2	0	1>	0.523-A	0.706-C
SR-101 Freeway NB Ramps/Canwood Street (EW) - #3	TS	1	2	1>	0	3	1	1	0	1	1.5	0.5	2	0.673-B	0.801-D
SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4	TS	0	2.5	0.5	1	2	1>	1.3	0.4	1.3	1	0	1	0.727-C	0.786-C
Agoura Road (EW) - #5	TS	1	1.5	0.5	1	1	1	1	0.5	0.5	1	1	1	0.686-B	0.640-B
Clareton Drive (NS) at:															
Canwood Street (EW) - #6	CSS	0	0	0	0	1	0	0	1	0	0	1	0	13.4-B	19.4-C
Derry Avenue (NS) at:															
Canwood Street (EW) - #10	CSS	0	0	0	1	0	d	1	1	0	0	0.5	0.5	11.4-B	12.1-B
Colodny Drive (NS) at:															
Canwood Street (EW) - #11	CSS	0	0	0	0	1	0	1	1	0	0	0.5	0.5	11.2-B	10.4-B
Chesebro Road/Canwood Street (NS) at:															
Driver Avenue/Palo Comado Canyon Road (EW) - #12	AWS	0.5	0.5	1	0	1	0	0.5	0.5	d	1	0.5	0.5	10.7-B	15.7-C
Palo Comado Canyon Road (NS) at:															
SR-101 Freeway NB Ramps (EW) - #13	CSS	0.5	0.5	0	0	1	1	0	0	0	1	0	1	17.6-C	99.9-F ⁴
Chesebro Road (EW) - #14	CSS	0.5	0.5	0	0	1	1	1	0	d	0	0	0	10.8-B	14.0-B
SR-101 Freeway SB Ramps (NS) at:															
Dorothy Drive (EW) - #15	AWS	0	1	0	0.5	0.5	1	0.5	0.5	d	0	1	0	17.1-C	16.0-C


¹ When a right turn lane is designated, the lane can either be striped or unstriped. To function as a right turn lane, there must be sufficient width for right turning vehicles to travel outside the through lanes.


L = Left; T = Through; R = Right; d = Defacto Right Turn; > = Right Turn Overlap


² V/C or Delay has been calculated using the following analysis software: Traffix, Version 7.9.0215 (2008). Per the 2000 Highway Capacity Manual, for intersections with cross street stop control, the delay and level of service for the worst individual movement (or movements sharing a single lane) are shown.


³ TS = Traffic Signal; CSS = Cross Street Stop; AWS = All Way Stop

⁴ 99.9-F = Delay High, Intersection Unstable, Level of Service F.









V. Project Traffic

The Agoura Business Center North project consists of 103,070 square feet of light industrial. The project site will have access to Canwood Street.

A. <u>Trip Generation</u>

The traffic generated by the project is determined by multiplying an appropriate trip generation rate by the quantity of land use. Trip generation rates are predicated on the assumption that energy costs, the availability of roadway capacity, the availability of vehicles to drive, and our life styles remain similar to what we know today. A major change in these variables may affect trip generation rates.

Trip generation rates were determined for daily traffic, morning peak hour inbound and outbound traffic, and evening peak hour inbound and outbound traffic for the proposed land use. By multiplying the traffic generation rates by the land use quantity, the traffic volumes are determined. Table 2 exhibits the traffic generation rates and peak hour volumes and project daily traffic volumes. The traffic generation rates are from the Institute of Transportation Engineers, Trip Generation, 8th Edition, 2008.

The Agoura Business Center North project is projected to generate approximately 718 daily vehicle trips, 94 of which will occur during the morning peak hour and 100 of which will occur during the evening peak hour.

B. <u>Trip Distribution</u>

Figures 7 and 8 contain the directional distributions of the "North" project traffic for the proposed land use.

To determine the traffic distributions for the proposed project, peak hour traffic counts of the existing directional distribution of traffic for existing areas in the vicinity of the site, and other additional information on future development and traffic impacts in the area were reviewed.

C. <u>Trip Assignment</u>


Based on the identified traffic generation and distributions, "North" project average daily traffic volumes have been calculated and shown on Figure 9. Morning and evening peak hour intersection turning movement volumes expected from the "North" project are shown on Figures 10 and 11, respectively.


Project Traffic Generation¹


				Peak Hour									
					Morning								
Project	Land Use	Quantity	Units ²	Inbound	Outbound	Total	Inbound	Outbound	Total	Daily			
Trip Generation Rates													
Agoura Business Center North	Light Industrial	103.070	TSF	0.81	0.11	0.92	0.12	0.85	0.97	6.97			
Trips Generated													
Agoura Business Center North	Light Industrial	103.070	TSF	83	11	94	12	88	100	718			


¹ Source: Institute of Transportation Engineers, <u>Trip Generation</u>, 8th Edition, 2008, Land Use Category 110.


² TSF = Thousand Square Feet











VI. Opening Year (2022) Traffic Conditions

In this section, Opening Year (2022) traffic conditions without and with the project are discussed. Figures 12 to 17 depict the Opening Year (2022) traffic conditions.

A. <u>Method of Projection</u>

To account for areawide growth on roadways, Opening Year (2022) traffic volumes have been calculated based on a 0.75 percent annual growth rate of existing traffic volumes over a ten (10) year period. The areawide growth rate has been obtained from previous traffic studies conducted in the City of Agoura Hills.

Areawide growth has been added to daily and peak hour traffic volumes on surrounding roadways, in addition to traffic generated by the project.

B. Opening Year (2022) Average Daily Traffic Volumes

Opening Year (2022) Without Project average daily traffic volumes are as illustrated on Figure 12. The Opening Year (2022) With "North" Project average daily traffic volumes are as illustrated on Figure 13.

C. Opening Year (2022) Levels of Service

The technique used to assess the operation of a signalized intersection is known as Intersection Capacity Utilization, as described in Appendix C. To calculate an Intersection Capacity Utilization value, the volume of traffic using the intersection is compared with the capacity of the intersection. The Intersection Capacity Utilization represents that portion of the hour required to provide sufficient capacity to accommodate all intersection traffic if all approaches operate at capacity.

The technique used to assess the capacity needs of an unsignalized intersection is known as the Intersection Delay Method (see Appendix C). To calculate delay, the volume of traffic using the intersection is compared with the capacity of the intersection.

The Intersection Capacity Utilization/Delay for the Opening Year (2022) Without Project traffic conditions have been calculated and are shown in Table 3. Opening Year (2022) Without Project morning and evening peak hour intersection turning movement volumes are shown on Figures 14 and 15, respectively.

The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Opening Year (2022) Without Project traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the evening peak hour (see Table 3):

Kanan Road (NS) at: SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4 Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

Opening Year (2022) Without Project Intersection Capacity Utilization/Delay worksheets are provided in Appendix C.

The Intersection Capacity Utilization/Delay for the Opening Year (2022) With "North" Project traffic conditions have been calculated and are shown in Table 4. Opening Year (2022) With "North" Project morning and evening peak hour intersection turning movement volumes are shown on Figures 16 and 17, respectively.

The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Opening Year (2022) With "North" Project traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the evening peak hour (see Table 4):

Kanan Road (NS) at: SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4

Clareton Drive (NS) at: Canwood Street (EW) - #6

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

Opening Year (2022) With "North" Project Intersection Capacity Utilization/Delay worksheets are provided in Appendix C.

D. Significant Transportation Impact

In the City of Agoura Hills, a proposed project is considered to result in a significant impact if, prior to mitigation, the proposed project:

-												
	Study Intersections											
Pi	re-Project											
LOS	V/C	Increase in V/C										
С	0.71 - 0.80	0.04 or more										
D	0.81 - 0.90	0.02 or more										
E/F	0.91 or more	0.01 or more										

i. Degrades operations at a signalized intersection as follows:

or

ii. Degrades the Level of Service (LOS) at an unsignalized intersection to an unacceptable level of LOS D or worse; or

- iii. Increases delay at an unsignalized intersection operating at an unacceptable level by five or more seconds; or
- Results in satisfying the most recent <u>California Manual on Uniform Traffic Control</u> <u>Devices (CAMUTCD)</u> peak hour volume warrant or other warrants for traffic signal installation at the intersection; or
- v. Increases the volume to capacity (v/c) ratio on a roadway segment operating at an unacceptable level (LOS D, E or F) by 0.05 or more.

The project traffic does <u>not</u> significantly impact the study area intersections for Opening Year (2022) traffic conditions, with traffic signal improvements (see Table 5).

Opening Year (2022) Without Project Levels of Service

			Intersection Approach Lanes ¹										Peak Hour		
	Traffic	No	rthbo	und	Southbound Ea			Ea	astbound		We	estbou	und	V/C or	Delay ²
Intersection	Control ³	L	Т	R	L	Т	R	L	Т	R	L	Т	R	Morning	Evening
Kanan Road (NS) at:															
Thousand Oaks Boulevard (EW) - #1	TS	1	2	d	1	2	d	2	2	d	1	2	d	0.777-C	0.795-C
Canwood Street (EW) - #2	TS	0	2	1	2	3	0	0	0	0	2	0	1>	0.560-A	0.757-C
SR-101 Freeway NB Ramps/Canwood Street (EW) - #3	TS	1	2	1>	0	3	1	1	0	1	1.5	0.5	2	0.721-C	0.859-D
SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4	TS	0	2.5	0.5	1	2	1>	1.3	0.4	1.3	1	0	1	0.780-C	0.843-D
Agoura Road (EW) - #5	TS	1	1.5	0.5	1	1	1	1	0.5	0.5	1	1	1	0.735-C	0.686-B
Clareton Drive (NS) at:															
Canwood Street (EW) - #6															
- Without Improvements	CSS	0	0	0	0	1	0	0	1	0	0	1	0	14.2-B	23.4-C
- With Improvements	<u>TS</u>	0	0	0	0	1	0	<u>1</u>	1	0	0	1	0	0.309-A	0.581-A
Derry Avenue (NS) at:															
Canwood Street (EW) - #10	CSS	0	0	0	1	0	d	1	1	0	0	0.5	0.5	11.7-B	12.7-B
Colodny Drive (NS) at:															
Canwood Street (EW) - #11	CSS	0	0	0	0	1	0	1	1	0	0	0.5	0.5	11.5-B	10.6-B
Chesebro Road/Canwood Street (NS) at:															
Driver Avenue/Palo Comado Canyon Road (EW) - #12	AWS	0.5	0.5	1	0	1	0	0.5	0.5	d	1	0.5	0.5	11.2-B	18.5-C
Palo Comado Canyon Road (NS) at:															
SR-101 Freeway NB Ramps (EW) - #13															
- Without Improvements	CSS	0.5	0.5	0	0	1	1	0	0	0	1	0	1	20.9-C	262.7-F
- With Improvements	<u>TS</u>	<u>1</u>	1	0	0	1	1	0	0	0	1	0	1	0.480-A	0.686-B
Chesebro Road (EW) - #14	CSS	0.5	0.5	0	0	1	1	1	0	d	0	0	0	11.1-B	15.0-C
SR-101 Freeway SB Ramps (NS) at:															
Dorothy Drive (EW) - #15	AWS	0	1	0	0.5	0.5	1	0.5	0.5	d	0	1	0	20.7-C	18.9-C

¹ When a right turn lane is designated, the lane can either be striped or unstriped. To function as a right turn lane, there must be sufficient width for right turning vehicles to travel outside the through lanes.

L = Left; T = Through; R = Right; d = Defacto Right Turn; > = Right Turn Overlap; <u>1</u> = Improvement

² V/C or Delay has been calculated using the following analysis software: Traffix, Version 7.9.0215 (2008). Per the 2000 Highway Capacity Manual, for intersections with cross street stop control, the delay and level of service for the worst individual movement (or movements sharing a single lane) are shown.

 3 TS = Traffic Signal; CSS = Cross Street Stop; AWS = All Way Stop

Opening Year (2022) With "North" Project Levels of Service

		Intersection Approach Lanes ¹										Peak Hour			
	Traffic	No	rthbo	und	Southbound			Eastbound			We	estbou	und	V/C or	Delay ²
Intersection	Control ³	L	Т	R	L	Т	R	L	Т	R	L	Т	R	Morning	Evening
Kanan Road (NS) at:															
Thousand Oaks Boulevard (EW) - #1	TS	1	2	d	1	2	d	2	2	d	1	2	d	0.781-C	0.796-C
Canwood Street (EW) - #2	TS	0	2	1	2	3	0	0	0	0	2	0	1>	0.562-A	0.776-C
SR-101 Freeway NB Ramps/Canwood Street (EW) - #3	TS	1	2	1>	0	3	1	1	0	1	1.5	0.5	2	0.722-C	0.861-D
SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4	TS	0	2.5	0.5	1	2	1>	1.3	0.4	1.3	1	0	1	0.781-C	0.844-D
Agoura Road (EW) - #5	TS	1	1.5	0.5	1	1	1	1	0.5	0.5	1	1	1	0.736-C	0.689-B
Clareton Drive (NS) at:															
Canwood Street (EW) - #6															
- Without Improvements	CSS	0	0	0	0	1	0	0	1	0	0	1	0	15.1-C	28.7-D
- With Improvements	<u>TS</u>	0	0	0	0	1	0	1	1	0	0	1	0	0.341-A	0.619-B
Agoura Business Center North Driveway (NS) at:															
Canwood Street (EW) - #7	<u>CSS</u>	0	0	0	0	<u>1</u>	0	<u>1</u>	1	0	0	0.5	0.5	10.4-B	11.7-B
Derry Avenue (NS) at:															
Canwood Street (EW) - #10	CSS	0	0	0	1	0	d	1	1	0	0	0.5	0.5	12.0-B	13.0-B
Colodny Drive (NS) at:															
Canwood Street (EW) - #11	CSS	0	0	0	0	1	0	1	1	0	0	0.5	0.5	11.8-B	10.7-B
Chesebro Road/Canwood Street (NS) at:															
Driver Avenue/Palo Comado Canyon Road (EW) - #12	AWS	0.5	0.5	1	0	1	0	0.5	0.5	d	1	0.5	0.5	11.5-B	19.3-C
Palo Comado Canyon Road (NS) at:															
SR-101 Freeway NB Ramps (EW) - #13															
- Without Improvements	CSS	0.5	0.5	0	0	1	1	0	0	0	1	0	1	20.9-В	280.6-F
- With Improvements	<u>TS</u>	<u>1</u>	1	0	0	1	1	0	0	0	1	0	1	0.498-A	0.704-C
Chesebro Road (EW) - #14	CSS	0.5	0.5	0	0	1	1	1	0	d	0	0	0	11.1-B	15.1-C
SR-101 Freeway SB Ramps (NS) at:															
Dorothy Drive (EW) - #15	AWS	0	1	0	0.5	0.5	1	0.5	0.5	d	0	1	0	21.0-C	21.1-C

¹ When a right turn lane is designated, the lane can either be striped or unstriped. To function as a right turn lane, there must be sufficient width for right turning vehicles to travel outside the through lanes.

L = Left; T = Through; R = Right; d = Defacto Right Turn; > = Right Turn Overlap; <u>1</u> = Improvement

² V/C or Delay has been calculated using the following analysis software: Traffix, Version 7.9.0215 (2008). Per the 2000 Highway Capacity Manual, for intersections with cross street stop control, the delay and level of service for the worst individual movement (or movements sharing a single lane) are shown.


³ TS = Traffic Signal; CSS = Cross Street Stop; AWS = All Way Stop


Opening Year (2022) Project Traffic Contribution


		Opening Year (2022)							
		Withou	t Project		Project	V/C or			
	Peak	V/C or	Level of	V/C or	Level of		Significant		
Intersection	Hour	Delay	Service	Delay	Service	Increase	Impact?		
Kanan Road (NS) at:									
Thousand Oaks Boulevard (EW) - #1	Morning	0.777	с	0.781	с	0.004	No		
	Evening	0.795	С	0.796	с	0.001	No		
Canwood Street (EW) - #2	Morning	0.560	А	0.562	А	0.002	No		
	Evening	0.757	С	0.776	С	0.019	No		
SR-101 Freeway NB Ramps/Canwood Street (EW) - #3	Morning	0.721	С	0.722	С	0.001	No		
	Evening	0.859	D	0.861	D	0.002	No		
SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4	Morning	0.780	С	0.781	С	0.001	No		
	Evening	0.843	D	0.844	D	0.001	No		
Agoura Road (EW) - #5	Morning	0.735	С	0.736	С	0.001	No		
	Evening	0.686	В	0.689	В	0.003	No		
Clareton Drive (NS) at:									
Canwood Street (EW) - #6									
- Without Improvements	Morning	14.2	В	15.1	С	0.9	No		
	Evening	23.4	С	28.7	D	5.3	Yes		
- With Improvements ¹	Morning	0.309	А	0.341	А	0.032	No		
	Evening	0.581	А	0.619	В	0.038	No		
Agoura Business Center North Driveway (NS) at:									
Canwood Street (EW) - #7	Morning	N/A	N/A	10.4	В	N/A	N/A		
	Evening	N/A	N/A	11.7	В	N/A	N/A		
Derry Avenue (NS) at:									
Canwood Street (EW) - #10	Morning	11.7	В	12.0	В	0.3	No		
	Evening	12.7	В	13.0	В	0.3	No		
Colodny Drive (NS) at:									
Canwood Street (EW) - #11	Morning	11.5	В	11.8	В	0.3	No		
	Evening	10.6	В	10.7	В	0.1	No		
Chesebro Road/Canwood Street (NS) at:									
Driver Avenue/Palo Comado Canyon Road (EW) - #12	Morning	11.2	В	11.5	В	0.3	No		
	Evening	18.5	С	19.3	С	0.8	No		
Palo Comado Canyon Road (NS) at:									
SR-101 Freeway NB Ramps (EW) - #13									
- Without Improvements	Morning	20.9	С	20.9	В	0.0	No		
	Evening	262.7	F	280.6	F	17.9	Yes		
- With Improvements ²	Morning	0.480	А	0.498	Α	0.018	No		
	Evening	0.686	В	0.704	С	0.018	No		
Chesebro Road (EW) - #14	Morning	11.1	В	11.1	В	0.0	No		
	Evening	15.0	С	15.1	С	0.1	No		
SR-101 Freeway SB Ramps (NS) at:									
Dorothy Drive (EW) - #15	Morning	20.7	С	21.0	С	0.3	No		
	Evening	18.9	С	21.1	С	2.2	No		


¹ Prior to construction, the project shall complete a focused traffic analysis to determine if a traffic signal is warranted.


 $^{\rm 2}\,$ Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation.














VII. Cumulative Traffic Conditions

In this section, cumulative traffic conditions without and with the project are discussed. Figures 18 to 24 depict the cumulative traffic conditions.

A. <u>Method of Projection</u>

To account for areawide growth on roadways, cumulative traffic forecasts were developed from existing traffic volumes plus 0.75 percent annual growth rate over a ten (10) year period plus the approved and pending project tracking list. Table 6 lists the proposed land uses for the other development (see Figure 18).

Other development average daily traffic volumes are as illustrated on Figure 19. Other development morning and evening peak hour intersection turning movement volumes are shown on Figures 20 and 21, respectively.

B. <u>Cumulative Average Daily Traffic Volumes</u>

Cumulative Without Project average daily traffic volumes are as illustrated on Figure 22. The Cumulative With "North" Project average daily traffic volumes are as illustrated on Figure 23.

C. <u>Cumulative Levels of Service</u>

The technique used to assess the operation of a signalized intersection is known as Intersection Capacity Utilization, as described in Appendix C. To calculate an Intersection Capacity Utilization value, the volume of traffic using the intersection is compared with the capacity of the intersection. The Intersection Capacity Utilization represents that portion of the hour required to provide sufficient capacity to accommodate all intersection traffic if all approaches operate at capacity.

The technique used to assess the capacity needs of an unsignalized intersection is known as the Intersection Delay Method (see Appendix C). To calculate delay, the volume of traffic using the intersection is compared with the capacity of the intersection.

The Intersection Capacity Utilization/Delay for the Cumulative Without Project traffic conditions have been calculated and are shown in Table 7. Cumulative Without Project morning and evening peak hour intersection turning movement volumes are shown on Figures 24 and 25, respectively.

The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Cumulative Without Project traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the peak hours (see Table 7):

Kanan Road (NS) at: Thousand Oaks Boulevard (EW) - #1 SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4

Clareton Drive (NS) at: Canwood Street (EW) - #6

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Cumulative Without Project traffic conditions, with traffic signal improvements at the following study area intersection (see Table 7):

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13 Cumulative Without Project Intersection Capacity Utilization/Delay worksheets are provided in Appendix C.

The Intersection Capacity Utilization/Delay for the Cumulative With "North" Project traffic conditions have been calculated and are shown in Table 8. Cumulative With "North" Project morning and evening peak hour intersection turning movement volumes are shown on Figures 26 and 27, respectively.

The study area intersections are projected to operate within acceptable Levels of Service during the peak hours for Cumulative With "North" Project traffic conditions, except for the following study area intersections that are projected to operate at unacceptable Levels of Service during the peak hours (see Table 8):

Kanan Road (NS) at: Thousand Oaks Boulevard (EW) - #1 Canwood Street (EW) - #2 SR-101 Freeway NB Ramps/Canwood Street (EW) - #3 SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4

Clareton Drive (NS) at: Canwood Street (EW) - #6

Palo Comado Canyon Road (NS) at: SR-101 Freeway NB Ramps (EW) - #13

SR-101 Freeway SB Ramps (NS) at: Dorothy Drive (EW) - #15

Cumulative With "North" Project Intersection Capacity Utilization/Delay worksheets are provided in Appendix C.

D. Significant Transportation Impact

In the City of Agoura Hills, a proposed project is considered to result in a significant impact if, prior to mitigation, the proposed project:

	Study Intersections										
Pr	re-Project	Increase in V/C									
LOS	V/C	Increase in V/C									
С	0.71 - 0.80	0.04 or more									
D	0.81 - 0.90	0.02 or more									
E/F	0.91 or more	0.01 or more									

i. Degrades operations at a signalized intersection as follows:

or

- ii. Degrades the Level of Service (LOS) at an unsignalized intersection to an unacceptable level of LOS D or worse; or
- iii. Increases delay at an unsignalized intersection operating at an unacceptable level by five or more seconds; or
- Results in satisfying the most recent <u>California Manual on Uniform Traffic Control</u> <u>Devices (CAMUTCD)</u> peak hour volume warrant or other warrants for traffic signal installation at the intersection; or
- v. Increases the volume to capacity (v/c) ratio on a roadway segment operating at an unacceptable level (LOS D, E or F) by 0.05 or more.

The project traffic does <u>not</u> significantly impact the study area intersections for Cumulative traffic conditions, with traffic signal improvements (see Table 9).

Other Development Traffic Generation¹

Traffic							Peak	Hour			
Analysis						Morning			Evening		
Zone ²	Project	Land Use	Quantity	Units ²	Inbound	Outbound	Total	Inbound	Outbound	Total	Daily
1	Von Buck	Single-Family Detached Residential	1	DU	-	1	1	1	-	1	10
	Stockton/Lamburg	Single-Family Detached Residential	1	DU	-	1	1	1	-	1	10
	Allen Adel	Single-Family Detached Residential	1	DU	-	1	1	1	-	1	10
	Jonathan Shuken	Single-Family Detached Residential	1	DU	-	1	1	1	-	1	10
2	Sunbelt Enterprises	Medical Office	25.2	TSF	46	12	58	23	64	87	910
3	Shops at Oak Creek	Shopping Center	34.66	TSF	21	14	35	63	66	129	1,488
4	Scheu Development Co.	Office	71.844	TSF	98	14	112	18	89	107	791
	Conrad Hilton Foundation	Corporate Headquarters	90.3	TSF	126	9	135	13	114	127	721
5	Agoura Landmark, LP	Office	99.194	TSF	135	19	154	25	123	148	1,092
	Vinod & Chanresh Gupta Trust	Office	12.7	TSF	17	2	19	3	16	19	140
6	Joseph Luithyly	Office	1.062	TSF	1	-	1	-	1	1	12
	Agoura Medical Partners, LLC	Medical Office	40.733	TSF	74	20	94	38	103	141	1,472
	Ashnoor Pirouti	Single-Family Detached Residential	1	DU	-	1	1	1	-	1	10
	Ashnoor Pirouti	Single-Family Detached Residential	1	DU	-	1	1	1	-	1	10
	Keith Blinkinsoph	Single-Family Detached Residential	1	DU	-	1	1	1	-	1	10
7	27489 Agoura Road	Office	30.0	TSF	41	6	47	8	37	45	330
8	Riopharm USA, Inc.	Single-Family Detached Residential	24	DU	5	13	18	15	9	24	230
9	Agoura Business Center West ³	Specialty Retail	20.661	TSF	17	11	28	25	31	56	916
Total					581	127	708	238	653	891	8,172

¹ Source: Institute of Transportation Engineers, Trip Generation, 8th Edition, 2008, Land Use Categories 820, 720, 714, 710, and 210.

 $^{\rm 2}$ DU = Dwelling Unit; TSF = Thousand Square Feet ; ST = Students

³ Source: Derry Avenue/Canwood Street Retail Project Traffic Impact Analysis (Revised), Kunzman Associates, Inc., May 18, 2009.

Table 7

Cumulative Without Project Levels of Service

Intersection Approach Lanes ¹											Peak Hour				
	Traffic	No	rthbo	und	Sou	thbo	und	Ea	stbou	Ind	W	estbou	und	V/C or	Delay ²
Intersection	Control ³	L	Т	R	L	Т	R	L	Т	R	L	Т	R	Morning	Evening
Kanan Road (NS) at:															
Thousand Oaks Boulevard (EW) - #1	TS	1	2	d	1	2	d	2	2	d	1	2	d	0.800-D	0.804-D
Canwood Street (EW) - #2	TS	0	2	1	2	3	0	0	0	0	2	0	1>	0.575-A	0.797-C
SR-101 Freeway NB Ramps/Canwood Street (EW) - #3	TS	1	2	1>	0	3	1	1	0	1	1.5	0.5	2	0.758-C	0.906-E
SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4	TS	0	2.5	0.5	1	2	1>	1.3	0.4	1.3	1	0	1	0.785-C	0.871-D
Agoura Road (EW) - #5	TS	1	1.5	0.5	1	1	1	1	0.5	0.5	1	1	1	0.744-C	0.754-C
Clareton Drive (NS) at:															
Canwood Street (EW) - #6															
- Without Improvements	CSS	0	0	0	0	1	0	0	1	0	0	1	0	14.6-B	27.0-D
- With Improvements	<u>TS</u>	0	0	0	0	1	0	1	1	0	0	1	0	0.317-A	0.602-B
Derry Avenue (NS) at:															
Canwood Street (EW) - #10	CSS	0	0	0	1	0	d	1	1	0	0	0.5	0.5	12.2-B	13.8-B
Colodny Drive (NS) at:															
Canwood Street (EW) - #11	CSS	0	0	0	0	1	0	1	1	0	0	0.5	0.5	11.7-B	10.8-B
Chesebro Road/Canwood Street (NS) at:															
Driver Avenue/Palo Comado Canyon Road (EW) - #12	AWS	0.5	0.5	1	0	1	0	0.5	0.5	d	1	0.5	0.5	11.4-B	19.6-C
Palo Comado Canyon Road (NS) at:															
SR-101 Freeway NB Ramps (EW) - #13															
- Without Improvements	CSS	0.5	0.5	0	0	1	1	0	0	0	1	0	1	26.1-D	361.9-F
- With Improvements	<u>TS</u>	<u>1</u>	1	0	0	1	1	0	0	0	1	0	1	0.506-A	0.717-C
Chesebro Road (EW) - #14	CSS	0.5	0.5	0	0	1	1	1	0	d	0	0	0	11.5-B	18.3-C
SR-101 Freeway SB Ramps (NS) at:															
Dorothy Drive (EW) - #15	AWS	0	1	0	0.5	0.5	1	0.5	0.5	d	0	1	0	22.3-C	23.2-C

¹ When a right turn lane is designated, the lane can either be striped or unstriped. To function as a right turn lane, there must be sufficient width for right turning vehicles to travel outside the through lanes.

L = Left; T = Through; R = Right; d = Defacto Right Turn; > = Right Turn Overlap

² V/C or Delay has been calculated using the following analysis software: Traffix, Version 7.9.0215 (2008). Per the 2000 Highway Capacity Manual, for intersections with cross street stop control, the delay and level of service for the worst individual movement (or movements sharing a single lane) are shown.

 3 TS = Traffic Signal; CSS = Cross Street Stop; AWS = All Way Stop

Table 8

Cumulative With "North" Project Levels of Service

		Intersection Approach Lanes ¹											Peak Hour		
	Traffic	No	rthbo	und	Sou	uthbo	und	Ea	stbou	nd	We	estbou	und	V/C or	Delay ²
Intersection	Control ³	L	Т	R	L	Т	R	L	Т	R	L	Т	R	Morning	Evening
Kanan Road (NS) at:															
Thousand Oaks Boulevard (EW) - #1	TS	1	2	d	1	2	d	2	2	d	1	2	d	0.805-D	0.806-D
Canwood Street (EW) - #2	TS	0	2	1	2	3	0	0	0	0	2	0	1>	0.577-A	0.815-D
SR-101 Freeway NB Ramps/Canwood Street (EW) - #3	TS	1	2	1>	0	3	1	1	0	1	1.5	0.5	2	0.760-C	0.908-E
SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4	TS	0	2.5	0.5	1	2	1>	1.3	0.4	1.3	1	0	1	0.786-C	0.873-D
Agoura Road (EW) - #5	TS	1	1.5	0.5	1	1	1	1	0.5	0.5	1	1	1	0.745-C	0.757-C
Clareton Drive (NS) at:															
Canwood Street (EW) - #6															
- Without Improvements	CSS	0	0	0	0	1	0	0	1	0	0	1	0	15.5-C	34.2-D
- With Improvements	<u>TS</u>	0	0	0	0	1	0	<u>1</u>	1	0	0	1	0	0.349-A	0.640-B
Agoura Business Center North Driveway (NS) at:															
Canwood Street (EW) - #7	<u>CSS</u>	0	0	0	0	1	0	1	1	0	0	0.5	0.5	10.5-B	12.1-B
Derry Avenue (NS) at:															
Canwood Street (EW) - #10	CSS	0	0	0	1	0	d	1	1	0	0	0.5	0.5	12.5-B	14.2-B
Colodny Drive (NS) at:															
Canwood Street (EW) - #11	CSS	0	0	0	0	1	0	1	1	0	0	0.5	0.5	11.9-B	10.9-B
Chesebro Road/Canwood Street (NS) at:															
Driver Avenue/Palo Comado Canyon Road (EW) - #12	AWS	0.5	0.5	1	0	1	0	0.5	0.5	d	1	0.5	0.5	11.7-B	20.5-C
Palo Comado Canyon Road (NS) at:															
SR-101 Freeway NB Ramps (EW) - #13															
- Without Improvements	CSS	0.5	0.5	0	0	1	1	0	0	0	1	0	1	26.1-D	384.8-F
- With Improvements	<u>TS</u>	<u>1</u>	1	0	0	1	1	0	0	0	1	0	1	0.508-A	0.735-C
Chesebro Road (EW) - #14	CSS	0.5	0.5	0	0	1	1	1	0	d	0	0	0	11.5-B	18.3-C
SR-101 Freeway SB Ramps (NS) at:															
Dorothy Drive (EW) - #15	AWS	0	1	0	0.5	0.5	1	0.5	0.5	d	0	1	0	22.6-C	26.5-D

¹ When a right turn lane is designated, the lane can either be striped or unstriped. To function as a right turn lane, there must be sufficient width for right turning vehicles to travel outside the through lanes.

L = Left; T = Through; R = Right; d = Defacto Right Turn; > = Right Turn Overlap

² V/C or Delay has been calculated using the following analysis software: Traffix, Version 7.9.0215 (2008). Per the 2000 Highway Capacity Manual, for intersections with cross street stop control, the delay and level of service for the worst individual movement (or movements sharing a single lane) are shown.

 $^3\,$ TS = Traffic Signal; CSS = Cross Street Stop; AWS = All Way Stop


Table 9


Cumulative Project Traffic Contribution


		Cumulative						
		Without	t Project		Project	V/C or		
	Peak		Level of	V/C or	Level of	Delay	Significant	
Intersection	Hour	Delay	Service	Delay	Service	Increase	Impact?	
Kanan Road (NS) at:	noui	Denay	U CI IIICE	Delay	U CI TICC	increase	mpacer	
Thousand Oaks Boulevard (EW) - #1	Morning	0.800	D	0.805	D	0.005	No	
	Evening	0.804	D	0.806	D	0.002	No	
Canwood Street (EW) - #2	Morning	0.575	А	0.577	А	0.002	No	
	Evening	0.797	с	0.815	D	0.018	No	
SR-101 Freeway NB Ramps/Canwood Street (EW) - #3	Morning	0.758	с	0.760	С	0.002	No	
	Evening	0.906	Е	0.908	Е	0.002	No	
SR-101 Freeway SB Ramps/Roadside Drive (EW) - #4	Morning	0.785	С	0.786	С	0.001	No	
	Evening	0.871	D	0.873	D	0.002	No	
Agoura Road (EW) - #5	Morning	0.744	С	0.745	С	0.001	No	
	Evening	0.754	С	0.757	С	0.003	No	
Clareton Drive (NS) at:								
Canwood Street (EW) - #6								
- Without Improvements	Morning	14.6	В	15.5	С	0.9	No	
	Evening	27.0	D	34.2	D	7.2	Yes	
- With Improvements ¹	Morning	0.317	А	0.349	А	0.032	No	
	Evening	0.602	В	0.640	В	0.038	No	
Agoura Business Center North Driveway (NS) at:								
Canwood Street (EW) - #7	Morning	N/A	N/A	10.5	В	N/A	N/A	
	Evening	N/A	N/A	12.1	В	N/A	N/A	
Derry Avenue (NS) at:								
Canwood Street (EW) - #10	Morning	12.2	В	12.5	В	0.3	No	
	Evening	13.8	В	14.2	В	0.4	No	
Colodny Drive (NS) at:								
Canwood Street (EW) - #11	Morning	11.7	В	11.9	В	0.2	No	
	Evening	10.8	В	10.9	В	0.1	No	
Chesebro Road/Canwood Street (NS) at:								
	Morning	11.4	В	11.7	В	0.3	No	
	Evening	19.6	С	20.5	С	0.9	No	
Palo Comado Canyon Road (NS) at:								
SR-101 Freeway NB Ramps (EW) - #13								
- Without Improvements	Morning	26.1	D	26.1	D	0.0	No	
	Evening	361.9	F	384.8	F	22.9	Yes	
- With Improvements ²	Morning	0.506	А	0.508	А	0.002	No	
	Evening	0.717	С	0.735	С	0.018	No	
Chesebro Road (EW) - #14	Morning	11.5	В	11.5	В	0.0	No	
	Evening	18.3	С	18.3	С	0.0	No	
SR-101 Freeway SB Ramps (NS) at:								
Dorothy Drive (EW) - #15	Morning	22.3	С	22.6	С	0.3	No	
	Evening	23.2	С	26.5	D	3.3	No	


¹ Prior to construction, the project shall complete a focused traffic analysis to determine if a traffic signal is warranted.


 $^{2}\,$ Based upon discussions with City of Agoura Hills staff, a traffic signal is programmed for installation.


























VIII. Recommendations

A. Site Access

The project site will have access to Canwood Street.

B. <u>Suggested Traffic Conditions</u>

1. <u>On- Site</u>

Site-specific circulation and access recommendations are depicted on Figure 28.

Sufficient on-site parking shall be provided to meet City of Agoura Hills parking code requirements.


Sight distance at the project access should be reviewed with respect to California Department of Transportation/City of Agoura Hills standards in conjunction with the preparation of final grading, landscaping, and street improvement plans.

On-site traffic signing and striping should be implemented in conjunction with detailed construction plans for the project.

2. <u>Off-Site</u>

The Agoura Business Center West LLC/Agoura Business Center North LLC shall construct additional Canwood Street roadway improvements in front of their properties and just to the west of the "North" parcel, as well as the City's vacant property (28661 Canwood Street), which is in between the two properties (see Appendix D).

As is the case for any roadway design, the City of Agoura Hills should periodically review traffic operations in the vicinity of the project once the project is constructed to assure that the traffic operations are satisfactory.



Appendices

- Appendix A Glossary of Transportation Terms
- Appendix B Traffic Count Worksheets
- Appendix C Explanation and Calculation of Intersection Capacity Utilization/Delay
- Appendix D Canwood Street Improvement Plans

APPENDIX A

Glossary of Transportation Terms

GLOSSARY OF TRANSPORTATION TERMS

COMMON ABBREVIATIONS

AC:	Acres
ADT:	Average Daily Traffic
Caltrans:	California Department of Transportation
DU:	Dwelling Unit
ICU:	Intersection Capacity Utilization
LOS:	Level of Service
TSF:	Thousand Square Feet
V/C:	Volume/Capacity
VMT:	Vehicle Miles Traveled

<u>TERMS</u>

AVERAGE DAILY TRAFFIC: The total volume during a year divided by the number of days in a year. Usually only weekdays are included.

BANDWIDTH: The number of seconds of green time available for through traffic in a signal progression.

BOTTLENECK: A constriction along a travelway that limits the amount of traffic that can proceed downstream from its location.

CAPACITY: The maximum number of vehicles that can be reasonably expected to pass over a given section of a lane or a roadway in a given time period.

CHANNELIZATION: The separation or regulation of conflicting traffic movements into definite paths of travel by the use of pavement markings, raised islands, or other suitable means to facilitate the safe and orderly movements of both vehicles and pedestrians.

CLEARANCE INTERVAL: Nearly same as yellow time. If there is an all red interval after the end of a yellow, then that is also added into the clearance interval.

CORDON: An imaginary line around an area across which vehicles, persons, or other items are counted (in and out).

CYCLE LENGTH: The time period in seconds required for one complete signal cycle.

CUL-DE-SAC STREET: A local street open at one end only, and with special provisions for turning around.

DAILY CAPACITY: The daily volume of traffic that will result in a volume during the peak hour equal to the capacity of the roadway.

DELAY: The time consumed while traffic is impeded in its movement by some element over which it has no control, usually expressed in seconds per vehicle.

DEMAND RESPONSIVE SIGNAL: Same as traffic-actuated signal.

DENSITY: The number of vehicles occupying in a unit length of the through traffic lanes of a roadway at any given instant. Usually expressed in vehicles per mile.

DETECTOR: A device that responds to a physical stimulus and transmits a resulting impulse to the signal controller.

DESIGN SPEED: A speed selected for purposes of design. Features of a highway, such as curvature, superelevation, and sight distance (upon which the safe operation of vehicles is dependent) are correlated to design speed.

DIRECTIONAL SPLIT: The percent of traffic in the peak direction at any point in time.

DIVERSION: The rerouting of peak hour traffic to avoid congestion.

FORCED FLOW: Opposite of free flow.

FREE FLOW: Volumes are well below capacity. Vehicles can maneuver freely and travel is unimpeded by other traffic.

GAP: Time or distance between successive vehicles in a traffic stream, rear bumper to front bumper.

HEADWAY: Time or distance spacing between successive vehicles in a traffic stream, front bumper to front bumper.

INTERCONNECTED SIGNAL SYSTEM: A number of intersections that are connected to achieve signal progression.

LEVEL OF SERVICE: A qualitative measure of a number of factors, which include speed and travel time, traffic interruptions, freedom to maneuver, safety, driving comfort and convenience, and operating costs.

LOOP DETECTOR: A vehicle detector consisting of a loop of wire embedded in the roadway, energized by alternating current and producing an output circuit closure when passed over by a vehicle.

MINIMUM ACCEPTABLE GAP: Smallest time headway between successive vehicles in a traffic stream into which another vehicle is willing and able to cross or merge.

MULTI-MODAL: More than one mode; such as automobile, bus transit, rail rapid transit, and bicycle transportation modes.

OFFSET: The time interval in seconds between the beginning of green at one intersection and the beginning of green at an adjacent intersection.

PLATOON: A closely grouped component of traffic that is composed of several vehicles moving, or standing ready to move, with clear spaces ahead and behind.

ORIGIN-DESTINATION SURVEY: A survey to determine the point of origin and the point of destination for a given vehicle trip.

PASSENGER CAR EQUIVALENTS (PCE): One car is one Passenger Car Equivalent. A truck is equal to 2 or 3 Passenger Car Equivalents in that a truck requires longer to start, goes slower, and accelerates slower. Loaded trucks have a higher Passenger Car Equivalent than empty trucks.

PEAK HOUR: The 60 consecutive minutes with the highest number of vehicles.

PRETIMED SIGNAL: A type of traffic signal that directs traffic to stop and go on a predetermined time schedule without regard to traffic conditions. Also, fixed time signal.

PROGRESSION: A term used to describe the progressive movement of traffic through several signalized intersections.

SCREEN-LINE: An imaginary line or physical feature across which all trips are counted, normally to verify the validity of mathematical traffic models.

SIGNAL CYCLE: The time period in seconds required for one complete sequence of signal indications.

SIGNAL PHASE: The part of the signal cycle allocated to one or more traffic movements.

STARTING DELAY: The delay experienced in initiating the movement of queued traffic from a stop to an average running speed through a signalized intersection.

TRAFFIC-ACTUATED SIGNAL: A type of traffic signal that directs traffic to stop and go in accordance with the demands of traffic, as registered by the actuation of detectors.

TRIP: The movement of a person or vehicle from one location (origin) to another (destination). For example, from home to store to home is two trips, not one.

TRIP-END: One end of a trip at either the origin or destination; i.e. each trip has two trip-ends. A trip-end occurs when a person, object, or message is transferred to or from a vehicle.

TRIP GENERATION RATE: The quality of trips produced and/or attracted by a specific land use stated in terms of units such as per dwelling, per acre, and per 1,000 square feet of floor space.

TRUCK: A vehicle having dual tires on one or more axles, or having more than two axles.

UNBALANCED FLOW: Heavier traffic flow in one direction than the other. On a daily basis, most facilities have balanced flow. During the peak hours, flow is seldom balanced in an urban area.

VEHICLE MILES OF TRAVEL: A measure of the amount of usage of a section of highway, obtained by multiplying the average daily traffic by length of facility in miles.

APPENDIX B

Traffic Count Worksheets

N-S STREET:	Kanan F	۶d			DATE: 8	8/7/200	7		TION: (City of A	lgoura H	lills		
E-W STREET:	I-101 Fi	reeway N	NB Ramp	DS	DAY: TUESDAY PF					PROJECT# 07-2380-001				
<u></u>	NO	RTHBOL	JND	ŝc	UTHBOL	IND	EA	STBOUN	ND	W	STBOU	ND		
LANES:	NL 1	NT 2	NR 1	SL 0	ST 2	SR 2	EL 1	ET 0	ER 1	WL 2	WT 1	WR 1	TOTAL	
6:00 AM 6:15 AM 6:30 AM 6:45 AM 7:00 AM 7:15 AM 7:30 AM 7:45 AM 8:00 AM 8:15 AM 8:30 AM 8:45 AM 9:00 AM 9:15 AM 9:30 AM 9:30 AM 10:15 AM 10:30 AM 10:45 AM 11:45 AM	3 8 9 10 12 10 9 7	78 111 126 145 174 203 185 170	34 63 69 49 42 50 43 28		203 307 318 340 363 423 426 393	77 115 128 123 132 127 122 105	12 18 21 19 16 12 9 11		27 31 37 35 29 26 24 21	107 120 127 130 131 140 142 127	4 7 9 7 5 10 7 12	100 111 105 120 115 109 107 135	645 891 949 978 1019 1110 1074 1009	
TOTAL VOLUMES =	NL 68	NT 1192	NR 378	SL 0	ST 2773	SR 929	EL 118	ET 0	ER 230	WL 1024	WT 61	WR 902	TOTAL 7675	
AM F	Peak Hr B	egins at:	800	AM										
PEAK Volumes =	38	732	163	0	1605	486	48	0	100	540	34	466	4212	
PEAK HR. FACTOR:		0.887			0.950			0.822			0.949		0.949	
CONTROL:	Signal	ized												

N-S STREET:	Kanan F	Rd			DATE: 8	DATE: 8/7/2007 LOCA					LOCATION: City of Agoura Hills				
E-W STREET:	I-101 F	reeway N	NB Ram	os	DAY:	TUESDA	Y		PROJ	ECT#	07-238	30-001			
		DTUDOI						CTROUN			CTROLIN				
	NO	RTHBOL	JND	SU	UTHBOU	IND	EA	STBOUN	D	VVt	ESTBOU	ND			
LANES:	NL 1	NT 2	NR 1	SL 0	ST 2	SR 2	EL 1	ET 0	ER 1	WL 2	WT 1	WR 1	TOTAL		
1:00 PM 1:15 PM 1:30 PM 1:45 PM 2:00 PM 2:15 PM 2:30 PM 2:45 PM 3:00 PM 3:15 PM 3:30 PM 3:45 PM 4:00 PM 4:15 PM 4:30 PM 4:45 PM 5:00 PM 5:15 PM 5:30 PM 5:45 PM 6:00 PM 6:15 PM	0 6 1 1 3 1 2 1	242 230 261 300 299 311 305 300	106 139 111 119 100 131 108 97		186 205 212 320 258 180 223 249	137 131 125 124 130 135 129 124	17 14 16 16 13 8 9		44 41 38 42 43 46 47 39	77 80 65 76 60 57 70 71	17 15 19 14 18 16 15 11	140 126 171 180 192 191 180 176	966 987 1021 1192 1119 1081 1087 1077		
TOTAL VOLUMES =	NL 15	NT 2248	NR 911	SL 0	ST 1833	SR 1035	EL 111	ЕТ 0	ER 340	WL 556	WT 125	WR 1356	TOTAL 8530		
PM P	eak Hr Be	egins at:	445	PM											
peak Volumes =	7	1215	458	0	981	518	53	0	178	263	63	743	4479		
PEAK HR. FACTOR:		0.948			0.844			0.979			0.990		0.939		
CONTROL:	Signal	ized													

Intersection Turning Movement Prepared by: National Data & Surveying Services

N-S STREET:	Kanan Rd	DATE: 8/7/2007	LOCATION: City of Agoura Hil	LOCATION:	
E-W STREET:	I-101 Freeway SB Ramps	DAY: TUESDAY	PROJECT# 07-2380-002	PROJECT#	

NORTHBOUND					SC	UTHBOU	ND	EASTBOUND WESTBOUND					ID			
LANES:	NL O	NT 1.5	Onto roadside NR 0.5	Onto I- 101 SB NRR	Onto roadside SL 1		Onto I- 101 SB SR 1		Onto roadside ET 0.5	ER 1	WL 1	WT 0	WR 1	TOTAL		
6:00 AM																
6:15 AM																
6:30 AM																
6:45 AM																
7:00 AM	0	53	2	18	21	174	242	39	23	74	3		17	648		
7:15 AM	0	84	8	36	16	186	242	56	16	57	0		16	681		
7:30 AM	0	116	4	50	31	192	296	71	25	63	6		26	830		
7:45 AM	0	116	8	59	36	183	268	96	31	75	4		19	836		
8:00 AM	0	101	3	58	36	207	238	80	38	51	6		19	779		
8:15 AM	0	115	12	58	25	251	247	73	32	47	3		19	824		
8:30 AM	0	139	11	67	26	292	239	92	25	75	7		37	943		
8:45 AM	0	138	4	40	37	321	226	100	38	80	5		19	968		
9:00 AM																
9:15 AM																
9:30 AM																
9:45 AM																
10:00 AM																
10:15 AM																
10:30 AM																
10:45 AM																
11:00 AM																
11:15 AM																
11:30 AM 11:45 AM																
11:45 AM																
TOTAL	NL	NT	NR	PEDS	SL	ST	SR	EL	ET	ER	WL	WT	WR	TOTAL		
Volumes =	0	862	52		228	1806	1998	607	228	522	34	0	172	6509		
	1							1								
	I			386	I			I			I			1		
AM Peak Hr Be	egins at:	80	MA 0													
PEAK																
VOLUMES =	0	493	30		124	1071	950	345	133	253	21	0	94	3514		
	0.000				0.020	1 0 024		0.000	0.075	1 0 701	0.750		0.625			
PEAK HR.	0.000	0.887	0.625		0.838	0.834	0.962	0.863		0.791	0.750		0.635	0.000		
FACTOR:	I		0.872		I	0.918		1	0.838		I	0.653		0.908		
CONTROL:	Signalize	ed														

Intersection Turning Movement

Prepared by: National Data & Surveying Services

N-S STREET: Kanan Rd F-W STREET: I-101 Freeway SB Ramps

DATE: 8/7/2007

LOCATION: City of Agoura Hil

ε	- 99	21	REE	1-101	rieeway	20	Ram

PROJECT# 07-2380-002

	NORTHBOUND					UTHBOU	ND	E	ASTBOUN	D	W			
LANES:	NL O	NT 1.5	Onto roadside NR 0.5	Onto I- 101 SB NRR	Onto roadside SL 1	ST 2	Onto I- 101 SB SR 1	EL 1.5	Onto roadside ET 0.5	ER 1	WL 1	WT 0	WR 1	TOTAL
3:00 PM														
3:15 PM														
3:30 PM														
3:45 PM														
4:00 PM	0	231	5	70	49	188	132	80	16	161	8	0	63	933
4:15 PM	0	298	11	78	42	169	142	46	26	128	3	0	68	933
4:30 PM	0	240	16	60	32	161	107	60	18	103	5	0	70	812
4:45 PM	0	275	22	80	37	158	123	59	21	124	4	0	49	872
5:00 PM	0	240	8	72	47	167	154	75	20	122	3	0	65	901
5:15 PM	0	239	3	79	45	155	162	78	23	182	5	0	85	977
5:30 PM	0	255	7	80	37	161	85	81	19	137	7	0	70	859
5:45 PM	0	236	5	81	50	197	120	135	22	131	4	0	62	962
6:00 PM														
6:15 PM														
6:30 PM														
6:45 PM														
7:00 PM														
7:15 PM														
TOTAL	NL	NT	NR	PEDS	SL	ST	SR	EL	ET	ER	WL	WT	WR	TOTAL
VOLUMES =	0	2014	77		339	1356	1025	614	165	1088	39	0	532	7249
				600										
AM Peak Hr Be	gins at:	50	0 PM											
PEAK														
VOLUMES =	0	970	23		179	680	521	369	84	572	19	0	282	3699
. 5101 (10														
PEAK HR.	0.000	0.951	0.719		0.895	0.863	0.804	0.683	0.913	0.786	0.679	0.000	0.388	
FACTOR:			0.948			0.938			0.890			0.836		0.947
	•										-			

CONTROL: Signalized

Intersection Turning Movement

Prepared by: National Data & Surveying Services

N-S STREET:	Clareton	Clareton Dr DATE: 5/15/2007								LOCATION: City of Agoura Hills				
E-W STREET:	Canwoo	d St			DAY: TI	JESDA	Y		PROJE	CT#	07-224	5-001		
								<u></u>		<u></u>				
	NO	RTHBOUI	ND	SOL	JTHBOUN	D	EA	STBOUN	D	WE	STBOUN	D		
LANES:	NL	NT	NR	SL 0	ST 1	SR 0	EL 0	ET 1	ER	WL	WT 1	WR 0	TOTAL	
6:00 AM 6:15 AM 6:30 AM 6:45 AM 7:00 AM 7:15 AM 7:30 AM 7:45 AM 8:00 AM 8:15 AM 8:30 AM 8:45 AM 9:00 AM 9:15 AM 9:30 AM 9:45 AM 10:00 AM 10:15 AM				8 5 9 7 15 24 4 8		2 8 9 8 7 15 6 6	20 29 25 30 33 40 13 18	34 48 67 60 70 74 70 63			8 9 15 16 17 17 14 15	2 24 24 22 18 19 4 7	74 123 149 143 160 189 111 117	
10:45 AM 11:00 AM 11:15 AM 11:30 AM 11:45 AM		NT	ND	SL		SR	T EL	ET	ER	WL	WT	WR	TOTAL	
TOTAL VOLUMES =	NL 0	NT O	NR 0	80	0	61	208	486	0	0	111	120	1066	
	 Peak Hr B	egins at:	730	AM			I			8				
peak Volumes =	0	0	0	55	0	39	128	271	0	0	65	83	641	
PEAK HR. FACTOR:		0.000			0.603			0.875			0.949		0.848	

CONTROL:

N-S STREET:	Claretor	Clareton Dr DATE: 5/15/2007								LOCATION: City of Agoura Hills				
E-W STREET:	Canwoo	d St			DAY: T	UESDA	Y		PROJE	ECT#	07-224	6-001		
			****			_								
	NO	RTHBOL	IND	SOL	JTHBOUN	ND	EA	STBOUN	ID	W	ESTBOUN	ND		
LANES:	NL	NT	NR	SL 0	ST 1	SR 0	EL O	ET 1	ER	WL	WT 1	WR 0	TOTAL	
1:00 PM 1:15 PM 1:30 PM 1:45 PM 2:00 PM 2:15 PM 2:30 PM 2:45 PM 3:00 PM 3:15 PM 3:30 PM 3:45 PM 4:00 PM 4:15 PM 4:30 PM 5:15 PM 5:30 PM 5:30 PM 5:30 PM 6:15 PM 6:30 PM 6:45 PM				19 18 20 25 27 27 25 23		57 48 51 52 54 62 60 58	41 27 35 30 41 40 40 36	36 36 37 38 39 29 29 29 25			41 43 45 50 60 34 40 31	16 18 18 28 26 15 23 15	210 190 206 223 247 207 217 188	
TOTAL VOLUMES =	NL 0	NT 0	NR 0	SL 184	ST 0	SR 442	EL 290	ET 269	ER 0	WL 0	WT 344	WR 159	TOTAL 1688	
PMI	Peak Hr B	egins at	: 445	i PM										
peak Volumes =	0	0	0	104	0	228	151	135	0	0	184	92	894	
PEAK HR. FACTOR:		0.000)		0.933			0.894			0.802		0.905	
CONTROL:														

N-S STREET:	Derry Av	re i			DATE: 5		LOCATION: City of Agoura Hills						
E-W STREET:	Canwoo	d St			DAY: 1	UESDAY	/		Proji	ECT#	07-224	6-002	
<u></u>	NÖ	RTHBOU	IND	SO	JTHBOU	ND	ĒA	STBOUN	ID	W	ESTBOUI	ND	
LANES:	NL O	NT 1	NR 0	SL 0	ST 1	SR 0	EL 1	ЕТ 1	ER 0	WL 1	WT 1	WR 0	TOTAL
6:00 AM 6:15 AM 6:30 AM 6:45 AM 7:00 AM 7:15 AM 7:30 AM 7:45 AM 8:00 AM 8:15 AM 8:30 AM 8:45 AM 9:00 AM 9:15 AM 9:30 AM 9:30 AM 10:15 AM 10:30 AM 10:45 AM 11:00 AM 11:15 AM	0 0 0 0 0 0	0 0 0 0 0 0	0 1 0 0 0 0 1	8 4 6 1 3 12 9 4	0 0 0 0 0 0	3 4 6 7 6 6 10	17 18 24 33 23 25 20 26	19 34 50 44 39 61 74 57	0 0 0 0 2 0	0 0 0 0 0 0 1	11 27 15 26 27 32 28 22	15 12 25 31 23 17 15	73 100 121 135 130 159 156 136
TOTAL VOLUMES =	NL 0	NT 0	NR 2	SL 47	ST 0	SR 46	EL 186	ET 378	ER 2	WL 1	WT 188	WR 160	TOTAL 1010
AM	l Peak Hr Begins at:			AM									
peak Volumes =	O	0	1	28	0	29	94	231	2	1	109	86	581
PEAK HR. FACTOR:		0.250)		0.792	1 -		0.852			0.845	;	0.914
CONTROL:													

Prepared by: National Data & Surveying Services

N-S STREET:	Derry A	/e			DATE: 5,		LOCATION: City of Agoura Hills						
E-W STREET:	Canwoo	d St			DAY: T	UESDA	Y		PROJE	ECT#	07-224	6-002	
	NO	RTHBOU	IND	SOL	JTHBOU	ND.	EA	STBOUN	ID	WI	ESTBOUI	ND	
LANES:	NL O	NT 1	NR 0	SL 0	ST 1	SR 0	EL 1	ET 1	ER 0	WL 1	WT 1	WR 0	TOTAL
1:00 PM 1:15 PM 1:30 PM 1:45 PM 2:00 PM 2:15 PM 2:30 PM 2:45 PM 3:00 PM 3:15 PM 3:30 PM 3:45 PM 4:00 PM 4:15 PM 4:30 PM 4:30 PM 5:15 PM 5:30 PM 5:30 PM 5:30 PM 6:45 PM 6:45 PM	0 0 1 0 1 0 2 0	0 0 0 1 0 0 0 1	0 1 1 0 2 1 0	26 28 36 30 39 24 33 20	1 0 0 1 0 0 0 1	37 30 44 21 47 18 33 17	27 42 17 16 5 20 10 17	37 22 45 32 35 43 39 37	0 1 2 1 0 1 0 1	1 1 1 0 0 0 1 0	29 35 28 31 43 28 20	18 20 11 14 12 20 13 8	176 180 186 144 170 171 160 122
TOTAL VOLUMES =	NL 4	NT 2	NR 5	SL 236	ST 3	SR 247	EL 154	ЕТ 290	ER 6	WL 4	WT 242	WR 116	TOTAL 1309
PM	Peak Hr B	egins at	: 400	PM									
peak Volumes =	1	1	2	120	2	132	102	136	4	3	1 20	63	686
PEAK HR. FACTOR:		0.500	I		0.794		i.	0.931			0.830		0.922
CONTROL:													

N-S STREET:	Colodny	Dr			DATE: 5		LOCATION: City of Agoura Hills						
E-W STREET:	Canwoo	d St			DAY: T	UESDA	Y		PROJE	CT#	07-224	5-003	
	NO	RTHBOL			UTHBOU			STBOUN	<u> </u>		ESTBOUN		
	NO			500			CP	SIDUUN	U	vv	ESTRUUN	D	
LANES:	NL	NT	NR	SL 0	ST 1	SR 0	EL 1	ET 1	ER	WL	WT 1	WR 0	TOTAL
6:00 AM 6:15 AM 6:30 AM 6:45 AM 7:00 AM 7:15 AM 7:30 AM 7:45 AM 8:00 AM 8:15 AM 8:30 AM 8:45 AM 9:00 AM 9:15 AM 9:30 AM 9:30 AM 10:15 AM 10:30 AM 10:45 AM				4 5 3 5 3 8 17 14		3 7 3 7 1 2 7 6	5 6 5 7 17 16 5 2	36 33 33 57 52 44 45 51			29 34 39 56 29 34 29 54	3 4 3 6 1 2 1 6	80 89 86 138 103 106 104 133
11:30 AM 11:45 AM								FT	ER	WL	WT	WR	TOTAL
TOTAL VOLUMES =	NL 0	NT 0	NR 0	SL 59	ST 0	SR 36	EL 63	ET 351	0	0	304	26	839
AM	Peak Hr E	Begins at	: 745	S AM									
peak Volumes =	0	0	0	33	0	17	45	198	0	0	148	10	451
PEAK HR. FACTOR:		0.000	ł		0.521			0.880			0.637		0.817
CONTROL:													

N-S STREET:	Colodny	Dr			DATE: 5		LOCATION: City of Agoura Hills						
E-W STREET:	Canwoo	d St			DAY: 1	UESDA	Y		PROJE	ECT#	07-224	46-003	
		DTUDO						CTROL IN					
	NO	RTHBOL	JND	SO	UTHBOU	ND	EA	STBOUN	ND	W	ESTBOU	ND	
LANES:	NL	NT	NR	SL 0	ST 1	SR 0	EL 1	ET 1	ER	WL	WT 1	WR 0	TOTAL
1:00 PM 1:15 PM 1:30 PM 1:45 PM 2:00 PM 2:15 PM 2:30 PM 2:45 PM 3:00 PM 3:15 PM 3:30 PM 3:45 PM 4:00 PM 4:15 PM 4:30 PM 4:45 PM 5:00 PM 5:15 PM 5:30 PM 5:45 PM 6:00 PM 6:15 PM 6:30 PM				5 4 4 4 2 5		10 11 12 5 6 6 5	8 7 11 8 9 9 3	45 50 48 61 62 60 48			35 44 40 34 39 48 29 22	6 7 2 4 2 3 1	109 123 118 124 121 129 109 84
TOTAL VOLUMES =	NL 0	NT 0	NR 0	SL 30	ST 0	SR 60	EL 62	ET 442	ER 0	WL 0	WT 291	WR 32	TOTAL 917
PM	Peak Hr B	egins at	:: 430	PM									
PEAK VOLUMES =	0	0	0	14	0	28	35	239	0	0	161	15	492
PEAK HR. FACTOR:		0.000)		0.656			0.867	,		0.880)	0.953
CONTROL:													


N-S STREET:	Cheseb	ro Rd			DATE: 8	LOCATION: City of Agoura Hills							
E-W STREET:	Driver A	lve			DAY:	TUESDA	Y		PROJ	ECT#	07-23	80-003	
<u>. </u>		RTHBOI			UTHBOU			ASTBOUN			CTDOL		
	nc		UND	SU		MD	E/	4516001	U	vv	ESTBOU	ND	
LANES:	NL 0	NT 1	NR 0	SL 0	ST 1	SR 0	EL 1	ET 1	ER 0	WL 0	WT 1	WR 0	TOTAL
6:00 AM 6:15 AM 6:30 AM 6:45 AM 7:00 AM 7:15 AM 7:30 AM	1 0 1	0 0 2	20 21 22	6 7 6	0 1 0	5 0 1	3 2 1	37 65 40	2 0 0	24 43 35	18 34 21	6 4 3	122 177 132
7:45 AM 8:00 AM 8:15 AM 8:30 AM 8:45 AM	0 3 1 1 1	0 0 1 1	29 32 26 25 27	9 12 9 11 15	0 0 2 1 2	1 3 0 2	2 4 2 1	72 67 57 59 60	1 2 0 0 0	57 59 41 36 35	35 48 23 29 34	7 16 6 9 5	213 246 170 173 183
9:00 AM 9:15 AM 9:30 AM 9:45 AM 10:00 AM 10:15 AM 10:30 AM 10:45 AM 11:00 AM 11:15 AM 11:30 AM													
TOTAL VOLUMES =	NL 8	NT 4	NR 202	SL 75	ST 6	SR 15	EL 16	ET 457	ER 5	WL 330	WT 242	WR 56	TOTAL 1416
AM P	eak Hr Be	r Begins at: 745 AM											
Peak Volumes =	5	1	112	41	3	7	9	255	3	193	135	38	802
PEAK HR. FACTOR:		0.843			0.850			0.890			0.744		0.815
CONTROL:	4-Way												

Prepared by: National Data & Surveying Services

N-S STREET:	Chesebr	ro Rd			DATE: 8		LOCATION: City of Agoura Hills						
E-W STREET:	Driver A	we			DAY: 1	TUESDA	Y		PROJ	ECT#	07-23	80-003	
											_		
	NO	RTHBOU	JND	SO	UTHBOU	IND	Ē/	ASTBOUN	ND	W	ESTBOU	ND	
LANES:	NL O	NT 1	NR 0	SL 0	ST 1	SR 0	EL 1	ET 1	ER 0	WL 0	WT 1	WR 0	TOTAL
1:00 PM 1:15 PM 1:30 PM 1:45 PM 2:00 PM 2:15 PM 2:30 PM 2:45 PM 3:00 PM 3:15 PM 3:30 PM 3:45 PM 4:00 PM 4:15 PM 4:30 PM 5:15 PM 5:30 PM 5:15 PM 5:30 PM 6:15 PM 6:30 PM 6:45 PM	2 1 2 1 3 1 4 3	0 1 1 1 0 3 2 0	65 54 69 60 82 66 50 54	11 8 9 4 8 5 10	2 0 0 4 0 2 0	4 1 0 2 1 2 1 5	2 7 4 2 4 3 2	38 42 63 33 46 42 44 45	1 3 1 5 1 3 3	25 33 37 32 28 29 31 24	47 82 81 70 76 105 113 93	12 6 12 8 13 10 11 16	209 238 281 221 264 271 269 255
Total Volumes =	NL 17	NT 8	NR 500	SL 64	ST 8	SR 16	EL 28	ET 353	ER 20	WL 239	WT 667	WR 88	TOTAL 2008
PM P	eak Hr Be	egins at:	500	PM									
Peak Volumes =	11	5	252	27	6	9	11	177	12	112	387	50	1059
PEAK HR. FACTOR:		0.788			0.700			0.943			0.885		0.977
CONTROL:	4-Way	Stop											


N-S STREET:	Cheseb	ro Rd			DATE: 8/7/2007					LOCATION: City of Agoura Hills			
E-W STREET:	I-101 Fi	reeway N	B Ram	ps	DAY: 1	TUESDA	Y		PROJ	ECT#	07-238	30-004	
	NO	RTHBOU	IND	SC	UTHBOU	IND	E	ASTBOUN	ID	W	ESTBOU	ND	
LANES:	NL O	NT 1	NR 0	SL 0	ST 1	SR 1	EL 0	ET 0	ER 0	WL 1	WT 0.5	WR 0.5	TOTAL
6:00 AM 6:15 AM 6:30 AM 6:45 AM 7:00 AM 7:15 AM 7:30 AM 7:45 AM 8:00 AM 8:15 AM 8:30 AM 8:45 AM 9:00 AM 9:15 AM 9:30 AM 9:15 AM 10:00 AM 10:15 AM 10:30 AM 10:45 AM 11:30 AM 11:45 AM	2 6 5 9 8 17 18 13	16 24 22 28 42 36 31 32			33 68 68 83 78 88 86 76	2 15 18 22 23 26 28 24				19 45 47 49 66 59 54 52		31 44 49 55 59 68 56 51	103 202 209 246 276 294 273 248
Total Volumes =	NL 78	NT 231	NR 0	SL 0	ST 580	SR 158	EL 0	ET 0	ER 0	WL 391	WT 0	WR 413	TOTAL 1851
	l Peak Hr Be	egins at:	800	AM			I			I			1 1
Peak Volumes =	56	141	0	0	328	101	0	0	0	231	0	234	1091
PEAK HR. FACTOR:		0.929			0.941			0.000			0.915		0.928
CONTROL:	1-Way	Stop W											

N-S STREET:	Chesebr	ro Rd			DATE: 8/7/2007 LOC					TION:	City of A	lgoura H	ills
E-W STREET:	I-101 Fr	eeway N	IB Ram	os	DAY:	TUESDA	Y		PROJ	ECT#	07-23	80-004	
	NO	RTHBOL			UTHBOU		Ē	ASTBOUN	<u></u>		ESTBOU		
LANES:	NL 0	NT 1	NR 0	SL 0	ST 1	SR 1	EL 0	ET 0	ER 0	WL 1	WT 0.5	WR 0.5	TOTAL
1:00 PM 1:15 PM 1:30 PM 1:45 PM 2:00 PM 2:15 PM 2:30 PM 2:45 PM 3:00 PM 3:15 PM 3:30 PM 3:45 PM 4:00 PM 4:15 PM 4:30 PM 5:15 PM 5:30 PM 5:30 PM 5:45 PM 6:30 PM 6:30 PM 6:45 PM	22 27 31 44 67 65 70 62	49 51 60 50 64 62 69 60			54 58 97 94 105 95 91 87	25 29 32 30 30 32 33 31				46 57 58 57 54 59 54 53	0 0 0 0 0 0 0 0	56 64 61 70 67 68 68 65	252 286 339 345 387 381 385 358
TOTAL VOLUMES =	NL 388	NT 465	NR 0	SL 0	ST 681	SR 242	EL 0	ЕТ 0	ER 0	WL 438	WT 0	WR 519	TOTAL 2733
PM P	Peak Hr Be	egins at:	500	PM									
peak Volumes =	264	255	0	0	378	126	0	0	0	220	0	268	1511
PEAK HR. FACTOR:		0.933			0.933			0.000			0.961		0.976
CONTROL:	1-Way	Stop W											



goura Hills Business Park Project

Associated Transportation Engineers



APPENDIX C

Explanation and Calculation of Intersection Capacity Utilization/Delay

EXPLANATION AND CALCULATION OF INTERSECTION CAPACITY UTILIZATION

Overview

The ability of a roadway to carry traffic is referred to as capacity. The capacity is usually greater between intersections and less at intersections because traffic flows continuously between them and only during the green phase at them. Capacity at intersections is best defined in terms of vehicles per lane per hour of green. If capacity is 1,600 vehicles per lane per hour of green, and if the green phase is 50 percent of the cycle and there are three lanes, then the capacity is 1,600 times 50 percent times 3 lanes, or 2,400 vehicles per hour for that approach.

The technique used to compare the volume and capacity at a signalized intersection is known as Intersection Capacity Utilization. Intersection Capacity Utilization, usually expressed as a percent, is the proportion of an hour required to provide sufficient capacity to accommodate all intersection traffic if all approaches operate at capacity. If an intersection is operating at 80 percent of capacity (i.e., an Intersection Capacity Utilization of 80 percent), then 20 percent of the signal cycle is not used. The signal could show red on all indications 20 percent of the time and the signal would just accommodate approaching traffic.

Intersection Capacity Utilization analysis consists of (a) determining the proportion of signal time needed to serve each conflicting movement of traffic, (b) summing the times for the movements, and (c) comparing the total time required to the total time available. For example, if for north-south traffic the northbound traffic is 1,600 vehicles per hour, the southbound traffic is 1,200 vehicles per hour, and the capacity of either direction is 3,200 vehicles per hour, then the northbound traffic is critical and requires 1,600/3,200 or 50 percent of the signal time. If for east-west traffic, 30 percent of the signal time is required, then it can be seen that the Intersection Capacity Utilization is 50 plus 30, or 80 percent. When left turn arrows (left turn phasing) exist, they are incorporated into the analysis. The critical movements are usually the heavy left turn movements and the opposing through movements.

The Intersection Capacity Utilization technique is an ideal tool to quantify existing as well as future intersection operation. The impact of adding a lane can be quickly determined by examining the effect the lane has on the Intersection Capacity Utilization.

Intersection Capacity Utilization Worksheets That Follow This Discussion

The Intersection Capacity Utilization worksheet table contains the following information:

- 1. Peak hour turning movement volumes.
- 2. Number of lanes that serve each movement.
- 3. For right turn lanes, whether the lane is a free right turn lane, whether it has a right turn arrow, and the percent of right turns on red that are assumed.
- 4. Capacity assumed per lane.
- 5. Capacity available to serve each movement (number of lanes times capacity per lane).
- 6. Volume to capacity ratio for each movement.
- 7. Whether the movement's volume to capacity ratio is critical and adds to the Intersection Capacity Utilization value.
- 8. The yellow time or clearance interval assumed.
- 9. Adjustments for right turn movements.
- 10. The Intersection Capacity Utilization and Level of Service.

The Intersection Capacity Utilization Worksheet also has two graphics on the same page. These two graphics show the following:

- 1. Peak hour turning movement volumes.
- 2. Number of lanes that serve each movement.
- 3. The approach and exit leg volumes.
- 4. The two-way leg volumes.
- 5. An estimate of daily traffic volumes that is fairly close to actual counts and is based strictly on the peak hour leg volumes multiplied by a factor.

- 6. Percent of daily traffic in peak hours.
- 7. Percent of peak hour leg volume that is inbound versus outbound.

A more detailed discussion of Intersection Capacity Utilization and Level of Service follows.

Level of Service

Level of Service is used to describe the quality of traffic flow. Levels of Service A to C operate quite well. Level of Service C is typically the standard to which rural roadways are designed.

Level of Service D is characterized by fairly restricted traffic flow. Level of Service D is the standard to which urban roadways are typically designed. Level of Service E is the maximum volume a facility can accommodate and will result in possible stoppages of momentary duration. Level of Service F occurs when a facility is overloaded and is characterized by stop-and-go traffic with stoppages of long duration.

A description of the various Levels of Service appears at the end of the Intersection Capacity Utilization description, along with the relationship between Intersection Capacity Utilization and Level of Service.

Signalized Intersections

Although calculating an Intersection Capacity Utilization value for an unsignalized intersection is invalid, the presumption is that a signal can be installed and the calculation shows whether the geometrics are capable of accommodating the expected volumes with a signal. A traffic signal becomes warranted before Level of Service D is reached for a signalized intersection.

Signal Timing

The Intersection Capacity Utilization calculation assumes that a signal is properly timed. It is possible to have an Intersection Capacity Utilization well below 100 percent, yet have severe traffic congestion. This would occur if one or more movements is not getting sufficient green time to satisfy its demand, and excess green time exists on other movements. This is an operational problem that should be remedied.

Lane Capacity

Capacity is often defined in terms of roadway width; however, standard lanes have approximately the same capacity whether they are 11 or 14 feet wide. Our data indicates a typical lane, whether a through lane or a left turn lane, has a capacity of approximately 1,750 vehicles per hour of green time, with nearly all locations showing a capacity greater than 1,600 vehicles per hour of green per lane. Right turn lanes have a slightly lower capacity; however 1,600 vehicles per hour is a valid capacity assumption for right turn lanes.

This finding is published in the August 1978 issue of Institute of Transportation Engineers Journal in the article entitled, "Another Look at Signalized Intersection Capacity" by William Kunzman. A capacity of 1,600 vehicles per hour per lane with no yellow time penalty, or 1,700 vehicles per hour with a 3 or 5 percent yellow time penalty is reasonable.

Yellow Time

The yellow time can either be assumed to be completely used and no penalty applied, or it can be assumed to be only partially usable. Total yellow time accounts for approximately 10 percent of a signal cycle, and a penalty of 3 to 5 percent is reasonable.

During peak hour traffic operation the yellow times are nearly completely used. If there is no left turn phasing, the left turn vehicles completely use the yellow time. Even if there is left turn phasing, the through traffic continues to enter the intersection on the yellow until just a split second before the red.

Shared Lanes

Shared lanes occur in many locations. A shared lane is often found at the end of an off ramp where the ramp forms an intersection with the cross street. Often at a diamond interchange off ramp, there are three lanes. In the case of a diamond interchange, the middle lane is sometimes shared, and the driver can turn left, go through, or turn right from that lane.

If one assumes a three lane off ramp as described above, and if one assumes that each lane has 1,600 capacity, and if one assumes that there are 1,000 left turns per hour, 500 right turns per hour, and 100 through vehicles per hour, then how should one assume that the three lanes operate. There are three ways that it is done.

One way is to just assume that all 1,600 vehicles (1,000 plus 500 plus 100) are served simultaneously by three lanes. When this is done, the capacity is 3 times 1,600 or 4,800, and the amount of green time needed to serve the ramp is 1,600 vehicles divided by 4,800 capacity or 33.3 percent. This assumption effectively assumes perfect lane distribution between the three lanes that is not realistic. It also means a left turn can be made from the right lane.

Another way is to equally split the capacity of a shared lane and in this case to assume there are 1.33 left turn lanes, 1.33 right turn lanes, and 0.33 through lanes. With this assumption, the critical movement is the left turns and the 1,000 left turns are served by a capacity of 1.33 times 1,600, or 2,133. The volume to capacity ratio of the critical move is 1,000 divided by 2,133 or 46.9 percent.

The first method results in a critical move of 33.3 percent and the second method results in a critical move of 46.9 percent. Neither is very accurate, and the difference in the calculated Level of Service will be approximately 1.5 Levels of Service (one Level of Service is 10 percent).

The way Kunzman Associates does it is to assign fractional lanes in a reasonable way. In this example, it would be assumed that there is 1.1 right turn lanes, 0.2 through lanes, and 1.7 left turn lanes. The volume to capacity ratios for each movement would be 31.3 percent for the through traffic, 28.4 percent for the right turn movement, and 36.8 percent for the left turn movement. The critical movement would be the 36.8 percent for the left turns.

Right Turn on Red

Kunzman Associates' software treats right turn lanes in one of five different ways. Each right turn lane is classified into one of five cases. The five cases are (1) free right turn lane, (2) right turn lane with separate right turn arrow, (3) standard right turn lane with no right turns on red allowed, (4) standard right turn lane with a certain percentage of right turns on red allowed, and (5) separate right turn arrow and a certain percentage of right turns on red allowed.

Free Right Turn Lane

If it is a free right turn lane, then it is given a capacity of one full lane with continuous or 100 percent green time. A Free right turn lane occurs when there is a separate approach lane for right turning vehicles, there is a separate departure lane for the right turning vehicles after they turn and are exiting the intersection, and the through cross street traffic does not interfere with the vehicles after they turn right.

Separate Right Turn Arrow

If there is a separate right turn arrow, then it is assumed that vehicles are given a green indication and can proceed on what is known as the left turn overlap.

The left turn overlap for a northbound right turn is the westbound left turn. When the left turn overlap has a green indication, the right turn lane is also given a green arrow indication. Thus, if there is a northbound right turn arrow, then it can be turned green for the period of time that the westbound left turns are proceeding.

If there are more right turns than can be accommodated during the northbound through green and the time that the northbound right turn arrow is on, then an adjustment is made to the Intersection Capacity Utilization to account for the green time that needs to be added to the northbound through green to accommodate the northbound right turns.

Standard Right Turn Lane, No Right Turns on Red

A standard right turn lane, with no right turn on red assumed, proceeds only when there is a green indication displayed for the adjacent through movement. If additional green time is needed above that amount of time, then in the Intersection Capacity Utilization calculation a right turn adjustment green time is added above the green time that is needed to serve the adjacent through movement.

Standard Right Turn Lane, With Right Turns on Red

A standard right turn lane with say 20 percent of the right turns allowed to turn right on a red indication is calculated the same as the standard right turn case where there is no right turn on red allowed, except that the right turn adjustment is reduced to account for the 20 percent of the right turning vehicles that can logically turn right on a red light. The right turns on red are never allowed to exceed the time the overlap left turns take plus the unused part of the green cycle that the cross street traffic moving from left to right has.

As an example of how 20 percent of the cars are allowed to turn right on a red indication, assume that the northbound right turn volume needs 40 percent of the signal cycle to be satisfied. To allow 20 percent of the northbound right turns to turn right on red, then during 8 percent of the signal cycle (40 percent of signal cycle times 20 percent that can turn right on red) right turns on red will be allowed if it is feasible.

For this example, assume that 15 percent of the signal cycle is green for the northbound through traffic, and that means that 15 percent of the signal cycle is

available to satisfy northbound right turns. After the northbound through traffic has received its green, 25 percent of the signal cycle is still needed to satisfy the northbound right turns (40 percent of the signal cycle minus the 15 percent of the signal cycle that the northbound through used).

Assume that the westbound left turns require a green time of 6 percent of the signal cycle. This 6 percent of the signal cycle is used by northbound right turns on red. After accounting for the northbound right turns that occur on the westbound overlap left turn, 19 percent of the signal cycle is still needed for the northbound right turns (25 percent of the cycle was needed after the northbound through green time was accounted for [see above paragraph], and 6 percent was served during the westbound left turn overlap). Also, at this point 6 percent of the signal cycle has been used for northbound right turns on red, and still 2 percent more of the right turns will be allowed to occur on the red if there is unused eastbound through green time.

For purpose of this example, assume that the westbound through green is critical, and that 15 percent of the signal cycle is unused by eastbound through traffic. Thus, 2 percent more of the signal cycle can be used by the northbound right turns on red since there is 15 seconds of unused green time being given to the eastbound through traffic.

At this point, 8 percent of the signal cycle was available to serve northbound right turning vehicles on red, and 15 percent of the signal cycle was available to serve right turning vehicles on the northbound through green. So 23 percent of the signal cycle has been available for northbound right turns.

Because 40 percent of the signal cycle is needed to serve northbound right turns, there is still a need for 17 percent more of the signal cycle to be available for northbound right turns. What this means is the northbound through traffic green time is increased by 17 percent of the cycle length to serve the unserved right turn volume, and a 17 percent adjustment is added to the Intersection Capacity Utilization to account for the northbound right turns that were not served on the northbound through green time or when right turns on red were assumed.

Separate Right Turn Arrow, With Right Turns on Red

A right turn lane with a separate right turn arrow, plus a certain percentage of right turns allowed on red is calculated the same way as a standard right turn lane with a certain percentage of right turns allowed on red, except the turns which occur on the right turn arrow are not counted as part of the percentage of right turns that occur on red.

Critical Lane Method

Intersection Capacity Utilization parallels another calculation procedure known as the Critical Lane Method with one exception. Critical Lane Method dimensions capacity in terms of standardized vehicles per hour per lane. A Critical Lane Method result of 800 vehicles per hour means that the intersection operates as though 800 vehicles were using a single lane continuously. If one assumes a lane capacity of 1,600 vehicles per hour, then a Critical Lane Method calculation resulting in 800 vehicles per hour is the same as an Intersection Capacity Utilization calculation of 50 percent since 800/1,600 is 50 percent. It is our opinion that the Critical Lane Method is inferior to the Intersection Capacity Utilization method simply because a statement such as "The Critical Lane Method value is 800 vehicles per hour" means little to most persons, whereas a statement such as "The Intersection Capacity Utilization is 50 percent" communicates clearly. Critical Lane Method results directly correspond to Intersection Capacity Utilization results. The correspondence is as follows, assuming a lane capacity of 1,600 vehicles per hour and no clearance interval.

<u>Critical Lane Method</u> <u>Result</u>	Intersection Capacity Utilization Result
800 vehicles per hour	50 percent
960 vehicles per hour	60 percent
1,120 vehicles per hour	70 percent
1,280 vehicles per hour	80 percent
1,440 vehicles per hour	90 percent
1,600 vehicles per hour	100 percent
1,760 vehicles per hour	110 percent

INTERSECTION CAPACITY UTILIZATION LEVEL OF SERVICE DESCRIPTION¹

Level of		Volume to
Service	Description	Capacity Ratio
A	Level of Service A occurs when progression is extremely favorable and vehicles arrive during the green phase. Most vehicles do not stop at all. Short cycle lengths may also contribute to low delay.	0.600 and below
В	Level of Service B generally occurs with good progression and/or short cycle lengths. More vehicles stop than for Level of Service A, causing higher levels of average delay.	0.601 to 0.700
С	Level of Service C generally results when there is fair progression and/or longer cycle lengths. Individual cycle failures may begin to appear in this level. The number of vehicles stopping is significant at this level, although many still pass through the intersection without stopping.	0.701 to 0.800
D	Level of Service D generally results in noticeable congestion. Longer delays may result from some combination of unfavorable progression, long cycle lengths, or high volume to capacity ratios. Many vehicles stop, and the proportion of vehicles not stopping declines. Individual cycle failures are noticeable.	0.801 to 0.900
E	Level of Service E is considered to be the limit of acceptable delay. These high delay values generally indicate poor progression, long cycle lengths, and high volume to capacity ratios. Individual cycle failures are frequent.	0.901 to 1.000
F	Level of Service F is considered to be unacceptable to most drivers. This condition often occurs when oversaturation, i.e., when arrival flow rates exceed the capacity of the intersection. It may also occur at high volume to capacity ratios below 1.00 with many individual cycle failures. Poor progression and long cycle lengths may also be major contributing causes to such delay levels.	1.001 and up

¹ Source: <u>Highway Capacity Manual</u> Special Report 209, Transportation Research Board, National Research Council Washington D.C., 2000.

EXPLANATION AND CALCULATION OF INTERSECTION LEVEL OF SERVICE USING DELAY METHODOLOGY

The levels of service at the unsignalized intersections are calculated using the delay methodology in the <u>2000 Highway Capacity Manual</u>. This methodology views an intersection as consisting of several lane groups. A lane group is a set of lanes serving a movement. If there are two northbound left turn lanes, then the lane group serving the northbound left turn movement has two lanes. Similarly, there may be three lanes in the lane group serving the northbound right turn movement, and so forth. It is also possible for one lane to serve two lane groups. A shared lane might result in there being 1.5 lanes in the northbound left turn lane group and 2.5 lanes in the northbound through lane group.

For each lane group, there is a capacity. That capacity is calculated by multiplying the number of lanes in the lane group times a theoretical maximum lane capacity per lane times 12 adjustment factors.

Each of the 12 adjustment factors has a value of approximately 1.00. A value less than 1.00 is generally assigned when a less than desirable condition occurs.

The 12 adjustment factors are as follows:

- 1. Peak hour factor (to account for peaking within the peak hour)
- 2. Lane utilization factor (to account for not all lanes loading equally)
- 3. Lane width
- 4. Percent of heavy trucks
- 5. Approach grade
- 6. Parking
- 7. Bus stops at intersections
- 8. Area type (CBD or other)
- 9. Right turns
- 10. Left turns

- 11. Pedestrian activity
- 12. Signal progression

The maximum theoretical lane capacity and the 12 adjustment factors for it are all unknowns for which approximate estimates have been recommended in the 2000 Highway Capacity Manual. For the most part, the recommended values are not based on statistical analysis but rather on educated estimates. However, it is possible to use the delay method and get reasonable results as will be discussed below.

Once the lane group volume is known and the lane group capacity is known, a volume to capacity ratio can be calculated for the lane group.

With a volume to capacity ratio calculated, average delay per vehicle in a lane group can be estimated. The average delay per vehicle in a lane group is calculated using a complex formula provided by the 2000 Highway Capacity Manual, which can be simplified and described as follows:

Delay per vehicle in a lane group is a function of the following:

- 1. Cycle length
- 2. Amount of red time faced by a lane group
- 3. Amount of yellow time for that lane group
- 4. The volume to capacity ratio of the lane group

The average delay per vehicle for each lane group is calculated, and eventually an overall average delay for all vehicles entering the intersection is calculated. This average delay per vehicle is then used to judge Level of Service. The Level of Services are defined in the table that follows this discussion.

Experience has shown that when a maximum lane capacity of 1,900 vehicles per hour is used (as recommended in the 2000 Highway Capacity Manual), little or no yellow time penalty is used, and none of the 12 penalty factors are applied, calculated delay is realistic. The delay calculation for instance assumes that yellow time is totally unused. Yet experience shows that most of the yellow time is used.

An idiosyncrasy of the delay methodology is that it is possible to add traffic to an intersection and reduce the average total delay per vehicle. If the average total delay is 30 seconds per vehicle for all vehicles traveling through an intersection, and traffic is

added to a movement that has an average total delay of 15 seconds per vehicle, then the overall average total delay is reduced.

The delay calculation for a lane group is based on a concept that the delay is a function of the amount of unused capacity available. As the volume approaches capacity and there is no more unused capacity available, then the delay rapidly increases. Delay is not proportional to volume, but rather increases rapidly as the unused capacity approaches zero.

Because delay is not linearly related to volumes, the delay does not reflect how close an intersection is to overloading. If an intersection is operating at Level of Service C and has an average total delay of 18 seconds per vehicle, you know very little as to what percent the traffic can increase before Level of Service E is reached.

LEVEL OF SERVICE DESCRIPTION¹

Level Of		Average Total Delay Per Vehicle (Seconds)					
Service	Description	Signalized	Unsignalized				
A	Level of Service A occurs when progression is extremely favorable and most vehicles arrive during the green phase. Most vehicles do not stop at all. Short cycle lengths may also contribute to low delay.	0 to 10.00	0 to 10.00				
В	Level of Service B generally occurs with good progression and/or short cycle lengths. More vehicles stop than for Level of Service A, causing higher levels of average total delay.	10.01 to 20.00	10.01 to 15.00				
С	Level of Service C generally results when there is fair progression and/or longer cycle lengths. Individual cycle failures may begin to appear in this level. The number of vehicles stopping is significant at this level, although many still pass through the intersection without stopping.	20.01 to 35.00	15.01 to 25.00				
D	Level of Service D generally results in noticeable congestion. Longer delays may result from some combination of unfavorable progression, long cycle lengths, or high volume to capacity ratios. Many vehicles stop, and the proportion of vehicles not stopping declines. Individual cycle failures are noticeable.	35.01 to 55.00	25.01 to 35.00				
E	Level of Service E is considered to be the limit of acceptable delay. These high delay values generally indicate poor progression, long cycle lengths, and high volume to capacity ratios. Individual cycle failures are frequent occurrences.	55.01 to 80.00	35.01 to 50.00				
F	Level of Service F is considered to be unacceptable to most drivers. This condition often occurs with oversaturation, i.e., when arrival flow rates exceed the capacity of the intersection. It may also occur at high volume to capacity ratios below 1.00 with many individual cycle failures. Poor progression and long cycle lengths may also be major contributing causes to such delay levels.	80.01 and up	50.01 and up				

¹ Source: <u>Highway Capacity Manual</u> Special Report 209, Transportation Research Board, National Research Council, Washington, D.C., 2000.

Existing

Default Scenario

______ Agoura Business Center North Development Agreement Existing Morning Peak Hour Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) Intersection #1 Kanan Road (NS) at Thousand Oaks Boulevard (EW) Cycle (sec): 100 Critical Vol./Cap.(X): 0.725 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX С Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - RControl:ProtectedProtectedProtectedProtectedRights:IncludeIncludeIncludeIncludeMin. Green:000000 0 Lanes: 1 0 2 0 1 1 0 2 0 1 2 0 2 0 1 1 0 2 0 1 Volume Module: Base Vol: 110 720 90 110 1240 100 90 70 120 190 100 90 Initial Bse: 114 747 93 114 1287 104 93 73 125 197 104 93

 PHF Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 93
 73
 125
 197
 104
 93

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 1.00
 FinalVolume: 114 747 93 114 1287 104 93 73 125 197 104 93 Saturation Flow Module: Sat/Lane:1600160016001600160016001600160016001600Adjustment:1.001.001.001.001.001.001.001.001.001.00Lanes:1.002.001.002.001.002.001.001.001.001.00Final Sat.:1600320016003200160028803200160032001600 Capacity Analysis Module: Vol/Sat: 0.07 0.23 0.06 0.07 0.40 0.06 0.03 0.02 0.08 0.12 0.03 0.06 Crit Moves: **** * * * * **** **** *******

Default Scenario Mon Feb 6, 2012 16:48:06 Page 2-1 Agoura Business Center North Development Agreement Existing Evening Peak Hour _____ Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) Intersection #1 Kanan Road (NS) at Thousand Oaks Boulevard (EW) ******************* Cycle (sec): 100 Critical Vol./Cap.(X): 0.732 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX C ******** Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - R
 Control:
 Protected
 Protected
 Protected
 Protected

 Rights:
 Include
 Include
 Include
 Include

 Min. Green:
 0
 0
 0
 0
 0
 0
 0
 0

 Lanes:
 1
 0
 2
 0
 1
 0
 2
 0
 1
 0
 0
 1
 -----!!----!!-----!! Volume Module: Base Vol: 290 1290 290 120 920 150 300 240 170 130 170 120

 Base Vol:
 290
 120
 290
 120
 920
 150
 300
 240
 170
 130
 170
 120

 Growth Adj:
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 Reduced Vol: 301 1339 301 125 955 156 311 249 176 135 176 125
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 301 1339 301 125 955 156 311 249 176 135 176 125 _____/ Saturation Flow Module: Final Sat.: 1600 3200 1600 1600 3200 1600 2880 3200 1600 1600 3200 1600 -----!!-----!!-----!!-----!! Capacity Analysis Module: Vol/Sat: 0.19 0.42 0.19 0.08 0.30 0.10 0.11 0.08 0.11 0.08 0.06 0.08 Crit Moves: **** **** **** ****

Default Scenario Mon Feb 6, 2012 16:47:42 Page 3-1 _____ Agoura Business Center North Development Agreement Existing Morning Peak Hour Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) ********* Intersection #2 Kanan Road (NS) at Canwood Street (EW) Cycle (sec): 100 0.523 Critical Vol./Cap.(X): Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX А ********** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - RControl:ProtectedProtectedProtectedProtectedRights:IncludeIncludeIncludeOvlMin. Green:000000Lanes:00120000 Volume Module: Base Vol: 0 940 360 50 1820 0 0 0 220 0 50 0 Initial Bse: 0 976 374 52 1889 0 0 0 0 228 0 52

 PHF Volume:
 0
 976
 374
 52
 1889
 0
 0
 0
 228
 0
 52

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0

 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 0 976 374 52 1889 0 0 0 0 228 0 52 OvlAdjVol: 23 Saturation Flow Module: Adjustment:1.001.001.001.001.001.001.001.001.00Lanes:0.002.001.002.003.000.000.000.002.001.00Final Sat.:032001600288048000000288001600 Capacity Analysis Module: Vol/Sat: 0.00 0.30 0.23 0.02 0.39 0.00 0.00 0.00 0.00 0.08 0.00 0.03 OvlAdjV/S: 0.01Crit Moves: **** * * * * ****

Default Scenario

Agoura Business Center North Development Agreement

Existing

Evening Peak Hour

_____ Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) Intersection #2 Kanan Road (NS) at Canwood Street (EW) Critical Vol./Cap.(X): Cycle (sec): 100 0.706 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX С ***** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R
 Control:
 Protected
 Protected
 Protected
 Protected
 Protected

 Rights:
 Include
 Include
 Include
 Ovl

 Min. Green:
 0
 0
 0
 0
 0
 0
 0
 0

 Lanes:
 0
 0
 1
 2
 0
 0
 0
 0
 0
 0
 1
 0 Volume Module: Base Vol: 0 1590 230 60 1310 0 0 0 0 330 0 180 Initial Bse: 0 1651 239 62 1360 0 0 0 343 0 187

 PHF Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0 0 0 0 0 343 0 187 FinalVolume: 0 1651 239 62 1360 OvlAdjVol: 152 Saturation Flow Module: Sat/Lane:1600< _____/ Capacity Analysis Module: Vol/Sat: 0.00 0.52 0.15 0.02 0.28 0.00 0.00 0.00 0.00 0.12 0.00 0.12 OvlAdjV/S: 0.10 **** * * * * Crit Moves:

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

Agoura Business Center North Development Agreement

Existing

Morning Peak Hour

Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) ******* Intersection #3 Kanan Road (NS) at SR-101 Freeway NB Ramps/Canwood Street (EW) Cycle (sec):100Critical Vol./Cap.(X):Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: 0.673 XXXXXX B ******* Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - R
 Control:
 Protected
 Protected
 Split Phase
 Split Phase
 Split Phase
 Split Phase
 Include
 In Volume Module: Base Vol: 38 732 163 0 1605 486 48 0 100 540 34 466 Initial Bse: 39 760 169 0 1666 505 50 0 104 561 35 484

 PHF Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 1.00
 FinalVolume: 39 760 169 0 1666 505 50 0 104 561 35 484 0 OvlAdjVol: ______ Saturation Flow Module:

 Sat/Lane:
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1600
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00 Capacity Analysis Module: Vol/Sat: 0.02 0.24 0.11 0.00 0.35 0.32 0.03 0.00 0.06 0.19 0.19 0.15 OvlAdjV/S: 0.00 Crit Moves: **** * * * * **** **** *******************

Agoura Business Center North Development Agreement Existing Evening Peak Hour										
Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)										
			eway NB Ramps/Canwo *****							
Optimal Cycle	ec): 5 (Y e: 100	Level	ge Delay (sec/veh):	D						
Approach:	North Bound	South Bound	East Bound	West Bound						
Movement:	L - T - F	L – T – R	L - T - R	L – T – R						
Control:	Protected	Protected	Split Phase	Split Phase						
Rights:	Ovl	Include	Include	-						
Min. Green:	0 0	0 0 0 0	0 0 0	0 0 0						
Lanes:	1 0 2 0 1	0 0 3 0 1	1 0 0 0 1	1 1 0 0 2						

Volume Module: Base Vol: 7 1215 458 0 981 518 53 0 178 263 63 743 Initial Bse: 7 1261 475 0 1018 538 55 0 185 273 65 771 PHF Volume:712614750101853855018527365771Reduct Vol:00000000000Reduced Vol:712614750101853855018527365771 PCE Adj:1.001.001.001.001.001.001.001.001.00MLF Adj:1.001.001.001.001.001.001.001.001.00 FinalVolume: 7 1261 475 0 1018 538 55 0 185 273 65 771 90 OvlAdjVol: -----||------|| Saturation Flow Module: Adjustment:1.001.001.001.001.001.001.001.001.001.00Lanes:1.002.001.000.003.001.001.001.001.001.610.392.00Final Sat.:16003200160004800160016000160025826183200

Capacity Analysis Module: Vol/Sat: 0.00 0.39 0.30 0.00 0.21 0.34 0.03 0.00 0.12 0.11 0.11 0.24 0.06 OvlAdjV/S: Crit Moves: **** **** * * * *

Default Scenario

Crit Moves: ****

Agoura Business Center North Development Agreement Existing Morning Peak Hour Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) ****************** Intersection #4 Kanan Road (NS) at SR-101 Freeway SB Ramps/Roadside Drive (EW) Cycle (sec): 100 Critical Vol./Cap.(X): 0.727 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX C Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R
 Control:
 Protected
 Protected
 Split Phase
 Split Phase

 Rights:
 Include
 Ov1
 Include
 Include

 Min. Green:
 0
 0
 0
 0
 0
 0
 0
 0

 Lanes:
 0
 2
 1
 1
 0
 0
 1
 0 Volume Module:

 Base Vol:
 0
 493
 30
 124
 1071
 950
 345
 133
 253
 21
 0
 94

 Growth Adj:
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1. Reduced Vol: 0 512 31 129 1112 986 358 138 263 22 0 98
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 0 512 31 129 1112 986 358 138 263 22 0 98 733 OvlAdjVol: -----!----! Saturation Flow Module: Lanes: 0.00 2.83 0.17 1.00 2.00 1.00 1.42 0.54 1.04 1.00 0.00 1.00 Final Sat.: 0 4525 275 1600 3200 1600 2265 873 1661 1600 0 1600 -----||-----||------|| Capacity Analysis Module: Vol/Sat: 0.00 0.11 0.11 0.08 0.35 0.62 0.16 0.16 0.16 0.01 0.00 0.06 OvlAdjV/S: 0.46

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

* * * *

Default Scena	n Feb	6, 20)12 16:4	48:06				Page	5-1			
Agoura Business Center North Development Agreement Existing Evening Peak Hour												
Level Of Service Computation Report												
ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)												

Intersection #4 Kanan Road (NS) at SR-101 Freeway SB Ramps/Roadside Drive (EW)												
	<pre>************************************</pre>											
Cycle (sec): Loss Time (se				-0 0 6		Average			(\mathbf{A}) :			
Optimal Cycle		10		-0.0 3	sec)	Level (•	~~~/	C
***********	- • * * * * * *	·*****		* * * * * *	****					*****	*****	
Approach:											est Bo	
Movement:			- R			- R			- R		т	- R
Control:	Control: Protected Protected Split Phase Split Phase											nase
Rights:		Inclu	ıde		Ovl			Inclu	ıde		Inclu	ıde
Min. Green:	-	0	0	-	0	-	0	•	0	0	-	0
Lanes:	-) 2				0 1			0 1			-
	•											
Volume Modul			0.0	100	600	5.0.1	260		530	1.0	0	000
Base Vol:		970	23	179	680	521	369	84	572	19	0	282
Growth Adj:		$1.04 \\ 1007$	1.04 24	1.04	1.04	$1.04 \\ 541$	383	1.04	1.04 594	1.04 20	1.04	1.04 293
Initial Bse: User Adj:		1.007	1.00		1.00	1.00		1.00	1.00	1.00	-	1.00
PHF Adj:		1.00	1.00		1.00	1.00		1.00	1.00	1.00		1.00
PHF Volume:		1007	24	186	706	541	383	87	594	20	0	293
Reduct Vol:		0	24	0	,00	0	0	0	0	0	õ	0
Reduced Vol:	-	1007	24	186	706	541	383	87	594	20	0	293
PCE Adi:		1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:	0	1007	24	186	706	541	383	87	594	20	0	293
OvlAdjVol:						186						
Saturation F									1 6 6 6	1.60.6	1.000	1
Sat/Lane:		1600			1600			1600			1600	
Adjustment:			1.00		1.00	1.00		1.00	1.00		1.00	1.00
Lanes:		2.93 4689	0.07 111		2.00	$1.00 \\ 1600$	1728	0.25	1.67 2679	1600	0.00	1.00 1600
Final Sat.:												!
Capacity Ana	•			,		1			I	,		I
			0.21	0.12	0.22	0.34	0.22	0.22	0.22	0.01	0.00	0.18
OvlAdjV/S:						0.12						
Crit Moves:		****		* * * *				****				****

Default Scenario Mon Feb 6, 2012 16:47:42 Page 6-1 Agoura Business Center North Development Agreement Existing Morning Peak Hour Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) Intersection #5 Kanan Road (NS) at Agoura Road (EW) Cycle (sec): 100 Critical Vol./Cap.(X): 0.686 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX B Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:ProtectedProtectedPermittedPermittedRights:IncludeIncludeIncludeIncludeMin. Green:000000Lanes:10101010 Volume Module: Base Vol: 50 420 20 110 700 220 90 90 90 50 60 100 1.04 104
 User Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00

 PHF Volume:
 52
 436
 21
 114
 727
 228
 93
 93
 52
 62
 104

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 Reduct Vol: Reduced Vol: 52 436 21 114 727 228 93 93 93 52 62 104
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 52 436 21 114 727 228 93 93 93 52 62 104 Saturation Flow Module: Capacity Analysis Module: Vol/Sat: 0.03 0.14 0.14 0.07 0.45 0.14 0.06 0.12 0.12 0.03 0.04 0.06 Crit Moves: **** **** **** *******

Default Scena	31,10	MO	n rep (6, 20	112 10:4	48:06				Page	6-1	
	Agoura E		l Even:	Exist ing E		ır		-				
TOU		Level O	f Serv	ice C	Computat	tion H	Report	Ľ				
. 1CU *********	l(Loss as ********	сусте п ******	******	5) №8 ****	******	3ase \ *****	/OLUM6	e Aiter ******	nacive *****	=) *****	******	
Intersection	#5 Kanan	Road (N	S) at i	Agour	a Road	(EW)						
Cycle (sec):	1	00			Critica	al Vol	L./Cay	o.(X):		0.	640	
Cycle (sec): Loss Time (se	ec):	5 (Y+R	=0.0 s	ec)	Average	e Dela	ay (se	ec/veh)	:	XXXX	xxx	
Optimal Cycle	e: 1	00			Level (Of Sei	rvice	:			В	

										West Bound		
Movement:	L - T	- R	, L -	Т	- R	, L -	- T	- R	_ L -	- Т	- R	
Control:	Protec		 Dr/	otect		۱ ر	Pormit	 + + od		Pormi	!	
Rights: Min. Green:	0 () 0	0	0	0	0	1101	0	0		0	
Lanes:	1 0 1	1 0	1 0	1	0 1	1 (ວັັ	1 0	1 (0 1	
Volume Module	e:											
Base Vol:	50 650		150	490	130	150	120	30	70	140	220	
Growth Adj:	1.04 1.04		1.04	1.04	1.04		1.04			1.04		
Initial Bse:			156		135		125			145		
User Adj:			1.00		1.00		1.00			1.00		
PHF Adj:			1.00		1.00		1.00			1.00		
PHF Volume:			156	509	135		125	31		145		
Reduct Vol: Reduced Vol:			0 156	0 509	0 135	0 156	0 125		0	0 145	-	
PCE Adj:	1.00 1.00		1.00		1.00		1.00			1.00		
MLF Adj:			1.00		1.00		1.00			1.00		
FinalVolume:			156		135		125	31		145		
Saturation F	low Module	e:										
Sat/Lane:	1600 1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	1600	
Adjustment:			1.00	1.00	1.00	1.00	1.00		1.00	1.00	1.00	
Lanes:			1.00		1.00		0.80			1.00		
Final Sat.:			1600					320		1600		
					!			- {				
Capacity Ana			0.10	0 22	0.00	0 10	0 10	0 10	0.05	A 00	0.14	
Vol/Sat: Crit Moves:	0.03 0.2	0.22		0.3Z	0.08	0.10 ****	0.10	0.10	0.05	0.09	0.14 ****	
**************************************		******			******		*****	******	*****	*****		

Agoura Business Center North Development Agreement

Existing

Morning Peak Hour

Level Of Service Computation Report

2000 HCM Unsignalized Method (Base Volume Alternative)

Intersection #6 Clareton Drive (NS) at Canwood Street (EW)

Average Delay (sec/veh): 3.5 Worst Case Level Of Service: B[13.4] ******

Movement:	North Bound South Boun L T R L T -					– R	L ·	- т	- R	L - T - R			
Control: Rights:	Stop Sign Include			St	Stop Sign Include 0 0 1! 0 0						Uncontrolled Include		
Lanes:													
												!	
	0	0	0	55	0	39	128	271	0	0	65	83	
Growth Adj:	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	
Initial Bse:	0	0	0	57	0	40	133	281	0	0	67	86	
User Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	
PHF Volume:	0	0	0	57	0	40	133	281	0	0	67	86	
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0	
FinalVolume:	0	0	0	57	0	40	133	281	0	0	67	86	
Critical Gap	Modu	le:											
Critical Gp::	KXXXX	XXXX	XXXXX	6.4	6.5	6.2	4.1	XXXX	XXXXX	XXXXX	xxxx	XXXXX	
FollowUpTim::					4.0	3.3			XXXXX				
Capacity Modu	le:												
Cnflict Vol:	XXXX	XXXX	XXXXX	658	658	111	154	XXXX	XXXXX	XXXX	XXXX	XXXXX	
Potent Cap.:	XXXX	XXXX	XXXXX	432	387	948			XXXXX		XXXX	XXXXX	
Move Cap.:				399	348	948			XXXXX		XXXX	XXXXX	
Volume/Cap:					0.00	0.04			XXXX			XXXX	
	,												
Level Of Ser	vice I	Module	e:										
2Way95thQ:							0.3	XXXX	XXXXX	XXXX	XXXX	XXXXX	
Control Del:									XXXXX				
LOS by Move:						*	A	*	*	*	*	*	
Movement:			- RT	LT ·	- LTR		\mathbf{LT}	- LTR	- RT	LT ·	- LTR	- RT	
Shared Cap.:				XXXX		XXXXX	XXXX	XXXX	XXXXX	XXXX	XXXX	XXXXX	
SharedQueue:	xxxxx	XXXX	XXXXX	XXXXX	0.7	XXXXX	0.3	XXXX	XXXXX	XXXXX	XXXX	XXXXX	
Shrd ConDel:						XXXXX	7.8	XXXX	XXXXX			XXXXX	
Shared LOS:	*		*	*	В	*	A	*	*	*	*	*	
ApproachDel:	X	XXXXX			13.4		X	xxxxx		x	xxxx		
ApproachLOS:		*						*			*		
*****									*****	*****	* * * * *	*****	
Note: Queue reported is the number of cars per lane.													

Agoura Business Center North Development Agreement Existing Evening Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #6 Clareton Drive (NS) at Canwood Street (EW) Average Delay (sec/veh): 8.6 Worst Case Level Of Service: C[19.4] ************* Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:Stop SignStop SignUncontrolledUncontrolledRights:IncludeIncludeIncludeIncludeLanes:0000100010 Volume Module: Base Vol:0010402281511350018492Growth Adj:1.041.041.041.041.041.041.041.041.041.04

 Initial Bse:
 0
 0
 108
 0
 237
 157
 140
 0
 0
 191
 96

 User Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00<

 PHF Volume:
 0
 0
 108
 0
 237
 157
 140
 0
 0
 191
 96

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 191
 96

 FinalVolume:
 0
 0
 108
 0
 237
 157
 140
 0
 0
 191
 96

 -----||-----||------|| Critical Gap Module: Critical Gp:xxxxx xxxx xxxx 6.4 6.5 6.2 4.1 xxxx xxxxx xxxx xxxx xxxx FollowUpTim:xxxxx xxxx xxxx 3.5 4.0 3.3 2.2 xxxx xxxxx xxxx xxxx xxxx xxxx Capacity Module: 692 692 239 287 xxxx xxxxx xxxx xxxx xxxx Cnflict Vol: xxxx xxxx xxxx Potent Cap.: xxxx xxxx xxxxx 413 370 805 1287 xxxx xxxxx xxxx xxxx xxxx xxxx Move Cap.: xxxx xxxx xxxx 370 320 805 1287 xxxx xxxxx xxxx xxxx xxxx Volume/Cap: xxxx xxxx xxxx 0.29 0.00 0.29 0.12 xxxx xxxx xxxx xxxx xxxx -----!!----!! Level Of Service Module: LOS by Move: * * * * * * * * * * * * * * * Movement: LT - LTR - RT SharedQueue:xxxxx xxxx xxxxx xxxxx 3.8 xxxxx 0.4 xxxx xxxxx xxxxx xxxx xxxx Shrd ConDel:xxxxx xxxx xxxxx 19.4 xxxxx 8.2 xxxx xxxxx xxxxx xxxx xxxxx Shared LOS: * * * * C * A * * * * * 19.4 xxxxxx ApproachDel: xxxxxx XXXXXX ApproachLOS: С Note: Queue reported is the number of cars per lane.

Agoura Business Center North Development Agreement

Existing Morning Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) ******* Intersection #10 Derry Avenue (NS) at Canwood Street (EW) ****** Average Delay (sec/veh): 2.4 Worst Case Level Of Service: B[11.4] ***** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - RControl:Stop SignStop SignUncontrolledRights:IncludeIncludeIncludeLanes:0001001 Volume Module:

 Volume Module:

 Base Vol:
 0
 0
 28
 0
 29
 94
 231
 0
 0
 109
 86

 Growth Adj:
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 Critical Gap Module: Critical Gp:xxxxx xxxx xxxxx 6.4 xxxx 6.2 4.1 xxxx xxxxx xxxxx xxxx xxxxx Capacity Module: Cnflict Vol: xxxx xxxx xxxx 593 xxxx 158 202 xxxx xxxxx xxxx xxxx xxxx Potent Cap.: XXXX XXXX XXXXX 472 XXXX 893 1381 XXXX XXXXX XXXX XXXX XXXX Move Cap.: xxxx xxxx xxxx 446 xxxx 893 1381 xxxx xxxxx xxxx xxxx xxxx Volume/Cap: XXXX XXXX XXXX 0.07 XXXX 0.03 0.07 XXXX XXXX XXXX XXXX XXXX Level Of Service Module: 2Way95thQ: xxxx xxxx xxxx 0.2 xxxx 0.1 0.2 xxxx xxxx xxxx xxxx xxxx Control Del:xxxxx xxxx xxxxx 13.6 xxxx 9.2 7.8 xxxx xxxxx xxxxx xxxxx xxxxx LOS by Move: * * * B * A A * * * * * Movement: LT - LTR - RT

 Shared LOS:
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 <td ApproachDel: xxxxxx ApproachLOS: * ApproachLOS: В Note: Queue reported is the number of cars per lane. *************

Default Scenario Mon Feb 6, 2012 16:48:06 Page 11-1 Agoura Business Center North Development Agreement Existing Evening Peak Hour ______ Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #10 Derry Avenue (NS) at Canwood Street (EW) Average Delay (sec/veh): 5.7 Worst Case Level Of Service: B[12.1] ****** Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - R Control:Stop SignStop SignUncontrolledUncontrolledRights:IncludeIncludeIncludeIncludeLanes:0000100010 -----!|-----||------|| Volume Module: Base Vol: 0 0 0 120 0 132 102 136 0 0 120 63

 Initial Bse:
 0
 0
 125
 0
 137
 106
 141
 0
 0
 125
 65

 User Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00<

 PHF Volume:
 0
 0
 125
 0
 137
 106
 141
 0
 0
 125
 65

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 125
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 65
 -----||-----||------|| Critical Gap Module: Critical Gp:xxxxx xxxx xxxx 6.4 xxxx 6.2 4.1 xxxx xxxxx xxxx xxxx xxxx FollowUpTim:xxxxx xxxx xxxx 3.5 xxxx 3.3 2.2 xxxx xxxxx xxxx xxxx xxxx Capacity Module: Cnflict Vol: xxxx xxxx 510 xxxx 157 190 xxxx xxxx xxxx xxxx xxxx Potent Cap.: xxxx xxxx 527 xxxx 893 1396 xxxx xxxx xxxx xxxx xxxx Move Cap.: xxxx xxxx 496 xxxx 893 1396 xxxx xxxx xxxx xxxx xxxx Volume/Cap: xxxx xxxx xxxx 0.25 xxxx 0.15 0.08 xxxx xxxx xxxx xxxx xxxx Level Of Service Module: 2Way95thQ: xxxx xxxx xxxx 1.0 xxxx 0.5 0.2 xxxx xxxx xxxx xxxx xxxx Control Del:xxxxx xxxxx xxxxx 14.7 xxxx 9.8 7.8 xxxx xxxxx xxxxx xxxxx xxxxx LOS by Move: * * * B * A A * * * * * Movement: LT - LTR - RT Shared LOS: * * * * * * * * * * * * * * 12.1 B ***** ApproachDel: xxxxxx ApproachLOS: * XXXXXX * * Note: Queue reported is the number of cars per lane.

Agoura Business Center North Development Agreement

Existing

Morning Peak Hour

Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) *********************** Intersection #11 Colodny Drive (NS) at Canwood Street (EW) ***** Average Delay (sec/veh): 2.0 Worst Case Level Of Service: B[11.2] ***** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - RControl:Stop SignStop SignUncontrolledRights:IncludeIncludeIncludeLanes:0000 Volume Module: Base Vol: 0 0 0 33 0 17 45 198 0 0 148 10

 Growth Adj:
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04</td -----!!-----!!------!! Critical Gap Module: Critical Gp:xxxxx xxxx xxxxx 6.4 6.5 6.2 4.1 xxxx xxxxx xxxxx xxxxx xxxxx FollowUpTim:xxxxx xxxx xxxxx 3.5 4.0 3.3 2.2 xxxx xxxxx xxxxx xxxxx xxxxx Capacity Module: Cnflict Vol: xxxx xxxx xxxx 458 458 159 164 xxxx xxxxx xxxx xxxx xxxx Potent Cap.: XXXX XXXX 565 502 892 1427 XXXX XXXXX XXXX XXXX XXXXX Move Cap.: xxxx xxxx xxxx 551 486 892 1427 xxxx xxxxx xxxx xxxx xxxx Volume/Cap: xxxx xxxx xxxx 0.06 0.00 0.02 0.03 xxxx xxxx xxxx xxxx xxxx Level Of Service Module: LOS by Move: * * * * * * * A * * * * * LT - LTR - RT Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT Shrd ConDel:xxxxx xxxx xxxxx xxxxx 11.2 xxxxx xxxxx xxxxx xxxxx xxxxx xxxxx

 Shared LOS:
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 <td ApproachLOS: в Note: Queue reported is the number of cars per lane.

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

Default Scenario Mon Feb 6, 2012 16:48:06 Page 12-1 Agoura Business Center North Development Agreement Existing Evening Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #11 Colodny Drive (NS) at Canwood Street (EW) Average Delay (sec/veh): 1.4 Worst Case Level Of Service: B[10.4] ****** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - RControl:Stop SignStop SignUncontrolledRights:IncludeIncludeIncludeLanes:0000 Volume Module: Base Vol: 0 0 0 14 0 28 35 239 0 0 161 15 Initial Bse:0015029362480016716User Adj:1.001.001.001.001.001.001.001.001.001.00PHF Adj:1.001.001.001.001.001.001.001.001.001.00

 PHF Volume:
 0
 0
 15
 0
 29
 36
 248
 0
 0
 167
 16

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 16
 16

 FinalVolume:
 0
 0
 0
 15
 0
 29
 36
 248
 0
 0
 167
 16 Critical Gap Module: Critical Gp:xxxxx xxxx xxxx 6.4 6.5 6.2 4.1 xxxx xxxxx xxxx xxxx xxxx FollowUpTim:xxxx xxxx xxxx 3.5 4.0 3.3 2.2 xxxx xxxxx xxxx xxxx xxxx Capacity Module:

 Cnflict Vol: xxxx xxxx
 496
 496
 175
 183 xxxx xxxx
 xxxx xxxx xxxx

 Potent Cap.: xxxx xxxx
 537
 478
 874
 1405 xxxx xxxx
 xxxx xxxx xxxx

 Move Cap.: xxxx xxxx
 526
 466
 874
 1405 xxxx xxxx
 xxxx xxxx xxxx

 Volume/Cap: xxxx xxxx
 0.03
 0.00
 0.03
 0.03
 xxxx xxx
 xxxx xxx

 _____/ Level Of Service Module: LOS by Move: * * * * * * * * * * * * * * Movement: LT - LTR - RT Shared LOS:**</h</th>*< ApproachLOS: * Note: Queue reported is the number of cars per lane. ***********

Default Scenario Mon Feb 6, 2012 16:47:42 Page 13-1 Agoura Business Center North Development Agreement Existing Morning Peak Hour Level Of Service Computation Report 2000 HCM 4-Way Stop Method (Base Volume Alternative) ***** Intersection #12 Chesbro Road/Canwood Street (NS) at Driver Avenue/Palo Comado C Cycle (sec): 0 Critical Vol./Cap.(X): 0.423 Loss Time (sec):0 (Y+R=4.0 sec)Average Delay (sec/veh):Optimal Cycle:0Level Of Service: 10.7 B ****************** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R
 Control:
 Stop Sign
 <th Volume Module: Base Vol: 5 1 112 41 3 7 9 255 3 193 135 38 Initial Bse: 5 1 116 43 3 7 9 265 3 200 140 39

 PHF Volume:
 5
 1
 116
 43
 3
 7
 9
 265
 3
 200
 140
 39

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0

 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00

 FinalVolume:
 5
 1
 116
 43
 3
 7
 9
 265
 3
 200
 140
 39
 Saturation Flow Module: Adjustment:1.001.001.001.001.001.001.001.001.00Lanes:0.830.171.000.800.060.140.030.971.001.000.780.22 Final Sat.: 425 85 608 420 31 72 22 626 736 610 535 150 Capacity Analysis Module: Vol/Sat: 0.01 0.01 0.19 0.10 0.10 0.10 0.42 0.42 0.00 0.33 0.26 0.26 **** ****

 Delay/Veh:
 9.4
 9.3
 10.0
 10.0
 11.9
 11.9
 7.4
 11.2
 9.6
 9.6

 Delay Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.04
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00 Crit Moves: **** **** Delay Adj: ApprAdjDel: 1.00 1.00 1.00 1.00 9.3 A 10.0 11.8 10.4 LOS by Appr: Α В B AllWayAvgQ: 0.0 0.0 0.2 0.1 0.1 0.1 0.7 0.7 0.0 0.5 0.3 0.3 Note: Queue reported is the number of cars per lane.

Agoura Business Center North Development Agreement Existing Evening Peak Hour _____ Level Of Service Computation Report 2000 HCM 4-Way Stop Method (Base Volume Alternative) ********** Intersection #12 Chesbro Road/Canwood Street (NS) at Driver Avenue/Palo Comado C ************* Cycle (sec): 0 Critical Vol./Cap.(X): 0.725 15.7 Loss Time (sec):0 (Y+R=4.0 sec)Average Delay (sec/veh):Optimal Cycle:0Level Of Service: ************** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - RControl:Stop SignStop SignStop SignRights:IncludeIncludeIncludeMin. Green:00000Lanes:010001 -----!!-----+!!--------!! Volume Module: Base Vol: 11 5 252 27 6 9 11 177 12 112 387 50 Initial Bse: 11 5 262 28 6 9 11 184 12 116 402 52

 PHF Volume:
 11
 5
 262
 28
 6
 9
 11
 184
 12
 116
 402
 52

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0

 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 11 5 262 28 6 9 11 184 12 116 402 52 Saturation Flow Module: Lanes: 0.69 0.31 1.00 0.65 0.14 0.21 0.06 0.94 1.00 1.00 0.89 0.11 Final Sat.: 339 154 581 299 66 100 33 523 619 562 554 72 Capacity Analysis Module: Vol/Sat: 0.03 0.03 0.45 0.09 0.09 0.09 0.35 0.35 0.02 0.21 0.72 0.72 Crit Moves: **** **** **** ****

 Delay/Veh:
 9.8
 9.8
 12.8
 10.6
 10.6
 12.0
 12.0
 8.3
 10.5
 21.2
 21.2

 Delay Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00</t

 ApproachDel:
 12.6
 10.6
 11.8
 19.0

 Delay Adj:
 1.00
 1.00
 1.00
 1.00

 ApprAdjDel:
 12.6
 10.6
 11.8
 19.0

 LOS by Appr:
 B
 B
 C

 AllWayAvgQ:
 0.0
 0.7
 0.1
 0.1
 0.5
 0.0
 0.2
 2.2

 2.2 ***** Note: Queue reported is the number of cars per lane.

Default Scenario Mon Feb 6, 2012 16:48:06 Page 13-1

Default Scenario Mon Feb 6, 2012 16:47:42 Page 14-1 Agoura Business Center North Development Agreement Existing Morning Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #13 Palo Comado Canyon Road (NS) at SR-101 Freeway NB Ramps (EW) Average Delay (sec/veh): 7.9 Worst Case Level Of Service: C[17.6] *********** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:UncontrolledUncontrolledStop SignStop SignRights:IncludeIncludeIncludeIncludeLanes:0 1 0 0 0 0 0 1 0 1 0 0 0 0 0 1 0 0 0 1 Volume Module: Base Vol: 56 141 0 0 328 101 0 0 231 0 234

 Initial Bse:
 58
 146
 0
 0
 340
 105
 0
 0
 240
 0
 243

 User Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00<

 PHF Volume:
 58
 146
 0
 0
 340
 105
 0
 0
 240
 0
 243

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 243
 0
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 243
 -----!!-----!!-----!!/------!!------!! Critical Gap Module: Critical Gp: 4.1 xxxx xxxxx xxxxx xxxx xxxxx xxxxx xxxx 6.4 xxxx 6.2 3.3 -----!|-----! Capacity Module:

 Cnflict Vol:
 445 xxxx xxxxx
 xxxx xxxx xxxx
 xxxx xxxx
 656 xxxx
 146

 Potent Cap.:
 1126 xxxx xxxx
 xxxx xxxx
 xxxx xxxx
 434 xxxx
 906

 Move Cap.:
 1126 xxxx xxxx
 xxxx xxxx
 xxxx xxxx
 416 xxxx
 906

 Volume/Cap:
 0.05 xxxx xxxx
 xxxx xxxx
 xxxx xxxx
 xxxx xxxx
 0.58 xxxx
 0.27

 Level Of Service Module: LOS by Move: A * * * * * * * * * C * B Movement: LT - LTR - RT

 Shared LOS:
 A
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 C
 *
 *
 *
 C
 *
 *
 *
 *
 C
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 <td ApproachLOS: * Note: Queue reported is the number of cars per lane.

Default Scenario Mon Feb 6, 2012 16:48:06 Page 14-1 _____ Agoura Business Center North Development Agreement Existing Evening Peak Hour _____ _____ _____ Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) ***** Intersection #13 Palo Comado Canyon Road (NS) at SR-101 Freeway NB Ramps (EW) Average Delay (sec/veh): 55.7 Worst Case Level Of Service: F[167.3] Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - R Control:UncontrolledUncontrolledStop SignStop SignRights:IncludeIncludeIncludeIncludeLanes:0 1 0 0 0 0 0 1 0 1 0 0 0 0 0 1 0 0 0 1 Volume Module: 0 220 0 268 264 255 0 0 378 126 0 0 Base Vol: Initial Bse: 274 265 0 0 392 131 0 0 0 228 0 278

 PHF Volume:
 274
 265
 0
 0
 392
 131
 0
 0
 0
 228
 0
 278

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 Critical Gap Module: 6.2 Capacity Module: 265 779 Move Cap.: 1054 xxxx xxxx xxxx xxxx xxxx xxxx xxxx 143 xxxx 779 Volume/Cap: 0.26 xxxx xxxx xxxx xxxx xxxx xxxx xxxx 1.60 xxxx 0.36 -----!|-----||------|| Level Of Service Module: 1.6 LOS by Move: A * * * * * * * * * * F * B LT - LTR - RT Movement: न ApproachLOS:

Note: Queue reported is the number of cars per lane.

Default Scenario Mon Feb 6, 2012 16:47:42 Page 15-1 Agoura Business Center North Development Agreement Existing Morning Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #14 Palo Comado Canyon Road (NS) at Chesebro Road (EW) Average Delay (sec/veh): 2.3 Worst Case Level Of Service: B[10.8] Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R -----!!-----! Control:UncontrolledUncontrolledStop SignRights:IncludeIncludeIncludeLanes:0 1 0 0 0 0 0 1 0 1 1 0 0 0 1 0 0 0 0 Volume Module:

 Volume Module:

 Base Vol:
 20
 80
 0
 140
 360
 120
 0
 20
 0
 0

 Growth Adj:
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 1.04
 Critical Gap Module: Critical Gp: 4.1 xxxx xxxxx xxxxx xxxxx 6.4 xxxx 6.2 xxxxx xxxx xxxx -----!|-----! Capacity Module: Cnflict Vol: 519 xxxx xxxxx xxxx xxxx xxxx 270 xxxx 145 xxxx xxxx xxxxx Potent Cap.: 1057 XXXX XXXXX XXXX XXXXX 724 XXXX 907 XXXX XXXX XXXXX Move Cap.: 1057 XXXX XXXXX XXXXX XXXXX 713 XXXX 907 XXXX XXXX XXXX Volume/Cap: 0.02 xxxx xxxx xxxx xxxx 0.17 xxxx 0.02 xxxx xxxx xxxx Level Of Service Module: 2Way95thQ: 0.1 xxxx xxxxx xxxx xxxxx 0.6 xxxx 0.1 xxxx xxxx xxxx LOS by Move: A * * * * * B * A * * * Movement: LT - LTR - RT Shared LOS: A * * * * * * * * * * * * * ***** 10.8 ApproachDel: xxxxxx xxxxxx * ApproachLOS: В

Note: Queue reported is the number of cars per lane.

Default Scenario Mon Feb 6, 2012 16:48:06 Page 15-1 Agoura Business Center North Development Agreement Existing Evening Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #14 Palo Comado Canyon Road (NS) at Chesebro Road (EW) ******* Average Delay (sec/veh): 3.4 Worst Case Level Of Service: B[14.0] Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R -----!|-----!|------!| Control:UncontrolledUncontrolledStop SignRights:IncludeIncludeIncludeLanes:0 1 0 0 0 0 0 1 0 1 1 0 0 0 1 0 0 0 0 Volume Module: Base Vol: 30 170 0 0 200 380 190 0 40 0 0 0 Initial Bse: 31 176 0 0 208 394 197 0 42 0 0 0 PHF Volume:3117600208394197042000Reduct Vol:00000000000FinalVolume:311760208394197042000 0 0 Critical Gap Module: _____| Capacity Module:
 Cnflict Vol:
 602 xxxx xxxxx
 xxxx xxxx xxxx
 446 xxxx
 208 xxxx xxxx xxxx xxxx

 Potent Cap.:
 985 xxxx xxxxx
 xxxx xxxx
 573 xxxx
 838 xxxx xxxx xxxx

 Move Cap.:
 985 xxxx xxxx
 xxxx xxxx
 559 xxxx
 838 xxxx xxxx xxxx

 Volume/Cap:
 0.03 xxxx xxxx
 xxxx xxxx
 0.35 xxxx
 0.05
 Level Of Service Module: 2Way95thQ: 0.1 xxxx xxxx xxxx xxxx xxxx 1.6 xxxx 0.2 xxxx xxxx xxxx Control Del: 8.8 xxxx xxxxx xxxxx xxxx xxxx 14.9 xxxx 9.5 xxxxx xxxx xxxx LOS by Move: A * * * * * B * A * * * Movement: LT - LTR - RT
 Shared LOS:
 A
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 ApproachLOS: * в Note: Queue reported is the number of cars per lane.

Default Scena	ario		MO	n reb	6, 20	012 16:4	17:42			1	Page 1	16-1
	Agou	ura Bu	siness		Exist	-	-	ent Ag	greemen			·
				Morr	iing i	Peak Hou						
****		HCM 4	-Way S	top Me	ethod	Computat (Base V	Jolume	e Âlte	ernativ			
Intersection	#15 £	SR-101	Freew	ay SB	Ramps	5 (NS) a	at Dor	rothy	Drive	(EW)		
Cycle (sec):			0			Critica						763
Loss Time (se	ec):		0 (Y+R	=4.0 s	sec)	Average	e Dela	av (se	ec/veh)	:	1	
Optimal Cycle	e:		0			Level (Of Ser	rvice	:			C
Approach:	Not	rth Bo	und	Sou	ith Bo	ound	Ea	ast Bo	ound	We	est Bo	ound
Movement:	L ·	- т	– R	L -	- т	– R	L -	- т	– R	L ·	- т	– R
Control:						ign 1de						
Rights: Min. Green:												1de 0
Lanes:			0 0			0 1			0 1			-
Volume Module												
Base Vol:	90	330	30	50	130	70	90	60		20	10	40
Growth Adj:	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04	1.04
Initial Bse:		343	31		135	73	93	62	73	21	10	42
User Adj:			1.00		1.00	1.00		1.00			1.00	
PHF Adj:			1.00		1.00	1.00		1.00			1.00	
PHF Volume:		343	31	52		73	93		73	21		42
Reduct Vol: Reduced Vol:			0 31	0	135	0 73	0 93		0 73	0 21	0 10	0 42
PCE Adj:			1.00		1.00	1.00		1.00			1.00	
MLF Adj:			1.00		1.00	1.00		1.00			1.00	
FinalVolume:		343	31		135	73	93		73	21		42
Saturation F												
Adjustment:				1 00	1 00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Lanes:			0.07									
Final Sat.:	122	449	41	156	405	643	295	197	569	138	69	276
Capacity Ana				0 00	0 00	0 11	0 20	0 20	0 1 0	0 15	0 15	0 1 5
Vol/Sat:	0.76	0.76		0.33			U.32 ****		0.13	0.15 ****	0.15	0.15
Crit Moves:	24.2	24.3	24.3		11.8			12.4	9.4		10.7	10.7
Delay/Veh: Delay Adj:		24.3	1.00		1.00	8.7 1.00		12.4 1.00	1.00		1.00	1.00
AdjDel/Veh:		24.3	24.3		11.8	8.7		12.4	9.4		10.7	10.7
LOS by Move:	21.5 C		21.0 C	в		A	В	B	A	B	В	В
ApproachDel:	0	24.3	Ũ	-	10.9			11.5			10.7	-
Delay Adj:		1.00			1.00			1.00			1.00	
ApprAdjDel:		24.3			10.9			11.5			10.7	
LOS by Appr:		С			В			В			В	
AllWayAvgQ:	2.6		2.6	0.4		0.1	0.4		0.1	0.1	0.1	0.1
**********									******	****	****	******
Note: Queue									*****	****	* * * * *	******

Default Scenario Mon Feb 6, 2012 16:48:06 Page 16-1 _____ _____ Agoura Business Center North Development Agreement Existing Evening Peak Hour ____ _____ Level Of Service Computation Report 2000 HCM 4-Way Stop Method (Base Volume Alternative) Intersection #15 SR-101 Freeway SB Ramps (NS) at Dorothy Drive (EW) Cycle (sec): 0 Critical Vol./Cap.(X): 0.729 Loss Time (sec):0 (Y+R=4.0 sec)Average Delay (sec/veh):Optimal Cycle:0Level Of Service: 16.0 С Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:Stop SignStop SignStop SignStop SignRights:IncludeIncludeIncludeIncludeMin. Green:000000 0 Lanes: 0 0 1! 0 0 0 1 0 0 1 0 1 0 0 1 0 0 1! 0 0 -----!!-----!!-----!!-----!! Volume Module: Base Vol: 50 310 70 40 80 70 100 60 60 20 70 20 Initial Bse: 52 322 73 42 83 73 104 62 62 21 73 21

 PHF Volume:
 52
 322
 73
 42
 83
 73
 104
 62
 62
 21
 73
 21

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 52 322 73 42 83 73 104 62 62 21 73 21 Saturation Flow Module:

 Adjustment:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00</td Capacity Analysis Module: Vol/Sat: 0.73 0.73 0.73 0.23 0.23 0.12 0.33 0.33 0.11 0.23 0.23 0.23

 Crit Moves:

 Delay/Veh:
 22.0
 22.0
 10.8
 10.8
 8.8
 12.5
 12.5
 9.1
 11.4
 11.4
 11.4

 Delay/Veh:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 LOS by Move: C C C B B A B B A B B ApproachDel: 22.0 Delay Adj: 1.00 ApprAdjDel: 22.0 10.1 11.6 11.41.00 1.00 1.00 ApprAdjDel: 22.0 LOS by Appr: C 10.1 11.6 11.4 в B R AllwayAvgQ: 2.2 2.2 2.2 0.3 0.3 0.1 0.4 0.4 0.1 0.2 0.2 0.2 Note: Queue reported is the number of cars per lane.

Opening Year (2022) Without Project

Default Scenario Mon Feb 6, 2012 17:19:28 Page 2-1 Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour _____ Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) Intersection #1 Kanan Road (NS) at Thousand Oaks Boulevard (EW) Cycle (sec):100Critical Vol./Cap.(X):Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: 0.777 XXXXXX Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:ProtectedProtectedProtectedProtectedRights:IncludeIncludeIncludeIncludeMin. Green:000000Lanes:10201201 -----!!----!!-----!! Volume Module: Base Vol: 110 720 90 110 1240 100 90 70 120 190 100 90 Initial Bse: 123 805 101 123 1387 112 101 78 134 213 112 101
 User Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 PHF Volume: 123 805 101 123 1387 112 101 78 134 213 112 101 Reduct Vol: 0 0 0 0 0 0 0 0 0 0 0 0 0 Reduced Vol: 123 805 101 123 1387 112 101 78 134 213 112 101
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 123 805 101 123 1387 112 101 78 134 213 112 101 -----!----! Saturation Flow Module: Adjustment:1.00</td -----|----|}

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

Vol/Sat: 0.08 0.25 0.06 0.08 0.43 0.07 0.03 0.02 0.08 0.13 0.03 0.06

**** ****

**** ****

Capacity Analysis Module:

Crit Moves:

Default Scenario Mon Feb 6, 2012 17:19:58 Page 2-1												
Agoura Business Center North Development Agreement Opening Year (2022) Without Project Evening Peak Hour												
Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)												
ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) ************************************												
<pre>************************************</pre>												

Approach:	Nort	h Bo	ound	Soi	ith Bo	ound	Ea	ist Bo	ound	We	est Bo	ound
Movement:												
						1			!			1
Control:												
Rights:]	[nclu	ıde		Inclu	ıde		Inclu	ıde		Inclu	ude
Min. Green:	0	0	0	0	0	0	0	0	0	0	0	0
Lanes:			0 1			0 1						0 1
	1											1
Volume Module	e:											
Base Vol:	290 1	L290	290	120	920	150	300	240	170	130	170	120
Growth Adj:	1.12 1	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12
Initial Bse:	324 1	1443	324	134	1029	168	336	268	190	145	190	134
User Adj:	1.00 1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00 1	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume:	324 1	1443	324	134	1029	168	336	268	190	145	190	134
Reduct Vol:	0	0	0	0	0	0	0	0	0	0	0	0
Reduced Vol:	324 1	1443	324	134	1029	168	336		190	145	190	134
PCE Adj:	1.00 1	1.00	1.00	1.00	1.00	1.00		1.00	1.00		1.00	1.00
MLF Adj:			1.00		1.00	1.00		1.00	1.00		1.00	1.00
FinalVolume:			324		1029			268	190		190	134
			'									
Saturation F												
Sat/Lane:	1600 1		1600		1600			1600	1600		1600	1600
Adjustment:			1.00		1.00			1.00	1.00		1.00	1.00
Lanes:	1.00 2		1.00		2.00			2.00			2.00	1.00
Final Sat.:			1600		3200			3200			3200	
Vol/Sat:				0 00	0 22	0.10	0 1 2	0 00	0.12	0 00	0.06	0.08
Crit Moves:		U.45	0.20	****	0.32	0.10	0.12	0.08	U.1Z ****	****	0.06	0.08
Crit Moves:			******		* * * * *	******	*****	*****			* * * * * *	******

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

Vol/Sat: 0.00 0.33 0.25 0.02 0.42 0.00 0.00 0.00 0.00 0.09 0.00 0.03

* * * *

0.02

Capacity Analysis Module:

OvlAdjV/S:

Crit Moves: ****

Default Scena			Мо	n Feb	6, 20)12 17:	19:58				Page	3-1
Agoura Business Center North Development Agreement Opening Year (2022) Without Project Evening Peak Hour												
Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) ************************************												
<pre>Intersection #2 Kanan Road (NS) at Canwood Street (EW) ************************************</pre>												
Cycle (sec): Loss Time (se Optimal Cycle	ec): e:	10 10	0 5 (Y+R 0	=0.0 s	sec)	Critic Averag Level	al Vol e Dela Of Ser	L./Cap ay (se cvice:	o.(X): ec/veh)	:	0.7 xxxx	257 XXX C
Approach: Movement:	г -	- т	– R	ь -	- т	– R	L -	- т	- R	L -	est Bo • T	– R
Control: Rights: Min. Green: Lanes:	P1 0 0 (rotect Inclu 0) 2	ed de 0 0 1	P1 0 2 (rotect Inclu 0 0 3	ed ide 0 0 0	P1 0 0 0	otect Inclu 0 0 0	ed ide 0 0 0	Pr 0 2 0	otect Ovl 0	ed 0 0 1
Volume Module Base Vol:	e:	1590	230		1310	اا 0	0	0	 0	330	0	180
Growth Adj: Initial Bse: User Adj: PHF Adj:	1.12	1.12 1779 1.00	1.12 257 1.00 1.00	1.12 67 1.00	1.12 1465 1.00 1.00	1.12 0 1.00 1.00	1.12 0 1.00	1.12 0 1.00 1.00		1.12 369 1.00 1.00	1.12 0 1.00	1.12 201 1.00 1.00
PHF Volume: Reduct Vol: Reduced Vol: PCE Adj:	0 0		257 0 257 1.00	0 67	1465 0 1465 1.00	0 0 0 1.00	0 0 1.00	0 0 1.00	0 0 0 1.00	369 0 369 1.00	0 0 0 1.00	201 0 201 1.00
MLF Adj: FinalVolume: OvlAdjVol:	0	1779	1.00 257	67		1.00 0	0	·	1.00 0	1.00 369	0	1.00 201 164
Saturation F. Sat/Lane:	1600	1600	1600		1600			1600				1600
Adjustment: Lanes: Final Sat.:	0.00 0	2.00 3200	1.00 1.00 1600	2.00 2880	1.00 3.00 4800	0.00 0	0.00	1.00 0.00 0		2.00 2880	0.00	1.00 1.00 1600
Capacity Anal Vol/Sat: OvlAdjV/S: Crit Moves:	lysis 0.00	Modul	e:							•		
****	* * * * *	* * * * * *	*****	*****	*****	******	*****	*****	******	*****	*****	*****

D C 1	~	
Default	SCen	ario

Deradit Scena		мо 	n reb	0, 20		19:20			rage	4-1		
Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour												
Level Of Service Computation Report												
ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)												

Intersection *********	******	* * * * * * * * *	*****	*****	******	****	*****	******	* * * * * * * * *	* * * * * * *		
Cycle (sec): Loss Time (se Optimal Cycle	ec): : : * * * * * * * * *	100 5 (Y+R 100	=0.0 s	3ec)	Critic Averag Level	al Vo e Dela Of Se *****	L./Cap ay (se cvice: *****	o.(X): ec/veh) : *******	0. : xxx	721 xxx C *******		
Approach: Movement:	L - 2	r – R	г -	- T	– R	Ŀ	- т	- R	L – T	– R		
Control: Rights: Min. Green: Lanes:	Prote O 0 1 0	ected v1 0 0 2 0 1	P1 0 0 (rotect Inclu 0 3	ed de 0 1	Sp: 0 1 0	lit Ph Inclu 0) 0	nase nde 0 0 1	Split P Incl 0 0 1 1 0	hase ude 0 0 2		
						!			1	!		
Volume Module Base Vol: Growth Adj:	38 7			1605 1.12			0 1.12		540 34			
Initial Bse:				1795	$\begin{array}{c} 1.12 \\ 544 \end{array}$	1.12 54			1.12 1.12 604 38			
User Adj:				1.00	1.00		1.00		1.00 1.00			
PHF Adj:				1.00	1.00		1.00		1.00 1.00			
PHF Volume:	43 83	19 182	0	1795	544	54	0		604 38			
Reduct Vol:	0	0 0	0	0		0			0 0	0		
Reduced Vol:	43 8	19 182	0	1795	544	54	0	112	604 38	521		
PCE Adj:	1.00 1.0	00 1.00	1.00	1.00	1.00		1.00		1.00 1.00	1.00		
MLF Adj:				1.00	1.00		1.00		1.00 1.00			
FinalVolume:	43 8		0	1795	544	54	0	112	604 38	521		
OvlAdjVol:		0										
Saturation Fl					·							
			1600	1600	1600	1600	1600	1600	1600 1600	1600		
Adjustment:				1.00			1.00		1.00 1.00			
Lanes:				3.00			0.00		1.88 0.12	-		
Final Sat.:			0.00		1600		0		3010 190			
					{					}		
Capacity Anal Vol/Sat:	0.03 0.1	26 0.11	0.00	0.37	0.34	0.03	0.00	0.07	0.20 0.20	0.16		
OvlAdjV/S: Crit Moves:	****	0.00		****				****				
*********	******	******	*****	*****	*****	* * * * *	*****	******	*******	******		

Default Scena				n Feb	6, 20	012 17:					Page	4-1
Agoura Business Center North Development Agreement Opening Year (2022) Without Project Evening Peak Hour												
Level Of Service Computation Report												
ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)												
Intersection	#3 Ka	anan H	Road (N	S) at	SR-1	01 Free	way NE	3 Ram	os/Canw	ood St	reet	(EW)
Cycle (sec):			00			Critic						359
Loss Time (se	ec):		5 (Y+R	=0.0 s	sec)					:		
Optimal Cycle			00		,	Level				-		D
****				*****	****					*****	****	******
Approach:	Noi	rth Bo	ound	Sou	ith B	ound			ound		est Bo	ound
Movement:			– R			– R			- R		- т	
Control:	Pi	rotect	ted	Pı	otec	ted	Sp	lit Pl	nase	Spl	lit Pl	nase
Rights:		Ovl			TUCT	ude		TUCTI	uae		Inclu	ude
Min. Green:	0	0	-	0	-	-	-	0		0		0
Lanes:	1 (_	0 1			0 1		-	0 1		-	0 2
Volume Module		1015	150	~	0.01	510	5.2	0	1 70	0.00	60	742
Base Vol:		1215	458	0	981	518	53	0		263	63	743
Growth Adj:		1.12	1.12		1.12	1.12		1.12	1.12		1.12	1.12
Initial Bse:		1359	512		1097	579	59	0	199	294	70	831
User Adj:		1.00	1.00		1.00	1.00		1.00	1.00		1.00	1.00
PHF Adj:		1.00	1.00		1.00	1.00		1.00	1.00		1.00	1.00
PHF Volume:	-	1359	512	•	1097	579	59	0	199	294		831
Reduct Vol:	0		0	0	1007	0	0 59	0	0	0	0 70	0
Reduced Vol:		1359	512		1097	579		•	199	294		831
PCE Adj:		1.00	1.00		1.00	$1.00 \\ 1.00$		$1.00 \\ 1.00$	$1.00 \\ 1.00$		1.00	$1.00 \\ 1.00$
MLF Adj:		1.00 1359	$1.00 \\ 512$		1.00	579	1.00 59	1.00	199	294	1.00	831
FinalVolume: OvlAdjVol:	8	1328	51Z 97	0	1097	5/9	59	0	199	294	70	831
	I 			1			1			1		
Saturation F			-	1		1	I		1	1		
Sat/Lane:		1600		1600	1600	1600	1600	1600	1600	1600	1600	1600
Adjustment:		1.00	1.00		1.00			1.00	1.00		1.00	1.00
Lanes:		2.00	1.00		3.00			0.00	1.00		0.39	2.00
Final Sat.:		3200			4800		1600			2582		3200
	1			I								
Capacity Ana	-											
Vol/Sat:	0.00	0.42		0.00	0.23	0.36	0.04	0.00	0.12	0.11	0.11	0.26
OvlAdjV/S:			0.06									
Crit Moves:		* * * *		****					****			****
*******	*****	****	******	*****	* * * * *	******	*****	****	******	*****	* * * * *	******

Default Scenario Mon Feb 6, 2012 17:19:28 Page 5-1 Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour _____ Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) Intersection #4 Kanan Road (NS) at SR-101 Freeway SB Ramps/Roadside Drive (EW) ****** Cycle (sec): 100 Critical Vol./Cap.(X): 0.780 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX C Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:ProtectedProtectedSplit PhaseSplit PhaseRights:IncludeOvlIncludeIncludeMin. Green:00000 Lanes: 0 0 2 1 0 1 0 2 0 1 1 0 1 1 0 0 0 1 Volume Module: Base Vol: 0 493 30 124 1071 950 345 133 253 21 0 94 Initial Bse: 0 551 34 139 1198 1063 386 149 283 23 0 105

 PHF Volume:
 0
 551
 34
 139
 1198
 1063
 386
 149
 283
 23
 0
 105

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0

 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 790 OvlAdiVol: Saturation Flow Module: Sat/Lane:16001.00< -----!---! Capacity Analysis Module: Vol/Sat: 0.00 0.12 0.12 0.09 0.37 0.66 0.17 0.17 0.17 0.01 0.00 0.07 OvlAdjV/S: 0.49 Crit Moves: **** **** **** ****

_____ Agoura Business Center North Development Agreement Opening Year (2022) Without Project Evening Peak Hour _____ Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative) Intersection #4 Kanan Road (NS) at SR-101 Freeway SB Ramps/Roadside Drive (EW) ***** Cycle (sec):100Critical Vol./Cap.(X):Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: 0.843 XXXXXX D ********* Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:ProtectedProtectedSplit PhaseSplit PhaseRights:IncludeOvlIncludeIncludeMin. Green:000000 Lanes: 0 0 2 1 0 1 0 2 0 1 1 0 1! 0 1 1 0 0 0 1 Volume Module: Base Vol: 0 970 23 179 680 521 369 84 572 19 0 282 Initial Bse: 0 1085 26 200 761 583 413 94 640 21 0 315

 PHF Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0 FinalVolume: 0 1085 26 200 761 583 413 94 640 21 0 315 201 OvlAdjVol: Saturation Flow Module: Sat/Lane:1600< Capacity Analysis Module: Vol/sat: 0.00 0.23 0.23 0.13 0.24 0.36 0.24 0.24 0.24 0.01 0.00 0.20 OvlAdjV/S: 0.13 Crit Moves: **** **** 0.13 * * * * ****

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

Default Scena	ario		Мо	n Feb	6, 20	012 17:	19:28				Page	6-1
Default Scenario Mon Feb 6, 2012 17:19:28 Page 6-1 Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour												
Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)												
Intersection #5 Kanan Road (NS) at Agoura Road (EW)												
************************************											735 xxx C	
Approach:	Nor	th B	ound	So	uth Bo	ound	E	ast B	ound	We	est B	ound
Movement:	L -	·Т	– R	Ŀ	- т	– R	L ·	- т	— R	Ŀ	- Т	- R
Control: Rights:	Pr	otec	i ted ude 0	P	rotect	ted		Permi	tted	1	Permi	tted
Min. Green:												
Lanes:			1 0									
Volume Module			'	'		'	ţ		'	1		1
Base Vol:				110	700	220	90	90	90	50	60	100
Growth Adj:					1.12	1.12		1.12			1.12	1.12
Initial Bse:		470	22	123		246	101			56		
User Adj:			1.00		1.00	1.00		1.00			1.00	
PHF Adj:			1.00		1.00	1.00		1.00			1.00	
PHF Volume:				123		246		101		56		112
Reduct Vol:				0	0	0	0	-	-	0	-	0
Reduced Vol:					783	246			101	56		
PCE Adj:			1.00		1.00	1.00		1.00			1.00	
MLF Adj: FinalVolume:			1.00 22		1.00 783	$1.00 \\ 246$		1.00		1.00	1.00	1.00
Saturation F				1			1			I		
Sat/Lane:				1600	1600	1600	1600	1600	1600	1600	1600	1600
Adjustment:					1.00	1.00		1.00			1.00	
2	1.00				1.00			0.50			1.00	
Final Sat.:					1600			800			1600	
Capacity Ana												
Vol/Sat:	-			0.08			0.06		0.13		0.04	0.07
Crit Moves:	****				****			****		****		
* * * * * * * * * * * * *	* * * * * *	****	******	*****	****	*****	*****	****	* * * * * * *	*****	* * * * *	*****

Default Scen	ario	Mon ∃eb	6, 20	12 17:2	L9:58				Page	6-1		
Agoura Business Center North Development Agreement Opening Year (2022) Without Project Evening Peak Hour												
Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)												
ICU I(Loss as Cycle Length %) Method (Base Volume Alternative)												
Intersection #5 Kanan Road (NS) at Agoura Road (EW)												
Cycle (sec):	100			Critica	al Vol	L./Cay	o.(X);		0.	686		
Loss Time (s	ec): 5 e: 100	(Y+R=0.0 :	sec)	Average	e Dela	iy (se	ec/veh)	:	XXX	XXX		
Optimal Cycl	e: 100			Level (Of Ser	rvice	:			В		

	North Boun											
Movement:	L - T -	R L ·	- Т	- R	. L	- Т	- R	, L -	- T	- R		
Control:	Protected	! D·	rotect		ا	Dormi	ted	1	Dormi	++ ed		
Rights:	Include	. <u>.</u>	Incl	ide	1	Inclu	ude	1	Incl	ude		
Min. Green:		0 0	111010	0	0	0	0	0	1.001	0		
Lanes:		0 1	0 1	0 1	1 () 0	1 0	1 () 1	0 1		
								1				
Volume Modul	e:											
Base Vol:	50 650	20 150	490	130	150	120	30	70	140	220		
Growth Adj:			1.12	1.12		1.12			1.12			
Initial Bse:		22 168		145	168				157			
User Adj:	1.00 1.00 1		1.00	1.00		1.00	-		1.00			
PHF Adj:	1.00 1.00 1		1.00	1.00		1.00			1.00			
PHF Volume: Reduct Vol:			548 0	145 0		134 0			157 0			
Reduced Vol:				145			34		157			
PCE Adj:			1.00	1.00			1.00		1.00			
MLF Adj:			1.00	1.00		1.00			1.00			
FinalVolume:	56 727	22 168	548		168	134	34	78	157	246		
					1		!	! -				
Saturation F	low Module:											
	1600 1600 1		1600			1600			1600			
	1.00 1.00 1		1.00	1.00		1.00			1.00			
	1.00 1.94 (1.00				0.20		1.00			
	1600 3104			1600			320		1600			
	lysis Module:											
	0.03 0.23 (0.34	0.09	0.10	0.10	0.10	0.05	0.10	0.15		
Crit Moves:	****		****	0.05	****	0.10	0.10	0.05	0.10	****		
	*****	*****	*****	******	*****	* * * * *	******	*****	****	*****		

Default Scenario Mon Feb 6, 2012 17:19:58 Page 7-1 _____ Agoura Business Center North Development Agreement Opening Year (2022) Without Project Evening Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #6 Clareton Drive (NS) at Canwood Street (EW) Average Delay (sec/veh): 10.1 Worst Case Level Of Service: C[23.4] Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - RStop SignStop SignUncontrolledUncontrolledIncludeIncludeIncludeInclude0000010000010001 Control: Rights: Lanes: Volume Module: Base Vol: 0 0 0 104 0 228 151 135 0 0 184 92 Initial Bse: 0 0 0 116 0 255 169 151 0 0 206 103

 PHF Volume:
 0
 0
 0
 116
 0
 255
 169
 151
 0
 0
 206
 103

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 Critical Gap Module: Critical Gp:xxxxx xxxx xxxx 6.4 6.5 6.2 4.1 xxxx xxxxx xxxx xxxx xxxx xxxx FollowUpTim:xxxx xxxx xxxx 3.5 4.0 3.3 2.2 xxxx xxxxx xxxx xxxx xxxx Capacity Module:

 Cnflict Vol: xxxx xxxx
 746
 746
 257
 309 xxxx xxxxx
 xxxx xxxx xxxx

 Potent Cap.: xxxx xxxx
 384
 344
 786
 1263 xxxx xxxx
 xxxx xxxx xxxx

 Move Cap.: xxxx xxxx
 340
 293
 786
 1263 xxxx xxxx
 xxxx xxxx xxxx

 Volume/Cap: xxxx xxxx
 0.34
 0.00
 0.32
 0.13
 xxxx xxx xxx xxx xxx

 -----||-----||------||-------|| Level Of Service Module: 2Way95thQ: xxxx xxxx xxxx xxxx xxxx xxxx 0.5 xxxx xxxxx xxxx xxxx xxxx 8.3 XXXX XXXXX XXXXX XXXXX XXXXX Control Del:xxxxx xxxx xxxxx xxxxx xxxx LOS by Move: * * * * * * A * * * * * Movement: LT - LTR - RT SharedOueue:xxxxx xxxx xxxxx xxxxx 4.9 xxxxx 0.5 xxxx xxxxx xxxxx xxxx xxxx Shrd ConDel:xxxxx xxxx xxxxx 23.4 xxxxx 8.3 xxxx xxxxx xxxxx xxxx xxxx Shared LOS: * * * * C * ApproachDel: xxxxxx 23.4 A * * * * xxxxxx xxxxxx ****** ApproachLOS: * С * * Note: Queue reported is the number of cars per lane.

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

MITIG8 - Defa	ault S	Scenar	io Tu	e Feb	7,20	012 13:	43:33				Page	1-1
Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour - With Improvements												
Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Base Volume Alternative)												

Cycle (sec): 100 Critical Vol./Cap.(X): 0.309 Loss Time (sec): 5 (Y+R=0.0 sec) Average Delay (sec/veh): xxxxxx Optimal Cycle: 100 Level Of Service: A												
Approach:	Nor	th Bo	ound	Sou	ith Bo	ound	Ea	ast Bo	ound	We	st Bo	ound
Movement:	L -	т	- R	L -	- Т	- R	L.	- Т	- R	L -	т	- R
Control: Rights: Min. Green:	е 0	Permit Inclu 0	ted Ide 0	и 0	ermit? Inclu 0	ted 1de 0	1 0	Permit Inclu 0	tted 1de 0	P 0	ermit Inclu 0	ted de 0
Lanes:			0 0									1 0
Volume Module Base Vol:	e:				0		-		0	0		83
Growth Adj: Initial Bse:	1.12 0	1.12 0	1.12 0	1.12 62	1.12 0	1.12 44	1.12 143	1.12 303	1.12 0	1.12	1.12 73	1.12 93
User Adj: PHF Adj: PHF Volume:			1.00 1.00 0		1.00 1.00 0	$\begin{array}{r}1.00\\1.00\\44\end{array}$	1.00	1.00 1.00 303	1.00	1.00 1.00 0	1.00	
Reduct Vol: Reduced Vol:	0 0	0 0	0 0	0 62	0 0	0	143			0 0	0 73	
PCE Adj: MLF Adj: FinalVolume:	1.00 0	1.00 0	1.00 0	1.00	1.00	1.00	1.00 143	1.00 303	1.00 0	1.00	1.00 73	1.00 93
Saturation F												
Sat/Lane:				1600	1600	1600	1600	1600	1600	1600	1600	1600
Adjustment:									1.00			
Lanes: Final Sat.:	0	0	0	936	0	664	1600	1.00 1600	0	0	703	897
Capacity Ana												
Crit Moves:	*****	*****	******	*****	*****	****	****	*****	******	*****	**** ****	0.10

MITIG8 - Default Scenario Tue Feb 7, 2012 13:43:46

Agours Ducinoog Contex Newth Development Development												
Agoura Business Center North Development Agreement Opening Year (2022) Without Project												
						With						
TOU						Computa						
LCU]	L(LOSS *****	s as (:усте п ******	engtn *****	ে (ে ১) M∈	etnoa (Base v ******	'01UM	e Alter	native ******	e) * * * * * *	******
Intersection												
**********										* * * * * *	****	******
Cycle (sec):		10	00			Critic	al Vol	/Caj	o.(X):		0.5	581
Loss Time (se	ec):		5 (Y+R	.=0.0 s	sec)	Averag	e Dela	ıy (se	ec/veh)	:	XXXX	xxx
Optimal Cycle	Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):xxxx:al Cycle:100Level Of Service:											А

Approach:												ound
Movement:	- 11 	- T	- R	ь -	- ·I'	- R	ь- 1	· T	- R	ட்ட-	- T	- R
Control:	F	Permit	ted	11	Permit	ted	F	Permii	ted	1	Permi	l
Rights:	-	Inclu	ide	-	Inclu	ide	-	Inclu	ıde	-	Inclu	lde
Min. Green:	0	0	0			0				0	0	0
Lanes:	0 0	0 (0 0	0 () 1!	0 0	1 C) 1	0 0	0 (1 0
Volume Module												
Base Vol:									0			
Growth Adj:									1.12			
Initial Bse:		-	0	116	-	255		151	0	1 00	206	103
User Adj: PHF Adj:	1.00		$1.00 \\ 1.00$		1.00	-	$1.00 \\ 1.00$		1.00 1.00		1.00	
2	0		1.00	116	1.00	255		151	1.00	1.00		103
Reduct Vol:	ŏ		0	0	-		0	0	_	Ő	200	
Reduced Vol:			Ő	116		-	-	151	-	Ő	-	-
PCE Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
FinalVolume:		0	0			255		151	0	0		103
	•			!								
Saturation F						1 6 9 9			1 5 6 6		1	
Sat/Lane:		1600			1600						1600	
Adjustment:			$1.00 \\ 0.00$		1.00		1.00				1.00	
Lanes: Fínal Sat.:			0.00			$0.69 \\ 1099$			0.00	0.00		0.33 533
Capacity Anal						I				1 I		1
Vol/Sat:	-			0.07	0.00	0.23	0.11	0.09	0.00	0.00	0.19	0.19
Crit Moves:						* * * *	****				****	
******	* * * * * *	*****	*****	****	*****	******	*****	****	******	* * * * *	****	* * * * * * *

Default Scenario Mon Feb 6, 2012 17:19:28 Page 11-1 Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #10 Derry Avenue (NS) at Canwood Street (EW) Average Delay (sec/veh): 2.4 Worst Case Level Of Service: B[11.7] ****** Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - R L - T - R Control:Stop SignStop SignUncontrolledRights:IncludeIncludeIncludeLanes:0001001 Volume Module:

 Volume Module:

 Base Vol:
 0
 0
 28
 0
 29
 94
 231
 0
 0
 109
 86

 Growth Adj:
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.01
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 Critical Gap Module: Critical Gp:xxxxx xxxx xxxx 6.4 xxxx 6.2 4.1 xxxx xxxxx xxxx xxxx xxxx FollowUpTim:xxxxx xxxx xxxx 3.5 xxxx 3.3 2.2 xxxx xxxxx xxxx xxxx xxxx Capacity Module: Cnflict Vol: xxxx xxxx xxxx 639 xxxx 170 218 xxxx xxxxx xxxx xxxx xxxx Potent Cap.: xxxx xxxx xxxx 444 xxxx 879 1363 xxxx xxxx xxxx xxxx xxxx Move Cap.: XXXX XXXX XXXXX 417 XXXX 879 1363 XXXX XXXXX XXXX XXXX XXXX Volume/Cap: xxxx xxxx xxxx 0.08 xxxx 0.04 0.08 xxxx xxxx xxxx xxxx xxxx Level Of Service Module: 2Way95thO: XXXX XXXX XXXXX 0.2 XXXX 0.1 0.3 XXXX XXXXX XXXX XXXX XXXXX Control Del:xxxxx xxxx xxxx 14.3 xxxx 9.3 7.9 xxxx xxxxx xxxxx xxxx xxxx LOS by Move: * * * B * A A * * * * * Movement: LT - LTR - RT

 Shared LOS:
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 <td * * ApproachLOS: в Note: Queue reported is the number of cars per lane.

Traffix 7.9.0215 (c) 2008 Dowling Assoc. Licensed to KUNZMAN ASSOC, ORANGE CA

...

Default Scenario Mon Feb 6, 2012 17:19:58 Page 11-1 Agoura Business Center North Development Agreement Opening Year (2022) Without Project Evening Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #10 Derry Avenue (NS) at Canwood Street (EW) Average Delay (sec/veh): 5.9 Worst Case Level Of Service: B[12.7] ***** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:Stop SignStop SignUncontrolledRights:IncludeIncludeIncludeLanes:0001001 Volume Module:
 Base Vol:
 0
 0
 120
 0
 132
 102
 136
 0
 0
 120
 63

 Growth Adj:
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12

 Growth Adj:
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12</td Critical Gap Module: Critical Gp:xxxxx xxxx xxxx 6.4 xxxx 6.2 4.1 xxxx xxxxx xxxx xxxx xxxx FollowUpTim:xxxxx xxxx xxxx 3.5 xxxx 3.3 2.2 xxxx xxxx xxxx xxxx xxxx Capacity Module: Cnflict Vol: xxxx xxxx xxxxx 550 xxxx 169 205 xxxx xxxxx xxxx xxxx xxxx Potent Cap.: xxxx xxxx xxxx 500 xxxx 880 1379 xxxx xxxxx xxxx xxxx xxxx Move Cap.: xxxx xxxx xxxx 468 xxxx 880 1379 xxxx xxxxx xxxx xxxx xxxx Volume/Cap: xxxx xxxx xxxx 0.29 xxxx 0.17 0.08 xxxx xxxx xxxx xxxx xxxx Level Of Service Module: 2Way95thQ: xxxx xxxx xxxx 1.2 xxxx 0.6 0.3 xxxx xxxxx xxxx xxxx xxxx
 Shared LOS:
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 ******* Note: Queue reported is the number of cars per lane.

Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour ______ _____ Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) ***** Intersection #11 Colodny Drive (NS) at Canwood Street (EW) Average Delay (sec/veh): 2.0 Worst Case Level Of Service: B[11.5] Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R -----!!----!!-----!! Control:Stop SignStop SignUncontrolledUncontrolledRights:IncludeIncludeIncludeIncludeLanes:00001000010 Volume Module: Base Vol: 0 0 0 33 0 17 45 198 0 148 10 0 Initial Bse: 0 0 0 37 0 19 50 221 0 0 166 11

 PHF Volume:
 0
 0
 37
 0
 19
 50
 221
 0
 0
 166
 11

 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 10
 0
 166
 11
 11
 11
 11
 11
 11
 11
 11
 11
 11
 11
 11
 11
 11
 11
 11
 -----!!-----!!------!!-------!! Critical Gap Module: Critical Gp:xxxxx xxxx xxxx 6.4 6.5 6.2 4.1 xxxx xxxxx xxxxx xxxx xxxx FollowUpTim:xxxxx xxxx xxxx 3.5 4.0 3.3 2.2 xxxx xxxxx xxxx xxxx xxxx Capacity Module:

 Cnflict Vol: xxxx xxxx
 493
 493
 171
 177 xxxx xxxx
 xxxx xxxx xxxx

 Potent Cap.: xxxx xxxx
 539
 480
 878
 1412 xxxx xxxx
 xxxx xxxx xxxx

 Move Cap.: xxxx xxxx xxxx
 524
 463
 878
 1412 xxxx xxxx
 xxxx xxxx xxxx

 Volume/Cap: xxxx xxxx
 xxxx xxxx
 0.07
 0.00
 0.02
 0.04
 xxxx xxxx xxxx
 xxxx xxxx

 Level Of Service Module: LT - LTR - RT Movement:
 Shared LOS:
 *
 *
 *
 B
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 <th ApproachDel: xxxxx ApproachLOS: * * В Note: Queue reported is the number of cars per lane. *************

Default Scenario Mon Feb 6, 2012 17:19:28 Page 12-1

*

_____ Agoura Business Center North Development Agreement Opening Year (2022) Without Project

Evening Peak Hour

_____ Level Of Service Computation Report

2000 HCM Unsignalized Method (Base Volume Alternative)

Intersection #11 Colodny Drive (NS) at Canwood Street (EW)

Average Delay												
Approach:	Nor	th Bo	ound	Soi	ith Bo	ound	Ea	ast Bo	ound	Ŵe	est Bo	ound
Movement:												
Control:												
Rights:		Inclu	ıde		Inclu	ıde		Inclu	ıde		Inclu	ıde
Lanes:	0 0	0 0	0 0	0 () 1!	0 0	1 () 1	0 0	0 (0 0	1 0
Volume Module	:											
Base Vol:	0	0	0	14	0	28	35	239	0	0	161	15
Growth Adj:	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12
Initial Bse:				16	0	31	39	267	0	0	180	17
User Adj:	1.00	1.00	1.00	1.00		1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00		1.00	1.00	1.00	1.00	1.00
PHE Volume:	0	Ω	0	16	0	31	39	267	0	0	180	17
Reduct Vol: FinalVolume:	0	0	0	0	0	0	0	0	0	0	0	0
FinalVolume:	0	0	0	16	0	31	39	267	0	0	180	17
Critical Gap I												
Critical Gp:x:												
FollowUpTim:x												
Capacity Modu							1					
Cnflict Vol: :	xxxx	xxxx	xxxxx	534	534	188	197	xxxx	xxxxx	XXXX	xxxx	XXXXX
Potent Cap.: :	xxxx	xxxx	xxxxx	510	455	859	1388	xxxx	xxxxx	xxxx	xxxx	XXXXX
Move Cap.:	xxxx	XXXX	xxxxx	499	442	859	1388	xxxx	xxxxx	XXXX	XXXX	XXXXX
Volume/Cap:					0.00	0.04			XXXX		XXXX	
										!		
Level Of Serv	ice N	4odul	e:									
2Way95thQ:												
Control Del:x. LOS by Move:	XXXX	XXXX	XXXXX	XXXXX	XXXX	XXXXX	7.7	XXXX	XXXXX	XXXXX	XXXX	XXXXX
LOS by Move:	*	*	*	*	*	*	А	*	*	*	*	*
Movement:												
Shared Cap.:												
SharedQueue:x												
Shrd ConDel:x	XXXX	XXXX	XXXXX	XXXXX	10.6	XXXXX	XXXXX	XXXX	XXXXX	XXXXX	XXXX	XXXXX

Shared LOS:***</h> Note: Queue reported is the number of cars per lane.

Default Scenar	Default Scenario Mon Feb 6, 2012 17:19:28 Page 13-1										
	Agoura B		Cente Year Morn	r Nor (2022	th Deve) Witho eak Hou	elopme out Pr ir	ent Ag oject	reemen	t		
****	2000 HCM		f Serv top Me	rice C thod	omputat (Base V	tion F Volume	Report Alte	rnativ	e)		
Intersection #12 Chesbro Road/Canwood Street (NS) at Driver Avenue/Palo Comado C											
Cycle (sec): Loss Time (sec Optimal Cycle	Loss Time (sec):0 (Y+R=4.0 sec)Average Delay (sec/veh):11.2Optimal Cycle:0Level Of Service:B***********************************										
Approach: Movement:	L – T	– R	L -	т	– R	L -	- Т	– R	L -	- Т	– R
Control: Rights: Min. Green: Lanes:	Stop S Incl 0 0 0 1 0	ign ude 0 0 1	0 0 0 0	op Si Inclu 0 1!	gn de 0 0 0	St 0 0 1	top Si Inclu 0 1 0	.gn ide 0 0 1	St 0 1 (top Si Inclu 0 0	gn de 0 1 0
Volume Module Base Vol: Growth Adj: Initial Bse: User Adj: PHF Adj: PHF Volume: Reduct Vol: Reduced Vol: PCE Adj: MLF Adj: FinalVolume:	$\begin{array}{c} : \\ 5 & 1 \\ 1.12 & 1.12 \\ 6 & 1 \\ 1.00 & 1.00 \\ 1.00 & 1.00 \\ 6 & 1 \\ 0 & 0 \\ 6 & 1 \\ 1.00 & 1.00 \\ 1.00 & 1.00 \\ 6 & 1 \end{array}$	112 1.12 125 1.00 125 0 125 1.00 1.00 125	41 1.12 46 1.00 1.00 46 0 46 1.00 1.00 46	3 1.12 3 1.00 1.00 3 1.00 1.00 3	7 1.12 8 1.00 1.00 8 0 8 1.00 1.00 8	9 1.12 10 1.00 1.00 10 1.00 1.00 1.00 1.0	255 1.12 285 1.00 285 0 285 1.00 1.00 285	$ \begin{array}{r} 3\\ 1.12\\ 3\\ 1.00\\ 1.00\\ 3\\ 0\\ 3\\ 1.00\\ 1.00\\ 3\end{array} $	193 1.12 216 1.00 216 0 216 1.00 1.00 216	135 1.12 151 1.00 1.00 151 0 151 1.00 1.00 1.51	38 1.12 43 1.00 1.00 43 0 43 1.00 1.00 43
Saturation Fl Adjustment: Lanes: Final Sat.:	ow Module 1.00 1.00 0.83 0.17 416 83	1.00 1.00 592	1.00 0.80 409	1.00 0.06 30	1.00 0.14 70	1.00 0.03 22	1.00 0.97 615	1.00 1.00 720	1.00 1.00 601	1.00 0.78 525	1.00 0.22 148
Capacity Analysis Module: Vol/Sat: 0.01 0.01 0.21 0.11 0.11 0.11 0.46 0.46 0.00 0.36 0.29 0.29 Crit Moves: **** **** **** Delay/Veh: 9.5 9.5 9.7 10.2 10.2 10.2 12.7 12.7 7.5 11.7 9.9 9.9 Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00											
AllwayAvgg: 0.0 0.0 0.2 0.1 0.1 0.1 0.1 0.8 0.8 0.0 0.3 0.4 0.4 ************************************											

Default Scenar:	Default Scenario Mon Feb 6, 2012 17:19:58 Page 13-1										
2	Agoura Bu	siness pening	Cente Year	r Nor (2022	th Deve) Withd	elopme out Pr	ent Ag oject	reemen	t		
	1 000 HCM 4	evel Of -Way St	Serv	rice C thod	omputat (Base N	tion F Volume	eport Alte	rnativ	e)		
Intersection #:	Intersection #12 Chesbro Road/Canwood Street (NS) at Driver Avenue/Palo Comado C										
Cycle (sec):0Critical Vol./Cap.(X):0.798Loss Time (sec):0 (Y+R=4.0 sec)Average Delay (sec/veh):18.5Optimal Cycle:0Level Of Service:C***********************************											
Approach: Movement:	L - T	– R	L ~	Т	- R	L ~	- т	- R	L -	· T	– R
Control: Rights: Min. Green: Lanes:	Stop Si Inclu 0 0 0 1 0	gn ade 0 0 1	st 0 0 0	op Si Inclu 0 1!	gn de 0 0 0	St 0	cop Si Inclu 0 0	gn de 0 0 1	St 0 1 0	op Si Inclu 0) 0	gn de 0 1 0
	11 5 .12 1.12 12 6 .00 1.00 .00 1.00 12 6 .00 1.00 .00 1.00 .00 1.00 12 6 .00 1.00	252 1.12 282 1.00 1.00 282 0 282 1.00 1.00 282	27 1.12 30 1.00 1.00 30 1.00 1.00 30 	6 1.12 7 1.00 1.00 7 1.00 1.00 7	9 1.12 10 1.00 1.00 10 1.00 1.00 1.00 1.0	11 1.12 12 1.00 1.00 12 0 12 1.00 1.00 1.00 1.00 1.00 1.00	177 1.12 198 1.00 1.00 198 0 198 1.00 1.00 198	12 1.12 13 1.00 1.00 13 0 13 1.00 1.00 13 	112 1.12 125 1.00 1.00 125 1.00 1.00 1.00 1.25	387 1.12 433 1.00 1.00 433 0 433 1.00 1.00 433	50 1.12 56 1.00 1.00 56 0 56 1.00 1.00 56
Lanes: 0 Final Sat.:	.69 0.31 331 151	1.00 566	0.65 290	0.14 64	0.21 97	0.06 32	0.94 507	1.00 598	1.00 551	0.89 543	0.11 70
Capacity Analysis Module: Vol/Sat: 0.04 0.04 0.50 0.10 0.10 0.10 0.39 0.39 0.02 0.23 0.80 0.80 Crit Moves: **** **** belay/Veh: 10.0 10.0 14.0 11.0 11.0 11.0 12.9 12.9 8.5 10.9 26.7 26.7 Delay Adj: 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00											
AllWayAvgQ: 0.0 0.0 0.8 0.1 0.1 0.1 0.6 0.6 0.0 0.3 3.1 3.1 ************************************											

MITIG8 - Default Scenario Tue Feb 7, 2012 11:15:11 Page 1-1 _____ Agoura Business Center North Development Agreement Opening Year (2022) Without Project Morning Peak Hour Level Of Service Computation Report 2000 HCM Unsignalized Method (Base Volume Alternative) Intersection #13 Palo Comado Canyon Road (NS) at SR-101 Freeway NB Ramps (EW) Average Delay (sec/veh): 9.3 Worst Case Level Of Service: C[20.9] ***** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:UncontrolledUncontrolledStop SignStop SignRights:IncludeIncludeIncludeIncludeLanes:0 1 0 0 0 0 0 1 0 1 0 0 0 0 0 1 0 0 0 1 Volume Module: Base Vol: 56 141 0 0 328 101 0 0 0 231 0 234 Initial Bse:63158003671130002580262User Adj:1.001.001.001.001.001.001.001.001.001.00

 PHF Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 -----!!-----!!------!! Critical Gap Module: 6.2 3.3 Capacity Module:

 Cnflict Vol:
 480 xxxx xxxxx
 xxxx xxxx xxxxx
 xxxx xxxxx
 706 xxxx
 158

 Potent Cap.:
 1093 xxxx xxxxx
 xxxx xxxx
 xxxx xxxx
 xxxx xxxx
 405 xxxx
 893

 Move Cap.:
 1093 xxxx xxxx
 xxxx xxxx
 xxxx xxxx
 xxxx xxxx
 387 xxxx
 893

 Volume/Cap:
 0.06 xxxx
 xxxx xxxx
 xxxx xxxx
 xxxx
 xxxx
 0.67 xxxx
 0.29

 Level Of Service Module: LOS by Move: A * * * * * * * * * D * B Movement: LT - LTR - RT LT - LTR - RT LT - LTR - RT
 Shared LOS:
 A
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 *
 ApproachDel: xxxxx * ApproachLOS: * * C Note: Queue reported is the number of cars per lane. *************

MITIG8 - Defa	MITIG8 - Default Scenario Tue Feb 7, 2012 11:15:21 Page 1-1											
	Agoı		usiness Opening	y Year	(2022		nout Pi			nt		
2		ICM U	Level (nsignal	lized N	lethod	d (Base	e Volu	ne Alt	ternati		* * * * * *	*****
Intersection												
Average Delay (sec/veh):86.6Worst Case Level Of Service: F[262.7]***********************************												
Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R												
Control:UncontrolledUncontrolledStop SignStop SignRights:IncludeIncludeIncludeInclude										.gn ide		
Lanes:												
Base Vol:	264		0	0			0	-		220		268
Growth Adj:			1.12		1.12	1.12		1.12			1.12	1.12
Initial Bse:		285	0	0	423	141	0	0	0	246	0	300
	1.00		$1.00 \\ 1.00$		$1.00 \\ 1.00$	$1.00 \\ 1.00$		1.00	$1.00 \\ 1.00$		$1.00 \\ 1.00$	$1.00 \\ 1.00$
2	295	285	1.00	1.00	423	1.00	1.00	0.11	1.00	246	0.11	300
Reduct Vol:	0		-	0		141	0	-	0	240	0	0
FinalVolume:	295	285	0	0	423	141	0	0	0	246	Ő	300
Critical Gap												
Critical Gp:			xxxxx	xxxxx	xxxx	xxxxx	xxxxx	xxxx	xxxxx	б.4	xxxx	6.2
FollowUpTim:	2.2	XXXX	XXXXX	xxxxx	XXXX	xxxxx	XXXXX	XXXX	XXXXX		xxxx	3.3
Capacity Modu										1200		205
Cnflict Vol: Potent Cap.:						XXXXXX			XXXXX XXXXX		XXXX XXXX	285 759
Move Cap.:						XXXXX			XXXXX		XXXX	759
Volume/Cap:			XXXX			XXXX			XXXX		XXXX	0.40
Level Of Serv	vice N	Modul	e:									
2Way95thQ:												1.9
Control Del:				XXXXX					XXXXX		XXXX	12.8
LOS by Move:	A			*	*	*	*	*	*	F	*	В
Movement:			- RT			- RT		- LTR			- LTR	
Shared Cap.:									XXXXX			XXXXX
SharedQueue:			XXXXX									
Shrd ConDel: 10.0 xxxx xxxx												
ApproachDel: XXXXXX XXXXX XXXXX 262.7												
ApproachLOS:		*			*			*			F	

Note: Queue reported is the number of cars per lane.												

	MITIG8 - Default Scenario Tue Feb 7, 2012 13:44:15 Page 1-1									
		Opening	Year (202	2) Witl	velopment A nout Projec Improvemen	t				
ICU	l(Loss as			-	ation Report (Base Volum		tive)			
							* * * * * * * * * * * * * * *			
Intersection							B Ramps (EW)			
Cycle (sec):100Critical Vol./Cap.(X):0.480Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):xxxxxOptimal Cycle:100Level Of Service:A										
Approach: North Bound South Bound East Bound West Bound										
							L - T - R			
Control: Rights:	trol: Permitted Permitted Permitted Permitted									
Min. Green:							0 0 0			
Lanes:		0 0	0 0 1	0 1	0 0 0	0 0 1				
Base Vol:			0 328	101	0 0	0 2	231 0 234			
Growth Adj:			1.12 1.12				.12 1.12 1.12			
Initial Bse:			0 367		0 0	• -	258 0 262			
User Adj:			1.00 1.00				.00 1.00 1.00			
PHF Adj: PHF Volume:			1.00 1.00		1.00 1.00		.00 1.00 1.00 258 0 262			
Reduct Vol:		0 0	0 0			• •	0 0 0			
Reduced Vol:			0 367	-			258 0 262			
PCE Adj:		-	1.00 1.00				.00 1.00 1.00			
MLF Adj:			1.00 1.00	1.00	1.00 1.00		.00 1.00 1.00			
FinalVolume:	63 15	8 0	0 367	113	0 0	0 2	258 0 262			
	•									
Saturation F		÷ -	1 600 1 600	1						
Sat/Lane:			1600 1600				600 1600 1600			
Adjustment: Lanes:			1.00 1.00 0.00 1.00				.00 1.00 1.00 .00 0.00 1.00			
Final Sat.:			0.00 1.00		0.00 0.00		.00 0.00 1.00 600 0 1600			
Vol/Sat:	0.04 0.1		0.00 0.23	0.07	0.00 0.00		.16 0.00 0.16			
OTTC HOVED.	****		****				* * *			
* * * * * * * * * * * * * * * * * * * *										

MITIG8 - Defa	Page	1-1									
	-	Opening	Center Year (2 Peak Hou)22) Wit	hout Pro		it				
TCU	L(Loss as		f Service	+		port lume Alter	mative)				
*******	******	******	*******	*******	*******	*********	*******	*****			
<pre>Intersection #13 Palo Comado Canyon Road (NS) at SR-101 Freeway NB Ramps (EW) ************************************</pre>											
Cycle (sec):100Critical Vol./Cap.(X):0.686Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):xxxxxOptimal Cycle:100Level Of Service:B											

Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R											
			1	I – K	- L 	т - к l	L = T	- ĸ			
Control: Permitted Permitted Permitted Permitted											
Rights:		Include Include Include Include									
Min. Green:	0 (0 0	0	0 0	0	0 0		0			
Lanes:						0 0 0					
Volume Module:											
Base Vol:				78 126		0 0	220 0				
Growth Adj: Initial Bse:			$1.12 \ 1.0 \ 4$	L2 1.12 23 141		.12 1.12	1.12 1.12 246 0				
	1.00 1.00	-	1.00 1.		•	• •	1.00 1.00				
-	1.00 1.00		1.00 1.								
PHF Volume:				23 141		0 0	246 0				
Reduct Vol:			0		-	0 0	0 0				
Reduced Vol:	295 285	5 0	0 4	23 141	0	0 0	246 0	300			
2	1.00 1.00		1.00 1.	00 1.00	1.00 1	.00 1.00	1.00 1.00	1.00			
MLF Adj:			1.00 1.								
FinalVolume:			0 4	-	-	0 0	246 0				
Cotupotion D	•	•									
Saturation Fi Sat/Lane:			1600 16	00 1600	1600 1	600 1600	1600 1600	1600			
Adjustment:			1.0016								
Lanes:			0.00 1.								
Final Sat.:						0 0.00					
Capacity Analysis Module:											
Vol/Sat:		0.00	0.00 0.	26 0.09	0.00 0	.00 0.00	0.15 0.00	0.19			
Crit Moves: **** **** ****											

Default Scenario Mon Feb 6, 2012 17:19:28 Page 15-1												
	Agoı	C		y Year Morr	(2022 11ng E	?) With Peak Ho	nout Pr our	coject	greemer			
*****	2000 H	I ICM Ur	Level C nsignal)f Serv ized N	vice (Method	Computa 1 (Base	tion F Volum	Report ne Alt	: ternati	Lve)	*****	*****
Intersection *********											*****	******
Average Delay	/ (sec	c/veh)	:	2.3	*****	Worst	Case I	Level	Of Sei	cvice:	B[11	L.1] ******
Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - R L - T - R												
Control: Rights:	Und	contro Inclu	olled	Und	contro Inclu	olled nde	St	op Si Inclu	ign 1de	St	top Si Inclu	lgn 1de
Lanes:									0 1) 0 	
 Volume Module: Base Vol: 20 80 0 0 140 360 120 0 20 0 0 0												
Growth Adj: Initial Bse:	22	1.12 89	1.12 0	1.12 0	1.12	1.12	134	1.12	22	0	1.12	0
User Adj: PHF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
PHF Volume: Reduct Vol:	22 0		0 0	0	157 0	403 0	134 0	0	22 0	0	0	0
FinalVolume:	22	89	0	0	157	403	134	0	22	0	0	Ō
Critical Gap	Modu	le:										
Critical Gp: FollowUpTim:								XXXX XXXX	6.2 3.3	XXXXX XXXXX		
										[
Capacity Modu Cnflict Vol:		xxxx	xxxxx	xxxx	xxxx	xxxxx	291	xxxx	157	xxxx	xxxx	xxxxx
Potent Cap.:									894			XXXXX
Move Cap.: Volume/Cap:								XXXX XXXX				XXXXX XXXX
Level Of Ser							07	xxxx	0 1	xxxx		
2Way95thQ: Control Del:								XXXX		XXXXX		
LOS by Move:	A		*	*	*		В	*	A	*	*	*
Movement:	LT ·	- LTR	- RT	LT ·	- LTR	- RT	LT ·	- LTR	– RT	LT ·	- LTR	- RT
Shared Cap.:												XXXXX
SharedQueue:									XXXXX			
Shrd ConDel: Shared LOS:	8.6 A		* *	****	XXXX *	****	XXXXX *	XXXX *	****	*	XXXX *	*
ApproachDel:		xxxxx			xxxxx	~	<i>.</i>	11.1			xxxxx	
ApproachLOS:		*			*			В			*	
******									* * * * * *	******	* * * * *	******
	Note: Queue reported is the number of cars per lane.											

Default Scenario Mon Feb 6, 2012 17:19:58 Page 15-1												
	Agoi		usines: Openino	g Year	(2022		nout Pa	rojec	t	nt		
***	2000 1	HCM U	Level (nsignal	Lized I	Metho	d (Base	ation H e Volum	Repor me Al	t ternat:	ive)		*****
Intersection *********	#14	Palo (Comado	Canyo	n Road	d (NS)	at Ch	esebr	o Road	(EW)		
Average Delay	y (se	c/veh):	3.7		Worst	Case 1	Level	Of Se	rvice:	C[19	5.0]
Approach: North Bound South Bound East Bound West Bound Movement: L - T - R L - T - R L - T - R L - T - R												
Control: Rights: Lanes:	Uno	contro Inclu	olled ude	Un	contro Inclu	olled ude	S	top S Incl	ign	St		ign 1de
Volume Module												
Base Vol: Growth Adj: Initial Bse: User Adj: PHF Adj: PHF Volume:	30 1.12 34 1.00 1.00 34	1.12 190 1.00 1.00 190	0 1.12 0 1.00 1.00 0	1.12 0 1.00 1.00 0	1.12 224 1.00 1.00 224	1.12 425 1.00 1.00 425	213 1.00 1.00 213	1.12 0 1.00 1.00 0	45 1.00 1.00 45	1.12 0 1.00 1.00 0	1.12 0 1.00 1.00 0	1.12 0 1.00 1.00 0
Reduct Vol: FinalVolume:	34			0		425	0 213	0	0 45	0	0	-
Critical Gap Critical Gp: FollowUpTim:	Modu 4.1 2.2	le: xxxx xxxx	xxxxx xxxxx		**** ****	xxxxx xxxxx	6.4 3.5	xxxx xxxx	6.2 3.3	xxxxx xxxxx	**** ****	***** *****
Capacity Modu	le:											
Cnflict Vol: Potent Cap.: Move Cap.: Volume/Cap:	947 947 0.04	**** **** ****	xxxxx xxxxx xxxx	xxxx xxxx xxxx	xxxx xxxx xxxx	××××× ××××× ××××	548 532 0.40	×××× ×××× ××××	821 0.05	xxxx xxxx xxxx	×××× ×××× ××××	XXXXX XXXXX XXXXX XXXX
Level Of Serv	vice N	Modul	e:							11		1
2Way95thQ: Control Del: LOS by Move: Movement:	8.9 A LT	XXXX * - LTR	* * *	XXXXX t	×××× * - LTR	XXXXX + - RT	16.2 C LT		9.6 A - RT		XXXX * LTR	***** * - RT
Shared Cap.: SharedQueue: Shrd ConDel: Shared LOS:	0.1 8.9 A	xxxx xxxx *	xxxxx	***** *****	**** *		xxxxx	**** ****		***** *****	×××× ×××× *	
ApproachDel: ApproachLOS:		*****	* * * * * * *		*****	*****	******	15.0 C	*****		(XXXX *	

Default Scena	Default Scenario Mon Feb 6, 2012 17:19:28 Page 16-1										
	Agoura Bu	siness) pening	Cente Year Morr	er Nor (2022	th Dev) With Peak Hou	elopme out Pi	ent Aç roject	reemen :	t		
****	1 2000 HCM 4	level Of -Way St	f Serv top Me	vice C ethod	omputa (Base)	tion H Volume	Report e Alte	: ernativ	e)		
Intersection *********											*****
Cycle (sec):0Critical Vol./Cap.(X):0.839Loss Time (sec):0 (Y+R=4.0 sec)Average Delay (sec/veh):20.7Optimal Cycle:0Level Of Service:C											
Approach: Movement:	L – T	– R	ь -	- т	– R	г -	- Т	– R	L -	- T	- R
Control: Rights: Min. Green:	Stop Si Inclu 0 0	.gn ide 0	St 0	cop Si Inclu 0	.gn Ide 0	St 0	top Si Inclu 0	lgn ide 0	St 0	op Si Inclu 0	.gn ide 0
Lanes: Volume Module		0 0	0 1 1	L 0 	0 1	0	L 0	0 1 	0 () 1!	0 0
Base Vol:	90 330 1.12 1.12 101 369 1.00 1.00 1.00 1.00 101 369 0 0 101 369 1.00 1.00 1.00 1.00 1.00 1.00 1.01 369	30 1.12 34 1.00 1.00 34 0 34 1.00 1.00 34	50 1.12 56 1.00 1.00 56 1.00 1.00 56	130 1.12 145 1.00 1.00 145 1.00 1.00 1.00 1.45	70 1.12 78 1.00 1.00 78 0 78 1.00 1.00 78	90 1.12 101 1.00 1.00 101 1.00 1.00 1.00	60 1.12 67 1.00 1.00 67 1.00 1.00 67	70 1.12 78 1.00 1.00 78 0 78 1.00 1.00 78	20 1.12 22 1.00 1.00 22 0 22 1.00 1.00 22	10 1.12 11 1.00 1.00 11 0 11 1.00 1.00 1	40 1.12 45 1.00 1.00 45 0 45 1.00 1.00 45
Adjustment: Lanes: Final Sat.:	1.00 1.00 0.20 0.73	1.00 0.07	0.28	0.72	1.00	0.60	0.40	1.00	0.29		1.00 0.57 271
Capacity Analysis Module: Vol/Sat: 0.84 0.84 0.37 0.37 0.13 0.35 0.35 0.14 0.16 0.16 0.16 Crit Moves: **** **** **** **** **** **** Delay/Veh: 31.5 31.5 12.5 12.5 9.0 13.2 13.2 9.7 11.1 11.1 11.1 Delay/Veh: 31.5 31.5 12.5 12.5 9.0 13.2 13.2 9.7 11.1 11.1 11.1 Delay Adj: 1.00											
Note: Queue reported is the number of cars per lane.											

Default Scenario Mo	n Feb 6, 2012 17:19:58	Page 16-1							
Agoura Business Opening	Center North Development Agree Year (2022) Without Project Evening Peak Hour	ement							
Level O 2000 HCM 4-Way S	f Service Computation Report top Method (Base Volume Alterna	ative)							
Intersection #15 SR-101 Freew	ay SB Ramps (NS) at Dorothy Dri	ive (EW)							
Cycle (sec):0Loss Time (sec):0 (Y+ROptimal Cycle:0	**************************************	K): 0.802 veh): 18.9 C							
Movement: L - T - R	South Bound East Bound L - T - R L - T -	R L - T - R							
Control: Stop Sign Stop Sign Stop Sign Rights: Include Include Include									
Lanes: 0 0 1! 0 0	0 0 0 0 0 0 1 0 0 1 0 1 0 0	1 0 0 1! 0 0							
Volume Module:									
Base Vol: 50 310 70 Growth Adj: 1.12 1.12 1.12 Initial Bse: 56 347 78 User Adj: 1.00 1.00 1.00	45 89 78 112 67	60 20 70 20 .12 1.12 1.12 1.12 67 22 78 22 .00 1.00 1.00 1.00							
PHF Adj:1.001.00PHF Volume:56347Reduct Vol:00	1.00 1.00 1.00 1.00 1.00 1. 45 89 78 112 67	$\begin{array}{cccccccccccccccccccccccccccccccccccc$							
Reduced Vol:5634778PCE Adj:1.001.001.00MLF Adj:1.001.001.00	45 89 78 112 67 1.00 1.00 1.00 1.00 1.00 1.	67227822.001.001.001.00.001.001.001.00							
Adjustment:1.001.00Lanes:0.120.720.16Final Sat.:7043298	1.00 1.00 1.00 1.00 1 0.33 0.67 1.00 0.62 0.38 1 174 348 597 302 181 5	.00 0.18 0.64 0.18 560 87 303 87							
Capacity Analysis Module:	0.26 0.26 0.13 0.37 0.37 0.								
Delay/Veh: 27.7 27.7 27.7 Delay Adj: 1.00 1.00 1.00 AdjDel/Veh: 27.7 27.7 27.7	1.00 1.00 1.00 1.00 1.00 1.	9.412.012.012.0.001.001.001.009.412.012.012.0							
LOS by Move: D D D ApproachDel: 27.7 Delay Adj: 1.00 ApprAdjDel: 27.7 LOS by Appr: D	B B A B B 10.5 12.3 1.00 1.00 10.5 12.3 B B	A B B B 12.0 1.00 12.0 B							
AllWayAvgQ: 3.1 3.1 3.1 ***************************	******	0.1 0.3 0.3 0.3 ****							
Note: Queue reported is the number of cars per lane.									

Opening Year (2022) With "North" Project

Default Scenario Mon Feb 6)12 17:2		Page 3-1			
	Agoı			ar (20)22) V	th Deve Vith "No Peak Hou	elopme orth"	nt Ag			
		as Cy	cle Le	ngth 🖁	b) Met		uture	Volum	e Alte	rnative)	
*****										* * * * * * * * *	******
Intersection										* * * * * * * * * *	*****
Cycle (sec):		10				Critica					.781
Loss Time (sec): 5 (Y+R=0.0 sec) Average Delay (sec/veh): 5 Optimal Cycle: 100 Level Of Service: ************************************									: xx	C C	
Approach:North BoundSouth BoundEast BoundWest BoundMovement: $L - T - R$											
						!			1		
Control:	Control: Protected Protected Protected Protected										
Rights: Include Include Include Include											
Min. Green: Lanes:			0 1			0 1			0 1	+	
	1 (
Base Vol:	110	720	90	110	1240	100	90	70	120	190 10	90
Growth Adj:	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12	1.12 1.1	2 1.12
Initial Bse:	123	805	101	123	1387	112	101	78	134	213 11	
Added Vol:	0		0	0	-	0	0	0	2	-	0 0
PasserByVol:	0	0	0	0	0	0	0	0	0	_	0 0
Initial Fut:		806	101		1392	112	101	78	136	214 11	
User Adj:		1.00	1.00		1.00	$1.00 \\ 1.00$	$1.00 \\ 1.00$		$1.00 \\ 1.00$	1.00 1.0	
PHF Adj: PHF Volume:	123	1.00 806	$1.00 \\ 101$		1392	112	101	78	136	214 11	
Reduct Vol:	123		0		1352	0	0	0	150		0 0
Reduced Vol:	123	-	101	-	1392 [°]	112	101	78	136	214 11	
PCE Adj:		1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00 1.0	1.00
MLF Adj:	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00 1.0	0 1.00
FinalVolume:		806	101		1392	112	101	78	136	214 11	
				}							
Saturation Fl				1 6 0 0	1 (0 0	1 (0 0	1 (0 0	1 600	1.000	1000 100	1.000
Sat/Lane:		1600	1600		1600			1600	1600 1.00	1600 160	
5		1.00 2.00	$1.00 \\ 1.00$		1.00 2.00		2.00		1.00 1.00	1.00 1.0	
Final Sat.:		3200	1600		3200	1600		3200	1600	1600 320	
Capacity Anal	,										
Vol/Sat:	0.08	0.25		0.08	0.44	0.07	0.03	0.02	0.09	0.13 0.0	0.06
Crit Moves:	****				****				****	****	
*********	*****	*****	******	*****	* * * * *	* * * * * * *	*****	*****	*****	*******	******

Agoura Business Center North Development Agreement Opening Year (2022) With "North" Project Evening Peak Hour _____ Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Future Volume Alternative) Intersection #1 Kanan Road (NS) at Thousand Oaks Boulevard (EW) Cycle (sec): 100 Critical Vol./Cap.(X): 0.796 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX С ************ Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - RControl:ProtectedProtectedProtectedProtectedRights:IncludeIncludeIncludeIncludeMin. Green:000000Lanes:10201201 Volume Module: Base Vol:2901290290120920150300240170130170120Growth Adj:1.121.121.121.121.121.121.121.121.121.121.12

 Growth Adj:
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12</td Reduced Vol: 327 1448 325 134 1030 168 336 268 190 145 190 134
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 327 1448 325 134 1030 168 336 268 190 145 190 134 Saturation Flow Module: Final Sat.: 1600 3200 1600 1600 3200 1600 2880 3200 1600 1600 3200 1600 -----!!-----!!-----!! Capacity Analysis Module: Vol/Sat: 0.20 0.45 0.20 0.08 0.32 0.10 0.12 0.08 0.12 0.09 0.06 0.08 Crit Moves: **** **** ****

Agoura Business Center North Development Agreement Opening Year (2022) With "North" Project Morning Peak Hour Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Future Volume Alternative) Intersection #2 Kanan Road (NS) at Canwood Street (EW) ********** Cycle (sec): 100 Critical Vol./Cap.(X): 0.562 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX ***** Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R-----!|-----| Control:ProtectedProtectedProtectedProtectedRights:IncludeIncludeIncludeOvlMin. Green:000000Lanes:02012000 0 -----!!-----!!------!!------!! Volume Module: Base Vol: 0 940 360 50 1820 0 0 0 0 220 0 50

 Growth Adj:
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12
 1.12</td
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 0 1051 452 64 2036 0 0 0 0 252 0 57 OvlAdjVol: 21 Saturation Flow Module: Lanes: 0.00 2.00 1.00 2.00 3.00 0.00 0.00 0.00 0.00 2.00 0.00 1.00 Final Sat.: 0 3200 1600 2880 4800 0 0 0 0 2880 0 1600 Capacity Analysis Module: Vol/Sat: 0.00 0.33 0.28 0.02 0.42 0.00 0.00 0.00 0.00 0.09 0.00 0.04 OvlAdjV/S: 0.01 Crit Moves: **** **** **** ******

Default Scenario Mon Feb 6, 2012 17:21:03 Page 4-1 Agoura Business Center North Development Agreement Opening Year (2022) With "North" Project Evening Peak Hour _____ Level Of Service Computation Report ICU 1(Loss as Cycle Length %) Method (Future Volume Alternative) Intersection #2 Kanan Road (NS) at Canwood Street (EW) ***** Cycle (sec): 100 Critical Vol./Cap.(X): 0.776 Loss Time (sec):5 (Y+R=0.0 sec)Average Delay (sec/veh):Optimal Cycle:100Level Of Service: XXXXXX С Approach:North BoundSouth BoundEast BoundWest BoundMovement:L - T - RL - T - RL - T - RL - T - R Control:ProtectedProtectedProtectedProtectedRights:IncludeIncludeIncludeOvlMin. Green:000000Lanes:02012000 -----!!-----!! Volume Module: Base Vol: 0 1590 230 60 1310 0 0 0 0 330 0 180

 Initial Bse:
 0
 1779
 257
 67
 1465
 0
 0
 0
 369
 0
 201

 Added Vol:
 0
 0
 7
 1
 0
 0
 0
 0
 52
 0
 9

 PasserByVol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10
 10 PHF Volume: 0 1779 264 68 1465 0 0 0 421 0 210
 Reduct Vol:
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 <th
 PCE Adj:
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 1.00
 FinalVolume: 0 1779 264 68 1465 0 0 0 0 421 0 210 OvlAdjVol: 173 Saturation Flow Module: Lanes: 0.00 2.00 1.00 2.00 3.00 0.00 0.00 0.00 0.00 2.00 0.00 1.00 Final Sat.: 0 3200 1600 2880 4800 0 0 0 0 2880 0 1600 Capacity Analysis Module: Vol/Sat: 0.00 0.56 0.17 0.02 0.31 0.00 0.00 0.00 0.00 0.15 0.00 0.13 OvlAdjV/S: 0.11**** **** **** Crit Moves: ******