APPENDIX A

Optional Checklist for Determination

Of Whether a Facility is Categorically Excluded

Optional Checklist for Local Government To Determine Whether a Facility is Categorically Excluded

Purpose: The FCC has determined that many wireless facilities are unlikely to cause human exposures in excess of RF exposure guidelines. Operators of those facilities are exempt from routinely having to determine their compliance. These facilities are termed "categorically excluded." Section 1.1307(b)(1) of the Commission's rules defines those categorically excluded facilities. This checklist will assist state and local government agencies in identifying those wireless facilities that are categorically excluded, and thus are highly unlikely to cause exposure in excess of the FCC's guidelines. Provision of the information identified on this checklist may also assist FCC staff in evaluating any inquiry regarding a facility's compliance with the RF exposure guidelines.

BACKGROUND INFORMATION			
1.	Facility Operator's Legal Name:		
2.	Facility Operator's Mailing Address:		
3.	Facility Operator's Contact Name/Title:		
4.	Facility-Operator's Office Telephone:		
5.	Facility Operator's Fax:		
6.	Facility Name:		
7.	Facility Address:		
8.	Facility City/Community:		
9.	Facility State and Zip Code:		
10.	10. Latitude:		
11.	11. Longitude:		

Optional Local Government Checklist (page 2)

^{*&}quot;ERP" means "effective radiated power" and "EIRP" means "effective isotropic radiated power

 $\underline{\text{TABLE 1:}} \ \ \text{TRANSMITTERS, FACILITIES AND OPERATIONS SUBJECT TO ROUTINE} \\ \underline{\text{ENVIRONMENTAL EVALUATION}}$

SERVICE (TITLE 47 CFR RULE PART)	EVALUATION REQUIRED IF:
Experimental Radio Services (part 5)	power > 100 W ERP (164 W EIRP)
Multipoint Distribution Service (subpart K of part 21)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1640 W EIRP building-mounted antennas: power > 1640 W EIRP
Paging and Radiotelephone Service (subpart E of part 22)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1000 W ERP (1640 W EIRP) building-mounted antennas: power > 1000 W ERP (1640 W EIRP)
Cellular Radiotelephone Service (subpart H of part 22) -	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP) building-mounted antennas: total power of all channels > 1000 W ERP (1640 W EIRP)

TABLE 1 (cont.)

SERVICE (TITLE 47 CFR RULE PART)	EVALUATION REQUIRED IF:
Personal Communications Services (part 24)	(1) Narrowband PCS (subpart D): non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 1000 W ERP (1640 W EIRP) building-mounted antennas: total power of all channels > 1000 W ERP (1640 W EIRP) (2) Broadband PCS (subpart E): non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all channels > 2000 W ERP (3280 W EIRP) building-mounted antennas: total power of all channels > 2000 W ERP (3280 W EIRP)
Satellite-Communications (part 25)	all included
General Wireless Communications Service (part 26)	total power of all channels > 1640 W EIRP
Wireless Communications Service (part 27)	total power of all channels > 1640 W EIRP
Radio Broadcast Services (part 73)	all included

TABLE 1 (cont.)

SERVICE (TITLE 47 CFR RULE PART)	EVALUATION REQUIRED IF:
Experimental, auxiliary, and special broadcast and other program distributional services (part 74)	subparts A, G, L: power > 100 W ERP subpart I: non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1640 W EIRP building-mounted antennas: power > 1640 W EIRP
Stations in the Maritime Services (part 80)	ship earth stations only
Private Land Mobile Radio Services Paging Operations (part 90)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1000 W ERP (1640 W EIRP) building-mounted antennas: power > 1000 W ERP (1640 W EIRP)
Private Land Mobile Radio Services Specialized Mobile Radio (part 90)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and total power of all-channels > 1000 W ERP (1640 W EIRP) building-mounted antennas: total power of all channels > 1000 W ERP (1640 W EIRP)

TABLE 1 (cont.)

SERVICE (TITLE 47 CFR RULE PART)	EVALUATION REQUIRED IF:
Amateur Radio Service (part 97)	transmitter output power > levels specified in § 97.13(c)(1) of this chapter
Local Multipoint Distribution Service (subpart L of part 101)	non-building-mounted antennas: height above ground level to lowest point of antenna < 10 m and power > 1640 W EIRP building-mounted antennas: power > 1640 W EIRP LMDS licensees are required to attach a label to subscriber transceiver antennas that: (1) provides adequate notice regarding potential-radiofrequency safety hazards, e.g., information regarding the safe minimum separation distance required between users and transceiver antennas; and (2) references the applicable FCC-adopted limits for radiofrequency exposure specified in §
_	1.1310 of this chapter.

APPENDIX B

Estimated "Worst Case" Distances that Should be Maintained from Single Cellular, PCS, and Paging Base Station Antennas