

CONDITIONS OF APPROVAL (Case Nos. 05-SPR-001 & 05-OTP-028)

STANDARD CONDITIONS

1. This decision, or any aspect of this decision, can be appealed to the City Council within fifteen (15) days from the date of Planning Commission action, subject to filing the appropriate forms and related fees.
2. This action shall not be effective for any purpose until the applicant has agreed in writing that the applicant is aware of, and accepts all Conditions of these Permits with the Department of Planning and Community Development.
3. Except as modified herein, the approval of this action is limited to and requires complete conformation to the approved labeled exhibits: Site Plan; Elevation Plans; Floor Plans, Roof Plan, Landscape Plan and Grading Plan.
4. All exterior materials used in this project shall be in conformance with the materials samples submitted as a part of this application.
5. It is hereby declared to be the intent that if any provision of this Permit is held or declared to be invalid, the Permit shall be void and the privileges granted hereunder shall lapse.
6. It is further declared and made a Condition of this action that if any Condition herein is violated, the Permit shall be suspended and the privileges granted hereunder shall lapse; provided that the applicant has been given written notice to cease such violation and has failed to do so for a period of thirty (30) days.
7. All requirements of the Zoning Ordinance and of the specific zoning designation of the subject property must be complied with unless set forth in the Permit or on the approved Site Plan.
8. No occupancy shall be granted for any building until all Conditions of Approval have been complied with as determined by the Director of Planning and Community Development.
9. A minimum of two (2) enclosed parking spaces shall be provided on the subject property, in conformance with the City Parking Ordinance. A minimum interior clear space of 20 feet by 20 feet must be maintained within the garage.
10. The applicant shall comply with all applicable Public Health Statutes, Ordinances, and Regulations related to the disposal of sewage.
11. All structures shall conform to the requirements of the Division of Building and Safety of the City of Agoura Hills.
12. The applicant shall comply with the requirements of the Los Angeles County Fire Department prior to the issuance of Building or Grading Permits. The Forester and Fire Warden shall be

consulted to ascertain the required fire flows and fire hydrants to accommodate the proposed development.

13. Unless this permit is used within two (2) years from the date of City approval, Case No. 05-SPR-001 and 05-OTP-028 will expire. A written request for a one (1) year extension may be considered prior to the expiration date.
14. Prior to the issuance of Grading Permits or Building Permits, the applicant shall comply with the school impact fee requirements of the Las Virgenes Unified School District. The current fee is \$2.24/gross square foot for residential construction. Actual fees will be determined at the time of building permit issuance.
15. No roof-mounted equipment, other than attic ventilation systems and solar panels, as allowed by the Municipal Code, shall be permitted.
16. Prior to the issuance of a Building Permit, the applicant shall pay the Fire District Development Fee, at the rate in effect at the time of Building Permit issuance. The current rate is \$ 0.3877 per square foot of new floor area.
17. The City Building Code requires all new residences to be protected by a residential fire sprinkler system. Plans for the required system shall be approved by the Fire Department prior to the issuance of Building Permits for the residence.

CITY ENGINEER CONDITIONS

General

- ~~1~~18. All improvement plans, including, but not limited to, street, grading/drainage, sewer, storm drain, and striping/signage plans, for the entire project must be submitted as one package. This package must also include all supporting studies. All improvement plan sheets shall be 24" x 36" and must have the City's standard signature blocks and be legibly drawn to ensure proper reproduction and adequate record keeping. All lettering on plans shall be a minimum of 80 CL (.08 inch) in size to ensure proper reproduction and microfilming. All original plans shall be drawn in ink. All plans shall be prepared and signed by a California State Registered Civil Engineer.
- ~~2~~19. A soils report shall be prepared and submitted in accordance with the Agoura Hills Guidelines for geotechnical/geological reports.
- ~~3~~20. All block walls and retaining walls shall be limited to six feet in height.
21. A title report is required to be submitted with the project plans. The plans shall show all proposed and existing easements.
22. A Transportation Improvement Fee (TIF) in the amount of \$2,440 is due prior to issuance of Building Permit.

23. Provide an approximate 8.63 feet dedication for future street widening on Chesebro Road. The dedication documents shall be reviewed and approved by the City Engineer and recorded with the LA County Recorder's Office prior to issuance of a grading permit.

Grading

24. All grading shall conform to City's Grading Ordinance, Chapter 33 of the Uniform Building Code, as modified.
25. A site paving/drainage/grading plan shall be submitted for review and acceptance by the City Engineer. The plans, among other details, shall show proposed utilities, sewer connection or septic system, existing and proposed easements. The grading plan shall be accompanied by a Soils Report prepared in accordance with the Agoura Hills Guidelines for geotechnical/geological reports.
26. Prior to the issuance of a grading permit the following must be satisfied; the grading plan has been reviewed and accepted by the City Engineer, the applicable plan check, inspection and permit fees have been paid and the grading security has been posted.
27. For any grading operations conducted between October 1 and April 15 of each year, the applicant shall submit a wet weather erosion control plan for review and acceptance by the City Engineer.

Drainage

28. The SWPPP shall be prepared in compliance with the Development Construction Model Program for Stormwater Management within the County of Los Angeles, and shall be subject to approval by the City Engineer. The SWPPP shall identify pollutant sources, and shall include design and recommend construction and implementation of stormwater pollution prevention measures in order to reduce pollutants in stormwater discharges from the construction site during the construction period, and after construction as required.
29. Prior to issuance of a grading permit, the applicant shall prepare a Standard Urban Stormwater Mitigation Plan (SUSMP), as outlined in the Development Planning Model Program for Stormwater Management within the County of Los Angeles, subject to approval by the City Engineer. The plan will demonstrate treatment of the first ¾" of rainfall, as required by the Model Program.

Utilities

30. Applicant shall obtain plan approval for septic system purposes by the LA County Health Department prior to issuance of a grading permit.
31. The applicant shall submit evidence to the City Engineer that all sewer and water fees have been paid to Las Virgines Municipal Water District (LVMWD) and Los Angeles County prior to issuance of grading permit.

GEOTECHNICAL CONDITONS

32. The applicant shall comply with all of GeoDynamics, Inc.'s (The City of Agoura Hills' Geotechnical Consultant) Conditions of Approval letter dated October 31, 2005.

SOLID WASTE MANAGEMENT STANDARD CONDITIONS

33. To ensure that solid waste generated by the project is diverted from the landfill and reduced, reused, or recycled, the applicant shall submit a "Waste Reduction & Recycling Plan" to the City for review and approval. The plan shall provide for at least 50% of the waste generated on the project to be diverted from the landfill. Plans shall include the entire project area, even if tenants are pursuing or will pursue independent programs. The plan shall be submitted to and approved by the Department of Planning and Community Development prior to issuance of a building permit. The plan shall include the following information: material type to be recycled, reused, salvaged, or disposed; estimated quantities to be processed, management method used, and destination of material including the hauler name and facility location. The City's Waste Reduction & Recycling Plan form or a similar format shall be used.
34. The project shall comply with the plan and provide for the collection, recycling, and/or reuse of materials (i.e. concrete, wood, metal, cardboard, green waste, etc.) and document results during demolition and/or construction of the proposed project. After completion of demolition and/or construction, the applicant shall complete a Waste Reduction & Recycling Summary Report and provide legible copies of weight tickets, receipts, invoices or letters of verification for materials sent to disposal or reuse/recycling facilities. For other discarded or salvaged materials, the applicant shall provide documentation, on the disposal facility's letterhead, identifying where the materials were taken, type of materials, and tons or cubic yards disposed, recycled or reused and the project generating the discarded materials. The Waste Reduction & Recycling Summary Report shall be submitted and approved prior to issuance of a certificate of occupancy, or final inspection if issuance of a certificate of occupancy is not applicable.
35. The applicant shall arrange for materials collection during construction, demolition, and occupancy with a City permitted hauling company, or shall arrange for self-hauling to an authorized facility.

LANDSCAPE/OAK TREE CONDITIONS

Oak Trees

36. The applicant is permitted to encroach within the protected zone of Oak Tree Number TOT-2 to modify the existing fill slope above the tree. The grading limits shall not extend further west than the existing toe of the slope on the east side of the tree. Final grading plans shall be subject to the review and approval of the City Oak Tree Consultant.
37. All other oak trees shall be preserved in place with no direct impacts.

38. Prior to the start of any work or mobilization at the site, each oak tree to be preserved shall be fenced at the edge of the protected zone or at the approved work limits, in accordance with Article IX, Appendix A, Section V.C.1.1. The City Oak Tree Consultant shall approve the fencing locations.
39. The applicant shall provide a minimum of forty-eight (48) hours notice to the City Oak Tree Consultant prior to the start approved work within the protected zone of an oak tree.
40. No grading, scarifying or other soil disturbance shall be permitted within the portion of the protected zone of any oak tree not directly impacted by the project construction.
41. No vehicles, equipment, materials, spoil or other items shall be used or placed within the protected zone of any oak tree at any time, except as specifically required to complete the approved work.
42. Prior to occupancy, each oak tree shall be mulched throughout the dripline with three inches (3") of approved organic matter.
43. No irrigation or planting shall be installed within the dripline of any oak tree unless specifically approved by the City Oak Tree Consultant and the Director.
44. Within ten (10) calendar days of the completion of work and prior to removal of the protective fencing, the applicant shall contact the City Oak Tree Consultant to perform a final inspection. The applicant shall proceed with any remedial measures the City Oak Tree Consultant deems necessary to protect or preserve the health of the subject oak tree at that time.
45. No pruning of live wood shall be permitted unless specifically authorized by the City Oak Tree Consultant. Any authorized pruning shall be performed by a qualified arborist under the direct supervision of the applicant's oak tree consultant. Pruning operations shall be consistent with The Pruning Standards of the Western Chapter of the International Society of Arboriculture.
46. No herbicides shall be used within one hundred feet (100') of the dripline of any oak tree unless the program is first reviewed and endorsed by the City Oak Tree Consultant.
47. The project oak tree consultant shall submit certification letters for all work completed within the protected zone of any oak tree within ten (10) working days of the completion of said work. The letters shall describe all work performed, methods utilized, monitoring performed and shall state whether such work was completed in accordance with the above conditions of approval.

Landscaping

48. Since there are areas of 3:1 and 2:1 slopes, landscaping will be required for erosion control and slope stabilization. Recommended conditions of approval are as follows:
49. Prior to the approval of grading permits, the applicant shall submit three (3) sets of landscape plans meeting the following requirements:
 - a. A California-licensed landscape architect shall prepare, stamp and sign the plans.

- b. All plans shall be legible and clearly drawn.
 - c. Plans shall not exceed thirty inches (30") by forty-two inches (42") in size. Plans shall be a minimum of twenty-two inches (22") by thirty-six inches (36") in size.
 - d. A true north arrow and plan scale shall be noted. The scale shall be no smaller than one inch equals twenty feet (1"=20'), unless approved by the City Landscape Consultant.
 - e. A title block shall be provided, indicating the names, addresses and telephone numbers of the applicant and landscape architect.
 - f. The project identification number shall be shown on each sheet.
 - g. The plans shall accurately and clearly depict the following existing and proposed features:
 - Landscape trees, shrubs, ground cover and any other landscaping materials
 - Property lines
 - Streets, street names, right-of-ways, easements, driveways, walkways, bicycle paths, and any other paved areas
 - Buildings and structures
 - Parking areas, including lighting, striping and wheel stops
 - General contour lines
 - Grading areas, including tops and toes of slopes
 - Utilities, including street lighting and fire hydrants
 - Natural features, including watercourses, rock outcroppings
50. The Planting Plan shall indicate the botanical name and size of each plant.
 51. Plant symbols shall depict the size of the plants at maturity.
 52. Plant container sizes and/or spacing shall be provided. Minimum sizes shall be acceptable to the City Landscape Consultant and the Director.
 53. The Irrigation Plan shall be provided separate from but utilizing the same format as the Planting Plan.
 54. The irrigation design shall provide adequate coverage and sufficient water for the continued healthy growth of all proposed plantings with a minimum of waste and over spray on adjoining areas.

55. The Irrigation Plan shall be concise and accurate and shall include the manufacturer, model, size, demand, radius, and location of the following, as appropriate:
 - h. Design and static pressures
 - i. Point of connection
 - j. Backflow protection
 - k. Valves, piping, controllers, heads, quick couplers
 - l. Gallon requirements for each valve
56. Three (3) copies of details and specifications shall be provided, addressing but not limited to, planting, soil preparation, tree staking, guying, installation details, and post installation maintenance.
57. One copy of each of the following approved plans shall be submitted with the initial landscape plan check:
 - Site Plan
 - Elevations
 - Grading Plan
 - Conditions Of Approval
58. Native, drought resistant plants shall be utilized on the graded slope in accordance with the Old Agoura Design Overlay District requirements.
59. All landscaping shall be irrigated and maintained in perpetuity in accordance with the approved Landscape Plan.
60. Proposed plant material may not be considered invasive in the Santa Monica Mountains, as it could negatively impact the adjacent natural area. Lists of exotic material can be obtained from the California Native Plant Society and/or the California Exotic Pest Plant Council.

ENVIRONMENTAL CONDITIONS

61. In the event that archaeological resources are unearthed during project construction, all earth disturbing work within the vicinity of the find shall be temporarily suspended or redirected until a qualified archaeologist has evaluated the nature and significance of the find. After the find has been appropriately mitigated, work in the area may resume. A qualified Native American representative shall monitor any mitigation work associated with prehistoric cultural material.

SPECIAL CONDITIONS

62. All outstanding fees owned to the City, if any, shall be paid by the applicant within thirty (30) days from the date of this approval.

63. The driveway and hardscape surfaces on the lot shall consist of permeable or semi-permeable materials approved by the Director of Planning and Community Development.
64. All proposed retaining walls shall consist of split-faced block or other decorative materials subject to review and approval by the Director of Planning and Community Development.
65. All accessory structures shall be reviewed and approved by the Director of Planning and Community Development prior to submittal for a Building Permit.

END